

# TEST REPORT

Applicant Name : ZHENGZHOU DEWENWILS NETWORK TECHNOLOGY CO., LTD.  
Address : No.2602,26th Floor, Block B, Dongfang Building No.198-19,  
Songshan South Road, Erqi District, Zhengzhou, China  
Report Number : 2504V71149E-RF  
FCC ID: 2A4G9-017

## Test Standard (s)

47 CFR §1.1307& §2.1091

## Sample Description

Product Type: Low Voltage Landscape Transformer  
Model No.: MTM-300P-15TS-WiFi, MTM-200P-15TS-WiFi  
Trade Mark:   
Date Received: 2025-07-31  
Report Date: 2025-08-10

|              |  |
|--------------|--|
| Test Result: | The EUT complied with the standards above. |
|--------------|--|

## Prepared and Checked By:



Roger.Ling  
EMC Engineer

## Approved By:



Bob.Liao  
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.  
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: [www.atc-lab.com](http://www.atc-lab.com)

## TABLE OF CONTENTS

|  |          |
|--|----------|
| <b>DOCUMENT REVISION HISTORY</b> .....                   | <b>3</b> |
| <b>GENERAL INFORMATION</b> .....                         | <b>4</b> |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) ..... | 4        |
| OBJECTIVE .....  | 4        |
| TEST FACILITY .....                                      | 4        |
| <b>RF EXPOSURE</b> .....                                 | <b>5</b> |
| APPLICABLE STANDARD.....                                 | 5        |
| TEST RESULT .....  | 5        |
| <b>EXHIBIT A-EUT PHOTOGRAPHS</b> .....                   | <b>6</b> |

## DOCUMENT REVISION HISTORY

| Revision Number | Report Number  | Description of Revision | Date of Revision |
|-----------------|----------------|-------------------------|------------------|
| Rev.00          | 2504V71149E-RF | Original Report         | 2025-08-10       |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                               |  |
|-------------------------------|--|
| Product                       | Low Voltage Landscape Transformer  |
| Tested Model                  | MTM-300P-15TS-WiFi   |
| Multiple Model                | MTM-200P-15TS-WiFi   |
| Model Difference <sup>#</sup> | The difference between the two models is the model name and transformer coil power parameters. Please refer to DOS letter for more detail. The applicant provided "MTM-300P-15TS-WiFi" for full testing. |
| Voltage Range <sup>#</sup>    | AC 120V, 60Hz  |

|                                    |  |
|------------------------------------|--|
| Frequency Range                    | BLE 1M/2M: 2402-2480MHz<br>2.4G Wi-Fi: 2412-2472MHz          |
| Antenna Specification <sup>#</sup> | BLE & 2.4G Wi-Fi: 2.36dBi (It is provided by the applicant.) |
| Sample Serial Number               | MTM-300P-15TS-WiFi: 37BR-4 (Assigned by ATC, Shenzhen)       |
| Sample/EUT Status                  | Good condition   |

### Objective

This test report is in accordance with Part 1-Subpart I and Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with §1.1307 & §2.1091 rules.

### Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01.

## RF EXPOSURE

### Applicable Standard

According to FCC §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.4 –MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34                  | $1,920 R^2$ .         |
| 1.34-30                   | $3,450 R^2/f^2$ .     |
| 30-300                    | $3.83 R^2$ .          |
| 300-1,500                 | $0.0128 R^2f$ .       |
| 1,500-100,000             | $19.2R^2$ .           |

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

### Test result

For worst case:

| Mode      | Frequency Range (MHz) | Tune-Up Conducted Output Power <sup>#</sup> (dBm) | Antenna Gain <sup>#</sup> |       | ERP   |       | Evaluation Distance (cm) | MPE-Based Exemption (mW) |
|-----------|-----------------------|---|---------------------------|-------|-------|-------|--------------------------|--------------------------|
|           |                       |   | (dBi)                     | (dBd) | (dBm) | (mW)  |                          |                          |
| BLE       | 2402-2480             | 4.0   | 2.36                      | 0.21  | 4.21  | 2.64  | 20                       | 768.0                    |
| 2.4G WIFI | 2412-2472             | 17.5  | 2.36                      | 0.21  | 17.71 | 59.02 | 20                       | 768.0                    |

Note 1: The tune-up power and antenna gain are declared by the applicant.

Note 2:  $0\text{dBd}=2.15\text{dBi}$ .

Note 3: The BLE and 2.4G WIFI can't transmission simultaneously.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliance.**

## **EXHIBIT A-EUT PHOTOGRAPHS**

Please refer to the Attachment No.1 2504V71149E-RF EUT External Photos and Attachment No.2 2504V71149E-RF EUT Internal Photos.

\*\*\*\*\* END OF REPORT \*\*\*\*\*