

$$1 \text{ A/m} = 1.2566 \mu\text{T} \quad \text{H Limit: } 1.63 \text{ A/m}$$

Step 1 - Measure worst-case field on all other sides of the DUT.
Product duty cycle: 20.00%

Step 3: Measure at each grid location (30 cm from surface)

Product Perimeter

Approx. 1.8 meters from bottom of product to top of measurement zone

1 meter distance from the sides of the video to the edge of the measurement zone

Approx. 18" from bottom of product to bottom of measurement zone

**All measurements in µl

**Each point is 2.5" apart

Strength of Magnetic Field (RMS Measurement: Variable Position) (2.5 to 12 in. 40 in wide)																																																																																																																																																																																		
0.01	0.78	1	1.22	1.44	1.65	1.84	2.08	2.18	2.34	2.49	2.67	2.77	2.88	3.01	3.13	3.25	3.35	3.45	3.54	3.62	3.69	3.75	3.80	3.84	3.87	3.89	3.91	3.92	3.93	3.94	3.95	3.96	3.97	3.98	3.99	4.00	4.01	4.02	4.03	4.04	4.05	4.06	4.07	4.08	4.09	4.10	4.11	4.12	4.13	4.14	4.15	4.16	4.17	4.18	4.19	4.20	4.21	4.22	4.23	4.24	4.25	4.26	4.27	4.28	4.29	4.30	4.31	4.32	4.33	4.34	4.35	4.36	4.37	4.38	4.39	4.40	4.41	4.42	4.43	4.44	4.45	4.46	4.47	4.48	4.49	4.50	4.51	4.52	4.53	4.54	4.55	4.56	4.57	4.58	4.59	4.60	4.61	4.62	4.63	4.64	4.65	4.66	4.67	4.68	4.69	4.70	4.71	4.72	4.73	4.74	4.75	4.76	4.77	4.78	4.79	4.80	4.81	4.82	4.83	4.84	4.85	4.86	4.87	4.88	4.89	4.90	4.91	4.92	4.93	4.94	4.95	4.96	4.97	4.98	4.99	5.00																																										
0.02	0.81	1.07	1.28	1.44	1.60	1.76	1.90	2.07	2.24	2.4	2.56	2.71	2.85	2.98	3.09	3.19	3.28	3.35	3.39	3.41	3.43	3.44	3.45	3.46	3.47	3.48	3.49	3.50	3.51	3.52	3.53	3.54	3.55	3.56	3.57	3.58	3.59	3.60	3.61	3.62	3.63	3.64	3.65	3.66	3.67	3.68	3.69	3.70	3.71	3.72	3.73	3.74	3.75	3.76	3.77	3.78	3.79	3.80	3.81	3.82	3.83	3.84	3.85	3.86	3.87	3.88	3.89	3.90	3.91	3.92	3.93	3.94	3.95	3.96	3.97	3.98	3.99	4.00	4.01	4.02	4.03	4.04	4.05	4.06	4.07	4.08	4.09	4.10	4.11	4.12	4.13	4.14	4.15	4.16	4.17	4.18	4.19	4.20	4.21	4.22	4.23	4.24	4.25	4.26	4.27	4.28	4.29	4.30	4.31	4.32	4.33	4.34	4.35	4.36	4.37	4.38	4.39	4.40	4.41	4.42	4.43	4.44	4.45	4.46	4.47	4.48	4.49	4.50	4.51	4.52	4.53	4.54	4.55	4.56	4.57	4.58	4.59	4.60	4.61	4.62	4.63	4.64	4.65	4.66	4.67	4.68	4.69	4.70	4.71	4.72	4.73	4.74	4.75	4.76	4.77	4.78	4.79	4.80	4.81	4.82	4.83	4.84	4.85	4.86	4.87	4.88	4.89	4.90	4.91	4.92	4.93	4.94	4.95	4.96	4.97	4.98	4.99	5.00
0.04	0.85	1.05	1.29	1.52	1.74	1.94	2.13	2.31	2.47	2.63	2.79	2.93	3.07	3.19	3.29	3.38	3.45	3.51	3.55	3.58	3.61	3.64	3.67	3.69	3.72	3.74	3.76	3.78	3.80	3.82	3.84	3.86	3.88	3.90	3.92	3.94	3.96	3.98	4.00	4.02	4.04	4.06	4.08	4.10	4.12	4.14	4.16	4.18	4.20	4.22	4.24	4.26	4.28	4.30	4.32	4.34	4.36	4.38	4.40	4.42	4.44	4.46	4.48	4.50	4.52	4.54	4.56	4.58	4.60	4.62	4.64	4.66	4.68	4.70	4.72	4.74	4.76	4.78	4.80	4.82	4.84	4.86	4.88	4.90	4.92	4.																																																																																												

Value after applying duty cycle averaging:
