



# EMC TEST REPORT

**Applicant** Emerson White-Rodgers

**FCC ID** 2A4JN-ST765470

**Product** Sensi Touch 2

**Brand** Sensi

1F96U-42WFB; 1F96U-42WF; ST76; ST76W; ST76U;

**Model** ST76WU; 1F96U-42WFBC; 1F96U-42WFC; ST76C;  
ST76WC

**Report No.** R2211A1116-E1

**Issue Date** January 4, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2022)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Liu Wei

Approved by: Fan Guangchang

**TA Technology (Shanghai) Co., Ltd.**

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report .....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment Under Test .....	5
2.1	Applicant and Manufacturer Information.....	5
2.2	General Information .....	5
2.3	Applied Standards .....	7
2.4	Test Mode.....	8
3	Test Case Results .....	9
3.1	Radiated Emission .....	9
3.2	Conducted Emission .....	14
4	Uncertainty Measurement .....	17
5	Main Test Instruments .....	18
	ANNEX A: The EUT Appearance.....	19
	ANNEX B: Test Setup Photos.....	20



## Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: December 7, 2022 ~ December 19, 2022			
Date of Sample Received: November 29, 2022			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			



## 1 Test Laboratory

### 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2 Test Facility

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

### 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Fan Guangchang

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: <http://www.ta-shanghai.com>

E-mail: [fanguangchang@ta-shanghai.com](mailto:fanguangchang@ta-shanghai.com)



## 2 General Description of Equipment Under Test

### 2.1 Applicant and Manufacturer Information

Applicant	Emerson White-Rodgers
Applicant address	8100 West Florissant Ave St. Louis/United States of America
Manufacturer	Emerson White-Rodgers
Manufacturer address	8100 West Florissant Ave St. Louis/United States of America

### 2.2 General Information

EUT Description			
Device Type	Movable Device		
Model	1F96U-42WFB; 1F96U-42WF; ST76; ST76W; ST76U; ST76WU; 1F96U-42WFBC; 1F96U-42WFC; ST76C; ST76WC		
SN	LSR305240-62		
HW Version	0059-5470 REV.C		
SW Version	RT1052: 0170-1581v02_03.hex SUB-G: 0170-1640v01_02.hex		
Power Rating	AC 24V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	PCB Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	Model 900MHz	902.46 ~ 927.54	902.46 ~ 927.54
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 5G(U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5G(U-NII-2A)	5250 ~ 5350	5250 ~ 5350
	Wi-Fi 5G(U-NII-2C)	5470 ~ 5725	5470 ~ 5725
	Wi-Fi 5G(U-NII-3)	5725 ~ 5850	5725 ~ 5850
Note:			
1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			
2. The main test model is ST76 in this report.			



Model Difference Table				
Model Number	Description	Color	Channel	Instructions
1F96U-42WFB	Sensi Touch 2	Black	Pro	English
1F96U-42WF	Sensi Touch 2	White	Pro	English
ST76	Sensi Touch 2	Black	Retail	English
ST76W	Sensi Touch 2	White	Retail	English
ST76U	Sensi Touch 2	Black	Utility	English
ST76WU	Sensi Touch 2	White	Utility	English
1F96U-42WFBC	Sensi Touch 2	Black	Pro	French / English
1F96U-42WFC	Sensi Touch 2	White	Pro	French / English
ST76C	Sensi Touch 2	Black	Retail	French / English
ST76WC	Sensi Touch 2	White	Retail	French / English

Note: The customer declares that the models have the same PCB assembly, the only difference is color, package and sale channels.



## 2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### Test standards

**FCC Code CFR47 Part15B (2022)**

**ANSI C63.4-2014**



## 2.4 Test Mode

Test Mode	
Mode 1	Adapter + EUT +WLAN Receiver



### 3 Test Case Results

#### 3.1 Radiated Emission

##### Ambient Condition

Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

##### Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO


The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

## Test Setup

### Below 1GHz



### Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.


**Limits****Class B**

Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 <sup>th</sup> harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

## Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. The Emissions in the frequency band 18GHz – 40GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software. For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection. A symbol ( dB $\mu$ V/m) in the test plot below means (dB $\mu$ V/m)




Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
33.56	31.04	40.00	8.96	101.0	V	2.00	14
139.49	30.11	43.50	13.39	102.0	V	40.00	10
176.71	28.62	43.50	14.88	175.0	H	6.00	11
195.30	32.86	43.50	10.64	100.0	H	183.00	13
491.56	32.67	46.00	13.33	103.0	V	202.00	21
819.30	38.74	46.00	7.26	100.0	H	63.00	25

Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak



Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1146.63	---	30.22	54.00	23.78	500.00	200.0	H	260.00	-19
1146.63	40.31	---	74.00	33.69	500.00	200.0	H	260.00	-19
1473.88	---	33.88	54.00	20.12	500.00	100.0	H	359.00	-17
1473.88	41.46	---	74.00	32.54	500.00	100.0	V	207.00	-17
1637.50	---	33.18	54.00	20.82	500.00	100.0	H	210.00	-16
1637.50	43.82	---	74.00	30.18	500.00	100.0	V	290.00	-16
4100.38	---	30.35	54.00	23.65	500.00	100.0	V	64.00	-10
4170.50	41.42	---	74.00	32.58	500.00	200.0	V	276.00	-10
6726.88	48.44	---	74.00	25.56	500.00	200.0	H	78.00	-2
6797.00	---	36.42	54.00	17.58	500.00	200.0	H	0.00	-1
13858.38	57.83	---	74.00	16.17	500.00	100.0	H	134.00	8
13920.00	---	46.91	54.00	7.09	500.00	100.0	V	309.00	8

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Peak Margin = Limit -MAX Peak/ Average

## 3.2 Conducted Emission


### Ambient Condition

Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

### Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

### Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.


### Limits

Frequency (MHz)	Conducted Limits(dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 <sup>*</sup>	56 to 46 <sup>*</sup>
0.5 - 5	56	46
5 - 30	60	50

<sup>\*</sup>: Decreases with the logarithm of the frequency.

## Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.152250	47.26	---	65.88	18.62	1000.0	9.000	L1	ON	20.9
0.354750	---	15.03	48.85	33.82	1000.0	9.000	L1	ON	20.8
0.363750	34.90	---	58.64	23.74	1000.0	9.000	L1	ON	20.8
0.501000	---	13.47	46.00	32.53	1000.0	9.000	L1	ON	20.6
0.912750	---	14.16	46.00	31.84	1000.0	9.000	L1	ON	20.0
0.912750	17.30	---	56.00	38.70	1000.0	9.000	L1	ON	20.0
3.126750	14.26	---	56.00	41.74	1000.0	9.000	L1	ON	19.2
4.065000	---	14.26	46.00	31.74	1000.0	9.000	L1	ON	19.2
11.181750	24.69	---	60.00	35.31	1000.0	9.000	L1	ON	19.3
11.181750	---	16.41	50.00	33.59	1000.0	9.000	L1	ON	19.3
16.262250	32.62	---	60.00	27.38	1000.0	9.000	L1	ON	19.5
29.978250	---	23.16	50.00	26.84	1000.0	9.000	L1	ON	20.1

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.152250	48.31	---	65.88	17.57	1000.0	9.000	N	ON	20.9
0.361500	---	15.71	48.69	32.98	1000.0	9.000	N	ON	20.9
0.381750	38.48	---	58.24	19.76	1000.0	9.000	N	ON	20.8
0.717000	---	15.21	46.00	30.79	1000.0	9.000	N	ON	20.4
0.912750	23.34	---	56.00	32.66	1000.0	9.000	N	ON	20.1
0.912750	---	16.52	46.00	29.48	1000.0	9.000	N	ON	20.1
4.062750	20.58	---	56.00	35.42	1000.0	9.000	N	ON	19.2
4.560000	---	14.55	46.00	31.45	1000.0	9.000	N	ON	19.2
12.189750	---	16.93	50.00	33.07	1000.0	9.000	N	ON	19.4
12.189750	24.80	---	60.00	35.20	1000.0	9.000	N	ON	19.4
21.493500	---	22.51	50.00	27.49	1000.0	9.000	N	ON	19.8
24.380250	31.28	---	60.00	28.72	1000.0	9.000	N	ON	20.0

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz



## 4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96
Radiated Emission 18GHz – 26.5GHz	5.90 dB	1.96
Radiated Emission 26.5GHz – 40GHz	5.92 dB	1.96
Conducted Emission	2.57 dB	2



## 5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESCI3	100948	2022-05-25	2023-05-24
Signal Analyzer	R&S	FSV40	101186	2022-05-14	2023-05-13
Signal Analyzer	R&S	FSV40	101298	2022-05-14	2023-05-13
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	01111	2022-10-25	2025-10-24
Horn Antenna	Schwarzbeck	BBHA 9120D	430	2021-07-26	2024-07-25
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Horn Antenna	STEATITE	QSH-SL-26-40-K-15	16779	2019-12-24	2022-12-23
Software	R&S	EMC32	9.26.01	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2020-12-13	2022-12-12
				2022-12-13	2024-12-09
EMI Test Receiver	R&S	ESR	101667	2022-05-25	2023-05-24
Software	R&S	EMC32	10.35.10	/	/

\*\*\*\*\*END OF REPORT\*\*\*\*\*



## ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



## ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.