

WARNING CAUTION

- READ OWNER'S MANUAL BEFORE USE.
- AUTOMATIC RESET PROVIDED.
- FOR USE WITH ELECTRIC VEHICLES.
- VENTILATION NOT REQUIRED.
- THE SUITABILITY OF THE USE OF FLEXIBLE CORD IN ACCORDANCE WITH CE CODE. PART I, RULE 4-012, IS TO BE DETERMINED BY THE LOCAL INSPECTION AUTHORITY HAVING JURISDICTION.
- TO REDUCE THE RISK OF ELECTRIC SHOCK, CONNECT ONLY TO PROPERLY GROUNDED OUTLETS.
- DO NOT USE IF UNIT OR EV CABLE IS DAMAGED. SEE USER MANUAL FOR ADDITIONAL INFORMATION.
- RISK OF ELECTRIC SHOCK. DO NOT REMOVE COVER OR ATTEMPT TO OPEN THE ENCLOSURE. NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.
- RISK OF EXPLOSION. THIS EQUIPMENT HAS ARCING OR SPARKING PARTS THAT SHOULD NOT BE EXPOSED TO FLAMMABLE VAPORS.
- THIS DEVICE IS INTENDED ONLY FOR ELECTRIC VEHICLES NOT REQUIRING VENTILATION DURING CHARGING.
- TO AVOID A RISK OF FIRE OR ELECTRIC SHOCK, DO NOT USE THIS DEVICE WITH AN EXTENSION CORD.
- FCC ID: 2A4LRJB201NA
- THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:
 - (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
 - (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.
- Contains FCC ID: QOQWGM160P, QOQ13, N7NHL7802, R17LE910NAV2
- Contains IC: 5123A-WGM160P, 5123A-13, 2417C-HL7802, 5131A-LE910NAV2
- TYPE 4X / IP66 ENCLOSURE
- TEMPERATURE RATING:
 - 40°F to 140°F (-40°C to 60°C)
- MAXIMUM INPUT / OUTPUT CURRENT:
 - 32 A MAX
- FREQUENCY AND NUMBER OF PHASES:
 - 110-240VAC ~ 50/60Hz 1 PHASE



Model No
2JBX321AJ

MFG. DATE
04/04/2022



09100420012806
44025022699799
Serial Number
1099-4140-8093
Hardware Version
09.10.04
Firmware Version
20.01.28
SKU

2JBO321RNA-PJWX-200

JuiceBox® 32
enel x
Made in the USA