

TEST REPORT

Applicant Name : Shenzhen Srhythm Industry Co., Ltd.
Address : 1602 Zhongan Building, Guangchang Road Wenjing Community, Buji
St., Longgang Dist., Shenzhen, Guangdong, China, 518000
Report Number : SZNS1220309-08089E-00A
FCC ID: 2A4TBN2008

Test Standard (s)
FCC PART 15.247

Sample Description

Product Type: Bluetooth headphone
Model No.: S5
Date Received: 2022-03-09
Date of Test: 2022-03-28 to 2022-03-31
Report Date: 2022-04-06

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Black Ding
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk **. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
SPECIAL ACCESSORIES.....	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
SUMMARY OF TEST RESULTS.....	7
TEST EQUIPMENT LIST	8
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE.....	9
APPLICABLE STANDARD	9
TEST RESULT:	9
FCC §15.203 – ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	11
APPLICABLE STANDARD	11
EUT SETUP	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	12
TEST PROCEDURE	12
FACTOR & MARGIN CALCULATION	12
TEST DATA	12
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH.....	18
APPLICABLE STANDARD	18
TEST PROCEDURE	18
TEST DATA	18
FCC §15.247(b) (3) - Maximum CONDUCTED Output Power.....	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
FCC §15.247(d) – 100 kHz Bandwidth of Frequency Band Edge	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
FCC §15.247(e) - Power Spectral Density.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Bluetooth headphone
Tested Model No.	S5
Frequency Range	BLE: 2402-2480MHz
Maximum conducted Peak output power	-1.25dBm
Modulation Technique	BLE 1M/2M
Antenna Specification*	Internal Antenna: -1.95dBi(provided by the applicant)
Voltage Range	DC3.7V from battery
Sample number	SZNS1220309-08089E-RF-S1
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
AC Power Lines Conducted Emissions	2.72dB	
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
Temperature	1°C	
Humidity	6%	
Supply voltages	0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
...
...
...
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

EUT Exercise Software

Software “RTLBAPP”* was used during testing and the power level was Default power value*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From/Port	To
/	/	/	/

Block Diagram of Test Setup

For radiated emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Not Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note1: Bluetooth does not work when the sample is charged.

Note2: The right and left earbuds are identical, please refer to the Declaration letter for more detail, Per verified the output power of both unit, the output power for them is consistent, only the left earbud was full tested and reported.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Radiated Emission Test Software: e3 19821b (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2021/12/13	2022/12/12
WEINSCHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.32	RF-02	Each time	

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE**Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Test Result:**For worst case:**

Mode	Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE	2402-2480	-1.0	0.79	5	0.3	3.0	Yes

Result: Compliant.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal PCB Antenna arrangement, which was permanently attached and the antenna gain is -1.95dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	>1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$


Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	56 %
ATM Pressure:	101.2 kPa

The testing was performed by Chao Mo on 2022-03-31.


EUT operation mode: Transmitting (Scan with BLE 1M/BLE 2M mode at X axis, Y axis, Z axis, the worst case is at X axis)

Below 1GHz: BLE 1M High Channel (worst case)**Horizontal**

Site : chamber
Condition: 3m HORIZONTAL
Job No. : SZNS1220309-08089E-RF
Test Mode: BLE Transmitting

	Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	46.178	-9.99	31.15	21.16	40.00	-18.84	Peak
2	97.670	-12.26	31.49	19.23	43.50	-24.27	Peak
3	196.510	-11.57	30.83	19.26	43.50	-24.24	Peak
4	292.956	-9.28	31.01	21.73	46.00	-24.27	Peak
5	368.758	-7.37	31.31	23.94	46.00	-22.06	Peak
6	717.311	-1.34	32.72	31.38	46.00	-14.62	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : SZNS1220309-08089E-RF
Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	39.007	-10.58	29.87	19.29	40.00	-20.71	Peak
2	57.644	-9.95	29.59	19.64	40.00	-20.36	Peak
3	93.440	-12.87	30.89	18.02	43.50	-25.48	Peak
4	190.322	-11.52	30.64	19.12	43.50	-24.38	Peak
5	440.776	-5.64	30.43	24.79	46.00	-21.21	Peak
6	710.738	-1.47	32.03	30.56	46.00	-15.44	Peak

Above 1GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	
	Reading (dBuV)	PK/AV		Height	Polar					
				(m)	(H/V)					
BLE 1M Low Channel										
2310	45.18	PK	86	1.5	H	-7.23	37.95	74	-36.05	
2310	46.84	PK	337	1.7	V	-7.23	39.61	74	-34.39	
2390	53.44	PK	3	1.5	H	-7.21	46.23	74	-27.77	
2390	52.77	PK	38	2.1	V	-7.21	45.56	74	-28.44	
4804	43.83	PK	211	1.2	H	-3.52	40.31	74	-33.69	
4804	44.87	PK	142	2.1	V	-3.52	41.35	74	-32.65	
BLE 1M Middle Channel										
4880	44.5	PK	239	1.4	H	-3.38	41.12	74	-32.88	
4880	44.8	PK	183	1.9	V	-3.38	41.42	74	-32.58	
BLE 1M High Channel										
2483.5	48.42	PK	153	1.3	H	-7.2	41.22	74	-32.78	
2483.5	47.51	PK	330	1.4	V	-7.2	40.31	74	-33.69	
2500	46.06	PK	276	1.6	H	-7.18	38.88	74	-35.12	
2500	45.51	PK	67	2.0	V	-7.18	38.33	74	-35.67	
4960	45.99	PK	191	1.9	H	-3.01	42.98	74	-31.02	
4960	46.43	PK	85	1.5	V	-3.01	43.42	74	-30.58	
BLE 2M Low Channel										
2310	45.3	PK	60	1.7	H	-7.23	38.07	74	-35.93	
2310	47.38	PK	253	1.1	V	-7.23	40.15	74	-33.85	
2390	54.61	PK	163	1.6	H	-7.21	47.4	74	-26.6	
2390	52.63	PK	303	1.8	V	-7.21	45.42	74	-28.58	
4804	45.12	PK	169	1.4	H	-3.52	41.6	74	-32.4	
4804	45.85	PK	211	1.1	V	-3.52	42.33	74	-31.67	
BLE 2M Middle Channel										
4880	44.8	PK	132	1.5	H	-3.38	41.42	74	-32.58	
4880	45.49	PK	236	1.8	V	-3.38	42.11	74	-31.89	
BLE 2M High Channel										
2483.5	45.97	PK	228	1.3	H	-7.2	38.77	74	-35.23	
2483.5	46.3	PK	186	2.2	V	-7.2	39.1	74	-34.9	
2500	44.85	PK	214	1.3	H	-7.18	37.67	74	-36.33	
2500	45.23	PK	323	1.9	V	-7.18	38.05	74	-35.95	
4960	44.36	PK	120	1.5	H	-3.01	41.35	74	-32.65	
4960	44.9	PK	264	1.3	V	-3.01	41.89	74	-32.11	

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit


The other spurious emission which is in the noise floor level was not recorded.

For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


1 GHz - 18 GHz: (Pre-Scan plots)

BLE 1M High Channel (worst case)

Horizontal




Vertical




18-25GHz: (Pre-Scan plots)

BLE 1M High Channel(worst case)

Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	22 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa

The testing was performed by Key Pei on 2022-03-28.

EUT operation mode: Transmitting

Test Result

6 dB EMISSION BANDWIDTH:

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE 1M	Ant1	2402	0.668	2401.664	2402.332	0.5	PASS
		2440	0.532	2439.664	2440.196	0.5	PASS
		2480	0.536	2479.664	2480.200	0.5	PASS
BLE 2M	Ant1	2402	0.884	2401.412	2402.296	0.5	PASS
		2440	0.888	2439.412	2440.300	0.5	PASS
		2480	0.880	2479.412	2480.292	0.5	PASS


OCCUPIED BANDWIDTH

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE 1M	Ant1	2402	1.023	2401.504	2402.527	---	PASS
		2440	1.019	2439.504	2440.523	---	PASS
		2480	1.019	2479.504	2480.523	---	PASS
BLE 2M	Ant1	2402	2.05	2400.993	2403.043	---	PASS
		2440	2.05	2438.993	2441.043	---	PASS
		2480	2.05	2478.993	2481.043	---	PASS


Please refer to the below plots:

6 dB EMISSION BANDWIDTH


BLE 1M_Ant1_2402MHz



BLE 1M_Ant1_2440MHz




BLE 1M_Ant1_2480MHz




Date: 28.MAR.2022 15:20:03

BLE 2M_Ant1_2402MHz




Date: 28.MAR.2022 15:21:56

BLE 2M_Ant1_2440MHz



Date: 28.MAR.2022 15:23:48


BLE 2M_Ant1_2480MHz



Date: 28.MAR.2022 15:25:22


OCCUPIED BANDWIDTH

BLE 1M_Ant1_2402MHz



Date: 28.MAR.2022 15:14:59

BLE 1M_Ant1_2440MHz




Date: 28.MAR.2022 15:18:45

BLE 1M_Ant1_2480MHz




Date: 28.MAR.2022 15:20:19

BLE 2M_Ant1_2402MHz




Date: 28.MAR.2022 15:22:13

BLE 2M_Ant1_2440MHz



Date: 28.MAR.2022 15:24:05

BLE 2M_Ant1_2480MHz



Date: 28.MAR.2022 15:25:38


FCC §15.247(b) (3) - Maximum CONDUCTED Output Power

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	22 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa



The testing was performed by Key Pei on 2022-03-28.



EUT operation mode: Transmitting


Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE 1M	Ant1	2402	-2.31	<=30	PASS
		2440	-1.62	<=30	PASS
		2480	-1.25	<=30	PASS
BLE 2M	Ant1	2402	-2.38	<=30	PASS
		2440	-1.6	<=30	PASS
		2480	-1.25	<=30	PASS


Please refer to the below plots:

BLE 1M_Ant1_2402MHz**BLE 1M_Ant1_2440MHz**

BLE 1M_Ant1_2480MHz**BLE 2M_Ant1_2402MHz**

BLE 2M_Ant1_2440MHz

Date: 28.MAR.2022 15:24:17

BLE 2M_Ant1_2480MHz


Date: 28.MAR.2022 15:25:51

Duty Cycle


TestMode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE 1M	Ant1	2402	0.10	0.62	15.59
		2440	0.10	0.62	15.59
		2480	0.10	0.62	15.50
BLE 2M	Ant1	2402	0.06	0.62	9.62
		2440	0.06	0.62	9.52
		2480	0.06	0.62	9.51

Please refer to the below plots:


BLE 1M_Ant1_2402MHz



BLE 1M_Ant1_2440MHz




BLE 1M_Ant1_2480MHz





Date: 28.MAR.2022 15:19:37

BLE 2M_Ant1_2402MHz



Date: 28.MAR.2022 15:21:30

BLE 2M_Ant1_2440MHz**BLE 2M_Ant1_2480MHz**


FCC §15.247(d) – 100 kHz Bandwidth of Frequency Band Edge

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions


Temperature:	22°C
Relative Humidity:	46%
ATM Pressure:	101.1 kPa

The testing was performed by Key Pei on 2022-03-28.

EUT operation mode: Transmitting


Test Result: Pass

BLE 1M_Ant1_Low_2402MHz




Date: 28.MAR.2022 15:16:27

BLE 1M_Ant1_High_2480MHz




Date: 28.MAR.2022 15:20:59

BLE 2M_Ant1_ Low_2402MHz



BLE 2M_Ant1_ High_2480MHz




FCC §15.247(e) - Power Spectral Density

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	22 °C
Relative Humidity:	46 %
ATM Pressure:	101.1 kPa



The testing was performed by Key Pei on 2022-03-28.



EUT operation mode: Transmitting



Test Result

TestMode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE 1M	Ant1	2402	-20.83	<=8	PASS
		2440	-20.12	<=8	PASS
		2480	-19.72	<=8	PASS
BLE 2M	Ant1	2402	-21.62	<=8	PASS
		2440	-20.92	<=8	PASS
		2480	-20.51	<=8	PASS

Please refer to the below plots:

BLE 1M_Ant1_2402MHz**BLE 1M_Ant1_2440MHz**

BLE 1M_Ant1_2480MHz**BLE 2M_Ant1_2402MHz**

BLE 2M_Ant1_2440MHz**BLE 2M_Ant1_2480MHz**

***** END OF REPORT *****