

TEST REPORT

Applicant Name : Shenzhen Srhythm Industry Co.,Ltd
Address : 1602 Zhongan Building,Guangchang Road,Wenjing Community, Buji Street,Longgang District, Shenzhen, Guangdong ,China
Report Number: RA230426-22526E-RF
FCC ID: 2A4TBR1

Test Standard (s)
FCC Part 15.247

Sample Description

Product: Robot Vacuum
Model No.: Srhythm R1
Trade Name: 
Date Received: 2023-04-26
Date of Test: 2023-05-31 to 2023-06-02
Report Date: 2023-06-13

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Roger.Ling

Roger.Ling
EMC Engineer

Approved By:

Candy . Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".
Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE.....	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §1.1307(b) – RF EXPOSURE	11
TEST RESULT	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
FACTOR & MARGIN CALCULATION	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP.....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CALCULATION	18
TEST DATA	18
FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH.....	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
FCC §15.247(d) - 100KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
FCC §15.247(e) - POWER SPECTRAL DENSITY	28

APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
APPENDIX A: 6dB Emission Bandwidth	29
APPENDIX B: Occupied Channel Bandwidth	33
APPENDIX C: Maximum Conducted Output Power	37
APPENDIX D: Band Edge Measurements.....	38
APPENDIX E: Maximum Power Spectral Density	41
APPENDIX F: Duty Cycle.....	45

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230426-22526E-RF	Original Report	2023-06-13

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Robot Vacuum		
Tested Model	Srhythm R1		
Frequency Range	Wi-Fi: 2412-2462MHz (802.11b/g/n20)		
Maximum Conducted Average Power	Wi-Fi:		
	12.11dBm(802.11b)	9.60dBm(802.11g)	9.86dBm(802.11n20)
Modulation Technique	Wi-Fi: DSSS, OFDM		
Antenna Specification*	Internal Antenna: 2.5dBi(provided by the applicant)		
Voltage Range	DC 14.1V from battery or DC 19V from adapter		
Sample serial number	RA230426-22526E-RF-S1(RF Radiated Test) RA230426-22526E-RF-S2(RF Conducted Test) (Assigned by ATC, Shenzhen)		
Sample/EUT Status	Good condition		
Adapter information	Model No.: GSCU0600S019V12E Input: 100V-240V~ 50/60Hz, 0.5A MAX Output: 19V ---0.6A		

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, and KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.71dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.74dB
Emissions, Radiated	9kHz - 30MHz	2.06dB
	30MHz - 1GHz	5.08dB
	1GHz - 18GHz	4.96dB
	18GHz - 26.5GHz	5.16dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, and 802.11n-HT20, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

Software “MP-Tool-1V3”* was used during testing and power level as below:

Mode	Data Rate (Mbps)	Power Level*
802.11 b	1	Default
802.11 g	6	Default
802.11 n20	MCS0	Default

The worse-case data rates are determined to be as above for each mode based upon investigations by measuring the output power and PSD across all data rates, bandwidths and modulations.

Duty cycle

Test Result: Compliant. Please refer to the Appendix F

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Detachable DC Cable	1.8	EUT	Adapter

Block Diagram of Test Setup

For Conducted Emission



For Radiated Emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b)	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 191218 (V9)					
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2022/11/08	2023/11/07
SCHWARZBECK	LOOP ANTENNA	FMZB1516	1516131	2021/12/22	2024/12/21
Schwarzbeck	Bilog Antenna	VULB9163	9163-194	2023/02/14	2026/02/13
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24
Wainwright	Band Reject Filter	WRCG2400/2 485-2375/251 0-60/11SS	10	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Radiated Emission Test Software: e3 191218 (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2022/11/25	2023/11/24
Agilent	USB wideband power sensor	U2021XA	MY54250003	2022/6/27	2023/06/26
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2022/11/25	2023/11/24
WEINSCHHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.33	RF-03	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) – RF EXPOSURE

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.4–MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

Test Result

For worst case:

Mode	Frequency Range (MHz)	Tune-up Output Power		Antenna Gain		ERP		Evaluation Distance (cm)	MPE-Based Exemption Limit (mW)
		(dBm)	(mW)	(dBi)	(dBd)	(dBm)	(mW)		
2.4G Wi-Fi	2412-2462	12.5	17.78	2.5	0.35	12.85	19.28	20	768

Note 1: The tune-up power was declared by the applicant.

Note 2: 0dBd=2.15dBi.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement for 2.4G Wi-Fi, which was permanently attached and the antenna gain is 2.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

FrequencyRange	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data


Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Jerry Wu on 2023-06-02.

EUT operation mode: 2.4G Wi-Fi Transmitting (Worst case for 802.11B High channel as below)


AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : RA230426-22526E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.175	10.33	19.75	30.08	54.74	-24.66	Average
2	0.175	10.33	32.26	42.59	64.74	-22.15	QP
3	0.212	10.30	14.48	24.78	53.12	-28.34	Average
4	0.212	10.30	26.74	37.04	63.12	-26.08	QP
5	0.343	10.45	12.87	23.32	49.13	-25.81	Average
6	0.343	10.45	21.27	31.72	59.13	-27.41	QP
7	0.599	10.62	16.76	27.38	46.00	-18.62	Average
8	0.599	10.62	22.86	33.48	56.00	-22.52	QP
9	2.937	10.49	9.32	19.81	46.00	-26.19	Average
10	2.937	10.49	16.87	27.36	56.00	-28.64	QP
11	29.921	10.12	10.92	21.04	50.00	-28.96	Average
12	29.921	10.12	21.43	31.55	60.00	-28.45	QP

AC 120V/60 Hz, Neutral





Site : Shielding Room
 Condition: Neutral
 Job No. : RA230426-22526E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.174	10.28	20.00	30.28	54.78	-24.50	Average
2	0.174	10.28	31.61	41.89	64.78	-22.89	QP
3	0.250	10.32	11.44	21.76	51.76	-30.00	Average
4	0.250	10.32	20.79	31.11	61.76	-30.65	QP
5	0.468	10.45	11.43	21.88	46.56	-24.68	Average
6	0.468	10.45	19.89	30.34	56.56	-26.22	QP
7	0.585	10.47	19.26	29.73	46.00	-16.27	Average
8	0.585	10.47	24.22	34.69	56.00	-21.31	QP
9	2.995	10.53	12.56	23.09	46.00	-22.91	Average
10	2.995	10.53	21.27	31.80	56.00	-24.20	QP
11	5.480	10.51	10.94	21.45	50.00	-28.55	Average
12	5.480	10.51	18.19	28.70	60.00	-31.30	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300 Hz	1kHz	/	PK
150 kHz – 30MHz	10 kHz	30 kHz	/	PK
30MHz – 1000 MHz	100 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23-24 °C
Relative Humidity:	55-56 %
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng and Jeef Huang on 2023-05-31 and 2023-06-01.


EUT operation mode: 2.4G Wi-Fi Transmitting

Note: For 9kHz - 30MHz, the spurious emission is 20dB below to the limit or in the noise floor level was not recorded.

30MHz-1GHz:

802.11 b High Channel (Worst case)


Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : RA230426-22526E-RF
 Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	35.655	-11.32	32.63	21.31	40.00	-18.69	Peak
2	107.557	-11.98	41.79	29.81	43.50	-13.69	Peak
3	144.019	-15.52	45.94	30.42	43.50	-13.08	Peak
4	252.727	-10.68	48.22	37.54	46.00	-8.46	Peak
5	293.856	-9.27	49.59	40.32	46.00	-5.68	QP
6	838.814	0.26	29.02	29.28	46.00	-16.72	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : RA230426-22526E-RF
 Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	35.765	-11.28	45.30	34.02	40.00	-5.98	QP
2	39.420	-10.48	44.00	33.52	40.00	-6.48	QP
3	108.077	-11.99	46.80	34.81	43.50	-8.69	QP
4	188.083	-11.81	42.79	30.98	43.50	-12.52	Peak
5	293.599	-9.28	45.24	35.96	46.00	-10.04	Peak
6	791.312	-0.16	28.79	28.63	46.00	-17.37	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	55.71	PK	180	1.6	H	-10.36	45.35	74	-28.65
2310	57.01	PK	84	1.1	V	-10.36	46.65	74	-27.35
2390	57.08	PK	151	1.1	H	-10.71	46.37	74	-27.63
2390	56.45	PK	287	1.1	V	-10.71	45.74	74	-28.26
4824	52.69	PK	112	1.9	H	-6.11	46.58	74	-27.42
4824	51.16	PK	64	2.1	V	-6.11	45.05	74	-28.95
802.11B, Middle Channel									
4874	52.2	PK	208	1.4	H	-5.94	46.26	74	-27.74
4874	49.7	PK	167	1.1	V	-5.94	43.76	74	-30.24
11B, High Channel									
2483.5	57.19	PK	163	2.2	H	-10.55	46.64	74	-27.36
2483.5	56.71	PK	209	1.9	V	-10.55	46.16	74	-27.84
2500	57.45	PK	358	1.4	H	-10.42	47.03	74	-26.97
2500	57.27	PK	122	2.1	V	-10.42	46.85	74	-27.15
4924	54.35	PK	114	2.2	H	-5.67	48.68	74	-25.32
4924	54.22	PK	147	1.5	V	-5.67	48.55	74	-25.45
802.11G, Low Channel									
2310	55.64	PK	64	1.2	H	-10.36	45.28	74	-28.72
2310	56.05	PK	103	2.1	V	-10.36	45.69	74	-28.31
2390	57.84	PK	34	1.3	H	-10.71	47.13	74	-26.87
2390	57.03	PK	188	1.6	V	-10.71	46.32	74	-27.68
4824	51.42	PK	9	1.8	H	-6.11	45.31	74	-28.69
4824	49.96	PK	316	1.9	V	-6.11	43.85	74	-30.15
802.11G, Middle Channel									
4874	52.58	PK	331	1.9	H	-5.94	46.64	74	-27.36
4874	52.98	PK	308	1.7	V	-5.94	47.04	74	-26.96
802.11G, High Channel									
2483.5	59.19	PK	308	1.7	H	-10.55	48.64	74	-25.36
2483.5	59.86	PK	146	1.9	V	-10.55	49.31	74	-24.69
2500	56.73	PK	202	2.1	H	-10.42	46.31	74	-27.69
2500	57.06	PK	202	2.1	V	-10.42	46.64	74	-27.36
4924	53	PK	54	1.7	H	-5.67	47.33	74	-26.67
4924	53.35	PK	292	1.3	V	-5.67	47.68	74	-26.32

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
802.11N20, Low Channel									
2310	57.22	PK	188	1.6	H	-10.36	46.86	74	-27.14
2310	56.67	PK	282	1.4	V	-10.36	46.31	74	-27.69
2390	56.39	PK	9	1.8	H	-10.71	45.68	74	-28.32
2390	57.3	PK	175	1.5	V	-10.71	46.59	74	-27.41
4824	53.72	PK	331	1.9	H	-6.11	47.61	74	-26.39
4824	54.48	PK	4	2.0	V	-6.11	48.37	74	-25.63
802.11N20, Middle Channel									
4874	51.71	PK	26	1.6	H	-5.94	45.77	74	-28.23
4874	52.31	PK	146	1.9	V	-5.94	46.37	74	-27.63
802.11N20, High Channel									
2483.5	58.2	PK	146	1.9	H	-10.55	47.65	74	-26.35
2483.5	64.17	PK	54	1.7	V	-10.55	53.62	74	-20.38
2500	57.14	PK	292	1.3	H	-10.42	46.72	74	-27.28
2500	58.15	PK	292	1.3	V	-10.42	47.73	74	-26.27
4924	50.06	PK	181	1.9	H	-5.67	44.39	74	-29.61
4924	51.31	PK	318	1.7	V	-5.67	45.64	74	-28.36

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level (Corrected Amplitude) – Limit


The other spurious emission which is in the noise floor level was not recorded.

For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


1-18 GHz (Pre-scan plots):

802.11 b High Channel (Worst case)

Horizontal




Vertical




18 -25GHz (Pre-scan plots):

802.11 b High Channel (Worst case)

Horizontal



Vertical



FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013, section 11.8 and section 6.9

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-05-31.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix A and Appendix B.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013, section 11.9.2.3.2

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-05-31.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix C.

FCC §15.247(d) - 100KHZ BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013, section 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-05-31.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix D.

FCC §15.247(e) - POWER SPECTRAL DENSITY


Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013, section 11.10.3& section 11.10.5

1. Use this procedure when the maximum average conducted output power in the fundamental emission is used to demonstrate compliance.
2. Measure the duty cycle (D) of the transmitter output signal as described in 11.6 of ANSI C63.10-2013
3. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Set the span to 1.5 times the DTS bandwidth.
6. Detector = power averaging (rms) or sample detector (when rms not available)
7. Sweep time = auto couple.
8. Employ trace averaging (rms) mode over a minimum of 100 traces.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If the duty cycle less than 98%, add $[10 \log (1 / D)]$, where D is the duty cycle measured in step 2), to the measured PSD to compute the average PSD during the actual transmission time
12. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-05-31.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix E.

APPENDIX A: 6dB Emission Bandwidth**Test Result**


Test Mode	Antenna	Channel[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.28	0.5	PASS
		2437	8.48	0.5	PASS
		2462	8.28	0.5	PASS
11G	Ant1	2412	16.40	0.5	PASS
		2437	16.36	0.5	PASS
		2462	16.32	0.5	PASS
11N20 SISO	Ant1	2412	17.56	0.5	PASS
		2437	17.32	0.5	PASS
		2462	17.32	0.5	PASS

Test Graphs

11B_Ant1_2412




11B_Ant1_2437



11B_Ant1_2462




11G_Ant1_2412




Date: 31.MAY.2023 19:23:52

11G_Ant1_2437




Date: 31.MAY.2023 19:25:56

11G_Ant1_2462




Date: 31.MAY.2023 19:26:46

11N20SISO_Ant1_2412




Date: 31.MAY.2023 19:27:52

11N20SISO_Ant1_2437



Date: 31.MAY.2023 19:28:54

11N20SISO_Ant1_2462




Date: 31.MAY.2023 19:29:35

APPENDIX B: Occupied Channel Bandwidth**Test Result:**


Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.388	---	PASS
		2437	12.468	---	PASS
		2462	12.507	---	PASS
11G	Ant1	2412	17.742	---	PASS
		2437	18.382	---	PASS
		2462	18.262	---	PASS
11N20 SISO	Ant1	2412	18.541	---	PASS
		2437	19.301	---	PASS
		2462	19.66	---	PASS

Test Graphs:


11B_Ant1_2412




11B_Ant1_2437



11B_Ant1_2462




11G_Ant1_2412




Date: 31.MAY.2023 19:23:58

11G_Ant1_2437




Date: 31.MAY.2023 19:26:01

11G_Ant1_2462




Date: 31.MAY.2023 19:26:52


11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462




APPENDIX C: Maximum Conducted Output Power**Test Result**

Test Mode	Antenna	Channel	Average power [dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	12.11	<=30	PASS
		2437	9.60	<=30	PASS
		2462	11.57	<=30	PASS
11G	Ant1	2412	8.28	<=30	PASS
		2437	7.67	<=30	PASS
		2462	9.60	<=30	PASS
11N20 SISO	Ant1	2412	8.58	<=30	PASS
		2437	8.09	<=30	PASS
		2462	9.86	<=30	PASS


APPENDIX D: Band Edge Measurements

Test Graphs


11B_Ant1_Low_2412




11B_Ant1_High_2462




11G_Ant1_Low_2412




11G_Ant1_High_2462



11N20SISO_Ant1_Low_2412



11N20SISO_Ant1_High_2462




APPENDIX E: Maximum Power Spectral Density**Test Result**

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.98	<=8	PASS
		2437	-21.78	<=8	PASS
		2462	-19.81	<=8	PASS
11G	Ant1	2412	-24.15	<=8	PASS
		2437	-24.45	<=8	PASS
		2462	-22.63	<=8	PASS
11N20 SISO	Ant1	2412	-24.39	<=8	PASS
		2437	-24.41	<=8	PASS
		2462	-23.08	<=8	PASS

Note: the duty cycle factor has added into the plot.


Test Graphs

11B_Ant1_2412




Date: 31.MAY.2023 19:16:20

11B_Ant1_2437




Date: 31.MAY.2023 19:17:25

11B_Ant1_2462




Date: 31.MAY.2023 19:18:52

11G_Ant1_2412




Date: 31.MAY.2023 19:24:11

11G_Ant1_2437




Date: 31.MAY.2023 19:26:14

11G_Ant1_2462




Date: 31.MAY.2023 19:27:05

11N20SISO_Ant1_2412




Date: 31.MAY.2023 19:28:11

11N20SISO_Ant1_2437



Date: 31.MAY.2023 19:29:13

11N20SISO_Ant1_2462



Date: 31.MAY.2023 19:29:53

APPENDIX F: Duty Cycle

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-05-31.


EUT operation mode: Transmitting

Test Result


Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]	1/T Minimum VBW[kHz]
11B	Ant1	2412	50.00	50.00	100.00	/	/
		2437	50.00	50.00	100.00	/	/
		2462	50.00	50.00	100.00	/	/
11G	Ant1	2412	2.07	2.10	98.57	/	/
		2437	2.07	2.10	98.57	/	/
		2462	2.08	2.11	98.58	/	/
11N20 SISO	Ant1	2412	1.93	1.97	97.97	0.09	0.52
		2437	1.93	1.97	97.97	0.09	0.52
		2462	1.93	1.98	97.47	0.11	0.52

Test Graphs


11B_Ant1_2412




11B_Ant1_2437



11B_Ant1_2462




11G_Ant1_2412




Date: 31.MAY.2023 19:23:45

11G_Ant1_2437




Date: 31.MAY.2023 19:25:48

11G_Ant1_2462




Date: 31.MAY.2023 19:26:39

11N20SISO_Ant1_2412




Date: 31.MAY.2023 19:27:45

11N20SISO_Ant1_2437



Date: 31.MAY.2023 19:28:47

11N20SISO_Ant1_2462



Date: 31.MAY.2023 14:43:23

***** END OF REPORT *****