

Acknowledgment Letter

SPECIFICATION FOR APPROVAL

CUSTOMER: Jinzhizhuo Technology Co., Ltd

CUSTOMER P/N:

DESCRIPTION : DATE:2024/5/30

SPECIFICATION : Watch coil 8.1UH 8MM long REV.NO.:A0

Hongri Shengwei Technology acknowledges, signs and seals

depart ment	confirm	to examine	ratify	Stamped with the company seal
qual ity	Dong Wanhong	Lv Hui	Wei Hanman	
engineering	He Weihua	Wei Lihong	Wei Lihong	

notes:

Jin Zhizhuo Technology acknowledges, signs, and stamps

depart ment	Confirmation/Date	Review/Date	Approved/date	Stamped with the company seal
development engineering				
pr ocur e				
qual ity				

notes:

Shenzhen Hongrishengwei Technology Co., Ltd

or, Building 1, No. 48 Guanlan Huanguan Middle Road, Longhu
TEL: 15112254520/13682412162

SPECIFICATION FOR APPROVAL																																												
1.MECHANICAL DIMENSION (UNIT:mm)					2. SCHEMATICS:																																							
					1. Magnet: 8 * 2.45 3200 Gauss																																							
<table><tr><td>A</td><td>B</td><td>C</td><td>D</td><td>F</td><td>G</td><td>I</td><td></td><td></td><td></td></tr><tr><td>20±2</td><td>14±1</td><td>2.8±0.5</td><td>8±2</td><td>3±1.5</td><td>25REF</td><td>7.8±0.5</td><td></td><td></td><td></td></tr></table>										A	B	C	D	F	G	I				20±2	14±1	2.8±0.5	8±2	3±1.5	25REF	7.8±0.5																		
A	B	C	D	F	G	I																																						
20±2	14±1	2.8±0.5	8±2	3±1.5	25REF	7.8±0.5																																						
3.WINDING:																																												
<table><tr><td>STEP</td><td>START-FINISH</td><td colspan="2">WIRE TYPE</td><td>TURNS</td><td>TAPE</td><td>REMARK</td></tr><tr><td>N1</td><td>S-F</td><td colspan="2">0.08*24mm 2UEW</td><td>14TS (Ref)</td><td></td><td></td></tr></table>										STEP	START-FINISH	WIRE TYPE		TURNS	TAPE	REMARK	N1	S-F	0.08*24mm 2UEW		14TS (Ref)																							
STEP	START-FINISH	WIRE TYPE		TURNS	TAPE	REMARK																																						
N1	S-F	0.08*24mm 2UEW		14TS (Ref)																																								
4. ELECTRICAL SPECIFICATION:																																												
<table><tr><td>ITEM</td><td>L</td><td>DCR</td><td>IDC</td><td></td><td colspan="2">HI-POT</td></tr><tr><td rowspan="2">TEST CON</td><td>S-F</td><td>S-F</td><td>S-F</td><td></td><td colspan="2"></td></tr><tr><td>100KHz, 0.25V</td><td>AT 25℃</td><td>AT 25℃</td><td></td><td></td><td></td></tr><tr><td>SPEC</td><td>8.1uH±5%</td><td>130mΩ(Max)</td><td>2.5A</td><td></td><td></td><td></td></tr></table>										ITEM	L	DCR	IDC		HI-POT		TEST CON	S-F	S-F	S-F				100KHz, 0.25V	AT 25℃	AT 25℃				SPEC	8.1uH±5%	130mΩ(Max)	2.5A											
ITEM	L	DCR	IDC		HI-POT																																							
TEST CON	S-F	S-F	S-F																																									
	100KHz, 0.25V	AT 25℃	AT 25℃																																									
SPEC	8.1uH±5%	130mΩ(Max)	2.5A																																									
5.BILF OF MATERIAL:																																												
<table><tr><td>NO.</td><td>ITEM</td><td>MATERIAL SPECIFICATION</td><td>MANUFACTURER</td><td>SGS NO.</td></tr><tr><td>1</td><td>CORE</td><td>UG25软磁</td><td>NANJINGJINNINGCO,LTD</td><td></td></tr><tr><td>2</td><td>magnet</td><td>8 * 2.45 3200 Gauss</td><td>NANJINGJINNINGCO,LTD</td><td></td></tr><tr><td>3</td><td>Copper wire</td><td>0.08mm*24 2UEW</td><td>TAIYI CO.,LTD</td><td></td></tr><tr><td>4</td><td>Adhesive backing</td><td>18 double-sided adhesive backing</td><td>HONGBAOJEICO,LTD</td><td></td></tr><tr><td>5</td><td>Solder Bar</td><td>Solder Bar</td><td>QIANDAO CO.,LTD</td><td></td></tr><tr><td>6</td><td>glue</td><td>9999</td><td>CUDAK CO.,LTD</td><td></td></tr></table>										NO.	ITEM	MATERIAL SPECIFICATION	MANUFACTURER	SGS NO.	1	CORE	UG25软磁	NANJINGJINNINGCO,LTD		2	magnet	8 * 2.45 3200 Gauss	NANJINGJINNINGCO,LTD		3	Copper wire	0.08mm*24 2UEW	TAIYI CO.,LTD		4	Adhesive backing	18 double-sided adhesive backing	HONGBAOJEICO,LTD		5	Solder Bar	Solder Bar	QIANDAO CO.,LTD		6	glue	9999	CUDAK CO.,LTD	
NO.	ITEM	MATERIAL SPECIFICATION	MANUFACTURER	SGS NO.																																								
1	CORE	UG25软磁	NANJINGJINNINGCO,LTD																																									
2	magnet	8 * 2.45 3200 Gauss	NANJINGJINNINGCO,LTD																																									
3	Copper wire	0.08mm*24 2UEW	TAIYI CO.,LTD																																									
4	Adhesive backing	18 double-sided adhesive backing	HONGBAOJEICO,LTD																																									
5	Solder Bar	Solder Bar	QIANDAO CO.,LTD																																									
6	glue	9999	CUDAK CO.,LTD																																									
<table><tr><td colspan="3" rowspan="2">Hongrishengwei Technology Co., Ltd</td><td colspan="2">PART NO</td><td colspan="3"></td></tr><tr><td colspan="2">TITLE</td><td colspan="3">Watch coil 8.1UH 8MM long</td></tr><tr><td colspan="3">DRAWN BY</td><td colspan="3">CHECKED BY</td><td colspan="3">APPROVED BY</td></tr><tr><td colspan="3">XIECHAO</td><td colspan="3">HEWEIHUA</td><td colspan="3">WEILIHONG</td></tr></table>										Hongrishengwei Technology Co., Ltd			PART NO					TITLE		Watch coil 8.1UH 8MM long			DRAWN BY			CHECKED BY			APPROVED BY			XIECHAO			HEWEIHUA			WEILIHONG						
Hongrishengwei Technology Co., Ltd			PART NO																																									
			TITLE		Watch coil 8.1UH 8MM long																																							
DRAWN BY			CHECKED BY			APPROVED BY																																						
XIECHAO			HEWEIHUA			WEILIHONG																																						