



FCC Part 15C Test Report

FCC ID: 2A4UX-Q8

Applicant: Shenzhen Jingrui Weiye Technology Co., Ltd.

Address: 7/f, building B, Tea Tree Phase II, Gushu Sanwei industrial zone, Xixiang Street, Bao 'an district, Shenzhen

Manufacturer: Shenzhen Jingrui Weiye Technology Co., Ltd.

Address: 7/f, building B, Tea Tree Phase II, Gushu Sanwei industrial zone, Xixiang Street, Bao 'an district, Shenzhen

EUT: MP3

Trade Mark: N/A

Model Number: Q8

Date of Receipt: Feb. 23, 2022

Test Date: Feb. 23, 2022 - Mar. 01 , 2022

Date of Report: Mar. 01 , 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.247
ANSI C63.10: 2013

Test Result: Pass

Report Number: DL-20220225016

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents

Page

1. SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY.....	5
2. GENERAL INFORMATION.....	6
2.1 GENERAL DESCRIPTION OF EUT.....	6
2.2 DESCRIPTION OF TEST MODES.....	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED.....	7
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE).....	7
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING.....	7
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS.....	8
3. EMC EMISSION TEST.....	9
3.1 CONDUCTED EMISSION MEASUREMENT.....	9
3.2 POWER LINE CONDUCTED EMISSION Limits.....	9
3.3TEST PROCEDURE.....	9
3.4 DEVIATION FROM TEST STANDARD.....	9
3.5 TEST SETUP.....	10
3.6 EUT OPERATING CONDITIONS.....	10
3.7 TEST RESULTS.....	10
4. RADIATED EMISSION MEASUREMENT.....	13
4.1 RADIATED EMISSION LIMITS.....	13
4.2 TEST PROCEDURE.....	14
4.3 DEVIATION FROM TEST STANDARD.....	14
4.4 TEST SETUP.....	14
4.5 EUT OPERATING CONDITIONS.....	15
4.6 TEST RESULTS.....	15
5. RADIATED BAND EMISSION MEASUREMENT.....	19
5.1 TEST REQUIREMENT:.....	19
5.2 TEST PROCEDURE.....	19
5.3 DEVIATION FROM TEST STANDARD.....	19
5.4 TEST SETUP.....	20
5.5 EUT OPERATING CONDITIONS.....	20
5.6 TEST RESULT.....	21

**Table of Contents****Page**

6. PEAK OUTPUT POWER.....	22
6.1 APPLIED PROCEDURES / LIMIT.....	22
6.2 TEST PROCEDURE.....	22
6.3 DEVIATION FROM STANDARD.....	22
6.4 TEST SETUP.....	22
6.5 EUT OPERATION CONDITIONS.....	22
6.6 TEST RESULTS.....	22
7. POWER SPECTRAL DENSITY TEST.....	23
7.1 APPLIED PROCEDURES / LIMIT.....	23
7.2 TEST PROCEDURE.....	23
7.3 DEVIATION FROM STANDARD.....	23
7.4 TEST SETUP.....	23
7.5 EUT OPERATION CONDITIONS.....	23
7.6 TEST RESULTS.....	23
8. 6DB BANDWIDTH TEST.....	26
8.1 APPLIED PROCEDURES / LIMIT.....	26
8.2 TEST PROCEDURE.....	26
8.3 DEVIATION FROM STANDARD.....	26
8.4 TEST SETUP.....	26
8.5 EUT OPERATION CONDITIONS.....	26
8.6 TEST RESULTS.....	26
9. OUT OF BAND EMISSIONS TEST.....	27
9.1 APPLIED PROCEDURES / LIMIT.....	29
9.2 TEST PROCEDURE.....	29
9.3 DEVIATION FROM STANDARD.....	29
9.4 TEST SETUP.....	29
9.5 EUT OPERATION CONDITIONS.....	29
9.6 TEST RESULTS.....	29
10. SPURIOUS RF CONDUCTED EMISSION.....	31
10.1 APPLIED PROCEDURES / LIMIT.....	31
10.2 TEST PROCEDURE.....	31



Table of Contents	Page
10.3 DEVIATION FROM STANDARD.....	31
10.4 TEST SETUP.....	31
10.5 EUT OPERATION CONDITIONS.....	31
10.6 TEST RESULTS.....	32
11. ANTENNA REQUIREMENT.....	35
11.1 STANDARD REQUIREMENT.....	35
11.2 EUT ANTENNA.....	35
12. TEST SEUUP PHOTO.....	36



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.247(c)	Radiated Spurious Emission	PASS	
15.205	Band Edge Emission	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(2)	6dB Bandwidth	PASS	
15.247(e)	Power Spectral Density	PASS	
15.247(d)	Band edge measurements	PASS	
15.247(d)	Conducted Spurious Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

1.2 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add.: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: CN0118



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	MP3
Trademark:	N/A
Model No.:	Q8
Sample No.:	DL-20220225016 #1
Operation Frequency:	2402~2480 MHz
Channel Numbers:	40 Channels for BLE
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna Gain:	0 dBi
Power Supply:	DC 3.7V Battery

Note:

1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.The EUT's all information provided by client.

3.Channel List

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480




2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Low Channel	2402MHz
Middle Channel	2440MHz
High Channel	2480MHz

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
1	Notebook	Lenovo G475	GB14477457	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note: For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Max output power Setting		
Test software Version	Test Program: RTL8762x_RF Test Tool	/



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Dec. 06, 2021	Dec. 05, 2022
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Dec. 06, 2021	Dec. 05, 2022
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Dec. 06, 2021	Dec. 05, 2022
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Dec. 06, 2021	Dec. 05, 2022
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Dec. 06, 2021	Dec. 05, 2022
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Dec. 06, 2021	Dec. 05, 2022
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Dec. 06, 2021	Dec. 05, 2022
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Dec. 06, 2021	Dec. 05, 2022
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Dec. 06, 2021	Dec. 05, 2022
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Dec. 06, 2021	Dec. 05, 2022
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Dec. 06, 2021	Dec. 05, 2022
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Dec. 06, 2021	Dec. 05, 2022
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Dec. 06, 2021	Dec. 05, 2022
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Dec. 06, 2021	Dec. 05, 2022
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Dec. 06, 2021	Dec. 05, 2022
16	D.C. Power Supply	LongWei	PS-305D	010964729	Dec. 06, 2021	Dec. 05, 2022

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 25, 2019	Nov. 24, 2022
2	EMI Receiver	R&S	ESR	101421	Dec. 06, 2021	Dec. 05, 2022
3	LISN	Schwarzbeck	NNLK 8128	5089	Dec. 06, 2021	Dec. 05, 2022
4	843 Cable 1#	ChengYu	CE Cable	001	Dec. 06, 2021	Dec. 05, 2022

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	e3	EMC32	e3 190613(V9)
2	EMC radiation test system	e3	EMC32	e3 190613(V9)
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.2 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.4 DEVIATION FROM TEST STANDARD

No deviation

3.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


3.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.7 TEST RESULTS




Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz		



	Freq	Level	Limit	Over	
	MHz	dBuV	Line	Limit	Remark
			dBuV	dB	
1	0.476	26.96	46.41	-19.45	Average
2	0.476	35.62	56.41	-20.79	QP
3	0.535	26.89	46.00	-19.11	Average
4	0.535	35.62	56.00	-20.38	QP
5	0.627	26.43	46.00	-19.57	Average
6	0.627	34.96	56.00	-21.04	QP
7	0.775	28.74	46.00	-17.26	Average
8	0.775	35.41	56.00	-20.59	QP
9	1.027	25.34	46.00	-20.66	Average
10	1.027	34.76	56.00	-21.24	QP
11	1.381	25.13	46.00	-20.87	Average
12	1.381	33.62	56.00	-22.38	QP



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



	Freq	Level	Limit	Over	
	MHz	dBuV	Line	Limit	Remark
			dBuV	dB	
1	0.408	28.20	47.68	-19.48	Average
2	0.408	37.59	57.68	-20.09	QP
3	0.524	28.74	46.00	-17.26	Average
4	0.524	39.63	56.00	-16.37	QP
5	0.614	28.78	46.00	-17.22	Average
6	0.614	40.26	56.00	-15.74	QP
7	0.775	29.19	46.00	-16.81	Average
8	0.775	37.62	56.00	-18.38	QP
9	0.918	27.07	46.00	-18.93	Average
10	0.918	37.53	56.00	-18.47	QP
11	1.519	25.56	46.00	-20.44	Average
12	1.519	33.69	56.00	-22.31	QP



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



4.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.3 DEVIATION FROM TEST STANDARD


No deviation

4.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS


Note: 1. All modes were tested at Low, Middle, and High channel, only the worst result of GFSK Low Channel was reported.

2. By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.



Below 1GHz Test Results

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 3.7V		
Test Mode :	Transmitting mode of GFSK 2402MHz		



		Preamp	Read	CableAntenna			Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	34.85	31.38	46.58	0.56	15.94	31.70	40.00	-8.30	QP
2	59.10	31.35	55.21	0.75	7.44	32.05	40.00	-7.95	QP
3 !	131.85	31.20	61.58	1.12	8.32	39.82	43.50	-3.68	QP
4 !	141.55	31.22	59.40	1.22	8.49	37.89	43.50	-5.61	QP
5 !	151.25	31.25	59.18	1.22	9.02	38.17	43.50	-5.33	QP
6 !	158.04	31.23	59.21	1.30	9.16	38.44	43.50	-5.06	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 3.7V		
Test Mode :	Transmitting mode of GFSK 2402MHz		



		Preamp	Read	CableAntenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB
1 !	125.06	31.22	60.17	1.12	8.40	38.47	43.50	-5.03 QP
2 !	131.85	31.20	60.47	1.12	8.32	38.71	43.50	-4.79 QP
3	138.64	31.21	57.45	1.22	8.39	35.85	43.50	-7.65 QP
4	289.96	30.93	51.56	1.87	13.48	35.98	46.00	-10.02 QP
5	299.66	30.92	48.00	1.94	13.79	32.81	46.00	-13.19 QP
6	342.34	30.70	45.58	2.10	15.19	32.17	46.00	-13.83 QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Above 1GHz Test Results

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	4804.00	62.19	51.74	3.08	31.25	44.78	74.00	-29.22	PK
V	4804.00	46.24	51.74	3.08	31.25	28.83	54.00	-25.17	AV
V	7206.00	69.27	49.98	7.16	36.63	63.08	74.00	-10.92	PK
V	7206.00	53.40	49.98	7.16	36.63	47.21	54.00	-6.79	AV
V	16086.00	49.22	51.53	11.34	41.52	50.55	74.00	-23.45	PK
H	4804.00	62.19	51.74	3.08	31.25	44.78	74.00	-29.22	PK
H	4804.00	46.24	51.74	3.08	31.25	28.83	54.00	-25.17	AV
H	7206.00	67.51	49.98	7.16	36.63	61.32	74.00	-12.68	PK
H	7206.00	53.44	49.98	7.16	36.63	47.25	54.00	-6.75	AV
H	16086.00	49.18	51.53	11.34	41.52	50.51	74.00	-23.49	PK
operation frequency:2440									
V	4880.00	61.42	51.77	3.03	31.34	44.02	74.00	-29.98	PK
V	4880.00	45.60	51.77	3.03	31.34	28.20	54.00	-25.80	AV
V	7320.00	69.47	50.02	7.24	36.63	63.32	74.00	-10.68	PK
V	7320.00	53.50	50.02	7.24	36.63	47.35	54.00	-6.65	AV
V	16087.00	48.85	51.53	11.34	41.52	50.18	74.00	-23.82	PK
H	4880.00	61.42	51.77	3.03	31.34	44.02	74.00	-29.98	PK
H	4880.00	45.60	51.77	3.03	31.34	28.20	54.00	-25.80	AV
H	7320.00	69.56	50.02	7.24	36.63	63.41	74.00	-10.59	PK
H	7320.00	53.61	50.02	7.24	36.63	47.46	54.00	-6.54	AV
H	16087.00	48.81	51.53	11.34	41.52	50.14	74.00	-23.86	PK
operation frequency:2480									
V	4960.00	62.18	51.69	3.05	31.39	44.93	74.00	-29.07	PK
V	4960.00	46.22	51.69	3.05	31.39	28.97	54.00	-25.03	AV
V	7440.00	69.26	50.11	7.25	36.58	62.98	74.00	-11.02	PK
V	7440.00	53.39	50.11	7.25	36.58	47.11	54.00	-6.89	AV
V	16087.00	49.20	51.53	11.34	41.52	50.53	74.00	-23.47	PK
H	4960.00	62.18	51.69	3.05	31.39	44.93	74.00	-29.07	PK
H	4960.00	46.22	51.69	3.05	31.39	28.97	54.00	-25.03	AV
H	7440.00	67.49	50.11	7.25	36.58	61.21	74.00	-12.79	PK
H	7440.00	54.42	50.11	7.25	36.58	48.14	54.00	-5.86	AV
H	16087.00	49.16	51.53	11.34	41.52	50.49	74.00	-23.51	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-Amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	76.55	52.12	2.73	27.38	54.54	74	-19.46	PK
V	2390.00	65.24	52.12	2.73	27.38	43.23	54	-10.77	AV
V	2400.00	76.68	52.16	2.78	27.41	54.71	74	-19.29	PK
V	2400.00	64.01	52.16	2.78	27.41	42.04	54	-11.96	AV
H	2390.00	76.38	52.12	2.73	27.38	54.37	74	-19.63	PK
H	2390.00	64.92	52.12	2.73	27.38	42.91	54	-11.09	AV
H	2400.00	76.22	52.16	2.78	27.41	54.25	74	-19.75	PK
H	2400.00	65.09	52.16	2.78	27.41	43.12	54	-10.88	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	76.33	52.23	2.86	27.44	54.4	74	-19.6	PK
V	2483.50	65.02	52.23	2.86	27.44	43.09	54	-10.91	AV
V	2500.00	75.97	52.26	2.88	27.49	54.08	74	-19.92	PK
V	2500.00	64.08	52.26	2.88	27.49	42.19	54	-11.81	AV
H	2483.50	76.48	52.23	2.86	27.44	54.55	74	-19.45	PK
H	2483.50	65.72	52.23	2.86	27.44	43.79	54	-10.21	AV
H	2500.00	76.45	52.26	2.88	27.49	54.56	74	-19.44	PK
H	2500.00	65.13	52.26	2.88	27.49	43.24	54	-10.76	AV

Remark:

1. Emission Level = Reading Level+Antenna Factor+Cable loss-Preamp Factor.
2. Over Limit= Absolute Level - Limit.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.
4. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation)



6. PEAK OUTPUT POWER

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.2 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

Test Mode	Channel	Peak Power[dBm]	Conducted Limit[dBm]	Verdict
GFSK	2402	-1.98	≤30	PASS
	2440	-0.34	≤30	PASS
	2480	0.26	≤30	PASS



7. POWER SPECTRAL DENSITY TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 3kHz
VB	VBW $\geq$ 3RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP




7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

TestMode	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
GFSK	2402	-11.081	≤ 8	PASS
	2440	-9.400	≤ 8	PASS
	2480	-8.117	≤ 8	PASS





8. 6DB BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$	2400-2483.5	PASS

8.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

Test Mode	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
GFSK	2402	0.6995	0.5	PASS
	2440	0.6820	0.5	PASS
	2480	0.6925	0.5	PASS



BLE_Ant1_2402



BLE_Ant1_2440







9. OUT OF BAND EMISSIONS TEST

9.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

9.2 TEST PROCEDURE

1. Set RBW = 100kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS


Test Mode	ChName	Channel	Result[dB]	Limit[dB]	Verdict
GFSK	Low	2402	42.083	> 20	PASS
	High	2480	47.686	> 20	PASS



BLE_Ant1_Low_2402



BLE_Ant1_Low_2480





10. SPURIOUS RF CONDUCTED EMISSION

10.1 APPLIED PROCEDURES / LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.
3. For below 30MHz, For 9KHz-150kHz, 150K-10MHz, We use the RBW 1KHz, 10KHz, So the limit need to be calculated by " $10\lg(BW1/BW2)$ ". for example For 9KHz-150kHz, RBW 1KHz, The Limit = the highest emission level - $20 - 10\lg(100/1) =$ the highest emission level - 40.

10.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.

10.3 DEVIATION FROM STANDARD

No deviation.


10.4 TEST SETUP



10.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

10.6 TEST RESULTS





BLE Ant1 2440 0~Reference




BLE Ant1 2440 30~25000





BLE Ant1 2480 0~Reference



BLE Ant1 2480 30~25000





11. ANTENNA REQUIREMENT

11.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

11.2 EUT ANTENNA

The EUT antenna is PCB antenna,. It comply with the standard requirement.

12. TEST SEUUP PHOTO

Radiated Measurement Photos





Conducted Measurement Photos



***** END OF REPORT *****