

FCC ID: 2A4VYHJ-XKD09

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.429	2.77	5 \pm 1	6.00	3.98	<5	1.23400	3.00	YES
	2.44	4.879	3.08	5 \pm 1	6.00	3.98	<5	1.24373	3.00	YES
	2.480	4.029	2.53	5 \pm 1	6.00	3.98	<5	1.25388	3.00	YES
Pi/4 DQPSK	2.402	4.341	2.72	5 \pm 1	6.00	3.98	<5	1.23400	3.00	YES
	2.441	4.403	2.76	5 \pm 1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	3.592	2.29	4 \pm 1	5.00	3.16	<5	0.99599	3.00	YES

Conclusion:

For the max result : 1.25388W/Kg \leq FCC Limit 3.0 for 1g SAR.