



Wireless Water Leakage Alarm Operation Instructions




Please read this manual carefully before installation and use

• Full water sensing alarm.




Product Description




Install Battery


① Find the side opening position and open the bottom cover.




② Align the positive and negative directions respectively, and install 2 AAA batteries.



③ Find the corresponding position of the side opening and install the bottom cover back.




④ Test alarm.



Independent Alarm Usage Method


- Drip sensing alarm.



Pairing Wireless Receiver Host For Use

⚠ Host Receiving Wireless Frequency: 433.92MHz

① Operate the wireless receiver to enter pairing mode.
② Trigger the wireless water leakage alarm.



Specification Parameters

- Input voltage: 3V
- Static current: 10 μ A
- Alarm current: 100mA
- Alarm volume: \leq 100dB
- Wireless frequency: 433.92MHz
- Working temperature: -10°C - +50°C
- Battery: Two AAA batteries

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC warning:

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.
-Increase the separation between the equipment and receiver.
-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
-Consult the dealer or an experienced radio/TV technician for help.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.