



RF Exposure evaluation

Report Reference No.: **CTL2506252041-WFH**

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Tested by:
(position+printed name+signature)

Lynn Tang
(Test Engineer)

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)

Happy Guo
华检检测
Lynn Tang
Shenzhen CTL Testing Technology Co., Ltd.
Ivan Xie

Product Name: Water Leakage Detector

Model/Type reference: SQ400C

List Model(s): SQ100C, SQ500C, SQ600C, SQ200C

Trade Mark: N/A

FCC ID: **2A53H-SQ400C**

Applicant's name: **Dongguan Daying Electronics Technology Co., LTD**

Address of applicant: 5th Floor, D, Futai High-Tech Park, No.8 Qingfeng South Road, Tangxia Town, Dongguan City China

Test Firm: **Shenzhen CTL Testing Technology Co., Ltd.**

Address of Test Firm: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

Test specification:

47CFR §1.1310

Standard: **47CFR §2.1091**

KDB447498 D01 General RF Exposure Guidance v06

TRF Originator: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF: Dated 2017-01

Date of receipt of test item: Jul. 17, 2025

Date of Test: Jul. 18, 2025 - Jul. 31, 2025

Date of Issue: Aug. 04, 2025

Result: **Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2506252041-WFH	Aug. 04, 2025
		Date of issue

Product Name : Water Leakage Detector

Sample No : CTL250625204004

Model /Type : SQ400C

Listed Models : SQ100C, SQ500C, SQ600C, SQ200C

Applicant : Dongguan Daying Electronics Technology Co.,LTD

Address : 5th Floor, D, Futai High-Tech Park, No.8 Qingfeng South Road,Tangxia Town, Dongguan City China

Manufacturer : Dongguan Daying Electronics Technology Co.,LTD

Address : 5th Floor, D, Futai High-Tech Park, No.8 Qingfeng South Road,Tangxia Town, Dongguan City China

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

Contents

1 GENERAL INFORMATION	5
1.1 ENVIRONMENTAL CONDITIONS	5
1.2 PRODUCT DESCRIPTION	5
1.3 TEST FACILITY	6
1.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
2 METHOD OF MEASUREMENT	7
2.1 APPLICABLE STANDARD	7
2.2 EVALUATION METHOD AND LIMIT	7
3 CONDUCTED POWER RESULTS	9
4 MANUFACTURING TOLERANCE	10
5 EVALUATION RESULTS	11
5.1 STANDALONE EVALUATION	11
6 CONCLUSION	11

1 GENERAL INFORMATION

1.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C -35°C
Relative Humidity:	35%-55 %
Air Pressure:	101 KPa

1.2 Product Description

Product Name:	Water Leakage Detector
Model/Type reference:	SQ400C
Power supply:	DC 2x1.5V (AAA*2)
Working voltage:	DC 2x1.5V (AAA*2)

Bluetooth Low Energy

Supported type:	Bluetooth Low Energy
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB Antenna
Antenna gain:	-0.23dBi

2.4G Wi-Fi

Supported type:	802.11b/802.11g/802.11n(H20)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11
Channel separation:	802.11b/802.11g/802.11n(H20)
Antenna type:	PCB Antenna
Antenna gain:	-0.23dBi

Note 1: For more details, refer to the user's manual of the EUT.

Note 2: Antenna gain and cable loss provided by the applicant.

Note3: This report is for 2.4G Wi-Fi only.

1.3 Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832.

1.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	±2.20 dB	(1)

Note 1: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

2 METHOD OF MEASUREMENT

2.1 Applicable Standard

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

2.2 Evaluation Method and Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3 Conducted Power Results

Bluetooth Low Energy

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
1M	2402	-0.64
	2440	0.07
	2480	0.66

2.4G WiFi

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	2412	15.20
	2437	14.49
	2462	15.47
802.11g	2412	14.54
	2437	14.15
	2462	14.57
802.11n (HT20)	2412	15.77
	2437	15.39
	2462	16.24

4 Manufacturing Tolerance

Bluetooth Low Energy

GFSK (Peak)			
Frequency	2402	2440	2480
Target (dBm)	-1.0	0.0	1.0
Tolerance \pm (dB)	1.0	1.0	1.0

2.4G WiFi

11B (Peak)

Channel	2412MHz	2437MHz	2462MHz
Target (dBm)	15.0	15.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0

11G (Peak)

Channel	2412MHz	2437MHz	2462MHz
Target (dBm)	15.0	14.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0

11N20 (Peak)

Channel	2412MHz	2437MHz	2462MHz
Target (dBm)	16.0	15.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0

5 Evaluation Results

5.1 Standalone Evaluation

Bluetooth Low Energy

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	Result	SAR Test Exclusion
			dBm	mW			
1M	2.402	20	0	1.00	0.9484	0.0002 <1.0	Yes
	2.440	20	1	1.26	0.9484	0.0002 <1.0	Yes
	2.480	20	2	1.58	0.9484	0.0003 <1.0	Yes

2.4G WiFi

Mode	f (GHz)	Antenna Distance (cm)	RF output power		G (Num.)	Result	SAR Test Exclusion
			dBm	mW			
802.11b	2.412	20	16	39.81	0.9484	0.0075 <1.0	Yes
	2.437	20	16	39.81	0.9484	0.0075 <1.0	Yes
	2.462	20	16	39.81	0.9484	0.0075 <1.0	Yes
802.11g	2.412	20	16	39.81	0.9484	0.0075 <1.0	Yes
	2.437	20	15	31.62	0.9484	0.0060 <1.0	Yes
	2.462	20	16	39.81	0.9484	0.0075 <1.0	Yes
802.11n (HT20)	2.412	20	17	50.12	0.9484	0.0095 <1.0	Yes
	2.437	20	16	39.81	0.9484	0.0075 <1.0	Yes
	2.462	20	17	50.12	0.9484	0.0095 <1.0	Yes

Simultaneous Transmission MPE:

$$0.0003/1 + 0.0075/1 + 0.0075/1 + 0.0075/1 = 0.0228 < 1.0$$

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is $\geq 20\text{cm}$, In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091

6 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

*****THE END*****