

RF Exposure evaluation

FCC ID: 2A553-XC-AX3000

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

XC-AX3000 can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
Bluetooth	/	External Antenna	2.0dBi for 2402-2480MHz;	
5GWIFI	/	External Antenna	4.2dBi for 5150-5250MHz for Ant1&2	
			4.2dBi for 5725-5875MHz for Ant1&2	

5. Manufacturing Tolerance

BT GFSK(Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance ±(dB)	1.0	1.0	1.0
BT Π/4DQPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	2.0	2.0	2.0
Tolerance ±(dB)	1.0	1.0	1.0
BT 8DPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	2.0	2.0	2.0
Tolerance ±(dB)	1.0	1.0	1.0
BLE GFSK(Peak)			
Channel	Channel 00	Channel 19	Channel 39
Target (dBm)	2.0	2.0	2.0
Tolerance ±(dB)	1.0	1.0	1.0

[5.2GHz WLAN] ANT 1

IEEE 802.11A (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	9.0	/	9.0
Tolerance ± (dB)	1.0	/	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	9.0	/	9.0
Tolerance ± (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5210	/
Target (dBm)	/	9.0	/
Tolerance ± (dB)	/	1.0	/

[5.2GHz WLAN] ANT 2

IEEE 802.11A (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	10.0	10.0	10.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	9.0	/	9.0

Tolerance ± (dB)	1.0	/	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	9.0	/	9.0
Tolerance ± (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5210	/
Target (dBm)	/	9.0	/
Tolerance ± (dB)	/	1.0	/

[5.8GHz WLAN] ANT1

IEEE 802.11A (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	8.0	/	8.0
Tolerance ± (dB)	1.0	/	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	8.0	/	8.0
Tolerance ± (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5775	/
Target (dBm)	/	8.0	/
Tolerance ± (dB)	/	1.0	/

[5.8GHz WLAN] ANT2

IEEE 802.11A (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	8.0	8.0	8.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n20 (Average)			

Frequency (MHz)	5745	5785	5825
Target (dBm)	8.0	8.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	8.0	8.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	8.0	/	8.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	8.0	/	8.0
Tolerance $\pm$ (dB)	1.0	/	1.0
IEEE 802.11ac80 (Average)			
Frequency (MHz)	/	5775	/
Target (dBm)	/	8.0	/
Tolerance $\pm$ (dB)	/	1.0	/

6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna is 0.0dBi, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT	3.0	1.9953	2.0	1.5849	0.0006	1.0000
5.2GWIFI ANT1	11.0	12.5893	2.0	1.5849	0.0040	1.0000
5.2GWIFI ANT1	11.0	12.5893	2.0	1.5849	0.0040	1.0000
5.8GWIFI ANT1	10.0	10.0000	2.0	1.5849	0.0032	1.0000
5.8GWIFI ANT1	10.0	10.0000	2.0	1.5849	0.0032	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7. simultaneous MPE Result

ANT1 MPE (Ratio)	ANT2 MPE (Ratio)	simultaneous MPE (Ratio)	MPE Limits (Ratio)
0.0040	0.0040	0.008	1.0000

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----