

TEST REPORT

Product Name: Carplay ai box
FCC ID: 2A5C8-MK665
Trademark: iHeylinkit
Model Number: MK665, CP450, CP480, MK610, MK808, MK550
Prepared For: Shenzhen Xinhai Vision Technology Co., Ltd.
Address: 1608 TOWER A Zhantao Technology Building, 1079 Minzhi Rd, Longhua, Shenzhen, China. 518131
Manufacturer: Shenzhen Xinhai Vision Technology Co., Ltd.
Address: 1608 TOWER A Zhantao Technology Building, 1079 Minzhi Rd, Longhua, Shenzhen, China. 518131
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: Floor 1&2, Building A, No. 26 of Xinhe Road, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China.
Sample Received Date: Aug. 18, 2022
Sample tested Date: Aug. 18, 2022 to Sep. 05, 2022
Issue Date: Sep. 05, 2022
Report No.: CTB220905037RFX
Test Standards: FCC Part 2, 22, 24E, 27
Test Results: PASS
Remark: This is LTE radio test report.

Compiled by:

Chen Zheng

Reviewed by:

Arron Liu

Approved by:

Bin Mei Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. “*” indicates the testing items were fulfilled by subcontracted lab. “#” indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION	3
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION AND TEST SETUP	6
4.1 Product Information	6
4.2 Test Setup Configuration	7
4.3 Support Equipment	7
4.4 Test Mode	7
4.5 Test Environment	7
5. TEST FACILITY AND TEST INSTRUMENT USED	8
5.1 Test Facility	8
5.2 Test Instrument Used	8
6. RF EXPOSURE	10
6.1 Standard Applicable	10
6.2 Test Result	10
7. RF OUTPUT POWER	11
7.1 Standard Applicable	11
7.2 Test Procedure	11
7.3 Summary of Test Results/Plots	12
8. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER	24
8.1 Standard Applicable	24
8.2 Test Procedure	24
8.3 Summary of Test Results	24
9. EMISSION BANDWIDTH	25
9.1 Standard Applicable	25
9.2 Test Procedure	25
9.3 Summary of Test Results/Plots	25
10. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL	26
10.1 Standard Applicable	26
10.2 Test Procedure	26
10.3 Summary of Test Results/Plots	27
11. SPURIOUS RADIATED EMISSIONS	28
11.1 Standard Applicable	28
11.2 Test Procedure	29
11.3 Summary of Test Results/Plots	29
12. FREQUENCY STABILITY	36
12.1 Standard Applicable	36
12.2 Test Procedure	36
12.3 Summary of Test Results/Plots	36

(Note: N/A means not applicable)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB220905037RFX	Sep. 05, 2022	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
Conducted output power	Part 2.1046(a)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
Effective Radiated Power of Transmitter(EIRP)	Part 22.913(a)(5)/Part27.50(h)(2)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
peak-to-average ratio	Part 27.50(d)	KDB 971168 D01v03r01	PASS
99% & 26dB Occupied Bandwidth	Part 2.1049(h)	KDB 971168 D01v03r01	PASS
Band Edge at antenna terminals	Part 2.1051/ Part 22.917(a)/Part 27.53(m) (4)	KDB 971168 D01v03r01	PASS
Spurious emissions at antenna terminals	Part 2.1051/ Part 22.917(a)/Part 27.53(m) (4)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
Field strength of spurious radiation	Part 2.1053/ Part 22.917(a)/Part 27.53(m) (4)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
Frequency stability	Part 2.1055/Part 27.54	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m chamber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Receiver Reference Sensitivity level	1.9dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63°C
frequency	1×10-7

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	MK665, CP450, CP480, MK610, MK808, MK550
Model Description:	All the model are the same circuit and RF module, only for model name. Test sample model: MK665
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	FDD-LTE BAND 2:1850-1910MHz FDD-LTE BAND 4:1710-1755MHz FDD-LTE BAND 5:824-849MHz FDD-LTE BAND 7:2500-2570MHz TDD-LTE BAND 12: 699-716MHz TDD-LTE BAND 17: 704-716MHz TDD-LTE BAND 41: 2555-2655MHz
Max. RF output power:	FDD-LTE BAND 2: 21.94 dBm FDD-LTE BAND 4: 22.85dBm FDD-LTE BAND 5: 22.48dBm FDD-LTE BAND 7: 22.55dBm TDD-LTE BAND 12: 21.77dBm TDD-LTE BAND 17: 21.72dBm TDD-LTE BAND 41: 22.31dBm
Type of Modulation:	QPSK, 16QAM
Antenna installation:	Internal antenna
Antenna Gain:	FDD-LTE BAND 2:2dBi FDD-LTE BAND 4:2dBi FDD-LTE BAND 5: 2dBi FDD-LTE BAND 7: 2dBi TDD-LTE BAND 12:2dBi TDD-LTE BAND 17:2dBi TDD-LTE BAND 41:2dBi
Ratings:	DC 5V charging from adapter

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
1	Adapter	JIYIN	JY-05100C	/	AE

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

Test Mode List		
Test Mode	Description	Remark
TM1	FDD-LTE BAND 2	Low, Middle, High Channels
TM2	FDD-LTE BAND 4	Low, Middle, High Channels
TM3	TDD-LTE BAND 5	Low, Middle, High Channels
TM4	TDD-LTE BAND 7	Low, Middle, High Channels
TM5	TDD-LTE BAND 12	Low, Middle, High Channels
TM6	TDD-LTE BAND 17	Low, Middle, High Channels
TM7	TDD-LTE BAND 41	Low, Middle, High Channels

4.5 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):	5V
Normal Temperature(°C)	23
Low Temperature(°C)	0
High Temperature(°C)	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Floor 1&2, Building A, No. 26 of Xinhe Road, Xinqiao Street, Baoan District, Shenzhen China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

Item	Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	2023.07.19
2	Power Sensor	Agilent	U2021XA	MY56120032	2023.07.19
3	Power Sensor	Agilent	U2021XA	MY56120034	2023.07.19
4	Communication test set	R&S	CMW500	108058	2023.07.19
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	2023.07.19
6	Signal Generator	Agilent	N5181A	MY50140365	2023.07.19
7	Vector signal generator	Agilent	N5182A	MY47420195	2023.07.19
8	Communication test set	Agilent	E5515C	MY50102567	2023.07.19
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	2023.07.19
10	5 GHz Filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	2023.07.19
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	2023.07.19
12	BT&WI-FI Automatic test software	Microwave	MTS8000	Ver. 2.0.0.0	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	2022.10.30
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	2023.07.19
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/
16	966 chamber	C.R.T.	966	/	2024.08.11
17	Receiver	R&S	ESPI	100362	2023.07.19
18	Amplifier	HP	8447E	2945A02747	2023.07.19
19	Amplifier	Agilent	8449B	3008A01838	2023.07.19
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	2023.07.22
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	2023.07.22

22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	2023.07.23
24	loop antenna	ZHINAN	ZN30900A	GTS534	/
25	40G Horn antenna	A/H/System	SAS-574	588	2024.10.30
26	Amplifier	AEROFLEX	Aeroflex	097	2024.10.30

6. RF EXPOSURE

6.1 Standard Applicable

According to §1.1307 and §2.1091, §2.1093, the portable transmitter must comply the RF exposure requirements.

6.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure report.

7. RF OUTPUT POWER

7.1 Standard Applicable

According to §22.913(a)(2), the ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

According to §27.50(c)(10), portable stations (hand-held devices) in the 698-746 MHz band are limited to 3 watts ERP.

7.2 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

7.3 Summary of Test Results/Plots

Max. Radiated Power:
FDD-LTE Band 2

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.43	<33	PASS
		H	21.07		PASS
	MCH	V	21.83		PASS
		H	21.65		PASS
	HCH	V	21.53		PASS
		H	20.53		PASS
16QAM	LCH	V	21.39	<33	PASS
		H	20.98		PASS
	MCH	V	21.39		PASS
		H	20.53		PASS
	HCH	V	21.90		PASS
		H	20.44		PASS
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.55	<33	PASS
		H	20.20		PASS
	MCH	V	19.95		PASS
		H	20.09		PASS
	HCH	V	20.45		PASS
		H	19.31		PASS
16QAM	LCH	V	20.50	<33	PASS
		H	20.17		PASS
	MCH	V	19.22		PASS
		H	19.60		PASS
	HCH	V	18.95		PASS
		H	20.48		PASS
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.86	<33	PASS
		H	19.35		PASS
	MCH	V	18.99		PASS
		H	19.55		PASS

	HCH	V	19.06	<33	PASS
		H	19.29		
16QAM	LCH	V	19.90	<33	PASS
		H	18.96		PASS
	MCH	V	20.24		PASS
		H	20.12		PASS
	HCH	V	19.28		PASS
		H	19.08		PASS
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.23	<33	PASS
		H	19.28		PASS
	MCH	V	20.41		PASS
		H	20.31		PASS
	HCH	V	19.15		PASS
		H	19.75		PASS
16QAM	LCH	V	20.36	<33	PASS
		H	20.39		PASS
	MCH	V	20.03		PASS
		H	19.16		PASS
	HCH	V	20.95		PASS
Channel Bandwidth: 15 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.87	<33	PASS
		H	20.04		PASS
	MCH	V	18.68		PASS
		H	19.04		PASS
	HCH	V	19.48		PASS
		H	19.40		PASS
16QAM	LCH	V	20.00	<33	PASS
		H	20.08		PASS
	MCH	V	19.19		PASS
		H	18.51		PASS
	HCH	V	18.86		PASS
		H	20.12		PASS

Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.67	<33	PASS
		H	21.41		PASS
	MCH	V	20.59		PASS
		H	21.89		PASS
	HCH	V	21.12		PASS
		H	20.40		PASS
16QAM	LCH	V	20.67	<33	PASS
		H	20.86		PASS
	MCH	V	21.94		PASS
		H	21.86		PASS
	HCH	V	20.43		PASS
		H	21.51		PASS

FDD-LTE Band 4

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.39	<34.77	PASS
		H	21.51		PASS
	MCH	V	21.50		PASS
		H	22.21		PASS
	HCH	V	21.72		PASS
		H	22.33		PASS
16QAM	LCH	V	21.38	<34.77	PASS
		H	22.05		PASS
	MCH	V	21.52		PASS
		H	22.45		PASS
	HCH	V	21.34		PASS
		H	20.80		PASS

Channel Bandwidth: 3 MHz

Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.48	<34.77	PASS
		H	21.66		PASS
	MCH	V	22.35		PASS
		H	21.14		PASS
	HCH	V	22.84		PASS

		H	22.17		
16QAM	LCH	V	21.72	<34.77	PASS
		H	20.93		PASS
	MCH	V	22.77		PASS
		H	22.44		PASS
	HCH	V	21.54		PASS
		H	21.59		PASS
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.09	<34.77	PASS
		H	20.92		PASS
	MCH	V	21.67		PASS
		H	20.86		PASS
	HCH	V	20.45		PASS
		H	21.00		PASS
16QAM	LCH	V	21.41	<34.77	PASS
		H	21.35		PASS
	MCH	V	21.16		PASS
		H	20.75		PASS
	HCH	V	22.19		PASS
		H	20.54		PASS
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.26	<34.77	PASS
		H	20.74		PASS
	MCH	V	20.74		PASS
		H	20.24		PASS
	HCH	V	20.34		PASS
		H	21.90		PASS
16QAM	LCH	V	20.40	<34.77	PASS
		H	21.50		PASS
	MCH	V	21.11		PASS
		H	21.86		PASS
	HCH	V	21.33		PASS

Channel Bandwidth: 15 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.37	<34.77	PASS
		H	22.08		PASS
	MCH	V	20.48		PASS
		H	22.02		PASS
	HCH	V	20.40		PASS
		H	20.43		PASS
16QAM	LCH	V	21.39	<34.77	PASS
		H	20.43		PASS
	MCH	V	21.87		PASS
		H	20.44		PASS
	HCH	V	20.74		PASS

Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.65	<34.77	PASS
		H	22.68		PASS
	MCH	V	21.77		PASS
		H	22.61		PASS
	HCH	V	22.62		PASS
		H	21.76		PASS
16QAM	LCH	V	21.10	<34.77	PASS
		H	21.65		PASS
	MCH	V	22.85		PASS
		H	22.32		PASS
	HCH	V	20.90		PASS

FDD-LTE Band 5

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.52	<38.45	PASS
		H	20.57		PASS
	MCH	V	20.42		PASS
		H	21.00		PASS
	HCH	V	20.76		PASS
		H	20.18		PASS
16QAM	LCH	V	20.39	<38.45	PASS

Modulation	MCH	H	20.95	Limit (dBm) <38.45	PASS
		V	21.38		
		H	20.03		
	HCH	V	21.10		PASS
		H	20.21		
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.73	<38.45	PASS
		H	20.86		PASS
	MCH	V	20.97		PASS
		H	20.56		PASS
	HCH	V	20.56		PASS
		H	21.54		PASS
16QAM	LCH	V	20.44	<38.45	PASS
		H	20.57		PASS
	MCH	V	20.54		PASS
		H	20.95		PASS
	HCH	V	21.84		PASS
		H	21.30		PASS
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.54	<38.45	PASS
		H	20.54		PASS
	MCH	V	20.87		PASS
		H	20.85		PASS
	HCH	V	19.64		PASS
		H	20.85		PASS
16QAM	LCH	V	21.14	<38.45	PASS
		H	21.16		PASS
	MCH	V	19.53		PASS
		H	20.31		PASS
	HCH	V	19.44		PASS
		H	19.68		PASS
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.29	<38.45	PASS
		H	22.31		

16QAM	MCH	V	20.88	<38.45	PASS
		H	21.15		PASS
	HCH	V	21.05		PASS
		H	22.25		PASS
	LCH	V	22.44		PASS
		H	21.65		PASS
	MCH	V	22.48		PASS
		H	22.17		PASS
	HCH	V	20.84		PASS
		H	22.28		PASS

FDD-LTE Band 7

Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.40	<34.77	PASS
		H	20.09		PASS
	MCH	V	21.85		PASS
		H	20.54		PASS
	HCH	V	19.96		PASS
		H	20.08		PASS
16QAM	LCH	V	21.25	<34.77	PASS
		H	21.73		PASS
	MCH	V	21.50		PASS
		H	21.00		PASS
	HCH	V	20.99		PASS
		H	19.99		PASS
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.52	<34.77	PASS
		H	22.37		PASS
	MCH	V	21.05		PASS
		H	21.76		PASS
	HCH	V	21.35		PASS
		H	21.16		PASS
16QAM	LCH	V	22.09	<34.77	PASS
		H	22.41		PASS
	MCH	V	21.13		PASS
		H	22.81		PASS

	HCH	V	21.55		PASS
		H	21.91		

Channel Bandwidth: 15 MHz

Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.53	<34.77	PASS
		H	21.03		PASS
	MCH	V	22.29		PASS
		H	21.79		PASS
	HCH	V	22.14		PASS
		H	21.93		PASS
16QAM	LCH	V	21.14	<34.77	PASS
		H	21.55		PASS
	MCH	V	22.35		PASS
		H	21.57		PASS
	HCH	V	21.39		PASS
		H	20.86		PASS

Channel Bandwidth: 20 MHz

Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.96	<34.77	PASS
		H	22.12		PASS
	MCH	V	20.83		PASS
		H	22.75		PASS
	HCH	V	21.14		PASS
		H	20.86		PASS
16QAM	LCH	V	22.19	<34.77	PASS
		H	22.27		PASS
	MCH	V	21.47		PASS
		H	22.55		PASS
	HCH	V	21.70		PASS
		H	21.36		PASS

TDD-LTE Band 12

Channel Bandwidth: 1.4 MHz

Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.88	<34.77	PASS
		H	20.46		PASS

16QAM	MCH	V	21.49	<34.77	PASS
		H	20.46		PASS
	HCH	V	20.03		PASS
		H	20.82		PASS
	LCH	V	21.33	<34.77	PASS
		H	20.23		PASS
	MCH	V	20.47		PASS
		H	20.71		PASS
QPSK	HCH	V	20.82	<34.77	PASS
		H	21.75		PASS
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
16QAM	LCH	V	20.97	<34.77	PASS
		H	20.83		PASS
	MCH	V	19.82		PASS
		H	19.60		PASS
	HCH	V	19.87	<34.77	PASS
		H	20.64		PASS
	LCH	V	19.32		PASS
		H	20.07		PASS
QPSK	MCH	V	19.92	<34.77	PASS
		H	19.27		PASS
	HCH	V	20.84		PASS
		H	20.35		PASS
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
16QAM	LCH	V	20.22	<34.77	PASS
		H	19.33		PASS
	MCH	V	19.79		PASS
		H	20.24		PASS
	HCH	V	20.85	<34.77	PASS
		H	20.08		PASS
	LCH	V	19.57		PASS
		H	20.29		PASS
QPSK	MCH	V	20.24	<34.77	PASS
		H	19.96		PASS
	HCH	V	20.41		PASS

		H	20.55		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.48	<34.77	PASS
		H	21.37		PASS
	MCH	V	20.18		PASS
		H	19.65		PASS
	HCH	V	20.53		PASS
		H	20.68		
	LCH	V	20.26		PASS
		H	21.77		PASS
	MCH	V	19.62		PASS
		H	20.17		PASS
	HCH	V	19.59		

TDD-LTE Band 17

Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.92	<34.77	PASS
		H	20.30		PASS
	MCH	V	19.52		PASS
		H	20.91		PASS
	HCH	V	20.69		PASS
		H	21.30		
	LCH	V	20.04		PASS
		H	20.19		PASS
	MCH	V	20.69		PASS
		H	21.49		PASS
	HCH	V	19.62		
		H	20.66		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.47	<34.77	PASS
		H	20.76		PASS
	MCH	V	20.55		
		H	20.46		
	HCH	V	21.52		

		H	21.64		
16QAM	LCH	V	21.22	<34.77	PASS
		H	21.29		PASS
	MCH	V	20.25		PASS
		H	20.34		PASS
	HCH	V	21.68		PASS
		H	21.72		

TDD-LTE Band 41

Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.19	<34.77	PASS
		H	22.05		PASS
	MCH	V	20.46		PASS
		H	22.14		PASS
	HCH	V	21.30		PASS
		H	20.56		
16QAM	LCH	V	22.12	<34.77	PASS
		H	21.48		PASS
	MCH	V	20.78		PASS
		H	21.76		PASS
	HCH	V	20.65		
		H	20.78		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.40	<34.77	PASS
		H	21.48		PASS
	MCH	V	22.07		PASS
		H	21.14		PASS
	HCH	V	20.36		PASS
		H	21.06		
16QAM	LCH	V	20.57	<34.77	PASS
		H	21.37		PASS
	MCH	V	21.29		PASS
		H	21.88		PASS
	HCH	V	21.29		
		H	22.00		
Channel Bandwidth: 15 MHz					

Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.97	<34.77	PASS
		H	20.43		PASS
	MCH	V	21.35		PASS
		H	21.55		PASS
	HCH	V	20.77		PASS
		H	20.50		PASS
16QAM	LCH	V	20.34	<34.77	PASS
		H	20.53		PASS
	MCH	V	20.13		PASS
		H	21.68		PASS
	HCH	V	20.22		PASS
		H	21.31		PASS
Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.90	<34.77	PASS
		H	22.27		PASS
	MCH	V	21.02		PASS
		H	21.72		PASS
	HCH	V	22.19		PASS
		H	20.58		PASS
16QAM	LCH	V	22.31	<34.77	PASS
		H	21.40		PASS
	MCH	V	21.77		PASS
		H	20.73		PASS
	HCH	V	20.85		PASS
		H	20.82		PASS

Max. Conducted Output Power

Please refer to Appendix A: Average Power Output Data

Test result: Pass

8. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER

8.1 Standard Applicable

According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51, in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

8.2 Test Procedure

According with KDB 971168

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Configuration for the emission bandwidth testing:



8.3 Summary of Test Results

Please refer to Appendix B: Peak-to-Average Ratio

Test result: Pass

9. EMISSION BANDWIDTH

9.1 Standard Applicable

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


According to §24.238(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

9.2 Test Procedure

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Test Configuration for the emission bandwidth testing:



9.3 Summary of Test Results/Plots

Please refer to Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test result: Pass

10. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL

10.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

According to §27.53 (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

According to §27.53(h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.


According to §27.53(g), for operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.

According to §27.53(m)(4), for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.

10.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10 th harmonic.

Test Configuration for the out of band emissions testing:



10.3 Summary of Test Results/Plots

Please refer to Appendix D & E: Band Edge & Conducted Spurious Emission
Test result: Pass

11. SPURIOUS RADIATED EMISSIONS

11.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;
- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

According to §27.53 (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

According to §27.53(h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log(P)$ dB.

According to §27.53(g) the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.

11.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-E and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log 10$ (power out in Watts)

11.3 Summary of Test Results/Plots

Note: 1. this EUT was tested in 3 orthogonal positions and the worst case position data was reported.
2. All test modes (different bandwidth and different modulation) are performed, but only the worst case is recorded in this report.

QPSK

Band 7 20775 channel/BW 5(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1369.93	148	341	-56.17	-13	-44.67	Pass	H
1602.14	154	196	-46.66	-13	-34.41	Pass	H
3891.07	147	80	-50.63	-13	-36.9	Pass	H
5934.45	150	313	-44.08	-13	-33.07	Pass	H
6602.01	146	149	-44.78	-13	-31.79	Pass	H
8032.47	147	156	-38.63	-13	-28.84	Pass	H
1197.04	153	267	-54.72	-13	-41.24	Pass	V
1509.81	151	89	-54.41	-13	-43.57	Pass	V
3585.08	154	34	-47.02	-13	-37.85	Pass	V
3880.92	148	234	-51.11	-13	-38.46	Pass	V
5881.75	151	277	-43.72	-13	-32.52	Pass	V
6528.64	148	300	-49.30	-13	-35.32	Pass	V

Band 7 21100 channel/BW 5 (middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1353.26	147	137	-55.38	-13	-42.38	Pass	H
1735.39	147	145	-46.21	-13	-33.21	Pass	H
3897.32	145	291	-49.68	-13	-36.68	Pass	H
6015.36	149	197	-40.66	-13	-27.66	Pass	H
6433.06	145	210	-43.53	-13	-30.53	Pass	H
8105.90	147	243	-42.96	-13	-29.96	Pass	H
1149.21	151	357	-56.82	-13	-43.82	Pass	V
1440.99	150	40	-56.58	-13	-43.58	Pass	V
3565.55	148	207	-47.46	-13	-34.46	Pass	V
3834.64	150	219	-47.07	-13	-34.07	Pass	V
5819.83	150	96	-40.03	-13	-27.03	Pass	V
6472.52	149	238	-46.33	-13	-33.33	Pass	V

Band 7 21425 channel/BW 5 (highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1388.24	149	165	-50.97	-13	-37.97	Pass	H
1666.68	146	208	-50.81	-13	-37.81	Pass	H
3844.34	146	4	-46.79	-13	-33.79	Pass	H
5801.08	150	198	-40.80	-13	-27.80	Pass	H
6579.99	146	341	-42.00	-13	-29.00	Pass	H
8041.09	150	235	-41.59	-13	-28.59	Pass	H
1248.37	146	292	-54.43	-13	-41.43	Pass	V
1464.02	150	158	-55.43	-13	-42.43	Pass	V
3635.06	149	55	-46.68	-13	-33.68	Pass	V
3863.50	150	319	-49.99	-13	-36.99	Pass	V
5765.41	146	118	-48.06	-13	-35.06	Pass	V
6496.14	150	155	-50.80	-13	-37.80	Pass	V

16QAM

Band 7 20775 channel/BW 5 (lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1426.36	150	78	-57.84	-13	-44.84	Pass	H
1631.17	149	291	-55.30	-13	-42.30	Pass	H
3975.45	151	213	-48.47	-13	-35.47	Pass	H
5819.52	150	89	-48.25	-13	-35.25	Pass	H
6418.86	151	329	-50.44	-13	-37.44	Pass	H
8092.44	148	138	-46.82	-13	-33.82	Pass	H
1159.77	149	99	-60.53	-13	-47.53	Pass	V
1434.67	148	217	-58.14	-13	-45.14	Pass	V
3660.75	150	12	-52.55	-13	-39.55	Pass	V
3773.70	150	137	-49.54	-13	-36.54	Pass	V
5809.67	146	356	-43.86	-13	-30.86	Pass	V
6583.76	146	95	-45.99	-13	-32.99	Pass	V

Band 7 21100 channel/BW 5 (middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1308.34	150	142	-59.07	-13	-46.07	Pass	H
1753.39	146	280	-56.42	-13	-43.42	Pass	H
3781.21	150	330	-51.26	-13	-38.26	Pass	H
5787.74	146	194	-43.45	-13	-30.45	Pass	H
6378.46	149	260	-50.48	-13	-37.48	Pass	H
7989.06	151	31	-48.32	-13	-35.32	Pass	H
1213.03	149	4	-57.13	-13	-44.13	Pass	V
1447.46	148	257	-64.51	-13	-51.51	Pass	V
3677.69	147	55	-54.48	-13	-41.48	Pass	V
3878.89	148	273	-53.75	-13	-40.75	Pass	V
5915.20	150	136	-52.38	-13	-39.38	Pass	V
6431.67	150	16	-48.62	-13	-35.62	Pass	V

Band 7 21425 channel/BW 5 (highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1301.63	149	156	-57.19	-13	-44.19	Pass	H
1595.38	149	170	-53.16	-13	-40.16	Pass	H
3826.07	149	127	-49.65	-13	-36.65	Pass	H
5852.20	146	42	-42.68	-13	-29.68	Pass	H
6438.74	147	69	-42.29	-13	-29.29	Pass	H
7908.23	151	110	-46.23	-13	-33.23	Pass	H
1188.96	148	61	-56.70	-13	-43.70	Pass	V
1353.04	147	266	-56.28	-13	-43.28	Pass	V
3496.07	148	303	-52.38	-13	-39.38	Pass	V
3826.28	149	195	-43.06	-13	-30.06	Pass	V
5732.54	147	323	-43.79	-13	-30.79	Pass	V
6533.05	146	325	-46.81	-13	-33.81	Pass	V

QPSK

Band 5 20407 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1378.62	143	40	-57.15	-13	-44.15	Pass	H
1642.98	158	203	-49.50	-13	-36.50	Pass	H
3966.75	157	107	-48.30	-13	-35.30	Pass	H
5899.16	143	28	-43.25	-13	-30.25	Pass	H
6541.14	153	196	-44.61	-13	-31.61	Pass	H
8088.67	154	336	-46.18	-13	-33.18	Pass	H
1290.13	150	337	-54.07	-13	-41.07	Pass	V
1510.51	144	262	-56.88	-13	-43.88	Pass	V
3650.95	142	232	-54.75	-13	-41.75	Pass	V
3824.92	147	172	-46.29	-13	-33.29	Pass	V
5737.38	154	204	-45.04	-13	-32.04	Pass	V
6507.90	155	100	-47.05	-13	-34.05	Pass	V

Band 5 20525 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1289.19	150	174	-55.85	-13	-42.85	Pass	H
1737.85	146	171	-51.74	-13	-38.74	Pass	H
3970.63	150	26	-48.32	-13	-35.32	Pass	H
5903.19	146	178	-47.92	-13	-34.92	Pass	H
6406.97	149	35	-51.01	-13	-38.01	Pass	H
7982.60	151	222	-48.99	-13	-35.99	Pass	H
1270.21	149	188	-55.70	-13	-42.70	Pass	V
1315.89	148	237	-57.91	-13	-44.91	Pass	V
3515.62	147	183	-55.58	-13	-42.58	Pass	V
3959.18	148	98	-52.90	-13	-39.90	Pass	V
5876.84	150	92	-49.02	-13	-36.02	Pass	V
6528.02	150	13	-45.59	-13	-32.59	Pass	V

Band 5 20643 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1340.71	150	54	-56.73	-13	-43.73	Pass	H
1669.90	150	202	-52	-13	-39	Pass	H
3845.50	145	355	-45.66	-13	-32.66	Pass	H
5906.91	151	113	-40.96	-13	-27.96	Pass	H
6531.65	151	69	-42.47	-13	-29.47	Pass	H
8000.07	148	126	-44.74	-13	-31.74	Pass	H
1257.63	152	304	-56.49	-13	-43.49	Pass	V
1403.18	146	265	-56.84	-13	-43.84	Pass	V
3525.24	151	110	-52.79	-13	-39.79	Pass	V
3912.13	154	33	-48.59	-13	-35.59	Pass	V
5788.31	146	148	-43.05	-13	-30.05	Pass	V
6576.29	147	307	-47.76	-13	-34.76	Pass	V

16QAM

Band 5 20407 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1385.78	147	47	-56.86	-13	-43.86	Pass	H
1591.18	155	299	-47.56	-13	-34.56	Pass	H
3833.19	153	219	-46.98	-13	-33.98	Pass	H
5914.33	147	15	-45.06	-13	-32.06	Pass	H
6626.32	147	84	-41.30	-13	-28.30	Pass	H
7909.95	150	139	-42.02	-13	-29.02	Pass	H
1198.01	146	255	-52.24	-13	-39.24	Pass	V
1524.75	146	14	-55.90	-13	-42.90	Pass	V
3554.19	151	249	-52.95	-13	-39.95	Pass	V
3929.45	148	273	-53.42	-13	-40.42	Pass	V
5782.45	145	74	-47.94	-13	-34.94	Pass	V
6624.65	151	45	-48.80	-13	-35.80	Pass	V

Band 5 20525 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1391.37	149	76	-56.40	-13	-41.45	Pass	H
1794.54	155	322	-47.56	-13	-37.85	Pass	H
3769.76	147	68	-46.66	-13	-35.2	Pass	H
5990.97	150	151	-43.11	-13	-30.39	Pass	H
6538.90	150	6	-44.11	-13	-32.24	Pass	H
8027.54	146	338	-41.23	-13	-30.22	Pass	H
1263.03	149	300	-57.93	-13	-44.9	Pass	V
1296.85	155	165	-53.59	-13	-43.63	Pass	V
3572.81	145	35	-50.68	-13	-35.94	Pass	V
3825.91	152	171	-49.81	-13	-36.01	Pass	V
5782.08	150	342	-47.15	-13	-33.75	Pass	V
6468.65	154	312	-44.23	-13	-32.41	Pass	V

Band 5 20643 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1408.62	153	126	-58.48	-13	-45.48	Pass	H
1682.02	148	192	-50.94	-13	-37.94	Pass	H
3908.96	148	329	-43.01	-13	-30.01	Pass	H
5926.56	151	262	-42.75	-13	-29.75	Pass	H
6588.86	155	123	-38.44	-13	-25.44	Pass	H
8047.96	151	307	-47.28	-13	-34.28	Pass	H
1149.91	152	274	-52.00	-13	-39.00	Pass	V
1492.00	145	100	-55.26	-13	-42.26	Pass	V
3455.60	150	222	-53.17	-13	-40.17	Pass	V
3871.95	152	316	-48.05	-13	-35.05	Pass	V
5813.58	150	129	-49.65	-13	-36.65	Pass	V
6530.86	150	251	-44.04	-13	-31.04	Pass	V

Note:

- 1) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 1GHz are attenuated more than 20 dB below the applicable limit and not required to be reported, the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 2) Tested with all kind of bandwidth, RB Size and RB Offset, Found the 1.4MHz with full RB were the worst case; and then Only the worst case is recorded in the report.

12. FREQUENCY STABILITY

12.1 Standard Applicable

According to §22.355, §24.235, §27.54 the limit is 2.5ppm.

12.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

12.3 Summary of Test Results/Plots

Note: 1. Normal Voltage NV=DC5V; Low Voltage LV=DC4.5; High Voltage HV=DC5.5V

Please refer to Appendix F: Frequency Stability

Test result: Pass

***** END OF REPORT *****