

**FCC RF - TEST REPORT**

Report Number	:	68.950.22.0095.01	Date of Issue:	2022-04-25
Model	:	SGCNW A0, SB911194, SB913877, SB913716, SB914867, PNSWPHCWL		
FCC ID	:	2A5E9414502		
Product Type	:	WIRELESS GAMING CONTROLLER		
Applicant	:	snakebyte distribution GmbH		
Address	:	Konrad-Zuse-Str.13, 58239 Schwerte, GERMANY		
Manufacturer	:	snakebyte distribution GmbH		
Address	:	Konrad-Zuse-Str.13, 58239 Schwerte, GERMANY		
Test Result	:	<input checked="" type="checkbox"/> Positive <input type="checkbox"/> Negative		
Total pages including Appendices	:	34		

*Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation chapter A-3.4.*

## 1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment under Test .....	4
4	Summary of Test Standards.....	5
5	Summary of Test Results .....	6
6	General Remarks.....	7
7	Test Setups.....	8
8	Systems test configuration .....	9
9	Technical Requirement .....	10
9.1	Conducted Emission .....	10
9.2	Conducted output power .....	13
9.3	6dB bandwidth .....	14
9.4	Power spectral density.....	16
9.5	Spurious RF conducted emissions .....	18
9.6	Band edge .....	23
9.7	Spurious radiated emissions for transmitter .....	25
10	Test Equipment List.....	33
11	System Measurement Uncertainty .....	34



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch  
Building 12&13, Zhiheng Wisdomland Business Park,  
Nantou Checkpoint Road 2, Nanshan District,  
Shenzhen City, 518052, P. R. China

FCC Designation Number: CN5009

FCC Registration No.: 514049

ISED#: 10320A

Telephone: 86 755 8828 6998  
Fax: 86 755 8828 5299

### 3 Description of the Equipment under Test

Product:	WIRELESS GAMING CONTROLLER
Model no.:	SGCNW A0, SB911194, SB913877, SB913716, SB914867, PNSWPHCWL
FCC ID:	2A5E9414502
PMN:	SGCNW A0, SB911194, SB913877, SB913716, SB914867, PNSWPHCWL
HVIN:	SGCNW A0, SB911194, SB913877, SB913716, SB914867, PNSWPHCWL
Input:	5VDC, 330mA charging by USB 3.7V 500Ah powered by Li-ion battery
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	40
Modulation:	GFSK
Antenna Type:	Internal Integrated Antenna
Antenna Gain:	0 dBi max for 2.4GHz
Description of the EUT:	The Equipment Under Test (EUT) is Grip supports Bluetooth Low Energy function support data rate 1 Mbps.
IAN number & Batch number:	IAN 414502_2110 is for this product.

## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2020 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

## 5 Summary of Test Results

Technical Requirements			
FCC Part 15 Subpart C			
Test Condition		Test Result	Test Site
§15.207	Conducted emission AC power port	Pass	Site 1
§15.247 (b) (3)	Conducted output power	Pass	Site 1
RSS-247 5.4(d)	Equivalent Isotropic Radiated Power	Pass	Site 1
§15.247(e)	Power spectral density	Pass	Site 1
§15.247(a)(2)	6dB bandwidth	Pass	Site 1
§15.247(a)(1)	20dB Occupied bandwidth	N/A	--
§15.247(a)(1)	Carrier frequency separation	N/A	--
§15.247(a)(1)(iii)	Number of hopping frequencies	N/A	--
§15.247(a)(1)(iii)	Dwell Time	N/A	--
§15.247(d)	Spurious RF conducted emissions	Pass	Site 1
§15.247(d)	Band edge	Pass	Site 1
§15.247(d) & §15.209 & §15.205	Spurious radiated emissions for transmitter	Pass	Site 1
§15.203	Antenna requirement	Pass See note 2	--

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an Integrated antenna, which gain is 0dBi. In accordance to §15.203 and RSS-Gen 6.8, it is considered sufficiently to comply with the provisions of this section.

## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2A5E9414502, complies with Section 15.209, 15.207, 15.205, 15.247 of the FCC Part 15, Subpart C.

The TX and RX range is 2402MHz-2480MHz.

This report is for the Bluetooth Low Energy.

### SUMMARY:

All tests according to the regulations cited on page 6 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: 2022-01-28

Testing Start Date: 2022-01-28

Testing End Date: 2022-03-17

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

Prepared by:

Tested by:



Cookies Bu  
Project Manager



Vincent Zheng  
Project Engineer




Carry Cai  
Test Engineer


## 7 Test Setups

### 7.1 Radiated test setups


Below 1GHz




Above 1GHz



### 7.2 Conducted RF test setups



### 7.3 AC Power Line Conducted Emission test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Laptop	Lenovo	X240	---

Test software information:

Test Software Version	BQB Test	
Modulation	Setting TX Power	Packet Type
GFSK	31(+6dBm)	Pseudo-Random bit sequence 9

The system was configured to channel 0, 19, and 39 for the test.

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

#### Limit


According to §15.207 & RSS-GEN 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

\*Decreasing linearly with logarithm of the frequency

## Conducted Emission

Product Type : WIRELESS GAMING CONTROLLER  
 M/N : IAN 414502\_2110  
 Operating Condition : Charging + Transmit  
 Test Specification : Power Line, Live  
 Comment : AC 120V/60Hz (External adapter)



## Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.162000	43.64	---	65.36	21.72	L1	9.26
0.286000	35.78	---	60.64	24.86	L1	9.22
0.534000	33.75	---	56.00	22.25	L1	9.20
1.486000	36.41	---	56.00	19.59	L1	9.22
4.190000	40.14	---	56.00	15.86	L1	9.28
9.998000	43.29	---	60.00	16.71	L1	9.39

Remark :


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

## Conducted Emission

Product Type : WIRELESS GAMING CONTROLLER  
 M/N : IAN 414502\_2110  
 Operating Condition : Charging + Transmit  
 Test Specification : Power Line, Neutral  
 Comment : AC 120V/60Hz (External adapter)



## Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.182000	44.25	---	64.39	20.15	N	9.40
1.482000	39.44	---	56.00	16.56	N	9.41
3.802000	40.13	---	56.00	15.87	N	9.46
6.634000	42.26	---	60.00	17.74	N	9.55
10.066000	43.96	---	60.00	16.04	N	9.61
18.202000	42.06	---	60.00	17.94	N	9.70

Remark :

Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

## 9.2 Conducted output power

### Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement.
2. Setting the highest output power level of the EUT
3. Record the power value.

### Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Test result as below table

Data rate	Frequency (MHz)	Conducted Output Power (dBm)	Result
1 Mbps	Low channel 2402MHz	2.64	Pass
	Middle channel 2440MHz	2.82	Pass
	High channel 2480MHz	2.45	Pass

### 9.3 6dB bandwidth

#### Test Method

1. Connect EUT test port to spectrum analyzer.
2. Use the following spectrum analyzer settings:  
RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
4. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]


≥500

#### Test result

Data rate	Channel (MHz)	Result (MHz)	Limit (KHz)	Verdict
1 Mbps	2402	1.019	≥500	PASS
	2440	1.019	≥500	PASS
	2480	1.023	≥500	PASS

#### Test Graphs

1 Mbps:





Date: 3. MAR. 2022 13:58:36

## BLE\_BT4.0\_Ant1\_2480



Date: 3. MAR. 2022 14:00:12

## 9.4 Power spectral density

### Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
3. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
4. Repeat above procedures until other frequencies measured were completed.

### Limit

Limit [dBm/3KHz]


≤8

### Test result

Data rate	Channel (MHz)	Result (dBm/3KHz)	Limit(dBm/3KHz)	Verdict
1 Mbps	2402	-8.06	8	PASS
	2440	-7.68	8	PASS
	2480	-8.17	8	PASS


### Test Graphs

1 Mbps:






## BLE\_Ant1\_2440



Date: 3 MAR 2022 13:58:48

## BLE\_Ant1\_2480



Date: 3 MAR 2022 14:00:24

## 9.5 Spurious RF conducted emissions

### Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.  
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
4. The level displayed must comply with the limit specified in this Section. Submit these plots.
5. Repeat above procedures until all frequencies measured were complete.

### Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20

**Test Result**

Remark: The emissions exceed limit is fundamental signal.


1 Mbps:

BLE\_BT4.0\_Ant1\_2402\_0~Reference




Date: 3.MAR.2022 13:57:11

BLE\_BT4.0\_Ant1\_2402\_30~1000




Date: 3.MAR.2022 13:57:17

BLE\_BT4.0\_Ant1\_2402\_1000~26500




Date: 3. MAR. 2022 13:57:25

## BLE\_BT4.0\_Ant1\_2440\_0~Reference




Date: 3. MAR. 2022 13:58:54

## BLE\_BT4.0\_Ant1\_2440\_30~1000




Date: 3. MAR. 2022 13:59:00

## BLE\_BT4.0\_Ant1\_2440\_1000~26500




Date: 3. MAR. 2022 13:59:08

## BLE\_BT4.0\_Ant1\_2480\_0~Reference




Date: 3. MAR. 2022 14:01:30

## BLE\_BT4.0\_Ant1\_2480\_30~1000



Date: 3. MAR. 2022 14:01:36

## BLE\_BT4.0\_Ant1\_2480\_1000~26500



Date: 3.MAR.2022 14:01:44

## 9.6 Band edge

### Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize, use the peak and delta measurement to record the result.
4. The level displayed must comply with the limit specified in this Section.
5. Repeat the test at the hopping off and hopping on mode, submit all the plots.

### Limit:


According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.

Frequency Range MHz	Limit (dBc)
30-25000	-20

## Test result


1 Mbps:

### BLE\_Ant1\_Low\_2402



Date: 3.MAR.2022 13:56:14

### BLE\_Ant1\_High\_2480



Date: 3.MAR.2022 14:00:33



## 9.7 Spurious radiated emissions for transmitter

### Test Method

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 100 KHz to 120KHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

a) RBW = 1MHz.

b) VBW \ [3 × RBW].

c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2.

Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty

cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

## Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK


## Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (1 Mbps) test result is listed in the report.


### Transmitting spurious emission test result as below:

Below 1G:



### Critical\_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
51.393889	21.47	40.00	18.53	100.0	H	37.0	20.80
110.887222	20.91	43.50	22.59	100.0	H	56.0	18.00
197.756111	21.54	43.50	21.96	200.0	H	34.0	18.78
347.728889	25.54	46.00	20.46	200.0	H	8.0	22.41
601.815000	31.43	46.00	14.57	100.0	H	355.0	27.49
873.145556	35.47	46.00	10.53	200.0	H	97.0	31.41



### Critical\_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.615556	22.32	40.00	17.68	100.0	V	322.0	20.93
104.043333	20.52	43.50	22.98	100.0	V	260.0	18.64
200.288889	21.88	43.50	21.62	100.0	V	268.0	18.35
299.983333	24.07	46.00	21.93	200.0	V	274.0	20.85
424.466667	27.48	46.00	18.52	200.0	V	203.0	24.05
612.700556	32.26	46.00	13.74	200.0	V	8.0	27.69

## Low channel 2402MHz



## Critical\_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2378.500000	51.02	74.00	22.98	150.0	H	222.0	-2.28
3992.000000	48.57	74.00	25.43	150.0	H	302.0	1.97
4804.000000	50.28	74.00	23.72	150.0	H	359.0	4.36
7200.500000	47.55	74.00	26.45	150.0	H	26.0	8.44
9468.000000	46.59	74.00	27.41	150.0	H	186.0	12.96
12606.000000	48.24	74.00	25.76	150.0	H	106.0	16.32



## Critical\_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2038.500000	43.65	74.00	30.35	150.0	V	68.0	-3.71
2378.000000	45.32	74.00	28.68	150.0	V	102.0	-2.28
4805.000000	52.80	74.00	21.20	150.0	V	196.0	4.36
7200.000000	47.60	74.00	26.40	150.0	V	85.0	8.43
8914.500000	44.95	74.00	29.05	150.0	V	185.0	11.79
10257.000000	44.97	74.00	29.03	150.0	V	248.0	12.98

## Middle channel 2440MHz



## Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2534.500000	45.53	74.00	28.47	150.0	H	176.0	-1.66
3689.000000	47.96	74.00	26.04	150.0	H	9.0	0.94
4190.000000	48.62	74.00	25.38	150.0	H	95.0	2.49
4881.000000	52.42	74.00	21.58	150.0	H	155.0	4.61
6573.500000	43.27	74.00	30.73	150.0	H	248.0	8.97
8806.500000	44.83	74.00	29.17	150.0	H	165.0	11.67



## Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2235.000000	43.94	74.00	30.06	150.0	V	285.0	-2.79
2775.500000	43.75	74.00	30.25	150.0	V	205.0	-1.21
3734.500000	46.68	74.00	27.32	150.0	V	158.0	1.18
4881.000000	50.74	74.00	23.26	150.0	V	48.0	4.61
5879.000000	51.73	74.00	22.27	150.0	V	252.0	6.89
7313.500000	47.13	74.00	26.87	150.0	V	63.0	8.85

## High channel 2480MHz



## Critical\_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2528.500000	49.31	74.00	24.69	150.0	H	238.0	-1.70
2576.500000	49.16	74.00	24.84	150.0	H	109.0	-1.54
3893.000000	46.97	74.00	27.03	150.0	H	350.0	1.47
4960.500000	51.20	74.00	22.80	150.0	H	324.0	4.54
7434.000000	48.60	74.00	25.40	150.0	H	44.0	8.93
11977.500000	47.16	74.00	26.84	150.0	H	166.0	14.73



## Critical\_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2576.500000	46.70	74.00	27.30	150.0	V	230.0	-1.54
3176.500000	46.33	74.00	27.67	150.0	V	191.0	0.33
4961.000000	52.35	74.00	21.65	150.0	V	311.0	4.54
6385.000000	48.02	74.00	25.98	150.0	V	185.0	8.70
7434.000000	51.27	74.00	22.73	150.0	V	5.0	8.93

Remark:

- (1) Data of measurement within frequency range 18-26GHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report,
- (2) These frequencies which exceed the limit are carrier frequency.
- (3) Level= Reading Level + Correction Factor
- (4) Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain  
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss  
(The Reading Level is recorded by software which is not shown in the sheet)



## 10 Test Equipment List

### Conducted Emission Test

Description	Manufacturer	Model no.	Serial no.	cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2022-6-4
LISN	Rohde & Schwarz	ENV4200	100249	2022-6-5
Attenuator	Shanghai Huaxiang	TS2-26-3	080928189	2022-6-3
Test software	Rohde & Schwarz	EMC32	Version9.15.00	N/A

### Radiated Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2022-6-4
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	284	2022-8-20
Horn Antenna	Rohde & Schwarz	HF907	102295	2022-8-5
Wideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	12827	2022-8-5
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2022-6-6
Pre-amplifier	Rohde & Schwarz	SCU 40A	100432	2022-7-30
Attenuator	Agilent	8491A	MY39264334	2022-6-3
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

### RF conducted test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	101030	2022-6-3
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157	101226/100851	2022-6-3
Power Splitter	Weinschel	1580	SC319	2022-6-3
Test software	Tonscend	System for BT/WIFI	Version 2.6	N/A

## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV432 or ENV4200)	3.62dB
Uncertainty for Radiated Emission 25MHz-3000MHz	Horizontal: 4.63dB; Vertical: 4.61dB;
Uncertainty for Radiated Emission 3000MHz-18000MHz	Horizontal: 4.65dB; Vertical: 4.64dB;
Uncertainty for Radiated Emission 18000MHz-40000MHz	Horizontal: 4.89dB; Vertical: 4.87dB;
Uncertainty for Conducted RF test	RF Power Conducted: 1.16dB Frequency test involved: $0.6 \times 10^{-7}$ or 1%

---The End---