



FCC TEST REPORT

FCC ID: 2A5EQ-2508MS1

Product	:	Mouse
Model Name	:	GM051
Brand	:	N/A
Report No.	:	PTC25062310401E-FC02
Prepared for		
LTC Networking Limited		
FLAT/RM 1205, 12/F Tai Sang Bank Building 130-132 DES Voeux Road Central HongKong		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



1 TEST RESULT CERTIFICATION

Applicant's name : LTC Networking Limited

Address : FLAT/RM 1205, 12/F Tai Sang Bank Building 130-132 DES Voeux Road
Central HongKong

Manufacture's name : GlobalMex SZ Technologies Ltd

Address : 1704# Huaide International Buliding Fuyong Street Bao'an
District,SZ,CN

Product name : Mouse

Model name : GM051

Standards : FCC Part15 Subpart C, Paragraph 15.249

Test procedure : ANSI C63.10: 2013

Test Date : Jul. 22, 2025 to Aug. 02, 2025

Date of Issue : Aug. 02, 2025

Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
2.1 TEST SITE	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF E.U.T.	7
3.2 CHANNEL LIST	8
4 EQUIPMENT DURING TEST	9
4.1 EQUIPMENTS LIST	9
4.2 MEASUREMENT UNCERTAINTY	11
4.3 DESCRIPTION OF SUPPORT UNITS	11
5 CONDUCTED EMISSION	12
5.1 E.U.T. OPERATION	12
5.2 EUT SETUP	12
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
5.4 MEASUREMENT PROCEDURE	13
5.5 CONDUCTED EMISSION LIMIT	13
5.6 MEASUREMENT DESCRIPTION	13
5.7 CONDUCTED EMISSION TEST RESULT	13
6 RADIATED EMISSION AND BAND EDGE	16
6.1 TEST STANDARD AND LIMIT	16
6.2 TEST SETUP	17
6.3 TEST PROCEDURE	18
6.4 TEST DATA	19
7 20DB BANDWIDTH TEST	26
7.1 TEST STANDARD AND LIMIT	26
7.2 TEST SETUP	26
7.3 TEST PROCEDURE	26
7.4 TEST DATA	27
8 ANTENNA REQUIREMENT	29
8.1 TEST STANDARD AND REQUIREMENT	29
8.2 ANTENNA CONNECTED CONSTRUCTION	29



Report No.: PTC25062310401E-FC02

9 APPENDIX I -- TEST SETUP PHOTOGRAPH	30
10 APPENDIX II -- EXTERNAL PHOTOGRAPH	32
11 APPENDIX III -- INTERNAL PHOTOGRAPH	36



2 Test Summary

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.249	Radiated Emission	PASS
15.215(c)	20dB Bandwidth	PASS
15.249(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		

Remark:N/A



Report No.: PTC25062310401E-FC02

2.1 Test Site

Precise Testing & Certification Co., Ltd.

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Mouse
Model Name	:	GM051
Operation Frequency	:	2405-2475MHz
Modulation	:	GFSK
Number of Channels	:	16
Antenna installation	:	PCB antenna
Antenna Gain	:	-0.71dBi
Power supply	:	Input:DC 3.3V Li-ion Battery : 902535 Voltage: 3.7V Capacity:850mAh 3.145Wh
Hardware Version	:	VR1.0
Software Version	:	VR1.0
Test sample No.	:	PTC25062310401E-1/2,PTC25062310401E-2/2.



3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)
00	2405
01	2408
02	2414
03	2419
04	2422
05	2426
06	2436
07	2439
08	2441
09	2445
10	2453
11	2459
12	2463
13	2466
14	2471
15	2475

Note:

1. Test of channel was included the lowest 2405MHz, middle 2445MHz and highest frequency 2475MHz in highest data rate and to perform the test, then record on this report.
2. EUT used the new batteries during test.



4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-26.5GHz	Aug.15, 2024	1 Year
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug.15, 2024	1 Year
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug.15, 2024	1 Year
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug.15, 2024	1 Year
DC power Supply	Agilent	E3642A	MY52420017	0-8V,5A/0-20 ,2.5A	Aug.15, 2024	1 Year
Humidity Chamber	AISRY	ASR-HW2-1000	20230926003	-40°C-150°C	Feb.23 ,2025	1year
Test S/W	Tonscend	JS1120-3	/	/	/	/

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESPI7	101671	9KHz-7GHz	Aug.15, 2024	1 Year
Loop Antenna	Schwarzbeck	FMZB 1519	192	9 KHz -30MHz	Nov.28, 2024	1 Year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Sep.10, 2024	1 Year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	9KHz-1GHz	Mar.21, 2025	1 Year
Cable	IMRO	AK-9515E(9m)	Cable-L	9KHz-3GHz	Aug.15, 2024	1 Year
Spectrum Analyzer	Rohde&Schwarz	FSV40	6625-01-588-5515	9KHz-40GHz	Aug.15, 2024	1 Year
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1246	1GHz-18GHz	Dec.12, 2024	1 Year



Report No.: PTC25062310401E-FC02

Power Amplifier	ZHINAN	ZN3380C	15002	1GHz-26.5GHz	Aug.15, 2024	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-1066	15GHz-40GHz	Jun. 24, 2025	1 Year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Jun. 23, 2025	1 Year
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug.15, 2024	1 Year
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug.15, 2024	1 Year
Test S/W	Tonscend	TS+	/	/	/	/

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Date	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESCI3	101417	9KHz-3GHz	Aug.15, 2024	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Oct.30, 2024	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Oct.30, 2024	1 Year
Limiter	R&S	ESH3-Z2	0357.8810.54-102808-NB	0Hz-30MHz	Aug.15, 2024	1 Year
RF Switch	DIAMOND ANTENNA	CX-210	/	0.09MHz-6GHz	Mar. 21,2025	1 Year
Test S/W	Tonscend	JS32-CE	/	/	/	/



4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Radiated Emission(9KHz~30MHz)	$\pm 3.15\text{dB}$

4.3 Description of Support Units

Equipment	Model No.	Series No.
Adapter	MDY-12	N/A

5 Conducted Emission

Test Requirement	: FCC CFR 47 Part 15 Section 15.207
Test Method	: ANSI C63.10: 2013
Test Result	: PASS
Frequency Range	: 150kHz to 30MHz
Class/Severity	: Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature	: 25.5 °C
Humidity	: 51 % RH
Atmospheric Pressure	: 101.2kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)

0.15-0.5

0.5-5.0

5.0-30.0

Quasi-peak

66-56

56

60

Average

56-46

46

50

Note:


1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

Line-AC 120V/60Hz




Final Data List

NO.	Freq. [MHz]	QP Reading	Factor [dB]	QP Value	QP Limit	QP Margin	AV Reading	AV Value	AV Limit	AV Margin	Verdict
1	0.150	45.62	9.81	55.43	66.00	10.57	24.09	33.90	56.00	22.10	PASS
2	0.159	45.45	9.81	55.26	65.52	10.26	23.57	33.38	55.52	22.14	PASS
3	0.209	40.47	9.81	50.28	63.26	12.98	22.03	31.84	53.26	21.42	PASS
4	0.654	29.71	9.82	39.53	56.00	16.47	16.31	26.13	46.00	19.87	PASS
5	0.866	29.51	9.82	39.33	56.00	16.67	22.09	31.91	46.00	14.09	PASS
6	1.212	28.60	9.83	38.43	56.00	17.57	17.41	27.24	46.00	18.76	PASS



Neutral-AC 120V/60Hz

Report No.: PTC25062310401E-FC02



Final Data List

NO.	Freq. [MHz]	QP Reading	Factor [dB]	QP Value	QP Limit	QP Margin	AV Reading	AV Value	AV Limit	AV Margin	Verdict
1	0.150	45.99	9.81	55.80	66.00	10.20	26.52	36.33	56.00	19.67	PASS
2	0.168	43.88	9.81	53.69	65.06	11.37	28.99	38.80	55.06	16.26	PASS
3	0.177	40.29	9.81	50.10	64.63	14.53	26.64	36.45	54.63	18.18	PASS
4	0.569	29.09	9.81	38.90	56.00	17.10	17.42	27.23	46.00	18.77	PASS
5	0.866	30.07	9.82	39.89	56.00	16.11	24.44	34.26	46.00	11.74	PASS
6	1.347	29.15	9.83	38.98	56.00	17.02	17.00	26.83	46.00	19.17	PASS

Note: QP Margin[dB]= QP Limit[dBμV]- QP Value[dBμV], AV Margin[dB]= AV Limit[dBμV]- AV Value[dBμV].



6 Radiated Emission and Band Edge

6.1 Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz~30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

(3)Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

Test Standard	FCC Part15 C Section 15.249					
Test Limit	Frequency (MHz)	Field Strength of fundamental (millivolts /meter)	Field Strength of Harmonics (microvolts/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	2400~2483.5	50	-	114.0	Peak	3
	2400~2483.5	50	-	94.0	Average	3
	2400~2483.5	-	500	74.0	Peak	3
	2400~2483.5	-	500	54.0	Average	3

Remark:

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

6.2 Test Setup

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz



6.3 Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:



RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.


6.4 Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, and found the Middle channel which is the worst case, only the worst case is recorded in the report




Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	57.40	27.34	-10.16	17.18	40.00	22.82	Horizontal	PASS
2	505.54	27.42	-3.51	23.91	46.00	22.09	Horizontal	PASS
3	592.84	26.97	-1.66	25.31	46.00	20.69	Horizontal	PASS
4	684.27	27.19	-0.35	26.84	46.00	19.16	Horizontal	PASS
5	776.17	28.76	1.14	29.90	46.00	16.10	Horizontal	PASS
6	870.99	29.86	2.20	32.06	46.00	13.94	Horizontal	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

Test plot for Vertical



Final Data List[QP]

NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	58.13	27.45	-10.20	17.25	40.00	22.75	Vertical	PASS
2	145.67	26.75	-9.68	17.07	43.50	26.43	Vertical	PASS
3	504.33	27.1	-3.56	23.54	46.00	22.46	Vertical	PASS
4	598.66	27.48	-1.37	26.11	46.00	19.89	Vertical	PASS
5	715.79	27.5	0.30	27.80	46.00	18.20	Vertical	PASS
6	827.58	28.29	1.58	29.87	46.00	16.13	Vertical	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



Test Frequency 1GHz-25GHz

Test Mode: CH00 (Low channel)									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector
2405.00	92.77	31.12	2.18	35.33	90.74	114	-23.26	V	Peak
2405.00	84.55	31.12	2.18	35.33	82.92	94	-11.08	V	AVG
4810.00	48.64	34.01	2.58	34.65	50.58	74	-23.42	V	Peak
4810.00	37.96	34.01	2.58	34.65	40.29	54	-13.71	V	AVG
7215.00	47.68	36.16	2.97	35.07	51.74	74	-22.26	V	Peak
7215.00	35.29	36.16	2.97	35.07	36.38	54	-17.62	V	AVG
2405.00	92.14	31.12	2.18	35.33	90.11	114	-23.89	H	Peak
2405.00	84.72	31.12	2.18	35.33	83.09	94	-10.91	H	AVG
4810.00	48.71	34.01	2.58	34.65	50.65	74	-23.35	H	Peak
4810.00	37.61	34.01	2.58	34.65	39.94	54	-14.06	H	AVG
7215.00	46.38	36.16	2.97	35.07	50.44	74	-23.56	H	Peak
7215.00	36.47	36.16	2.97	35.07	37.56	54	-16.44	H	AVG



Test Mode: CH09 (Middle channel)									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector
2445.00	92.21	31.12	2.2	34.51	91.86	114	-22.14	V	Peak
2445.00	81.49	31.22	2.2	34.51	81.18	94	-12.82	V	AVG
4890.00	48.34	34.98	2.49	34.14	53.26	74	-20.74	V	Peak
4890.00	37.42	34.98	2.49	34.14	41.02	54	-12.98	V	AVG
7335.00	47.21	36.01	3.01	34.56	51.25	74	-22.75	V	Peak
7335.00	36.07	36.01	3.01	34.56	40.64	54	-13.36	V	AVG
2445.00	95.42	31.12	2.2	34.51	92.07	114	-21.93	H	Peak
2445.00	81.94	31.12	2.2	34.51	81.35	94	-12.65	H	AVG
4890.00	48.32	34.98	2.49	34.14	52.49	74	-21.51	H	Peak
4890.00	36.68	34.98	2.49	34.14	42.21	54	-11.79	H	AVG
7335.00	47.14	36.01	3.01	34.56	52.27	74	-21.73	H	Peak
7335.00	35.18	36.01	3.01	34.56	41.48	54	-12.52	H	AVG



Test Mode: CH15(High channel)									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector
2475.00	93.96	31.65	2.23	36.07	92.54	114	-21.46	V	Peak
2475.00	82.29	31.65	2.23	36.07	81.07	94	-12.93	V	AVG
4950.00	48.08	35.06	2.6	34.93	51.95	74	-22.05	V	Peak
4950.00	37.40	35.06	2.6	34.93	41.62	54	-12.38	V	AVG
7425.00	46.86	36.19	3.12	35.11	52.32	74	-21.68	V	Peak
7425.00	36.18	36.19	3.12	35.11	41.25	54	-12.75	V	AVG
2475.00	92.96	31.65	2.23	36.07	92.92	114	-21.08	H	Peak
2475.00	83.20	31.65	2.23	36.07	81.2	94	-12.80	H	AVG
4950.00	48.60	35.06	2.6	34.93	52.32	74	-21.68	H	Peak
4950.00	37.22	35.06	2.6	34.93	41.7	54	-12.30	H	AVG
7425.00	46.40	36.19	3.12	35.11	52.41	74	-21.59	H	Peak
7425.00	35.09	36.19	3.12	35.11	40.76	54	-13.24	H	AVG

Note: 1. The testing has been conformed to $10 \times 2405\text{MHz} = 24050\text{MHz}$. $10 \times 2445\text{MHz} = 24450\text{MHz}$.
 $10 \times 2475\text{MHz} = 24750\text{MHz}$.

2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
 Emission Level = Reading + Factor
 Margin=Emission Level-Limit



Band edge

Report No.: PTC25062310401E-FC02

Test Mode: Low Channel 2405MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2390.00	40.22	29.15	3.41	34.01	38.77	74	-35.23	H	Peak
2400.00	58.37	29.16	3.43	34.01	56.95	74	-17.05	H	Peak
2390.00	40.61	29.15	3.41	34.01	39.16	74	-34.84	V	Peak
2400.00	57.39	29.16	3.43	34.01	55.97	74	-18.03	V	Peak
2390.00	35.47	29.15	3.41	34.01	34.02	54	-19.98	H	AV
2400.00	40.82	29.16	3.43	34.01	39.40	54	-14.60	H	AV
2390.00	35.77	29.15	3.41	34.01	34.32	54	-19.68	V	AV
2400.00	43.41	29.16	3.43	34.01	41.99	54	-12.01	V	AV


Test Mode: High Channel 2475MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2483.50	46.54	29.28	3.53	34.03	45.32	74	-28.68	H	Peak
2500.00	40.95	29.30	3.56	34.03	39.78	74	-34.22	H	Peak
2483.50	47.67	29.28	3.53	34.03	46.45	74	-27.55	V	Peak
2500.00	40.97	29.30	3.56	34.03	39.80	74	-34.20	V	Peak
2483.50	38.50	29.28	3.53	34.03	37.28	54	-16.72	H	AV
2500.00	33.84	29.30	3.56	34.03	32.67	54	-21.33	H	AV
2483.50	39.78	29.28	3.53	34.03	38.56	54	-15.44	V	AV
2500.00	33.18	29.30	3.56	34.03	32.01	54	-21.99	V	AV

7 20dB Bandwidth Test

7.1 Test Standard and Limit

Test Standard	According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
---------------	---

7.2 Test Setup



7.3 Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
 - RBW = 1% to 5% of the OBW, $VBW \geq 3 \times RBW$,
 - Detector= Average
 - Trace mode= Max hold.
 - Sweep- auto couple.
4. Mark the peak frequency and –20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.



7.4 Test Data

Test Item	: 20dB Bandwidth	Test Mode	: TX
Test Voltage	: DC 3.3V	Temperature	: 22.4°C
Test Result	: PASS	Humidity	: 55%RH

Frequency (MHz)	Bandwidth (MHz)	Result
2405MHZ	1.683	PASS
2445MHZ	1.589	PASS
2475MHZ	1.716	PASS





Test Mode: Low



Test Mode: Middle



Test Mode: High



8 Antenna Requirement

8.1 Test Standard and Requirement


Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8.2 Antenna Connected Construction


The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is -0.71 dBi. It complies with the standard requirement.

9 APPENDIX I -- TEST SETUP PHOTOGRAPH


CONDUCTED EMISSION TEST



RADIATED EMISSION TEST(Below 1G)



RADIATED EMISSION TEST(Above 1G)



10 APPENDIX II -- EXTERNAL PHOTOGRAPH


















11 APPENDIX III -- INTERNAL PHOTOGRAPH











*****THE END REPORT*****