

Product Specifications sheet



Specification No.	20240802001
Effective date	2024/8/2

Customer Name:	一起造
Product Model	N4 (Mobile phone coil)
DZ Part No.	TX-DZ43.505.300.65-K6.5-L10-L20 (double-slotted)
Customer item No	B. 10. 21060027-00

【New issue, version revision】

【This specification includes contents and 7 pages in total】 【RoHS Compliant Parts】

organize	Check	Approval
钟建立 Zhong jianli	/	马湘平 Ma xiangping

Guang Dong Top Wiser Electronic Technology Co., Ltd

Factory address:Address; 1F, 1231 Yingbin Avenue, Longmen County
, Huizhou City, Guangdong Province

Tel: 13147097490

【Within 30 days after the customer receives this acknowledgement, please return it with your signature and seal. If it is overdue, it will be deemed that the production will be carried out according to the standards of this acknowledgement】.

【customer approval】

Date:

Recognition status: full recognition conditional recognition refusal


Approval	Review	Recheck	Check

remark:

Product Specifications sheet

Customer Name:	一起造	item	B.10.21060027-00
DZ Part No.	TX-DZ43.505.300.65-K6.5-L10-L20 (double-slotted)	Specification No.	20240802001
Issue/Revision History			
Version	Effective date	Change content / reason	Approval
01	2024/8/2	New specification release	钟建立Zhong Jianli
organize	check	approval	
钟建立Zhong Jianli	/	马湘平 Ma XiangPing	

Product Specifications sheet

Customer Name:	一起造	Customer item No	B.10.21060027-00																				
DZ Part No	TX-DZ43.505.300.65-K6.5-L10-L20 (double-slitting)	Specification No.	20240802001	Version	01																		
◆ Overall dimensions					(unit: mm)																		
					<table border="1"> <tr> <td>A</td><td>5.3 ±1.5</td></tr> <tr> <td>B</td><td>20.5 ±1.5</td></tr> <tr> <td>C</td><td>38.5 ±1.5</td></tr> <tr> <td>D</td><td>43.5 ±1.5</td></tr> <tr> <td>E</td><td>43.0 ±1.5</td></tr> <tr> <td>F</td><td>20.0 ±2.0</td></tr> <tr> <td>F1</td><td>10.0 ±2.0</td></tr> <tr> <td>H</td><td>1.7 ±0.3</td></tr> <tr> <td>I</td><td>±0.2(Diskette 0.65 thickness)</td></tr> </table>	A	5.3 ±1.5	B	20.5 ±1.5	C	38.5 ±1.5	D	43.5 ±1.5	E	43.0 ±1.5	F	20.0 ±2.0	F1	10.0 ±2.0	H	1.7 ±0.3	I	±0.2(Diskette 0.65 thickness)
A	5.3 ±1.5																						
B	20.5 ±1.5																						
C	38.5 ±1.5																						
D	43.5 ±1.5																						
E	43.0 ±1.5																						
F	20.0 ±2.0																						
F1	10.0 ±2.0																						
H	1.7 ±0.3																						
I	±0.2(Diskette 0.65 thickness)																						
<p>(1)Wire diameter: 0.08 * 24P*2P enameled wire (2)Number of windings: 10TS (3)Whether the starting and ending lines cross: Yes (4)The coil and magnetic sheet shall be pasted in the center (5)Coil wrapped with 8mm high temperature adhesive tape (6) Disc back 42 rounds of white glue (7) As shown in the figure, the deep slot lead is set with 8mm sleeve Shallow groove sleeve 18mm casing</p>																							
◆ Electrical characteristics:																							
parameter	specification		Test conditions	Test instrument																			
L0	6.5 ±10%	μH	100KHz/1V	■TH1816B																			
Q	>30	min	100KHz/1V	■TH1816B																			
DCR	<95	mΩ	@ 25°C	■CH-502BC																			
◆ Temperature class:																							
Operating temperature	-40°C ~ 125°C																						
◆ list of materials:																							
Item	Product Name	Material specification	Supplier	Remark																			
1	Magnetic sheet	43.5*5.3*0.65T开双槽 (double-slitting)		PC40																			
2	Copper wire	0.08*24*2P		enameled wire																			
3	High temperature adhesive tape	棕色8MM		ROHS																			
4	tin	107H		ROHS																			
5	Double-sided tape	42 rounds of white glue		ROHS																			
6	glue	Yellow gum		ROHS																			
7	cannula	8mm/18mm black casing		ROHS																			
organize		check			approval																		
钟建立	Zhong Jianli	/			马湘平 Ma Xiangping																		