

Dongguan ETAN Pet Supplies Co., Ltd

TEST REPORT

SCOPE OF WORK

FCC TESTING–EHR25

REPORT NUMBER

211203031SZN-001

ISSUE DATE

11 February 2022

[REVISED DATE]

[-----]

PAGES

17

DOCUMENT CONTROL NUMBER

FCC ID 231_e

© 2017 INTERTEK



Intertek Report No.: 211203031SZN-001

Dongguan ETAN Pet Supplies Co., LtdApplication
For
Certification**FCC ID: 2A5I6-ETANEHR25****Functional Decor****Model: EHR25****Transmitter**

Report No.: 211203031SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-20]

Prepared and Checked by:**Approved by:**

Vito Pan
Project Engineer

Peter Kang
Senior Technical Supervisor
Date: 11 February 2022

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Service Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DSC - Part 15 Security Remote Control Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until :
date

Company Name agrees to notify the Commission by:
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-20] Edition] provision.

Report prepared by:

Vito Pan

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing
Community, GuanHu Subdistrict, LongHua District,
ShenZhen, P.R. China

Tel: (86 755) 8614 0651 Fax: (86 755) 8601 6751

Table of Contents

1.0	<u>Summary of Test results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
3.0	<u>System Test Configuration</u>	6
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	6
3.4	Measurement Uncertainty	6
3.5	Equipment Modification	6
3.6	Support Equipment List and Description	7
4.0	<u>Measurement Results</u>	8
4.1	Field Strength Calculation	8
4.2	Radiated Emission Configuration Photograph	9
4.3	Radiated Spurious Emission	9
5.0	<u>Equipment Photographs</u>	11
6.0	<u>Product Labelling</u>	11
7.0	<u>Technical Specifications</u>	11
8.0	<u>Instruction Manual</u>	11
9.0	<u>Miscellaneous Information</u>	12
9.1	Timing Plot	12
9.2	Measured Bandwidth	13
9.3	Discussion of Pulse Desensitization	14
9.4	Calculation of Average Factor	15
9.5	Emissions Test Procedures	16
10.0	<u>Test Equipment List</u>	17

1.0 Summary of Test results

Applicant: Dongguan ETAN Pet Supplies Co., Ltd

Applicant Address: No.3 JinXingEr Road, Qingxi Town, Dongguan City, Guangdong Province

Manufacturer: Dongguan ETAN Pet Supplies Co., Ltd

Manufacturer Address: No.3 JinXingEr Road, Qingxi Town, Dongguan City, Guangdong Province

Functional Decor

Model: EHR25

FCC ID: 2A5I6-ETANEHR25

TEST ITEM	REFERENCE	RESULTS
Transmitter Field Strength	15.231(e) & 15.205	Pass
Bandwidth	15.231(c)	Pass
Timing Requirement	15.231(e)	Pass

Notes: 1. The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a Functional Decor operating at 433.92MHz. The EUT is powered by DC 3.0 V from 2*AA battery. For more detailed features description, please refer to the user's manual.

Antenna Type: Integral Antenna

Modulation: FSK

Antenna Gain: 3dBi Max.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of the Functional Decor transmitter portion.

2.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-Anechoic chamber used to collect the radiated data is Intertek **Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by a new DC 3.0 V from 2*AA battery during the test. Only the worst case data was shown in the report.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Exhibit 4.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the styrene turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

3.2 EUT Exercising Software

There was no special software to exercise the device.

3.3 Special Accessories

No special accessories used.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by Dongguan ETAN Pet Supplies Co., Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Remark
N/A		

4.0 System Test Configuration

4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dBμV/m

RA = Receiver Amplitude (including preamplifier) in dBμV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0dBμV is obtained. The antenna factor of 7.4dB and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is 32dBμV/m. This value in dBμV/m was converted to its corresponding level in μV/m.

RA = 62.0dBμV

AF = 7.4 dB/m

CF = 1.6dB

AG = 29.0dB

PD = 0dB

AV = -10dB

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32\text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32\text{dB}\mu\text{V/m})/20] = 39.8\mu\text{V/m}$$

4.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

4.3 Radiated Spurious Emission

Worst Case Radiated Spurious Emission
at
433.92MHz

Judgement: Passed by 3.10dB margin

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

TEST PERSONNEL:

Sign on file

Vito Pan, Project Engineer

Typed/Printed Name

24 January 2022

Date

Applicant: Dongguan ETAN Pet Supplies Co., Ltd

Date of Test: 24 January 2022

Model: EHR25

Worst Case Operating Mode: Transmitting

Table 1
Radiated Emissions (9K-12.75G)

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)			Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV Factor(dB)	AV	PK	AV	PK	AV
433.92	H	69.77	0	69.77	92.87	72.87	-23.10	-3.10
1746.13	H	40.15	0	40.15	72.87	52.87	-32.72	-12.72
2169.13	H	48.05	0	48.05	72.87	52.87	-24.82	-4.82
3037.45	H	44.68	0	44.68	72.87	52.87	-28.19	-8.19
433.92	V	68.49	0	68.49	92.87	72.87	-24.38	-4.38
3036.86	V	44.21	0	44.21	72.87	52.87	-28.66	-8.66
4611.36	V	44.93	0	44.93	74.00	54.00	-29.07	-9.07
6365.64	V	49.11	0	49.11	72.87	52.87	-23.76	-3.76

- NOTES:
1. Peak Detector Data unless otherwise stated.
 2. All measurements were made at 3-meter. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. The EUT was pre-scanned 9K-30M, found all emissions were greater than 20 dB below the limit, so don't show data on this report.
 5. Averaging factor in dB=20log (duty cycle)
20log (Duty cycle) =20log (1) = 0dB

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.



9.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandwidth, the test procedure, calculation of timing requirements and pulse desensitization.

9.1 Timing Plot – Pursuant to FCC Part 15 Section 15.231(e)


Mode	Time seconds	Limit seconds	Verdict
Transmission	0.775	< 1	PASS
Silent	60.30	≥ 23.25	PASS

Note: Silent(s)/ Transmission(s) > 30



9.2 Measured Bandwidth

From the plot, the 20dB bandwidth is 2.05 kHz and less than the limit of 1.08MHz. It fulfils the requirement of 15.231(c).




9.3 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (T_{eff}) is approximately 775.00ms for a digital "1" bit which illustrated on technical specification. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

9.4 Calculation of Average Factor

Averaging factor in dB = $20 \log (\text{duty cycle})$
 $20 \log (\text{Duty cycle}) = 20 \log (1) = 0 \text{ dB}$

The test plots are attached as below.



9.5 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter, up to 1GHz 0.8m and above 1GHz 1.5m in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is based on the use of measurement instrumentation with a CISPR quasi-peak detector.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	04-Aug-2021	04-Aug-2024
SZ185-03	EMI Receiver	R&S	ESCI	100547	20-Dec-2021	20-Dec-2022
SZ061-08	Horn Antenna	ETS	3115	00092346	05-Sep-2021	05-Sep-2024
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	18-May-2021	18-May-2023
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	10-May-2021	10-May-2022
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	10-May-2021	10-May-2022
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	22-Dec-2021	22-Dec-2024
SZ062-23	RF Cable	RADIAL	SF104PE	--	26-Oct-2021	26-Oct-2022
SZ062-35	RF Cable	RADIAL	A50-3.5M3.5M-8M	--	26-Oct-2021	26-Oct-2022
SZ062-30	RF Cable	RADIAL	A50-3.5M3.5M-4.5M	--	26-Oct-2021	26-Oct-2022
SZ062-31	RF Cable	RADIAL	A50-3.5M3.5M-1M	--	26-Oct-2021	26-Oct-2022

***** End of Report *****