



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation

Report Reference No.: GTS20220216003-1-2

FCC ID.: 2A5K9-WM300

Compiled by

(position+printed name+signature) : File administrators Peter Xiao

Supervised by

(position+printed name+signature) : Test Engineer Oliver Ou

Approved by

(position+printed name+signature) : Manager Simon Hu



Date of issue : Mar.09, 2022

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address : No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.: Fuzhou Huiqixin Technology Co. , Ltd.

Address : Room 906, zone A, floor 9, yunzuo-3 building, no. 528 xihong road, gulou district, Fuzhou city, Fujian province, China

Test specification :

47CFR §1.1310

Standard : 47CFR §2.1093

KDB447498 D01 General RF Exposure Guidance v06

TRF Originator : Shenzhen Global Test Service Co.,Ltd.

Master TRF : Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : Lavalier Microphone

Trade Mark : FULAIM, Alilong, Fotowelt, Dazzne

Manufacturer : Fuzhou Huiqixin Technology Co. , Ltd.

Model/Type reference : WM300

Listed Models : WM100, WM400, WM600, WM700, WM800, WM900, WM1000, MK1, MK2, MK3, MK4, MK5, MK6, MK7, MK8, MK9, MK10, WS10, WS20, WS30, WS40, WS50, WS60, WS70, WS80, WS90, WS100, WM1, WM2, WM3, WM4, WM5, WM6, WM7, WM8, WM9, WM10, AL11, WL, WL1, WL2, WL3, WL4, WL5, FL01, FL02, FL03, FL04, FL05, LM1-C, LM1-R, LM1-E, LM1-P, LM1-E, AL10, AL12, AL13, AL14, AL15, AL1, AL2, AL3, AL4, AL5, AL6, ALU1, ALU2, ALU3, ALU4, ALU5, MH1, MH2, MH3, MH4, MH5, MH6, M1, M2, M3, M4, M5

Modulation Type : DQPSK

Operation Frequency : From 570.0-579.5MHz and 580.0-589.5MHz

Rating : DC 3.7V by battery

Recharged by DC 5.0V

Result : PASS

TEST REPORT

Test Report No. :	GTS20220216003-1-2	Mar.09, 2022
		Date of issue

Equipment under Test : Lavalier Microphone

Model /Type : WM300

Listed Models : WM100, WM400, WM600, WM700, WM800, WM900, WM1000, MK1, MK2, MK3, MK4, MK5, MK6, MK7, MK8, MK9, MK10, WS10, WS20, WS30, WS40, WS50, WS60, WS70, WS80, WS90, WS100, WM1, WM2, WM3, WM4, WM5, WM6, WM7, WM8, WM9, WM10, AL11, WL, WL1, WL2, WL3, WL4, WL5, FL01, FL02, FL03, FL04, FL05, LM1-C, LM1-R, LM1-E, LM1-P, LM1-E, AL10, AL12, AL13, AL14, AL15, AL1, AL2, AL3, AL4, AL5, AL6, ALU1, ALU2, ALU3, ALU4, ALU5, MH1, MH2, MH3, MH4, MH5, MH6, M1, M2, M3, M4, M5

Applicant : **Fuzhou Huiqixin Technology Co. , Ltd.**

Address : Room 906, zone A, floor 9, yunzuo-3 building, no. 528 xihong road, gulou district, Fuzhou city, Fujian province, China

Manufacturer : **Fuzhou Huiqixin Technology Co. , Ltd.**

Address : Room 906, zone A, floor 9, yunzuo-3 building, no. 528 xihong road, gulou district, Fuzhou city, Fujian province, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY	4
1.1 EUT configuration.....	4
1.2 Product Description	4
2. TEST ENVIRONMENT.....	5
2.1 Address of the test laboratory	5
2.2 Test Facility	5
2.3 Environmental conditions	5
2.4 Statement of the measurement uncertainty	5
3. METHOD OF MEASUREMENT	6
3.1 Applicable Standard	6
3.2 Evaluation method and Limit.....	6
4. CONDUCTED POWER RESULTS.....	7
5. MANUFACTURING TOLERANCE.....	8
6. MEASUREMENT RESULTS	9
6.1 Evaluation Results.....	9
6.2 Simultaneous Transmission MPE	9
7. CONCLUSION	10

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○ /	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name	Lavalier Microphone
Trade Mark	FULAIM, Alilong, Fotowelt, Dazzne
Model/Type reference	WM300
List Models	WM100, WM400, WM600, WM700, WM800, WM900, WM1000, MK1, MK2, MK3, MK4, MK5, MK6, MK7, MK8, MK9, MK10, WS10, WS20, WS30, WS40, WS50, WS60, WS70, WS80, WS90, WS100, WM1, WM2, WM3, WM4, WM5, WM6, WM7, WM8, WM9, WM10, AL11, WL, WL1, WL2, WL3, WL4, WL5, FL01, FL02, FL03, FL04, FL05, LM1-C, LM1-R, LM1-E, LM1-P, LM1-E, AL10, AL12, AL13, AL14, AL15, AL1, AL2, AL3, AL4, AL5, AL6, ALU1, ALU2, ALU3, ALU4, ALU5, MH1, MH2, MH3, MH4, MH5, MH6, M1, M2, M3, M4, M5
Model Declaration	PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power supply:	DC 3.7V by battery Recharged by DC 5.0V
Hardware Version	N/A
Software Version	N/A
Sample ID	GTS20220216003-1-1# & GTS20220216003-1-2#
Lavalier Microphone(Transmitter)	
Frequency Range	570.0-579.5MHz and 580.0-589.5MHz
Channel No.	20 Channels form 570.0-579.5MHz 20 Channels form 580.0-589.5MHz
Modulation Type	DQPSK
Rated Power	10mW
Antenna Description	External Antenna; 0dBi(Max.)

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is 165725.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[KDB447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

3.2 Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³”

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

4. Conducted Power Results

Channel A			
Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
DQPSK	01	570.0	7.432
	11	575.5	7.540
	20	579.5	8.685

Channel B			
Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
DQPSK	01	580.0	5.840
	11	585.5	5.202
	20	589.5	5.670

5. Manufacturing Tolerance

DQPSK (Peak) Channel A			
Channel	Channel 01	Channel 11	Channel 20
Target (dBm)	7.0	7.0	8.0
Tolerance \pm (dB)	1.0	1.0	1.0
DQPSK (Peak) Channel B			
Channel	Channel 01	Channel 11	Channel 20
Target (dBm)	5.0	5.0	5.0
Tolerance \pm (dB)	1.0	1.0	1.0

6. Measurement Results

6.1 Evaluation Results

Modulation Type	f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
DQPSK (Channel A)	0.570	5	9.0	7.94	1.20 < 3.0	Yes
DQPSK (Channel B)	0.580	5	6.0	3.98	0.61 < 3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 of KDB447498 D01 General RF Exposure Guidance v06 is applied to determine SAR test exclusion.

6.2 Simultaneous Transmission MPE

The sample support one Lavalier Microphone modular and one antenna, Not need consider simultaneous transmission ;

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....**End of Report**.....