



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



# TEST REPORT

**Applicant:** Aitek Inc

Address: 888 Washington St Suite 301 Dedham Massachusetts United States of America

**FCC ID:** 2A5L2-AMP500

**Product Name:** Aitek Miner Plus

**Model Number:** AMP-500-01

**Standard(s):** 47 CFR Part 15, Subpart C(15.247)  
ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number:** CR22040043-00D

**Date Of Issue:** 2022-04-27

**Reviewed By:** Sun Zhong

*Sun Zhong*

Title: Manager

**Test Laboratory:** China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,  
Guangdong, China  
Tel: +86-769-82016888

## Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

## Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## CONTENTS

<b>TEST FACILITY .....</b>	<b>2</b>
<b>DECLARATIONS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b>	<b>5</b>
<b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>	<b>8</b>
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details .....	9
1.2.3 Support Cable List and Details .....	9
1.2.4 Block Diagram of Test Setup.....	9
<b>1.3 MEASUREMENT UNCERTAINTY .....</b>	<b>11</b>
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>12</b>
<b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>13</b>
<b>3.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>13</b>
3.1.1 Applicable Standard.....	13
3.1.2 EUT Setup.....	14
3.1.3 EMI Test Receiver Setup .....	14
3.1.4 Test Procedure .....	15
3.1.5 Corrected Amplitude & Margin Calculation.	15
<b>3.2 RADIATION SPURIOUS EMISSIONS.....</b>	<b>16</b>
3.2.1 Applicable Standard.....	16
3.2.2 EUT Setup.....	16
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....	17
3.2.4 Test Procedure .....	17
3.2.5 Corrected Amplitude & Margin Calculation.	17
<b>3.3 6 dB EMISSION BANDWIDTH:.....</b>	<b>18</b>
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure .....	18
<b>3.4 MAXIMUM PEAK CONDUCTED OUTPUT POWER:.....</b>	<b>19</b>
3.4.1 Applicable Standard.....	19
3.4.2 EUT Setup.....	19
3.4.3 Test Procedure .....	19
<b>3.5 MAXIMUM POWER SPECTRAL DENSITY: .....</b>	<b>20</b>
3.5.1 Applicable Standard.....	20
3.5.2 EUT Setup.....	20
3.5.3 Test Procedure .....	20
<b>3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE: .....</b>	<b>21</b>
3.6.1 Applicable Standard.....	21
3.6.2 EUT Setup.....	21
3.6.3 Test Procedure .....	21
<b>3.7 DUTY CYCLE:.....</b>	<b>22</b>

3.7.1 EUT Setup.....	22
3.7.2 Test Procedure .....	22
<b>3.8 ANTENNA REQUIREMENT.....</b>	<b>22</b>
3.8.1 Applicable Standard.....	22
3.8.2 Judgment.....	22
<b>4. Test DATA AND RESULTS .....</b>	<b>23</b>
<b>4.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>23</b>
<b>4.2 RADIATION SPURIOUS EMISSIONS .....</b>	<b>28</b>
<b>4.3 6 dB EMISSION BANDWIDTH:.....</b>	<b>37</b>
<b>4.4 MAXIMUM CONDUCTED OUTPUT POWER:.....</b>	<b>39</b>
<b>4.5 MAXIMUM POWER SPECTRAL DENSITY: .....</b>	<b>41</b>
<b>4.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE: .....</b>	<b>43</b>
<b>4.7 DUTY CYCLE:.....</b>	<b>45</b>
<b>5. RF EXPOSURE EVALUATION .....</b>	<b>47</b>
<b>5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b>	<b>47</b>
<b>5.1.1 APPLICABLE STANDARD.....</b>	<b>47</b>
<b>5.1.2 PROCEDURE.....</b>	<b>47</b>
<b>5.1.3 CALCULATED DATA: .....</b>	<b>48</b>

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	Aitek Miner Plus
<b>EUT Model:</b>	AMP-500-01
<b>Operation Frequency:</b>	2412-2462 MHz(802.11b/g/n ht20) 2402-2480MHz(BLE) 923.3-927.5 MHz(Lora-DTS)
<b>Maximum Peak Output Power (Conducted):</b>	25.27 dBm(802.11b/g/n) 3.28 dBm(BLE) 27.46 dBm(Lora-DTS)
<b>Modulation Type:</b>	DSSS, OFDM(802.11b/g/n) GFSK(BLE) Lora(Lora-DTS)
<b>Rated Input Voltage:</b>	DC 12V from adapter
<b>Serial Number:</b>	CR22020030-RF-S1
<b>EUT Received Date:</b>	2022.03.09
<b>EUT Received Status:</b>	Good

#### Objective:

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15 section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

The EUT was only modified software for Lora-DTS by manufacturer based on FCC ID: 2A5L2AMP500, which was granted by FCC. The manufacturer modified software for Lora-DTS to:

- Increased the Lora-DTS power, reduced the Lora-DTS frequency to:923.3-927.5MHz and update the software version from V1.0.0 to V1.0.1

Others all identical with the original version. The changes between the previous device and the current one are stated and guaranteed by the applicant▲.

#### Operation Frequency Detail: For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2412
Middle	2437
Highest	2462

**For BLE:**

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2402
Middle	2440
Highest	2480

**For Lora-DTS:**

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	923.3	5	925.7
2	923.9	6	926.3
3	924.5	7	926.9
4	925.1	8	927.5

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	923.3
Middle	925.1
Highest	927.5

**Antenna Information Detail▲:**

For Bluetooth/WiFi Antenna:

Antenna Usage	Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
Bluetooth/WiFi	Aitek Inc	PCB	50	0.8dBi/ 2.4~2.5GHz	Compliant

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

For Lora Antenna:

Antenna Usage	Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
Lora	Aitek Inc	Monopole	50	0dBi/ 2.4~2.5GHz	Compliant

The Method of §15.203 Compliance:

Antenna must be permanently attached to the unit.  
 Antenna must use a unique type of connector to attach to the EUT.  
 Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

#### Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter 1#	IDEA POWER ELECTRONIC TECHNOLOGY (DONGGUAN)CO.,LTD.	AD012A120100UV	Input: 100-240V~50/60Hz 0.4A Output: 12V 1.0A
Adapter 2#	Dongguan City Gangqi Electronic Co., Ltd.	GQ12-120100-CU	Input: 100-240V~50/60Hz 0.4A Output: 12V 1.0A

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

#### For 802.11b/g/n:

<b>EUT Operation Mode:</b>	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
<b>Equipment Modifications:</b>	No		
<b>EUT Exercise Software:</b>	Engineering Mode		

The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:

Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	Default	Default	Default
802.11g	6Mbps	Default	Default	Default
802.11n ht20	MCS0	Default	Default	Default

The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

#### For BLE:

<b>EUT Operation Mode:</b>	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
<b>Equipment Modifications:</b>	No		
<b>EUT Exercise Software:</b>	Engineering Mode		

The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:

Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
BLE	Default	Default	Default

#### For Lora-DTS:

<b>EUT Operation Mode:</b>	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
<b>Equipment Modifications:</b>	No		
<b>EUT Exercise Software:</b>	Engineering Mode		

The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:

Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
Lora-DTS	Default	Default	Default

### 1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	G510	CB30920865
SanDisk	TF Card	CZ36	521253

### 1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
RJ45 Cable	No	No	10	EUT	Laptop
DC Cable	No	No	1.2	Adapter	EUT

### 1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

## 2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant

Note:

For WiFi and BLE, per Spot check the RF output power and Radiated Spurious emissions above 1GHz, the changes were not affect the test results of the item. The test results please refer to the report of FCC ID: 2A5L2AMP500. Report number: CR22020030-00D.

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtainig their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### 3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiation Spurious Emissions


### 3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 3.2.2 EUT Setup

**Below 1GHz:**



**Above 1GHz:**



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98% <98%	1MHz	10 Hz 1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### 3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

### 3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


### 3.3 6 dB Emission Bandwidth:

#### 3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.3.2 EUT Setup



#### 3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times \text{RBW}$ .
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


### 3.4 Maximum peak conducted output power:

#### 3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

#### 3.4.2 EUT Setup



#### 3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- a) Set the EUT in transmitting mode.
- b) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- c) Add a correction factor to the display.
- d) Set the power meter to test peak output power, record the result.


### 3.5 Maximum power spectral density:

#### 3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

#### 3.5.2 EUT Setup



#### 3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq [3 \cdot \text{RBW}]$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


### 3.6 100 kHz Bandwidth of Frequency Band Edge:

#### 3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 3.6.2 EUT Setup



#### 3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

### 3.7 Duty Cycle:

#### 3.7.1 EUT Setup



#### 3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set  $RBW$  to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both  $RBW$  and  $VBW$  are  $> 50/T$  and the number of sweep points across duration  $T$  exceeds 100. (For example, if  $VBW$  and/or  $RBW$  are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

### 3.8 Antenna Requirement

#### 3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### 3.8.2 Judgment

Please refer to the Antenna Information detail in Section 1.

## 4. Test DATA AND RESULTS

### 4.1 AC Line Conducted Emissions

Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-25
Test Site:	CE	Test Mode:	Transmitting
Tester:	Nick Tang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25.9	Relative Humidity: (%)	63	ATM Pressure: (kPa)	100.2


### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2022-04-01	2023-03-31
R&S	EMI Test Receiver	ESR3	102726	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2021-08-08	2022-08-07
Audix	Test Software	E3	190306 (V9)	N/A	N/A


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Adapter 1#**


Line:




No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Detector
1	0.158	27.46	9.61	37.07	65.54	28.47	QP
2	0.158	9.46	9.61	19.07	55.54	36.47	Average
3	0.180	22.80	9.61	32.41	64.49	32.08	QP
4	0.180	8.04	9.61	17.65	54.49	36.84	Average
5	0.350	31.19	9.61	40.80	58.97	18.17	QP
6	0.350	18.76	9.61	28.37	48.97	20.60	Average
7	0.482	13.86	9.61	23.47	56.31	32.84	QP
8	0.482	5.57	9.61	15.18	46.31	31.13	Average
9	1.661	15.52	9.63	25.15	56.00	30.85	QP
10	1.661	2.31	9.63	11.94	46.00	34.06	Average
11	11.355	20.74	9.67	30.41	60.00	29.59	QP
12	11.355	4.66	9.67	14.33	50.00	35.67	Average

**Neutral:**

No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Detector
1	0.156	26.77	9.61	36.38	65.65	29.27	QP
2	0.156	10.93	9.61	20.54	55.65	35.11	Average
3	0.350	33.56	9.61	43.17	58.97	15.80	QP
4	0.350	26.43	9.61	36.04	48.97	12.93	Average
5	0.586	14.00	9.62	23.62	56.00	32.38	QP
6	0.586	6.41	9.62	16.03	46.00	29.97	Average
7	0.698	20.36	9.62	29.98	56.00	26.02	QP
8	0.698	12.52	9.62	22.14	46.00	23.86	Average
9	1.688	20.50	9.63	30.13	56.00	25.87	QP
10	1.688	7.27	9.63	16.89	46.00	29.11	Average
11	11.267	21.89	9.67	31.56	60.00	28.44	QP
12	11.267	8.75	9.67	18.42	50.00	31.58	Average

**Adapter 2#****Line:**

No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Detector
1	0.163	30.45	9.61	40.06	65.31	25.25	QP
2	0.163	9.21	9.61	18.82	55.31	36.49	Average
3	0.180	26.57	9.61	36.18	64.50	28.32	QP
4	0.180	9.53	9.61	19.14	54.50	35.36	Average
5	0.423	30.73	9.61	40.34	57.39	17.05	QP
6	0.423	27.28	9.61	36.89	47.39	10.50	Average
7	0.481	15.97	9.61	25.58	56.32	30.74	QP
8	0.481	9.03	9.61	18.64	46.32	27.68	Average
9	0.802	11.44	9.62	21.06	56.00	34.94	QP
10	0.802	3.46	9.62	13.08	46.00	32.92	Average
11	1.721	19.15	9.63	28.78	56.00	27.22	QP
12	1.721	6.06	9.63	15.69	46.00	30.31	Average

**Neutral:**

No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Detector
1	0.152	29.53	9.61	39.14	65.89	26.75	QP
2	0.152	16.67	9.61	26.28	55.89	29.61	Average
3	0.422	29.95	9.61	39.56	57.40	17.84	QP
4	0.422	20.74	9.61	30.35	47.40	17.05	Average
5	0.517	15.28	9.61	24.90	56.00	31.10	QP
6	0.517	8.22	9.61	17.83	46.00	28.17	Average
7	0.787	14.59	9.62	24.21	56.00	31.79	QP
8	0.787	2.93	9.62	12.55	46.00	33.45	Average
9	1.709	22.45	9.63	32.08	56.00	23.92	QP
10	1.709	8.31	9.63	17.93	46.00	28.07	Average
11	2.212	14.29	9.63	23.92	56.00	32.08	QP
12	2.212	5.68	9.63	15.32	46.00	30.68	Average

## 4.2 Radiation Spurious Emissions

Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-22~2022-04-27
Test Site:	966-1,966-2	Test Mode:	Transmitting
Tester:	Great Qiao, Tommy Luo, Veyo Zhang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	20.7~24.3	Relative Humidity: (%)	52~69	ATM Pressure: (kPa)	100.6~101.4

### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
Audix	Test Software	E3	201021 (V9)	N/A	N/A
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2021-08-08	2022-08-07

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


### Test Data:

Please refer to the below table and plots.


Note: The device can be mounted in multiple orientations, test was performed with X, Y, Z Axis according to C63.10 figure 8, the worst orientation was photographed and it's data was recorded.

**1) 30MHz-1GHz(Lora-DTS Middle channel was the worst)**

Adapter 1#:

**Horizontal:**


No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	30.211	5.28	27.53	32.81	40.00	7.19	QP
2	36.895	7.81	22.38	30.19	40.00	9.81	Peak
3	128.113	9.10	19.94	29.04	43.50	14.46	Peak
4	143.326	10.73	19.31	30.04	43.50	13.46	Peak
5	475.499	10.76	24.67	35.43	46.00	10.57	Peak
6	737.071	11.22	27.97	39.19	46.00	6.81	Peak

**Vertical:**


No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	30.317	5.84	27.44	33.28	40.00	6.72	QP
2	33.328	7.80	25.12	32.92	40.00	7.08	Peak
3	39.437	10.75	20.42	31.17	40.00	8.83	Peak
4	124.133	10.01	19.82	29.83	43.50	13.67	Peak
5	443.294	10.55	23.94	34.49	46.00	11.51	Peak
6	726.805	11.48	27.86	39.34	46.00	6.66	Peak

Adapter 2#:

**Horizontal:**



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	30.105	5.59	27.61	33.20	40.00	6.80	QP
2	31.620	5.24	26.45	31.68	40.00	8.32	QP
3	141.330	10.28	19.32	29.60	43.50	13.90	Peak
4	454.310	10.96	24.30	35.26	46.00	10.74	Peak
5	776.878	11.04	28.45	39.49	46.00	6.51	Peak
6	30.105	5.59	27.61	33.20	40.00	6.80	QP

**Vertical:**

No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	30.105	5.52	27.61	33.13	40.00	6.87	QP
2	31.289	5.86	26.69	32.55	40.00	7.45	QP
3	37.416	9.81	22.00	31.81	40.00	8.19	Peak
4	126.772	8.83	19.86	28.69	43.50	14.81	Peak
5	455.906	10.44	24.31	34.75	46.00	11.25	Peak
6	691.987	11.76	27.50	39.26	46.00	6.74	Peak

## Lora-DTS:1-10GHz and Bandedge:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
Low Channel: 923.3MHz							
1846.60	41.49	PK	H	1.51	43.00	74.00	31.00
1846.60	36.66	AV	H	1.51	38.17	54.00	15.83
1846.60	37.06	PK	V	1.51	38.57	74.00	35.43
1846.60	32.87	AV	V	1.51	34.38	54.00	19.62
2769.90	50.98	PK	H	5.00	55.98	74.00	18.02
2769.90	45.80	AV	H	5.00	50.80	54.00	3.20
2769.90	46.37	PK	V	5.00	51.37	74.00	22.63
2769.90	43.81	AV	V	5.00	48.81	54.00	5.19
3693.20	34.54	PK	H	8.32	42.86	74.00	31.14
3693.20	21.39	AV	H	8.32	29.71	54.00	24.29
3693.20	34.83	PK	V	8.32	43.15	74.00	30.85
3693.20	21.39	AV	V	8.32	29.71	54.00	24.29
923.30	80.70	QP	H	29.63	110.33	N/A	N/A
923.30	91.10	QP	V	29.63	120.73	N/A	N/A
902.00	5.60	QP	V	29.46	35.06	100.73	65.67
Middle Channel: 925.1 MHz							
1850.20	42.27	PK	H	1.53	43.80	74.00	30.20
1850.20	37.23	AV	H	1.53	38.76	54.00	15.24
1850.20	39.81	PK	V	1.53	41.34	74.00	32.66
1850.20	34.36	AV	V	1.53	35.89	54.00	18.11
2775.30	49.03	PK	H	5.02	54.05	74.00	19.95
2775.30	45.43	AV	H	5.02	50.45	54.00	3.55
2775.30	47.96	PK	V	5.02	52.98	74.00	21.02
2775.30	43.73	AV	V	5.02	48.75	54.00	5.25
3700.40	35.41	PK	H	8.36	43.77	74.00	30.23
3700.40	23.34	AV	H	8.36	31.70	54.00	22.30
3700.40	35.01	PK	V	8.36	43.37	74.00	30.63
3700.40	22.90	AV	V	8.36	31.26	54.00	22.74
925.10	80.80	QP	H	29.66	110.46	N/A	N/A
925.10	91.20	QP	V	29.66	120.86	N/A	N/A
High Channel: 927.5MHz							
1855.00	42.88	PK	H	1.57	44.45	74.00	29.55
1855.00	38.77	AV	H	1.57	40.34	54.00	13.66
1855.00	39.75	PK	V	1.57	41.32	74.00	32.68
1855.00	35.57	AV	V	1.57	37.14	54.00	16.86
2782.50	50.28	PK	H	5.04	55.32	74.00	18.68
2782.50	45.72	AV	H	5.04	50.76	54.00	3.24
2782.50	49.26	PK	V	5.04	54.30	74.00	19.70
2782.50	44.07	AV	V	5.04	49.11	54.00	4.89
3710.00	35.88	PK	H	8.38	44.26	74.00	29.74
3710.00	23.34	AV	H	8.38	31.72	54.00	22.28
3710.00	35.81	PK	V	8.38	44.19	74.00	29.81
3710.00	22.99	AV	V	8.38	31.37	54.00	22.63
927.50	80.30	QP	H	29.70	110.00	N/A	N/A
927.50	90.40	QP	V	29.70	120.10	N/A	N/A
928.00	54.60	QP	V	29.70	84.30	100.10	15.80


**Simultaneous transmission:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
802.11b mode high channel+ Lora-DTS Middle channel							
4924.00	38.41	PK	H	11.18	49.59	74.00	24.41
4924.00	31.02	AV	H	11.18	42.20	54.00	11.80
7386.00	32.25	PK	H	14.89	47.14	74.00	26.86
7386.00	23.69	AV	H	14.89	38.58	54.00	15.42
1850.20	39.15	PK	H	1.53	40.68	74.00	33.32
1850.20	32.55	AV	H	1.53	34.08	54.00	19.92
1850.20	39.47	PK	V	1.53	41.00	74.00	33.00
1850.20	33.02	AV	V	1.53	34.55	54.00	19.45
2775.30	33.69	PK	H	5.02	38.71	74.00	35.29
2775.30	21.39	AV	H	5.02	26.41	54.00	27.59

**Spot Check Radiation Spurious Emissions for BLE and WiFi:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
802.11b mode high channel							
2462.00	80.73	PK	H	31.63	112.36	N/A	N/A
2462.00	74.91	AV	H	31.63	106.54	N/A	N/A
2462.00	77.33	PK	V	31.63	108.96	N/A	N/A
2462.00	70.76	AV	V	31.63	102.39	N/A	N/A
2483.50	32.71	PK	H	31.64	64.35	74.00	9.65
2483.50	17.39	AV	H	31.64	49.03	54.00	4.97
4924.00	37.99	PK	H	11.18	49.17	74.00	24.83
4924.00	30.56	AV	H	11.18	41.74	54.00	12.26
7386.00	35.51	PK	H	14.89	50.40	74.00	23.60
7386.00	23.51	AV	H	14.89	38.40	54.00	15.60
BLE Middle channel							
2440.00	67.59	PK	H	31.60	99.19	N/A	N/A
2440.00	67.12	AV	H	31.60	98.72	N/A	N/A
2440.00	59.25	PK	V	31.60	90.85	N/A	N/A
2440.00	57.16	AV	V	31.60	88.76	N/A	N/A
4880.00	34.29	PK	H	11.07	45.36	74.00	28.64
4880.00	21.36	AV	H	11.07	32.43	54.00	21.57
7320.00	33.97	PK	H	14.80	48.77	74.00	25.23
7320.00	21.91	AV	H	14.80	36.71	54.00	17.29

**Worst Test plots**(Low-DTS Low channel was the worst)



**4.3 6 dB Emission Bandwidth:**

Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	24.3	Relative Humidity: (%)	64	ATM Pressure: (kPa)	100.7
-------------------	------	------------------------	----	---------------------	-------


**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
Lora-DTS	923.3	0.640	0.5
	925.1	0.651	0.5
	927.5	0.607	0.5



#### 4.4 Maximum conducted output power:

Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.3	Relative Humidity: (%)	64	ATM Pressure: (kPa)	100.7

#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2021-07-22	2022-07-21
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### Test Data:

Test Modes	Test Channel	Test Frequency (MHz)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
Lora-DTS	Low	923.3	27.46	≤30
	Middle	925.1	27.36	≤30
	High	927.5	27.25	≤30

**Spot Check with 802.11 and BLE power:**

Test Modes	Test Channel	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b	Lowest	2412	21.67	30
	Middle	2437	21.31	30
	Highest	2462	21.47	30
802.11g	Lowest	2412	25.10	30
	Middle	2437	25.02	30
	Highest	2462	25.09	30
802.11n ht20	Lowest	2412	24.56	30
	Middle	2437	<b>25.27</b>	30
	Highest	2462	25.17	30
BLE	Lowest	2402	3.07	30
	Middle	2440	<b>3.28</b>	30
	Highest	2480	2.97	30

**4.5 Maximum power spectral density:**

Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	24.3	Relative Humidity: (%)	64	ATM Pressure: (kPa)	100.7
----------------------	------	---------------------------	----	------------------------	-------


**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Channel	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Lora-DTS	923.3	7.83	≤8.00
	925.1	7.59	≤8.00
	927.5	7.13	≤8.00



#### 4.6 100 kHz Bandwidth of Frequency Band Edge:


Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.3	Relative Humidity: (%)	64	ATM Pressure: (kPa)	100.7

#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



#### 4.7 Duty Cycle:

Serial Number:	CR22020030-RF-S1	Test Date:	2022-04-22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.3	Relative Humidity: (%)	64	ATM Pressure: (kPa)	100.7


#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### Test Data:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)
Lora-DTS	100	100	100.00



## 5. RF EXPOSURE EVALUATION

### 5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

#### 5.1.1 Applicable Standard

FCC §15.247 (i) & §1.1310 & §2.1091

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### 5.1.2 Procedure

Prediction of power density at the distance of the applicable MPE limit

S = PG/4πR<sup>2</sup> = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

### 5.1.3 Calculated Data:

Radio	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
Lora-DSS	902.3-914.9	0	1.00	21	125.89	20.00	0.03	0.60
Lora-DTS	923.3-927.5	0	1.00	27.5	562.34	20.00	0.11	0.62
Bluetooth	2402-2480	0.8	1.20	9	7.94	20.00	0.002	1.0
WLAN	2412-2462	0.8	1.20	26	398.11	20.00	0.10	1.0

The WLAN 2.4G or BLE can't transmit simultaneously, Wi-Fi/BLE can transmit simultaneously with Lora:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{WLAN}/S_{limit-WLAN} + S_{Lora}/S_{limit-Lora}$$

$$= 0.11/0.62 + 0.10/1$$

$$= 0.28$$

$$< 1.0$$

**Result:** The device meet FCC MPE at 20 cm distance

===== END OF REPORT =====