

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is an Drone Glow UFO 5inch operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: 2.0 dBm ( $\pm 3$ dB)

The nominal radiated output power (e.i.r.p) specified: 2.0 dBm ( $\pm 3$ dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 98.4 dB $\mu$ V/m at 3m in the frequency 2415MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = 3.17dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 96.2 dB $\mu$ V/m at 3m in the frequency 2472MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = 0.97dBm  
which is within the production variation.

The maximum conducted output power specified is 5.0dBm= 3.162mW

The source- based time-averaging conducted output power  
 $= 3.162 * \text{Duty cycle mW} = 3.162 \text{ mW} * 0.1314 = 0.415 \text{ mW}$

The SAR Exclusion Threshold Level:

$$P_{th}(\text{mW}) = \text{ERP}_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left( \frac{60}{\text{ERP}_{20\text{cm}} \sqrt{f}} \right))$$
$$= 3060 * (0.5/20)^{1.9} \text{ mW}$$
$$= 2.72 \text{ mW}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 10.1449ms

Effective period of the cycle = 1333.3 $\mu$ s x1 = 1.3333ms

DC = 1.3333ms / 10.1449ms = 0.1314 or 13.14%