



FCC Part 15C Test Report

FCC ID:2A5NQ-T2

Applicant: Shenzhen Xiyu Technology Co., Ltd.

Address: 1004, No.8, Dongfangbei Lane 4th Shawanxia Village, Nanwan St., Longgang Dist., Shenzhen, CHINA

Manufacturer: Shenzhen Xiyu Technology Co., Ltd.

Address: 1004, No.8, Dongfangbei Lane 4th Shawanxia Village, Nanwan St., Longgang Dist., Shenzhen, CHINA

EUT: Translator

Trade Mark: Ifanin, Alopoon, pulomi

Model Number: T2

Date of Receipt: Mar. 03, 2022

Test Date: Mar. 03, 2022 – Mar. 11, 2022

Date of Report: Mar. 11, 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.249
ANSI C63.10:2013

Test Result: Pass

Report Number: DL-20220311015E

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	6
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	7
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	7
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	7
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	8
3 . EMC EMISSION TEST	9
3.1 CONDUCTED EMISSION MEASUREMENT	9
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	9
3.1.2 TEST PROCEDURE	9
3.1.3 DEVIATION FROM TEST STANDARD	9
3.1.4 TEST SETUP	10
3.1.5 EUT OPERATING CONDITIONS	10
3.1.6 TEST RESULTS	10
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE	16
3.2.3 DEVIATION FROM TEST STANDARD	16
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	18
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	19
3.2.8 TEST RESULTS (1GHZ~25GHZ)	23
3.3 RADIATED BAND EMISSION MEASUREMENT	29
3.3.1 TEST REQUIREMENT:	29
3.3.2 TEST PROCEDURE	29
3.3.3 DEVIATION FROM TEST STANDARD	29
3.3.4 TEST SETUP	30
3.3.5 EUT OPERATING CONDITIONS	30
4 . BANDWIDTH TEST	37
4.1 APPLIED PROCEDURES / LIMIT	37
4.1.1 TEST PROCEDURE	37
4.1.2 DEVIATION FROM STANDARD	37
4.1.3 TEST SETUP	37
4.1.4 EUT OPERATION CONDITIONS	37



Table of Contents	Page
4.1.5 TEST RESULTS	38
5 . ANTENNA REQUIREMENT	50
5.1 STANDARD REQUIREMENT	50
5.2 EUT ANTENNA	50
6 . TEST SEUUP PHOTO	51
7 . EUT PHOTO	53



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.249(c)	Fundamental &Radiated Spurious Emission Measurement	PASS	
15.205	Band Edge Emission	PASS	
15.215	20dB Bandwidth	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Translator
Trademark	Ifanin, Alopooon, pulomi
Model No.:	T2
Model Difference	N/A
Operation Frequency:	2402~2480MHz
Channel numbers:	79 Channels
Transfer Rate:	1/2/3Mbps
Channel separation	1MHz
Modulation technology:	GFSK, PI/4 DQPSK, 8DPSK
Antenna Type:	Internal Antenna
Antenna gain:	2dBi
Power supply:	DC 3.7V from battery DC 5V from charger

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



3.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Mode(s) mentioned above was evaluated respectively.			
Pretest Mode		Description	
Mode 1	CH00	GFSK,PI/4 DQPSK, 8DPSK	
Mode 2	CH39		
Mode 3	CH78		
Mode 4	Link Mode		
For Conducted & Radiated Emission			
Final Test Mode		Description	
Mode 1	CH00	GFSK,PI/4 DQPSK, 8DPSK	
Mode 2	CH39		
Mode 3	CH78		
Mode 4	Link Mode		


Note:

(1) The measurements are performed at the highest, middle, lowest available channels.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Translator	T2	N/A	EUT
E-2	Adapter	HW-0501000E	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C1	No	No	0.5m	Mini USB Line

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Test software Version	Test program: Bluetest 3		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Setting of Software	0	0	0



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 20db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 06, 2021	Nov. 05, 2022
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 06, 2021	Nov. 05, 2022
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 06, 2021	Nov. 05, 2022
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 06, 2021	Nov. 05, 2022
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 06, 2021	Nov. 05, 2022
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 06, 2021	Nov. 05, 2022
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 06, 2021	Nov. 05, 2022
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 06, 2021	Nov. 05, 2022
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 06, 2021	Nov. 05, 2022
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 06, 2021	Nov. 05, 2022
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 06, 2021	Nov. 05, 2022
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 06, 2021	Nov. 05, 2022
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 06, 2021	Nov. 05, 2022
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 06, 2021	Nov. 05, 2022
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 06, 2021	Nov. 05, 2022
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 06, 2021	Nov. 05, 2022

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 25, 2019	Nov. 24, 2022
2	EMI Receiver	R&S	ESR	101421	Nov. 06, 2021	Nov. 05, 2022
3	LISN	R&S	ENV216	102417	Nov. 06, 2021	Nov. 05, 2022
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 06, 2021	Nov. 05, 2022

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.5 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4(module 1)




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3345	29.89	9.04	38.93	59.34	20.41	QP	P	
2	0.3345	19.25	9.04	28.29	49.34	21.05	AVG	P	
3 *	0.5055	43.78	9.19	52.97	56.00	3.03	QP	P	
4	0.5055	31.03	9.19	40.22	46.00	5.78	AVG	P	
5	0.9644	33.92	9.29	43.21	56.00	12.79	QP	P	
6	0.9644	18.05	9.29	27.34	46.00	18.66	AVG	P	
7	1.4008	30.26	9.51	39.77	56.00	16.23	QP	P	
8	1.4008	16.02	9.51	25.53	46.00	20.47	AVG	P	
9	2.2334	28.06	9.56	37.62	56.00	18.38	QP	P	
10	2.2334	14.45	9.56	24.01	46.00	21.99	AVG	P	
11	10.3290	35.15	9.89	45.04	60.00	14.96	QP	P	
12	10.3290	25.20	9.89	35.09	50.00	14.91	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4(module 1)




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3660	29.87	9.08	38.95	58.59	19.64	QP	P	
2	0.3660	11.92	9.08	21.00	48.59	27.59	AVG	P	
3 *	0.5055	41.95	9.19	51.14	56.00	4.86	QP	P	
4	0.5055	24.36	9.19	33.55	46.00	12.45	AVG	P	
5	0.9194	31.71	9.31	41.02	56.00	14.98	QP	P	
6	0.9194	14.74	9.31	24.05	46.00	21.95	AVG	P	
7	1.3469	28.24	9.48	37.72	56.00	18.28	QP	P	
8	1.3469	11.09	9.48	20.57	46.00	25.43	AVG	P	
9	4.3530	26.03	9.64	35.67	56.00	20.33	QP	P	
10	4.3530	6.39	9.64	16.03	46.00	29.97	AVG	P	
11	10.2705	38.99	9.89	48.88	60.00	11.12	QP	P	
12	10.2705	20.81	9.89	30.70	50.00	19.30	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4(module 2)




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3750	23.80	9.28	33.08	58.39	25.31	QP	P	
2	0.3750	4.64	9.28	13.92	48.39	34.47	AVG	P	
3 *	0.4740	33.05	9.34	42.39	56.44	14.05	QP	P	
4	0.4740	14.76	9.34	24.10	46.44	22.34	AVG	P	
5	0.8384	24.42	9.50	33.92	56.00	22.08	QP	P	
6	0.8384	7.25	9.50	16.75	46.00	29.25	AVG	P	
7	2.1389	18.39	9.84	28.23	56.00	27.77	QP	P	
8	2.1389	-0.94	9.84	8.90	46.00	37.10	AVG	P	
9	6.4320	20.63	9.85	30.48	60.00	29.52	QP	P	
10	6.4320	-0.68	9.85	9.17	50.00	40.83	AVG	P	
11	9.8025	34.27	9.99	44.26	60.00	15.74	QP	P	
12	9.8025	20.17	9.99	30.16	50.00	19.84	AVG	P	



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4(module 2)



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4020	25.29	9.41	34.70	57.81	23.11	QP	P	
2	0.4020	10.59	9.41	20.00	47.81	27.81	AVG	P	
3 *	0.4785	33.40	9.52	42.92	56.37	13.45	QP	P	
4	0.4785	20.63	9.52	30.15	46.37	16.22	AVG	P	
5	0.8519	23.70	9.47	33.17	56.00	22.83	QP	P	
6	0.8519	10.19	9.47	19.66	46.00	26.34	AVG	P	
7	1.4594	19.70	9.76	29.46	56.00	26.54	QP	P	
8	1.4594	4.41	9.76	14.17	46.00	31.83	AVG	P	
9	4.6905	19.25	9.93	29.18	56.00	26.82	QP	P	
10	4.6905	3.50	9.93	13.43	46.00	32.57	AVG	P	
11	9.9240	33.63	10.18	43.81	60.00	16.19	QP	P	
12	9.9240	23.59	10.18	33.77	50.00	16.23	AVG	P	

**3.2 RADIATED EMISSION MEASUREMENT****3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)**

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 - 928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. (Above 18GHz the distance is 3 meter and table is 1.5 metre).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4(module 1)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		53.1313	34.24	-11.40	22.84	40.00	17.16	QP
2		91.1746	34.88	-15.58	19.30	43.50	24.20	QP
3		234.1684	41.33	-12.24	29.09	46.00	16.91	QP
4		251.1804	41.65	-11.73	29.92	46.00	16.08	QP
5		379.9141	37.11	-9.58	27.53	46.00	18.47	QP
6	*	642.8613	36.54	-4.88	31.66	46.00	14.34	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4(module 1)		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		57.7962	35.22	-11.77	23.45	40.00	16.55	QP
2		92.4624	34.62	-15.03	19.59	43.50	23.91	QP
3		234.1684	40.37	-11.60	28.77	46.00	17.23	QP
4		249.4250	39.17	-10.97	28.20	46.00	17.80	QP
5		472.1760	34.41	-6.53	27.88	46.00	18.12	QP
6	*	818.8341	35.17	-1.02	34.15	46.00	11.85	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4(module 2)		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	43.6584	40.06	-13.93	26.13	40.00	13.87	QP
2		64.6594	34.15	-15.61	18.54	40.00	21.46	QP
3		112.1305	40.28	-17.82	22.46	43.50	21.04	QP
4		143.8295	42.31	-18.91	23.40	43.50	20.10	QP
5		260.1444	35.18	-13.62	21.56	46.00	24.44	QP
6		609.9217	34.99	-6.51	28.48	46.00	17.52	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz		
Test Mode :	Mode 4(module 2)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	51.8430	35.48	-13.29	22.19	40.00	17.81	QP
2		75.4464	35.52	-18.41	17.11	40.00	22.89	QP
3		148.4410	44.26	-19.19	25.07	43.50	18.43	QP
4		159.2251	41.40	-18.62	22.78	43.50	20.72	QP
5		264.7457	37.59	-13.79	23.80	46.00	22.20	QP
6		321.0608	37.55	-12.48	25.07	46.00	20.93	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;

**3.2.8 TEST RESULTS (1GHZ~25GHZ)**Module 1
GFSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2402.00	112.46	52.16	2.78	27.41	90.49	114	-23.51	PK
V	2402.00	102.60	52.16	2.78	27.41	80.63	94	-13.37	AV
V	4804.00	76.51	51.74	3.08	31.25	59.10	74	-14.90	PK
V	4804.00	59.91	51.74	3.08	31.25	42.50	54	-11.50	AV
V	16134.00	52.07	51.56	7.36	41.57	49.44	74	-24.56	PK
H	2402.00	111.75	52.16	2.78	27.41	89.78	114	-24.22	PK
H	2402.00	104.50	52.16	2.78	27.41	82.53	94	-11.47	AV
H	4804.00	75.73	51.74	3.08	31.25	58.32	74	-15.68	PK
H	4804.00	58.64	51.74	3.08	31.25	41.23	54	-12.77	AV
H	16134.00	51.77	51.56	7.36	41.57	49.14	74	-24.86	PK
operation frequency:2441									
V	2441.00	111.47	52.11	2.82	27.47	89.65	114	-24.35	PK
V	2441.00	105.11	52.11	2.82	27.47	83.29	94	-10.71	AV
V	4882.00	76.94	51.77	3.03	31.34	59.54	74	-14.46	PK
V	4882.00	59.93	51.77	3.03	31.34	42.53	54	-11.47	AV
V	16134.00	52.15	51.56	7.36	41.57	49.52	74	-24.48	PK
H	2441.00	111.51	52.11	2.82	27.47	89.69	114	-24.31	PK
H	2441.00	104.04	52.11	2.82	27.47	82.22	94	-11.78	AV
H	4882.00	75.99	51.77	3.03	31.34	58.59	74	-15.41	PK
H	4882.00	59.24	51.77	3.03	31.34	41.84	54	-12.16	AV
H	16134.00	51.88	51.56	7.36	41.57	49.25	74	-24.75	PK
operation frequency:2480									
V	2480.00	112.30	52.23	2.86	27.44	90.37	114	-23.63	PK
V	2480.00	105.51	52.23	2.86	27.44	83.58	94	-10.42	AV
V	4960.00	77.81	51.69	3.05	31.39	60.56	74	-13.44	PK
V	4960.00	59.84	51.69	3.05	31.39	42.59	54	-11.41	AV
V	16134.00	52.14	51.56	7.36	41.57	49.51	74	-24.49	PK
H	2480.00	112.45	52.23	2.86	27.44	90.52	114	-23.48	PK
H	2480.00	104.76	52.23	2.86	27.44	82.83	94	-11.17	AV
H	4960.00	77.16	51.69	3.05	31.39	59.91	74	-14.09	PK
H	4960.00	58.83	51.69	3.05	31.39	41.58	54	-12.42	AV
H	16134.00	51.94	51.56	7.36	41.57	49.31	74	-24.69	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



PI/4 DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2402									
V	2402.00	112.74	52.16	2.78	27.41	90.77	114	-23.23	PK
V	2402.00	103.20	52.16	2.78	27.41	81.23	94	-12.77	AV
V	4804.00	77.02	51.74	3.08	31.25	59.61	74	-14.39	PK
V	4804.00	61.27	51.74	3.08	31.25	43.86	54	-10.14	AV
V	16134.00	52.07	51.56	7.36	41.57	49.44	74	-24.56	PK
H	2402.00	112.95	52.16	2.78	27.41	90.98	114	-23.02	PK
H	2402.00	105.91	52.16	2.78	27.41	83.94	94	-10.06	AV
H	4804.00	78.90	51.74	3.08	31.25	61.49	74	-12.51	PK
H	4804.00	59.90	51.74	3.08	31.25	42.49	54	-11.51	AV
H	16134.00	51.81	51.56	7.36	41.57	49.18	74	-24.82	PK
operation frequency:2441									
V	2441.00	111.96	52.11	2.82	27.47	90.14	114	-23.86	PK
V	2441.00	105.09	52.11	2.82	27.47	83.27	94	-10.73	AV
V	4882.00	76.82	51.77	3.03	31.34	59.42	74	-14.58	PK
V	4882.00	61.01	51.77	3.03	31.34	43.61	54	-10.39	AV
V	16134.00	52.25	51.56	7.36	41.57	49.62	74	-24.38	PK
H	2441.00	112.03	52.11	2.82	27.47	90.21	114	-23.79	PK
H	2441.00	104.94	52.11	2.82	27.47	83.12	94	-10.88	AV
H	4882.00	75.84	51.77	3.03	31.34	58.44	74	-15.56	PK
H	4882.00	60.18	51.77	3.03	31.34	42.78	54	-11.22	AV
H	16134.00	51.80	51.56	7.36	41.57	49.17	74	-24.83	PK
operation frequency:2480									
V	2480.00	112.65	52.23	2.86	27.44	90.72	114	-23.28	PK
V	2480.00	104.72	52.23	2.86	27.44	82.79	94	-11.21	AV
V	4960.00	77.00	51.69	3.05	31.39	59.75	74	-14.25	PK
V	4960.00	60.28	51.69	3.05	31.39	43.03	54	-10.97	AV
V	16134.00	52.13	51.56	7.36	41.57	49.50	74	-24.50	PK
H	2480.00	112.85	52.23	2.86	27.44	90.92	114	-23.08	PK
H	2480.00	103.98	52.23	2.86	27.44	82.05	94	-11.95	AV
H	4960.00	75.93	51.69	3.05	31.39	58.68	74	-15.32	PK
H	4960.00	59.19	51.69	3.05	31.39	41.94	54	-12.06	AV
H	16134.00	52.09	51.56	7.36	41.57	49.46	74	-24.54	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



8 DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
operation frequency:2402									
V	2402.00	112.52	52.16	2.78	27.41	90.55	114	-23.45	PK
V	2402.00	103.00	52.16	2.78	27.41	81.03	94	-12.97	AV
V	4804.00	76.87	51.74	3.08	31.25	59.46	74	-14.54	PK
V	4804.00	61.15	51.74	3.08	31.25	43.74	54	-10.26	AV
V	16134.00	52.97	51.56	7.36	41.57	50.34	74	-23.66	PK
H	2402.00	112.72	52.16	2.78	27.41	90.75	114	-23.25	PK
H	2402.00	105.70	52.16	2.78	27.41	83.73	94	-10.27	AV
H	4804.00	78.75	51.74	3.08	31.25	61.34	74	-12.66	PK
H	4804.00	59.78	51.74	3.08	31.25	42.37	54	-11.63	AV
H	16134.00	52.71	51.56	7.36	41.57	50.08	74	-23.92	PK
operation frequency:2441									
V	2441.00	111.74	52.11	2.82	27.47	89.92	114	-24.08	PK
V	2441.00	104.88	52.11	2.82	27.47	83.06	94	-10.94	AV
V	4882.00	76.67	51.77	3.03	31.34	59.27	74	-14.73	PK
V	4882.00	60.89	51.77	3.03	31.34	43.49	54	-10.51	AV
V	16134.00	51.15	51.56	7.36	41.57	48.52	74	-25.48	PK
H	2441.00	111.81	52.11	2.82	27.47	89.99	114	-24.01	PK
H	2441.00	104.73	52.11	2.82	27.47	82.91	94	-11.09	AV
H	4882.00	75.69	51.77	3.03	31.34	58.29	74	-15.71	PK
H	4882.00	60.06	51.77	3.03	31.34	42.66	54	-11.34	AV
H	16134.00	52.70	51.56	7.36	41.57	50.07	74	-23.93	PK
operation frequency:2480									
V	2480.00	112.43	52.23	2.86	27.44	90.50	114	-23.50	PK
V	2480.00	104.51	52.23	2.86	27.44	82.58	94	-11.42	AV
V	4960.00	76.85	51.69	3.05	31.39	59.60	74	-14.40	PK
V	4960.00	60.16	51.69	3.05	31.39	42.91	54	-11.09	AV
V	16134.00	53.03	51.56	7.36	41.57	50.40	74	-23.60	PK
H	2480.00	112.63	52.23	2.86	27.44	90.70	114	-23.30	PK
H	2480.00	103.78	52.23	2.86	27.44	81.85	94	-12.15	AV
H	4960.00	75.78	51.69	3.05	31.39	58.53	74	-15.47	PK
H	4960.00	59.07	51.69	3.05	31.39	41.82	54	-12.18	AV
H	16134.00	51.99	51.56	7.36	41.57	49.36	74	-24.64	PK
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									

Module 2
GFSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2402.00	112.39	52.16	2.78	27.41	90.42	114	-23.58	PK
V	2402.00	102.54	52.16	2.78	27.41	80.57	94	-13.43	AV
V	4804.00	76.46	51.74	3.08	31.25	59.05	74	-14.95	PK
V	4804.00	59.87	51.74	3.08	31.25	42.46	54	-11.54	AV
V	16134.00	52.04	51.56	7.36	41.57	49.41	74	-24.59	PK
H	2402.00	111.68	52.16	2.78	27.41	89.71	114	-24.29	PK
H	2402.00	104.44	52.16	2.78	27.41	82.47	94	-11.53	AV
H	4804.00	75.68	51.74	3.08	31.25	58.27	74	-15.73	PK
H	4804.00	58.60	51.74	3.08	31.25	41.19	54	-12.81	AV
H	16134.00	51.74	51.56	7.36	41.57	49.11	74	-24.89	PK
operation frequency:2441									
V	2441.00	111.40	52.11	2.82	27.47	89.58	114	-24.42	PK
V	2441.00	105.05	52.11	2.82	27.47	83.23	94	-10.77	AV
V	4882.00	76.89	51.77	3.03	31.34	59.49	74	-14.51	PK
V	4882.00	59.89	51.77	3.03	31.34	42.49	54	-11.51	AV
V	16134.00	52.12	51.56	7.36	41.57	49.49	74	-24.51	PK
H	2441.00	111.44	52.11	2.82	27.47	89.62	114	-24.38	PK
H	2441.00	103.98	52.11	2.82	27.47	82.16	94	-11.84	AV
H	4882.00	75.94	51.77	3.03	31.34	58.54	74	-15.46	PK
H	4882.00	59.20	51.77	3.03	31.34	41.80	54	-12.20	AV
H	16134.00	51.85	51.56	7.36	41.57	49.22	74	-24.78	PK
operation frequency:2480									
V	2480.00	112.23	52.23	2.86	27.44	90.30	114	-23.70	PK
V	2480.00	105.45	52.23	2.86	27.44	83.52	94	-10.48	AV
V	4960.00	77.76	51.69	3.05	31.39	60.51	74	-13.49	PK
V	4960.00	59.80	51.69	3.05	31.39	42.55	54	-11.45	AV
V	16134.00	52.11	51.56	7.36	41.57	49.48	74	-24.52	PK
H	2480.00	112.38	52.23	2.86	27.44	90.45	114	-23.55	PK
H	2480.00	104.70	52.23	2.86	27.44	82.77	94	-11.23	AV
H	4960.00	77.11	51.69	3.05	31.39	59.86	74	-14.14	PK
H	4960.00	58.79	51.69	3.05	31.39	41.54	54	-12.46	AV
H	16134.00	51.91	51.56	7.36	41.57	49.28	74	-24.72	PK
Remark:									
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit									
2. If peak below the average limit, the average emission was no test.									
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



PI/4 DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2402.00	112.67	52.16	2.78	27.41	90.70	114	-23.30	PK
V	2402.00	103.14	52.16	2.78	27.41	81.17	94	-12.83	AV
V	4804.00	76.97	51.74	3.08	31.25	59.56	74	-14.44	PK
V	4804.00	61.23	51.74	3.08	31.25	43.82	54	-10.18	AV
V	16134.00	52.04	51.56	7.36	41.57	49.41	74	-24.59	PK
H	2402.00	112.88	52.16	2.78	27.41	90.91	114	-23.09	PK
H	2402.00	105.85	52.16	2.78	27.41	83.88	94	-10.12	AV
H	4804.00	78.85	51.74	3.08	31.25	61.44	74	-12.56	PK
H	4804.00	59.86	51.74	3.08	31.25	42.45	54	-11.55	AV
H	16134.00	51.78	51.56	7.36	41.57	49.15	74	-24.85	PK
operation frequency:2441									
V	2441.00	111.89	52.11	2.82	27.47	90.07	114	-23.93	PK
V	2441.00	105.03	52.11	2.82	27.47	83.21	94	-10.79	AV
V	4882.00	76.77	51.77	3.03	31.34	59.37	74	-14.63	PK
V	4882.00	60.97	51.77	3.03	31.34	43.57	54	-10.43	AV
V	16134.00	52.22	51.56	7.36	41.57	49.59	74	-24.41	PK
H	2441.00	111.96	52.11	2.82	27.47	90.14	114	-23.86	PK
H	2441.00	104.88	52.11	2.82	27.47	83.06	94	-10.94	AV
H	4882.00	75.79	51.77	3.03	31.34	58.39	74	-15.61	PK
H	4882.00	60.14	51.77	3.03	31.34	42.74	54	-11.26	AV
H	16134.00	51.77	51.56	7.36	41.57	49.14	74	-24.86	PK
operation frequency:2480									
V	2480.00	112.58	52.23	2.86	27.44	90.65	114	-23.35	PK
V	2480.00	104.66	52.23	2.86	27.44	82.73	94	-11.27	AV
V	4960.00	76.95	51.69	3.05	31.39	59.70	74	-14.30	PK
V	4960.00	60.24	51.69	3.05	31.39	42.99	54	-11.01	AV
V	16134.00	52.10	51.56	7.36	41.57	49.47	74	-24.53	PK
H	2480.00	112.78	52.23	2.86	27.44	90.85	114	-23.15	PK
H	2480.00	103.92	52.23	2.86	27.44	81.99	94	-12.01	AV
H	4960.00	75.88	51.69	3.05	31.39	58.63	74	-15.37	PK
H	4960.00	59.15	51.69	3.05	31.39	41.90	54	-12.10	AV
H	16134.00	52.06	51.56	7.36	41.57	49.43	74	-24.57	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



8 DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2402									
V	2402.00	112.45	52.16	2.78	27.41	90.48	114	-23.52	PK
V	2402.00	102.94	52.16	2.78	27.41	80.97	94	-13.03	AV
V	4804.00	76.82	51.74	3.08	31.25	59.41	74	-14.59	PK
V	4804.00	61.11	51.74	3.08	31.25	43.70	54	-10.30	AV
V	16134.00	52.94	51.56	7.36	41.57	50.31	74	-23.69	PK
H	2402.00	112.65	52.16	2.78	27.41	90.68	114	-23.32	PK
H	2402.00	105.64	52.16	2.78	27.41	83.67	94	-10.33	AV
H	4804.00	78.70	51.74	3.08	31.25	61.29	74	-12.71	PK
H	4804.00	59.74	51.74	3.08	31.25	42.33	54	-11.67	AV
H	16134.00	52.68	51.56	7.36	41.57	50.05	74	-23.95	PK
operation frequency:2441									
V	2441.00	111.67	52.11	2.82	27.47	89.85	114	-24.15	PK
V	2441.00	104.82	52.11	2.82	27.47	83.00	94	-11.00	AV
V	4882.00	76.62	51.77	3.03	31.34	59.22	74	-14.78	PK
V	4882.00	60.85	51.77	3.03	31.34	43.45	54	-10.55	AV
V	16134.00	51.12	51.56	7.36	41.57	48.49	74	-25.51	PK
H	2441.00	111.74	52.11	2.82	27.47	89.92	114	-24.08	PK
H	2441.00	104.67	52.11	2.82	27.47	82.85	94	-11.15	AV
H	4882.00	75.64	51.77	3.03	31.34	58.24	74	-15.76	PK
H	4882.00	60.02	51.77	3.03	31.34	42.62	54	-11.38	AV
H	16134.00	52.67	51.56	7.36	41.57	50.04	74	-23.96	PK
operation frequency:2480									
V	2480.00	112.36	52.23	2.86	27.44	90.43	114	-23.57	PK
V	2480.00	104.45	52.23	2.86	27.44	82.52	94	-11.48	AV
V	4960.00	76.80	51.69	3.05	31.39	59.55	74	-14.45	PK
V	4960.00	60.12	51.69	3.05	31.39	42.87	54	-11.13	AV
V	16134.00	53.00	51.56	7.36	41.57	50.37	74	-23.63	PK
H	2480.00	112.56	52.23	2.86	27.44	90.63	114	-23.37	PK
H	2480.00	103.72	52.23	2.86	27.44	81.79	94	-12.21	AV
H	4960.00	75.73	51.69	3.05	31.39	58.48	74	-15.52	PK
H	4960.00	59.03	51.69	3.05	31.39	41.78	54	-12.22	AV
H	16134.00	51.96	51.56	7.36	41.57	49.33	74	-24.67	PK
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit 2. If peak below the average limit, the average emission was no test. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.									



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.3.6 TEST RESULT

Module 1

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2402									
V	2390.00	75.70	52.12	2.73	27.38	53.69	74	-20.31	PK
V	2390.00	64.97	52.12	2.73	27.38	42.96	54	-11.04	AV
V	2400.00	75.65	52.16	2.78	27.41	53.68	74	-20.32	PK
V	2400.00	63.78	52.16	2.78	27.41	41.81	54	-12.19	AV
H	2390.00	76.18	52.12	2.73	27.38	54.17	74	-19.83	PK
H	2390.00	64.96	52.12	2.73	27.38	42.95	54	-11.05	AV
H	2400.00	75.84	52.16	2.78	27.41	53.87	74	-20.13	PK
H	2400.00	65.03	52.16	2.78	27.41	43.06	54	-10.94	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2480									
V	2483.50	75.82	52.23	2.86	27.44	53.89	74	-20.11	PK
V	2483.50	65.06	52.23	2.86	27.44	43.13	54	-10.87	AV
V	2500.00	76.18	52.26	2.88	27.49	54.29	74	-19.71	PK
V	2500.00	64.22	52.26	2.88	27.49	42.33	54	-11.67	AV
H	2483.50	76.04	52.23	2.86	27.44	54.11	74	-19.89	PK
H	2483.50	65.25	52.23	2.86	27.44	43.32	54	-10.68	AV
H	2500.00	76.09	52.26	2.88	27.49	54.20	74	-19.80	PK
H	2500.00	65.33	52.26	2.88	27.49	43.44	54	-10.56	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



PI/4 DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	75.81	52.12	2.73	27.38	53.80	74	-20.20	PK
V	2390.00	65.12	52.12	2.73	27.38	43.11	54	-10.89	AV
V	2400.00	75.74	52.16	2.78	27.41	53.77	74	-20.23	PK
V	2400.00	64.10	52.16	2.78	27.41	42.13	54	-11.87	AV
H	2390.00	75.68	52.12	2.73	27.38	53.67	74	-20.33	PK
H	2390.00	64.97	52.12	2.73	27.38	42.96	54	-11.04	AV
H	2400.00	75.78	52.16	2.78	27.41	53.81	74	-20.19	PK
H	2400.00	64.77	52.16	2.78	27.41	42.80	54	-11.20	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	75.80	52.23	2.86	27.44	53.87	74	-20.13	PK
V	2483.50	65.05	52.23	2.86	27.44	43.12	54	-10.88	AV
V	2500.00	75.74	52.26	2.88	27.49	53.85	74	-20.15	PK
V	2500.00	64.76	52.26	2.88	27.49	42.87	54	-11.13	AV
H	2483.50	76.00	52.23	2.86	27.44	54.07	74	-19.93	PK
H	2483.50	65.12	52.23	2.86	27.44	43.19	54	-10.81	AV
H	2500.00	75.71	52.26	2.88	27.49	53.82	74	-20.18	PK
H	2500.00	65.14	52.26	2.88	27.49	43.25	54	-10.75	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



8 DPSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	75.73	52.12	2.73	27.38	53.72	74	-20.28	PK
V	2390.00	65.05	52.12	2.73	27.38	43.04	54	-10.96	AV
V	2400.00	75.66	52.16	2.78	27.41	53.69	74	-20.31	PK
V	2400.00	64.03	52.16	2.78	27.41	42.06	54	-11.94	AV
H	2390.00	75.60	52.12	2.73	27.38	53.59	74	-20.41	PK
H	2390.00	64.90	52.12	2.73	27.38	42.89	54	-11.11	AV
H	2400.00	75.70	52.16	2.78	27.41	53.73	74	-20.27	PK
H	2400.00	64.70	52.16	2.78	27.41	42.73	54	-11.27	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	75.72	52.23	2.86	27.44	53.79	74	-20.21	PK
V	2483.50	64.98	52.23	2.86	27.44	43.05	54	-10.95	AV
V	2500.00	75.66	52.26	2.88	27.49	53.77	74	-20.23	PK
V	2500.00	64.69	52.26	2.88	27.49	42.80	54	-11.20	AV
H	2483.50	75.92	52.23	2.86	27.44	53.99	74	-20.01	PK
H	2483.50	65.05	52.23	2.86	27.44	43.12	54	-10.88	AV
H	2500.00	75.63	52.26	2.88	27.49	53.74	74	-20.26	PK
H	2500.00	65.07	52.26	2.88	27.49	43.18	54	-10.82	AV

Remark:

- Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
- If peak below the average limit, the average emission was no test.
- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Module 2
GFSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	75.65	52.12	2.73	27.38	53.64	74	-20.36	PK
V	2390.00	64.93	52.12	2.73	27.38	42.92	54	-11.08	AV
V	2400.00	75.60	52.16	2.78	27.41	53.63	74	-20.37	PK
V	2400.00	63.74	52.16	2.78	27.41	41.77	54	-12.23	AV
H	2390.00	76.13	52.12	2.73	27.38	54.12	74	-19.88	PK
H	2390.00	64.92	52.12	2.73	27.38	42.91	54	-11.09	AV
H	2400.00	75.79	52.16	2.78	27.41	53.82	74	-20.18	PK
H	2400.00	64.99	52.16	2.78	27.41	43.02	54	-10.98	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	75.77	52.23	2.86	27.44	53.84	74	-20.16	PK
V	2483.50	65.02	52.23	2.86	27.44	43.09	54	-10.91	AV
V	2500.00	76.13	52.26	2.88	27.49	54.24	74	-19.76	PK
V	2500.00	64.18	52.26	2.88	27.49	42.29	54	-11.71	AV
H	2483.50	75.99	52.23	2.86	27.44	54.06	74	-19.94	PK
H	2483.50	65.21	52.23	2.86	27.44	43.28	54	-10.72	AV
H	2500.00	76.04	52.26	2.88	27.49	54.15	74	-19.85	PK
H	2500.00	65.29	52.26	2.88	27.49	43.40	54	-10.60	AV

Remark:

- Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
- If peak below the average limit, the average emission was no test.
- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



PI/4 DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	75.76	52.12	2.73	27.38	53.75	74	-20.25	PK
V	2390.00	65.08	52.12	2.73	27.38	43.07	54	-10.93	AV
V	2400.00	75.69	52.16	2.78	27.41	53.72	74	-20.28	PK
V	2400.00	64.06	52.16	2.78	27.41	42.09	54	-11.91	AV
H	2390.00	75.63	52.12	2.73	27.38	53.62	74	-20.38	PK
H	2390.00	64.93	52.12	2.73	27.38	42.92	54	-11.08	AV
H	2400.00	75.73	52.16	2.78	27.41	53.76	74	-20.24	PK
H	2400.00	64.73	52.16	2.78	27.41	42.76	54	-11.24	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	75.75	52.23	2.86	27.44	53.82	74	-20.18	PK
V	2483.50	65.01	52.23	2.86	27.44	43.08	54	-10.92	AV
V	2500.00	75.69	52.26	2.88	27.49	53.80	74	-20.20	PK
V	2500.00	64.72	52.26	2.88	27.49	42.83	54	-11.17	AV
H	2483.50	75.95	52.23	2.86	27.44	54.02	74	-19.98	PK
H	2483.50	65.08	52.23	2.86	27.44	43.15	54	-10.85	AV
H	2500.00	75.66	52.26	2.88	27.49	53.77	74	-20.23	PK
H	2500.00	65.10	52.26	2.88	27.49	43.21	54	-10.79	AV

Remark:

3. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



8 DPSK

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2402									
V	2390.00	75.68	52.12	2.73	27.38	53.67	74	-20.33	PK
V	2390.00	65.01	52.12	2.73	27.38	43.00	54	-11.00	AV
V	2400.00	75.61	52.16	2.78	27.41	53.64	74	-20.36	PK
V	2400.00	63.99	52.16	2.78	27.41	42.02	54	-11.98	AV
H	2390.00	75.55	52.12	2.73	27.38	53.54	74	-20.46	PK
H	2390.00	64.86	52.12	2.73	27.38	42.85	54	-11.15	AV
H	2400.00	75.65	52.16	2.78	27.41	53.68	74	-20.32	PK
H	2400.00	64.66	52.16	2.78	27.41	42.69	54	-11.31	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2480									
V	2483.50	75.67	52.23	2.86	27.44	53.74	74	-20.26	PK
V	2483.50	64.94	52.23	2.86	27.44	43.01	54	-10.99	AV
V	2500.00	75.61	52.26	2.88	27.49	53.72	74	-20.28	PK
V	2500.00	64.65	52.26	2.88	27.49	42.76	54	-11.24	AV
H	2483.50	75.87	52.23	2.86	27.44	53.94	74	-20.06	PK
H	2483.50	65.01	52.23	2.86	27.44	43.08	54	-10.92	AV
H	2500.00	75.58	52.26	2.88	27.49	53.69	74	-20.31	PK
H	2500.00	65.03	52.26	2.88	27.49	43.14	54	-10.86	AV

Remark:

4. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



4. BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.215) , Subpart C	
Section	Test Item
15.215	Bandwidth

4.1.1 TEST PROCEDURE

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.





4.1.5 TEST RESULTS

Temperature:	25°C	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX Mode /CH00, CH39, CH78		


Module 1

	Frequency (MHz)	20dB Bandwidth (MHz)	Result
GFSK	2402	0.873	Pass
	2441	0.868	Pass
	2480	0.872	Pass
PI/4 DQPSK	2402	1.216	Pass
	2441	1.196	Pass
	2480	1.215	Pass
8 DPSK	2402	1.253	Pass
	2441	1.239	Pass
	2480	1.258	Pass






2441MHz




2480MHz




PI/4 DQPSK



2402MHz




2441MHz







8 DPSK



2402MHz




2441MHz







Module 2

	Frequency (MHz)	20dB Bandwidth (MHz)	Result
GFSK	2402	0.953	Pass
	2441	0.946	Pass
	2480	0.949	Pass
PI/4 DQPSK	2402	1.321	Pass
	2441	1.306	Pass
	2480	1.269	Pass
8 DPSK	2402	1.307	Pass
	2441	1.301	Pass
	2480	1.289	Pass






2441MHz




2480MHz




PI/4 DQPSK



2402MHz




2441MHz







8 DPSK



2402MHz



2441MHz





5. ANTENNA REQUIREMENT

5.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



5.2 EUT ANTENNA

The EUT antenna is Internal antenna, It comply with the standard requirement.



6. TEST SEUUP PHOTO

Radiated Measurement Photos





Conducted Measurement Photos





7. EUT PHOTO





***** END OF REPORT *****