



FCC RF Test Report

APPLICANT : Qingdao Chuangjian Weilai Technology Co., Ltd
EQUIPMENT : VR Motion Controller
BRAND NAME : PICO
MODEL NAME : C1C10
FCC ID : 2A5NV-C1C10L
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Oct. 02, 2023 ~ Oct. 09, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	8
2.4 EUT Operation Test Setup	9
2.5 Measurement Results Explanation Example.....	9
3 TEST RESULT	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	15
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	21
3.5 Radiated Band Edges and Spurious Emission Measurement	26
3.6 Antenna Requirements.....	30
4 LIST OF MEASURING EQUIPMENT.....	31
5 MEASUREMENT UNCERTAINTY.....	32
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR392708	Rev. 01	Initial issue of report	Nov. 01, 2023



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.50 dB at 2483.50 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Applicable	-
3.6	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Note: Not Applicable means after assessing, test items are not necessary to carry out.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Qingdao Chuangjian Weilai Technology Co., Ltd

3rd Floor, Building 4, 393 Songling Road, Laoshan District, Qingdao City, Shandong Province, China

1.2 Manufacturer

Qingdao Chuangjian Weilai Technology Co., Ltd

3rd Floor, Building 4, 393 Songling Road, Laoshan District, Qingdao City, Shandong Province, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	VR Motion Controller
Brand Name	PICO
Model Name	C1C10
FCC ID	2A5NV-C1C10L
SN	Conducted/Radiation: PA8S10DGH9200077A
HW Version	DVT1
SW Version	PR00xx
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Maximum Output Power to Antenna	7.47 dBm (0.0056 W)
99% Occupied Bandwidth	2.062MHz
Antenna Type / Gain	FPC Antenna with gain 0.43 dBi
Type of Modulation	nRF: GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH05-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	SPORTON	FCC 15C-15E Test Tools Ver10.0_210607	10.0
2.	03CH05-KS	AUDIX	E3	210616

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	nRF / GFSK
Conducted TCs	Mode 1: nRF TX CH00_2402 MHz
	Mode 2: nRF TX CH19_2440 MHz
	Mode 3: nRF TX CH39_2480 MHz
Radiated TCs	Mode 1: nRF TX CH00_2402 MHz
	Mode 2: nRF TX CH19_2440 MHz
	Mode 3: nRF TX CH39_2480 MHz

2.3 Connection Diagram of Test System

Radiated Emission:



2.4 EUT Operation Test Setup

For nRF function, the engineering test program was provided and enabled to make EUT continuous transmit.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.80 dB .

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.80 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


6 dB Bandwidth Plot on Channel 00



Date: 2.OCT.2023 11:40:12




6 dB Bandwidth Plot on Channel 19



Date: 2.OCT.2023 11:44:08

6 dB Bandwidth Plot on Channel 39




Date: 2.OCT.2023 11:47:07



3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

99% Occupied Bandwidth Plot on Channel 00






99% Occupied Bandwidth Plot on Channel 19



99% Occupied Bandwidth Plot on Channel 39



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 2.OCT.2023 11:40:50


PSD 100kHz Plot on Channel 19



Date: 2.OCT.2023 11:44:46



PSD 100kHz Plot on Channel 39




Date: 2.OCT.2023 11:47:45




3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 2.OCT.2023 11:40:31


PSD 3kHz Plot on Channel 19



Date: 2.OCT.2023 11:44:27



PSD 3kHz Plot on Channel 39



Date: 2.OCT.2023 11:47:26

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure


1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00




High Band Edge Plot on Channel 39




3.4.6 Test Result of Conducted Spurious Emission Plots


Conducted Spurious Emission Plot on GFSK Channel 00



Conducted Spurious Emission Plot on GFSK Channel 00




Conducted Spurious Emission Plot on GFSK Channel 19



Date: 2.OCT.2023 11:46:17


Conducted Spurious Emission Plot on GFSK Channel 19




Date: 2.OCT.2023 11:46:28



Conducted Spurious Emission Plot on GFSK Channel 39



Conducted Spurious Emission Plot on GFSK Channel 39



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Oct. 02, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Oct. 02, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Oct. 02, 2023	Jan. 04, 2024	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 13, 2022	Oct. 09, 2023	Oct. 12, 2023	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz, MAX 30dB	Mar. 24, 2023	Oct. 09, 2023	Mar. 23, 2024	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 16, 2022	Oct. 09, 2023	Oct. 15, 2023	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz~1GHz	Apr. 09, 2023	Oct. 09, 2023	Apr. 08, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Oct. 09, 2023	Apr. 05, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Oct. 09, 2023	Jan. 07, 2024	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 06, 2023	Oct. 09, 2023	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2023	Oct. 09, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz~18Ghz	Oct. 12, 2022	Oct. 09, 2023	Oct. 11, 2023	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 05, 2023	Oct. 09, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 09, 2023	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 09, 2023	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 09, 2023	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	± 0.46 dB
Conducted Emissions	± 2.26 dB
Occupied Channel Bandwidth	± 0.1 %
Conducted Power Spectral Density	± 0.88 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.28 dB
--	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.88 dB
--	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.26 dB
--	---------

----- THE END -----



Appendix A. Conducted Test Results

nRF

Test Engineer:	Long Wu	Temperature:	20~26	°C
Test Date:	2023.10.2	Relative Humidity:	40~51	%

nRF	
Power setting	
CH 00	8
CH 19	8
CH 39	8

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
nRF	2Mbps	1	0	2402	2.046	1.136	0.50	Pass
nRF	2Mbps	1	19	2440	2.050	1.132	0.50	Pass
nRF	2Mbps	1	39	2480	2.062	1.144	0.50	Pass

TEST RESULTS DATA
Peak Power TanRF

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
nRF	2Mbps	1	0	2402	7.31	30.00	0.43	7.74	36.00	Pass
nRF	2Mbps	1	19	2440	7.36	30.00	0.43	7.79	36.00	Pass
nRF	2Mbps	1	39	2480	7.47	30.00	0.43	7.90	36.00	Pass

TEST RESULTS DATA
Average Power TanRF
(Reporting Only)

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
nRF	2Mbps	1	0	2402	4.83	7.27
nRF	2Mbps	1	19	2440	4.83	7.34
nRF	2Mbps	1	39	2480	4.83	7.45

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
nRF	2Mbps	1	0	2402	6.33	-10.83	0.43	8.00	Pass
nRF	2Mbps	1	19	2440	6.21	-11.07	0.43	8.00	Pass
nRF	2Mbps	1	39	2480	6.35	-11.21	0.43	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. Radiated Spurious Emission

Test Engineer :	Carl Ni	Relative Humidity :	41 ~ 42 %
		Temperature :	22 ~ 23 °C

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	nRF	00	2402	2Mbps	-	-
Mode 2	2400-2483.5	1	nRF	19	2440	2Mbps	-	-
Mode 3	2400-2483.5	1	nRF	39	2480	2Mbps	-	-
Mode 4	2400-2483.5	1	nRF	39	2480	2Mbps		LF





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	nRF	00	2377.86	45.15	54.00	-8.85	H	AVERAGE	Pass	Band Edge
	nRF	00	4804.00	44.86	54.00	-9.14	V	AVERAGE	Pass	Harmonic
2	nRF	19	-	-	-	-	-	-	-	Band Edge
	nRF	19	4879.50	44.80	54.00	-9.20	V	Average	Pass	Harmonic
3	nRF	39	2483.50	49.50	54.00	-4.50	H	AVERAGE	Pass	Band Edge
	nRF	39	4960.50	41.46	54.00	-12.54	V	Average	Pass	Harmonic
4	nRF	39	959.26	32.37	46.00	-13.63	H	Peak	Pass	LF





Mode	1																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_nRF_CH00_2402MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2353.55</td><td>51.39</td><td>74.00</td><td>-22.61</td><td>43.29</td><td>31.96</td><td>7.05</td><td>36.91</td><td>6.00</td><td>238</td><td>287</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2353.55	51.39	74.00	-22.61	43.29	31.96	7.05	36.91	6.00	238	287	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>103.95</td><td>-----</td><td>-----</td><td>95.64</td><td>32.11</td><td>7.12</td><td>36.92</td><td>6.00</td><td>238</td><td>287</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	103.95	-----	-----	95.64	32.11	7.12	36.92	6.00	238	287	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2353.55	51.39	74.00	-22.61	43.29	31.96	7.05	36.91	6.00	238	287	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	103.95	-----	-----	95.64	32.11	7.12	36.92	6.00	238	287	PEAK																																																																																								
Avg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2377.86</td><td>45.15</td><td>54.00</td><td>-8.85</td><td>36.94</td><td>32.03</td><td>7.09</td><td>36.91</td><td>6.00</td><td>238</td><td>287</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2377.86	45.15	54.00	-8.85	36.94	32.03	7.09	36.91	6.00	238	287	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>101.96</td><td>-----</td><td>-----</td><td>93.65</td><td>32.11</td><td>7.12</td><td>36.92</td><td>6.00</td><td>238</td><td>287</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	101.96	-----	-----	93.65	32.11	7.12	36.92	6.00	238	287	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2377.86	45.15	54.00	-8.85	36.94	32.03	7.09	36.91	6.00	238	287	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	101.96	-----	-----	93.65	32.11	7.12	36.92	6.00	238	287	AVERAGE																																																																																								





Mode	1																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_nRF_CH00_2402MHz																																																																																																		
ANT	1																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2353.68</td><td>50.62</td><td>74.00</td><td>-23.38</td><td>42.52</td><td>31.96</td><td>7.05</td><td>36.91</td><td>6.00</td><td>312</td><td>250</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2353.68	50.62	74.00	-23.38	42.52	31.96	7.05	36.91	6.00	312	250	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>102.75</td><td>-----</td><td>-----</td><td>94.44</td><td>32.11</td><td>7.12</td><td>36.92</td><td>6.00</td><td>312</td><td>250</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	102.75	-----	-----	94.44	32.11	7.12	36.92	6.00	312	250
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2353.68	50.62	74.00	-23.38	42.52	31.96	7.05	36.91	6.00	312	250	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	102.75	-----	-----	94.44	32.11	7.12	36.92	6.00	312	250	PEAK																																																																																							
Avg																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2377.86</td><td>43.89</td><td>54.00</td><td>-10.11</td><td>35.68</td><td>32.03</td><td>7.09</td><td>36.91</td><td>6.00</td><td>312</td><td>250</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2377.86	43.89	54.00	-10.11	35.68	32.03	7.09	36.91	6.00	312	250	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>100.49</td><td>-----</td><td>-----</td><td>92.18</td><td>32.11</td><td>7.12</td><td>36.92</td><td>6.00</td><td>312</td><td>250</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	100.49	-----	-----	92.18	32.11	7.12	36.92	6.00	312	250
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2377.86	43.89	54.00	-10.11	35.68	32.03	7.09	36.91	6.00	312	250	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	100.49	-----	-----	92.18	32.11	7.12	36.92	6.00	312	250	AVERAGE																																																																																							







Mode	1																																																																																																													
	Harmonic																																																																																																													
	2400-2483.5_nRF_CH00_2402MHz																																																																																																													
ANT	1																																																																																																													
Pol.	Horizontal						Vertical																																																																																																							
Peak Avg																																																																																																														
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>43.16</td><td>74.00</td><td>-30.84</td><td>64.31</td><td>33.90</td><td>10.20</td><td>65.25</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	43.16	74.00	-30.84	64.31	33.90	10.20	65.25	0.00	---	---	PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>49.57</td><td>74.00</td><td>-24.43</td><td>70.72</td><td>33.90</td><td>10.20</td><td>65.25</td><td>0.00</td><td>302</td><td>122</td><td>PEAK</td></tr><tr><td>2</td><td>4804.00</td><td>44.86</td><td>54.00</td><td>-9.14</td><td>66.01</td><td>33.90</td><td>10.20</td><td>65.25</td><td>0.00</td><td>302</td><td>122</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	49.57	74.00	-24.43	70.72	33.90	10.20	65.25	0.00	302	122	PEAK	2	4804.00	44.86	54.00	-9.14	66.01	33.90	10.20	65.25	0.00	302	122
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	4804.00	43.16	74.00	-30.84	64.31	33.90	10.20	65.25	0.00	---	---	PEAK																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																					
1	4804.00	49.57	74.00	-24.43	70.72	33.90	10.20	65.25	0.00	302	122	PEAK																																																																																																		
2	4804.00	44.86	54.00	-9.14	66.01	33.90	10.20	65.25	0.00	302	122	AVERAGE																																																																																																		



Mode	2																																																																																																																																				
	Harmonic																																																																																																																																				
	2400-2483.5_nRF_CH19_2440MHz																																																																																																																																				
ANT	1																																																																																																																																				
Pol.	Horizontal						Vertical																																																																																																																														
Peak Avg																																																																																																																																					
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4881.00</td><td>44.61</td><td>74.00</td><td>-29.39</td><td>65.69</td><td>33.90</td><td>10.30</td><td>65.28</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7321.50</td><td>46.66</td><td>74.00</td><td>-27.34</td><td>64.72</td><td>35.70</td><td>12.72</td><td>66.48</td><td>0.00</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4881.00	44.61	74.00	-29.39	65.69	33.90	10.30	65.28	0.00	---	Peak	2	7321.50	46.66	74.00	-27.34	64.72	35.70	12.72	66.48	0.00	---	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4879.50</td><td>49.12</td><td>74.00</td><td>-24.88</td><td>70.20</td><td>33.90</td><td>10.30</td><td>65.28</td><td>0.00</td><td>300</td><td>127 Peak</td></tr><tr><td>2</td><td>4879.50</td><td>44.80</td><td>54.00</td><td>-9.20</td><td>65.88</td><td>33.90</td><td>10.30</td><td>65.28</td><td>0.00</td><td>300</td><td>127 Average</td></tr><tr><td>3</td><td>7321.50</td><td>45.45</td><td>74.00</td><td>-28.55</td><td>63.51</td><td>35.70</td><td>12.72</td><td>66.48</td><td>0.00</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4879.50	49.12	74.00	-24.88	70.20	33.90	10.30	65.28	0.00	300	127 Peak	2	4879.50	44.80	54.00	-9.20	65.88	33.90	10.30	65.28	0.00	300	127 Average	3	7321.50	45.45	74.00	-28.55	63.51	35.70	12.72	66.48	0.00	---
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	4881.00	44.61	74.00	-29.39	65.69	33.90	10.30	65.28	0.00	---	Peak																																																																																																																										
2	7321.50	46.66	74.00	-27.34	64.72	35.70	12.72	66.48	0.00	---	Peak																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	4879.50	49.12	74.00	-24.88	70.20	33.90	10.30	65.28	0.00	300	127 Peak																																																																																																																										
2	4879.50	44.80	54.00	-9.20	65.88	33.90	10.30	65.28	0.00	300	127 Average																																																																																																																										
3	7321.50	45.45	74.00	-28.55	63.51	35.70	12.72	66.48	0.00	---	Peak																																																																																																																										







Mode	3																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_nRF_CH39_2480MHz																																																																																																		
ANT	1																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>59.89</td><td>74.00</td><td>-14.11</td><td>51.07</td><td>32.52</td><td>7.26</td><td>36.96</td><td>6.00</td><td>259</td><td>294</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	59.89	74.00	-14.11	51.07	32.52	7.26	36.96	6.00	259	294	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>103.89</td><td>-----</td><td>-----</td><td>95.10</td><td>32.50</td><td>7.25</td><td>36.96</td><td>6.00</td><td>259</td><td>294</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	103.89	-----	-----	95.10	32.50	7.25	36.96	6.00	259	294
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.50	59.89	74.00	-14.11	51.07	32.52	7.26	36.96	6.00	259	294	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	103.89	-----	-----	95.10	32.50	7.25	36.96	6.00	259	294	PEAK																																																																																							
Avg																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.50</td><td>49.50</td><td>54.00</td><td>-4.50</td><td>40.68</td><td>32.52</td><td>7.26</td><td>36.96</td><td>6.00</td><td>259</td><td>294</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.50	49.50	54.00	-4.50	40.68	32.52	7.26	36.96	6.00	259	294	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>101.76</td><td>-----</td><td>-----</td><td>92.97</td><td>32.50</td><td>7.25</td><td>36.96</td><td>6.00</td><td>259</td><td>294</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	101.76	-----	-----	92.97	32.50	7.25	36.96	6.00	259	294
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.50	49.50	54.00	-4.50	40.68	32.52	7.26	36.96	6.00	259	294	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	101.76	-----	-----	92.97	32.50	7.25	36.96	6.00	259	294	AVERAGE																																																																																							





Mode	3																																																																																			
	Band Edge																																																																																			
	2400-2483.5_nRF_CH39_2480MHz																																																																																			
ANT	1																																																																																			
Pol.	Vertical	Fundamental																																																																																		
Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>57.06</td><td>74.00</td><td>-16.94</td><td>48.24</td><td>32.52</td><td>7.26</td><td>36.96</td><td>6.00</td><td>159 293 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.62	57.06	74.00	-16.94	48.24	32.52	7.26	36.96	6.00	159 293 PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>102.28</td><td>-----</td><td>-----</td><td>93.49</td><td>32.50</td><td>7.25</td><td>36.96</td><td>6.00</td><td>159 293 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	102.28	-----	-----	93.49	32.50	7.25	36.96	6.00	159 293 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	2483.62	57.06	74.00	-16.94	48.24	32.52	7.26	36.96	6.00	159 293 PEAK																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	2480.00	102.28	-----	-----	93.49	32.50	7.25	36.96	6.00	159 293 PEAK																																																																										
Avg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>47.69</td><td>54.00</td><td>-6.31</td><td>38.87</td><td>32.52</td><td>7.26</td><td>36.96</td><td>6.00</td><td>159 293 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.56	47.69	54.00	-6.31	38.87	32.52	7.26	36.96	6.00	159 293 AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>100.04</td><td>-----</td><td>-----</td><td>91.25</td><td>32.50</td><td>7.25</td><td>36.96</td><td>6.00</td><td>159 293 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	100.04	-----	-----	91.25	32.50	7.25	36.96	6.00	159 293 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	2483.56	47.69	54.00	-6.31	38.87	32.52	7.26	36.96	6.00	159 293 AVERAGE																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	2480.00	100.04	-----	-----	91.25	32.50	7.25	36.96	6.00	159 293 AVERAGE																																																																										



Mode	3																																																																																																																																				
	Harmonic																																																																																																																																				
	2400-2483.5_nRF_CH39_2480MHz																																																																																																																																				
ANT	1																																																																																																																																				
Pol.	Horizontal						Vertical																																																																																																																														
Peak Avg																																																																																																																																					
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Pream</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.50</td><td>45.83</td><td>74.00</td><td>-28.17</td><td>66.72</td><td>34.02</td><td>10.40</td><td>65.31</td><td>0.00</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7438.50</td><td>46.11</td><td>74.00</td><td>-27.89</td><td>64.40</td><td>35.74</td><td>12.78</td><td>66.81</td><td>0.00</td><td>---</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Pream	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.50	45.83	74.00	-28.17	66.72	34.02	10.40	65.31	0.00	---	Peak	2	7438.50	46.11	74.00	-27.89	64.40	35.74	12.78	66.81	0.00	---	Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Pream</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4960.50</td><td>46.91</td><td>74.00</td><td>-27.09</td><td>67.80</td><td>34.02</td><td>10.40</td><td>65.31</td><td>0.00</td><td>303</td><td>180 Peak</td></tr><tr><td>2</td><td>4960.50</td><td>41.46</td><td>54.00</td><td>-12.54</td><td>62.35</td><td>34.02</td><td>10.40</td><td>65.31</td><td>0.00</td><td>303</td><td>180 Average</td></tr><tr><td>3</td><td>7441.50</td><td>44.34</td><td>74.00</td><td>-29.66</td><td>62.63</td><td>35.74</td><td>12.79</td><td>66.82</td><td>0.00</td><td>---</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Pream	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.50	46.91	74.00	-27.09	67.80	34.02	10.40	65.31	0.00	303	180 Peak	2	4960.50	41.46	54.00	-12.54	62.35	34.02	10.40	65.31	0.00	303	180 Average	3	7441.50	44.34	74.00	-29.66	62.63	35.74	12.79	66.82	0.00	---
	Limit	Read	Ant	Cable	Pream	Aux	APos	TPos																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	4960.50	45.83	74.00	-28.17	66.72	34.02	10.40	65.31	0.00	---	Peak																																																																																																																										
2	7438.50	46.11	74.00	-27.89	64.40	35.74	12.78	66.81	0.00	---	Peak																																																																																																																										
	Limit	Read	Ant	Cable	Pream	Aux	APos	TPos																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	4960.50	46.91	74.00	-27.09	67.80	34.02	10.40	65.31	0.00	303	180 Peak																																																																																																																										
2	4960.50	41.46	54.00	-12.54	62.35	34.02	10.40	65.31	0.00	303	180 Average																																																																																																																										
3	7441.50	44.34	74.00	-29.66	62.63	35.74	12.79	66.82	0.00	---	Peak																																																																																																																										
Peak Avg																																																																																																																																					

Note: Only the worst case has assessed 18G ~25GHz to test.



Mode	4																																																																																																																																																																																																							
	LF																																																																																																																																																																																																							
	2400-2483.5_nRF_CH39_2480MHz																																																																																																																																																																																																							
ANT	1																																																																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																																																																	
Peak																																																																																																																																																																																																								
	<table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>30.00</td><td>22.61</td><td>-17.39</td><td>40.00</td><td>30.35</td><td>24.57</td><td>0.71</td><td>33.02</td><td>---</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>2</td><td>91.11</td><td>21.28</td><td>-22.22</td><td>43.50</td><td>37.35</td><td>15.35</td><td>1.43</td><td>32.85</td><td>---</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>3</td><td>299.66</td><td>17.75</td><td>-28.25</td><td>46.00</td><td>28.61</td><td>19.32</td><td>2.64</td><td>32.82</td><td>---</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>4</td><td>478.38</td><td>23.09</td><td>-22.91</td><td>46.00</td><td>29.81</td><td>22.97</td><td>3.31</td><td>33.00</td><td>---</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>5</td><td>735.19</td><td>28.90</td><td>-17.10</td><td>46.00</td><td>31.98</td><td>25.65</td><td>4.15</td><td>32.88</td><td>---</td><td>---</td><td>Peak HORIZONTAL</td></tr><tr><td>6</td><td>959.26</td><td>32.37</td><td>-13.63</td><td>46.00</td><td>31.63</td><td>27.52</td><td>4.74</td><td>31.52</td><td>---</td><td>---</td><td>Peak HORIZONTAL</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	30.00	22.61	-17.39	40.00	30.35	24.57	0.71	33.02	---	---	Peak HORIZONTAL	2	91.11	21.28	-22.22	43.50	37.35	15.35	1.43	32.85	---	---	Peak HORIZONTAL	3	299.66	17.75	-28.25	46.00	28.61	19.32	2.64	32.82	---	---	Peak HORIZONTAL	4	478.38	23.09	-22.91	46.00	29.81	22.97	3.31	33.00	---	---	Peak HORIZONTAL	5	735.19	28.90	-17.10	46.00	31.98	25.65	4.15	32.88	---	---	Peak HORIZONTAL	6	959.26	32.37	-13.63	46.00	31.63	27.52	4.74	31.52	---	---	Peak HORIZONTAL	<table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th><th>Pol/Phas</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>30.00</td><td>22.83</td><td>-17.17</td><td>40.00</td><td>30.57</td><td>24.57</td><td>0.71</td><td>33.02</td><td>---</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>2</td><td>82.38</td><td>17.14</td><td>-22.86</td><td>40.00</td><td>34.96</td><td>13.62</td><td>1.35</td><td>32.79</td><td>---</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>3</td><td>119.24</td><td>17.38</td><td>-26.12</td><td>43.50</td><td>31.78</td><td>16.81</td><td>1.64</td><td>32.85</td><td>---</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>4</td><td>357.86</td><td>19.95</td><td>-26.05</td><td>46.00</td><td>29.36</td><td>20.62</td><td>2.88</td><td>32.91</td><td>---</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>5</td><td>742.95</td><td>28.49</td><td>-17.51</td><td>46.00</td><td>31.40</td><td>25.75</td><td>4.17</td><td>32.83</td><td>---</td><td>---</td><td>Peak VERTICAL</td></tr><tr><td>6</td><td>954.41</td><td>31.20</td><td>-14.80</td><td>46.00</td><td>30.53</td><td>27.54</td><td>4.72</td><td>31.59</td><td>---</td><td>---</td><td>Peak VERTICAL</td></tr></table>						Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		1	30.00	22.83	-17.17	40.00	30.57	24.57	0.71	33.02	---	---	Peak VERTICAL	2	82.38	17.14	-22.86	40.00	34.96	13.62	1.35	32.79	---	---	Peak VERTICAL	3	119.24	17.38	-26.12	43.50	31.78	16.81	1.64	32.85	---	---	Peak VERTICAL	4	357.86	19.95	-26.05	46.00	29.36	20.62	2.88	32.91	---	---	Peak VERTICAL	5	742.95	28.49	-17.51	46.00	31.40	25.75	4.17	32.83	---	---	Peak VERTICAL	6	954.41	31.20	-14.80	46.00	30.53	27.54	4.72	31.59	---	---	Peak VERTICAL
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																														
	1	30.00	22.61	-17.39	40.00	30.35	24.57	0.71	33.02	---	---	Peak HORIZONTAL																																																																																																																																																																																												
	2	91.11	21.28	-22.22	43.50	37.35	15.35	1.43	32.85	---	---	Peak HORIZONTAL																																																																																																																																																																																												
	3	299.66	17.75	-28.25	46.00	28.61	19.32	2.64	32.82	---	---	Peak HORIZONTAL																																																																																																																																																																																												
	4	478.38	23.09	-22.91	46.00	29.81	22.97	3.31	33.00	---	---	Peak HORIZONTAL																																																																																																																																																																																												
	5	735.19	28.90	-17.10	46.00	31.98	25.65	4.15	32.88	---	---	Peak HORIZONTAL																																																																																																																																																																																												
	6	959.26	32.37	-13.63	46.00	31.63	27.52	4.74	31.52	---	---	Peak HORIZONTAL																																																																																																																																																																																												
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas																																																																																																																																																																																														
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																															
1	30.00	22.83	-17.17	40.00	30.57	24.57	0.71	33.02	---	---	Peak VERTICAL																																																																																																																																																																																													
2	82.38	17.14	-22.86	40.00	34.96	13.62	1.35	32.79	---	---	Peak VERTICAL																																																																																																																																																																																													
3	119.24	17.38	-26.12	43.50	31.78	16.81	1.64	32.85	---	---	Peak VERTICAL																																																																																																																																																																																													
4	357.86	19.95	-26.05	46.00	29.36	20.62	2.88	32.91	---	---	Peak VERTICAL																																																																																																																																																																																													
5	742.95	28.49	-17.51	46.00	31.40	25.75	4.17	32.83	---	---	Peak VERTICAL																																																																																																																																																																																													
6	954.41	31.20	-14.80	46.00	30.53	27.54	4.72	31.59	---	---	Peak VERTICAL																																																																																																																																																																																													

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
nRF	32.87	0.206	4.859	5.1kHz

nRF Mode

