

TEST REPORT

Product Name : Remote Controlled Toys

Model Number : 739AD,3700-1AK,3700-2AK,3700-1A,3700-2A,3700-3A,3701-1A,3701-2A,3701-3A,3702-1A,3702-2A,3702-3A,3703-1A,3703-2A,3703-3A,3705-1A,3705-2A,3705-3A,3706-1A,3706-2A,3706-3A,3707-1A,3707-2A,3707-3A,3708-1A,3708-2A,3708-3A,3709-1A,3709-2A,3709-3A,3710-1A,3710-2A,3710-3A,3711-1A,3711-2A,3711-3A,3712-1A,3712-2A,3712-3A,3715A,3715-1A,3715-2A,3716A,3716-1A,3716-2A,3717A,3717-1A,3717-2A,3718A,3718-1A,3718-2A,3719A,3719-1A,3719-2A,3720A,3720-1A,3720-2A,3725A,3725-1A,3725-2A,3726A,3726-1A,3726-2A,3727-1A,3727-2A,3727-3A,3728-1A,3728-2A,3728-3A,3729A,3729-1A,3729-2A,3730A,3730-1A,3730-2A,3731A,3731-1A,3731-2A,3732A,3732-1A,3732-2A,3732AD,3732-1AD,3732-2AD,3733A,3733-1A,3733-2A,3733AD,3733-1AD,3733-2AD,3735A,3735-1A,3735-2A,3735AD,3735-1AD,3735-2AD,3739A,3739-1A,3739-2A,3739-1AD,3739-2AD,3740-1A,3740-2A,3740-3A,3740-1AD,3740-2AD,3740-3AD,3741A,3741-1A,3741-2A,3741-3A,3741AD,3741-1AD,3741-2AD,3741-3AD,3742A,3742-1A,3742-2A,3742-3A,3742AD,3742-1AD,3742-2AD,3742-3AD,3743A,3743-1A,3743-2A,3743-3A,3743AD,3743-1AD,3743-2AD,3743-3AD,3745A,3745-1A,3745-2A,3745-3A,3745AD,3745-1AD,3745-2AD,3745-3AD,3746A,3746-1A,3746-2A,3746-3A,3746AD,3746-1AD,3746-2AD,3746-3AD

FCC ID : **2A5PO-3739AD**

Prepared for : SHANTOU CITY OURUI INDUSTRIAL Co., LTD

Address : NO.2, XIAOJIAN ROAD, SHANGKENG COMMUNITY, GUANGYI STREET, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA.

Prepared by : EMTEK (Dongguan) Co., Ltd.

Address : -1&2F., Building 2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No. 9, Xincheng Avenue, Songshanhu High-technology Industrial Development Zone, Dongguan, Guangdong, China

Tel : +86-0769-22807078
Fax: +86-0769-22807079

Report Number : EDG2501080030E00102R

Date(s) of Tests : January 08, 2025 to January 20, 2025

Date of issue : January 20, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



TEST RESULT CERTIFICATION

Applicant : SHANTOU CITY OURUI INDUSTRIAL Co., LTD
 Manufacturer : SHANTOU CITY OURUI INDUSTRIAL Co., LTD
 EUT : Remote Controlled Toys
 739AD,3700-1AK,3700-2AK,3700-1A,3700-2A,3700-3A,3701-1A,3701-2A,3701-3A,
 3702-1A,3702-2A,3702-3A,3703-1A,3703-2A,3703-3A,3705-1A,3705-2A,
 3705-3A,3706-1A,3706-2A,3706-3A,3707-1A,3707-2A,3707-3A,3708-1A,
 3708-2A,3708-3A,3709-1A,3709-2A,3709-3A,3710-1A,3710-2A,3710-3A,
 3711-1A,3711-2A,3711-3A,3712-1A,3712-2A,3712-3A,3715A,3715-1A,
 3715-2A,3716A,3716-1A,3716-2A,3717A,3717-1A,3717-2A,3718A,3718-1A,
 3718-2A,3719A,3719-1A,3719-2A,3720A,3720-1A,3720-2A,3725A,3725-1A,
 3725-2A,3726A,3726-1A,3726-2A,3727-1A,3727-2A,3727-3A,3728-1A,
 3728-2A,3728-3A,3729A,3729-1A,3729-2A,3730A,3730-1A,3730-2A,3731A,
 Model Name : 3731-1A,3731-2A,3732A,3732-1A,3732-2A,3732AD,3732-1AD,3732-2AD,
 3733A,3733-1A,3733-2A,3733AD,3733-1AD,3733-2AD,3735A,3735-1A,
 3735-2A,3735AD,3735-1AD,3735-2AD,3739A,3739-1A,3739-2A,
 3739-1AD,3739-2AD,3740-1A,3740-2A,3740-3A,3740-1AD,3740-2AD,
 3740-3AD,3741A,3741-1A · 3741-2A,3741-3A,3741AD,3741-1AD,3741-2AD,
 3741-3AD,3742A,3742-1A,3742-2A,3742-3A,3742AD,3742-1AD,3742-2AD,
 3742-3AD,3743A,3743-1A,3743-2A,3743-3A,3743AD,3743-1AD,3743-2AD,
 3743-3AD,3745A,3745-1A,3745-2A,3745-3A,3745AD,3745-1AD,3745-2AD,
 3745-3AD,3746A,3746-1A,3746-2A,3746-3A,3746AD,3746-1AD,3746-2AD,3746-3AD
 Trademark : N/A
 Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : January 08, 2025 to January 20, 2025


Prepared by : Warren Deng

Warren Deng /Editor

Reviewer : Tim Dong

Tim Dong /Supervisor

Approve & Authorized Signer : Sam Lv /Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2501080030E00102R	/	Original Report



1. EUT Specification

Characteristics	Description
Product:	Remote Controlled Toys
Model Number:	739AD,3700-1AK,3700-2AK,3700-1A,3700-2A,3700-3A,3701-1A,3701-2A,3701-3A,3702-1A,3702-2A,3702-3A,3703-1A,3703-2A,3703-3A,3705-1A,3705-2A,3705-3A,3706-1A,3706-2A,3706-3A,3707-1A,3707-2A,3707-3A,3708-1A,3708-2A,3708-3A,3709-1A,3709-2A,3709-3A,3710-1A,3710-2A,3710-3A,3711-1A,3711-2A,3711-3A,3712-1A,3712-2A,3712-3A,3715A,3715-1A,3715-2A,3716A,3716-1A,3716-2A,3717A,3717-1A,3717-2A,3718A,3718-1A,3718-2A,3719A,3719-1A,3719-2A,3720A,3720-1A,3720-2A,3725A,3725-1A,3725-2A,3726A,3726-1A,3726-2A,3727-1A,3727-2A,3727-3A,3728-1A,3728-2A,3728-3A,3729A,3729-1A,3729-2A,3730A,3730-1A,3730-2A,3731A,3731-1A,3731-2A,3732A,3732-1A,3732-2A,3732AD,3732-1AD,3732-2AD,3733A,3733-1A,3733-2A,3733AD,3733-1AD,3733-2AD,3735A,3735-1A,3735-2A,3735AD,3735-1AD,3735-2AD,3739A,3739-1A,3739-2A,3739-1AD,3739-2AD,3740-1A,3740-2A,3740-3A,3740-1AD,3740-2AD,3740-3AD,3741A,3741-1A,3741-2A,3741-3A,3741AD,3741-1AD,3741-2AD,3741-3AD,3742A,3742-1A,3742-2A,3742-3A,3742AD,3742-1AD,3742-2AD,3742-3AD,3743A,3743-1A,3743-2A,3743-3A,3743AD,3743-1AD,3743-2AD,3743-3AD,3745A,3745-1A,3745-2A,3745-3A,3745AD,3745-1AD,3745-2AD,3745-3AD,3746A,3746-1A,3746-2A,3746-3A,3746AD,3746-1AD,3746-2AD,3746-3AD
Sample:	2#
Modulation:	GFSK
Operating Frequency Range(s) :	2408MHz-2475MHz
Number of Channels:	68 Channels
Transmit Power Max:	63.21 dBuV@3m
Antenna Gain:	0.59 dBi
Power supply:	DC 3V from battery
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

2. Test Requirement

RF EXPOSURE EVALUATION

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

According to ANSI C63.10-2013

9.5 Equations to calculate EIRP

Calculate the EIRP from the radiated field strength in the far field using Equation (22):

$$\text{EIRP} = E + 20\log(d) - 104.7 \quad (22)$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E is the field strength of the emission at the measurement distance, in dB μ V/m

d is the measurement distance, in m

3. Measurement Result

Antenna gain:0.59 dBi

When a single module works, the measurement results are as follows:

2.4G

Channel Freq. (MHz)	Max Field Strength (dBuV/m)	peak output power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
2408	62.36	-32.7976	-33±1	-32	0.00019582	3
2442	62.63	-32.5276	-33±1	-32	0.00019720	3
2475	63.21	-31.9476	-32±1	-31	0.00024993	3

According to KDB 447498 D01 V06, no stand-alone required for Integrated antenna, and no simultaneous SAR measurement is required.

*** End of Report ***