

TEST REPORT

FCC ID	2A5PQ-P4W	
Test Report No.	TCT220224E026	
Date of issue	Sep. 30, 2022	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name.....	Beijing Viisan Technology Co., Ltd.	
Address.....	Unit A311, Information Center, ZhongGuanCun Software Z-Park HaiDian District, Beijing, 100193 China	
Manufacturer's name ...	Beijing Viisan Technology Co., Ltd.	
Address.....	Unit A311, Information Center, ZhongGuanCun Software Z-Park HaiDian District, Beijing, 100193 China	
Standard(s)	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name.....	4K Wireless Document Camera	
Trade Mark	VIISAN	
Model/Type reference.....	P4W, P4WXXXXX (X can be any alphanumeric, symbol or blank for marketing purposes)	
Rating(s)	Refer to EUT description of page 3	
Date of receipt of test item	Feb. 24, 2022	
Date (s) of performance of test.....	Feb. 24, 2022 ~ Sep. 30, 2022	
Tested by (+signature)....	Brews XU	
Check by (+signature)....	Beryl ZHAO	
Approved by (+signature):	Tomsin	
Remark	This test report was based on TCT220224E028; Change applicant, manufacturer, address, product model No., trade mark and add adapter.	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Test Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units.....	7
4. Facilities and Accreditations	8
4.1. Facilities	8
4.2. Location	8
4.3. Measurement Uncertainty.....	8
5. Test Results and Measurement Data	9
5.1. Antenna requirement	9
5.2. Conducted Emission.....	10
5.3. Maximum Conducted Output Power.....	14
5.4. 6dB Emission Bandwidth	16
5.5. 26dB Bandwidth and 99% Occupied Bandwidth	17
5.6. Power Spectral Density.....	18
5.7. Band edge	19
5.8. Unwanted Emissions	27
5.9. Frequency Stability Measurement	34

Appendix A: Test Result of Conducted Test**Appendix B: Photographs of Test Setup****Appendix C: Photographs of EUT**

1. General Product Information

1.1. EUT description

Product Name.....	4K Wireless Document Camera
Model/Type reference.....	P4W
Sample Number.....	TCT220224E027-0101
Operation Frequency	Band 1: 5180 MHz~5240 MHz
Channel Bandwidth.....	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz
Modulation Technology	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type.....	Internal Antenna
Antenna Gain.....	2dBi
Rating(s)	Adapter Information: MODEL: JF005WR-0500100UU INPUT: AC 100-240V, 50/60Hz, 0.18A OUTPUT: DC 5.0V, 1.0A, 5.0W Rechargeable Li-ion Battery DC 3.7V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	P4W	<input checked="" type="checkbox"/>
Other models	P4WXXXXX (X can be any alphanumeric, symbol or blank for marketing purposes)	<input type="checkbox"/>

Note: P4W is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of P4W can represent the remaining models.

1.3. Test Frequency

Band 1

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210
40	5200	46	5230		
48	5240				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. For the band 5.15-5.25GHz, EUT meet the requirements of 15.407(a)(ii).

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	SecureCRSSecureFX_x64
Power Level:	36
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with Fully-charged battery.
<p>The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps
802.11ac(VHT20)	6.5 Mbps
802.11ac(VHT40)	13.5 Mbps
802.11ac(VHT80)	29.3 Mbps

Final Test Mode:

Operation mode:	Keep the EUT in continuous transmitting with modulation
-----------------	---

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339


4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
E.U.T Antenna:	
<p>The WIFI antenna is internal antenna which permanently attached, and the best case gain of the antenna is 2dBi.</p> 	

5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p>Reference Plane</p> <p>Test table/Insulation plane</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + Transmitting Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jul. 03, 2023
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Feb. 24, 2023
Line-5	TCT	CE-05	/	Jul. 03, 2023
EMI Test Software	Shurples Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room Phase: **L1** Temperature: 25.3 (°C) Humidity: 56 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV	dB	Detector	Comment
1		0.1500	48.52	10.54	59.06	66.00	-6.94	QP
2		0.1500	28.40	10.54	38.94	56.00	-17.06	AVG
3		0.2220	45.82	10.28	56.10	62.74	-6.64	QP
4 *		0.2220	36.22	10.28	46.50	52.74	-6.24	AVG
5		0.3899	33.22	10.20	43.42	58.07	-14.65	QP
6		0.3899	22.40	10.20	32.60	48.07	-15.47	AVG
7		0.9460	31.23	10.11	41.34	56.00	-14.66	QP
8		0.9460	20.46	10.11	30.57	46.00	-15.43	AVG
9		2.4260	26.73	10.03	36.76	56.00	-19.24	QP
10		2.4260	15.27	10.03	25.30	46.00	-20.70	AVG
11		21.4260	29.57	10.45	40.02	60.00	-19.98	QP
12		21.4260	18.00	10.45	28.45	50.00	-21.55	AVG

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard


Margin (dB) = Measurement (dB μ V) - Limits (dB μ V)

QP. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room Phase: **N** Temperature: 25.3 (°C) Humidity: 56 %
Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz

No. Mk.	Freq. MHz	Reading Level dB μ V	Correct Factor dB	Measure- ment dB μ V	Limit dB μ V	Over	Detector	Comment
1 *	0.2179	46.05	10.28	56.33	62.90	-6.57	QP	
2	0.2179	32.81	10.28	43.09	52.90	-9.81	AVG	
3	0.4300	34.26	10.18	44.44	57.25	-12.81	QP	
4	0.4300	21.34	10.18	31.52	47.25	-15.73	AVG	
5	0.9659	31.91	10.11	42.02	56.00	-13.98	QP	
6	0.9659	20.85	10.11	30.96	46.00	-15.04	AVG	
7	1.4939	28.03	10.11	38.14	56.00	-17.86	QP	
8	1.4939	16.86	10.11	26.97	46.00	-19.03	AVG	
9	3.1018	26.25	10.13	36.38	56.00	-19.62	QP	
10	3.1018	14.57	10.13	24.70	46.00	-21.30	AVG	
11	17.7259	27.20	10.43	37.63	60.00	-22.37	QP	
12	17.7259	16.28	10.43	26.71	50.00	-23.29	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) – Limits (dB μ V)

Q.P. = Quasi-Peak


AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80) and the worst case Mode (Highest channel and 802.11ac(VHT40)) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046										
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E										
Limit:	<table border="1"> <thead> <tr> <th>Frequency Band (MHz)</th> <th>Limit</th> </tr> </thead> <tbody> <tr> <td>5180 - 5240</td> <td>24dBm(250mW) for client device</td> </tr> <tr> <td>5260 - 5320</td> <td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td> </tr> <tr> <td>5470 - 5725</td> <td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td> </tr> <tr> <td>5745 - 5825</td> <td>30dBm(1W)</td> </tr> </tbody> </table>	Frequency Band (MHz)	Limit	5180 - 5240	24dBm(250mW) for client device	5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz	5745 - 5825	30dBm(1W)
Frequency Band (MHz)	Limit										
5180 - 5240	24dBm(250mW) for client device										
5260 - 5320	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5470 - 5725	24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz										
5745 - 5825	30dBm(1W)										
Test Setup:	 <p>The diagram illustrates the test setup. A green rectangular box labeled 'Power meter' is connected to a yellow rectangular box labeled 'EUT' (Equipment Under Test) via a grey RF cable. A small white square labeled 'Attenuator' is positioned between the power meter and the EUT.</p>										
Test Mode:	Transmitting mode with modulation										
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 5. Measure the conducted output power and record the results in the test report. 										
Test Result:	PASS										
Remark:	Conducted output power= measurement power +10log(1/x) X is duty cycle=1, so 10log(1/1)=0 Conducted output power= measurement power										

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Power Meter	Agilent	E4418B	MY45100357	Jul. 04, 2023
Power Sensor	Agilent	8481A	MY41091497	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	 <p>Spectrum Analyzer EUT</p>
Test Mode:	Transmitting mode with modulation
Test Procedure:	<ol style="list-style-type: none"> 1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification


Test Requirement:	FCC Part15 E Section 15.407 (a)	
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F	
Limit:	<p>≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device)</p> <p>≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725</p> <p>≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz</p> <p>The e.i,r,p spectral density for Band 1 5150MHz – 5250 MHz should not exceed 10dBm/MHz</p>	
Test Setup:	<p style="text-align: center;">Spectrum Analyzer EUT</p>	
Test Mode:	Transmitting mode with modulation	
Test Procedure:	<ol style="list-style-type: none"> 1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW \geq 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment. 	
Test Result:	PASS	

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.7. Band edge

5.7.1. Test Specification

Test Requirement:	FCC CFR47 Part 15E Section 15.407																										
Test Method:	ANSI C63.10 2013																										
Limit:	<p>In un-restricted band: For Band 1&2A&2C: -27dBm/MHz For Band 3:</p> <table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Limit (dBm/MHz)</th> <th>Frequency (MHz)</th> <th>Limit (dBm/MHz)</th> </tr> </thead> <tbody> <tr> <td>< 5650</td> <td>-27</td> <td>5850~5855</td> <td>27~15.6</td> </tr> <tr> <td>5650~5700</td> <td>-27~10</td> <td>5855~5875</td> <td>15.6~10</td> </tr> <tr> <td>5700~5720</td> <td>10~15.6</td> <td>5875~5925</td> <td>10~27</td> </tr> <tr> <td>5720~5725</td> <td>15.6~27</td> <td>> 5925</td> <td>-27</td> </tr> </tbody> </table> <p>$E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] + 95.2 @3\text{m}$</p> <p>In restricted band:</p> <table border="1"> <thead> <tr> <th>Detector</th> <th>Limit@3m</th> </tr> </thead> <tbody> <tr> <td>Peak</td> <td>74dBμV/m</td> </tr> <tr> <td>AVG</td> <td>54dBμV/m</td> </tr> </tbody> </table>	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)	< 5650	-27	5850~5855	27~15.6	5650~5700	-27~10	5855~5875	15.6~10	5700~5720	10~15.6	5875~5925	10~27	5720~5725	15.6~27	> 5925	-27	Detector	Limit@3m	Peak	74dB μ V/m	AVG	54dB μ V/m
Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)																								
< 5650	-27	5850~5855	27~15.6																								
5650~5700	-27~10	5855~5875	15.6~10																								
5700~5720	10~15.6	5875~5925	10~27																								
5720~5725	15.6~27	> 5925	-27																								
Detector	Limit@3m																										
Peak	74dB μ V/m																										
AVG	54dB μ V/m																										
Test Setup:																											
Test Mode:	Transmitting mode with modulation																										
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold 																										


	Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jul. 03, 2023
Spectrum Analyzer	R&S	FSQ40	200061	Jul. 03, 2023
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 04, 2023
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 24, 2023
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Feb. 24, 2023
Pre-amplifier	HP	8447D	2727A05017	Jul. 03, 2023
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 11, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 05, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 05, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Apr. 10, 2023
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
Antenna Mast	Keleto	CC-A-4M	/	/
EMI Test Software	Shurples Technology	EZ-EMC	/	/


5.7.3. Test Data

AC20-5180



Site Polarization: **Horizontal** Temperature: 25(°C)
Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	46.38	-8.04	38.34	74.00	-35.66	peak	P	



Site Polarization: **Vertical** Temperature: 25(°C)
Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	47.30	-8.04	39.26	74.00	-34.74	peak	P	

AC20-5240



Site Polarization: **Horizontal** Temperature: 25(°C)
Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	46.82	-8.09	38.73	74.00	-35.27	peak	P	



Site Polarization: **Vertical** Temperature: 25(°C)
Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	46.80	-8.09	38.71	74.00	-35.29	peak	P	

AC40-5190



Site Polarization: **Horizontal** Temperature: 25(°C)
 Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	47.70	-8.04	39.66	74.00	-34.34	peak	P	



Site Polarization: **Vertical** Temperature: 25(°C)
 Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	50.51	-8.04	42.47	74.00	-31.53	peak	P	

AC40-5230



Site Polarization: **Horizontal** Temperature: 25(°C)
 Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	47.57	-8.09	39.48	74.00	-34.52	peak	P	



Site Polarization: **Vertical** Temperature: 25(°C)
 Limit: FCC part 15.407 band edge (PK) Power: DC 3.7 V Humidity: 36 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	46.74	-8.09	38.65	74.00	-35.35	peak	P	

AC80-5210



Site

 Polarization: **Horizontal**


Temperature: 25(°C)

Limit: FCC part 15.407 band edge (PK)

Power: DC 3.7 V

Humidity: 36 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	47.06	-8.04	39.02	74.00	-34.98	peak	P	
2	5350.000	46.39	-8.09	38.30	74.00	-35.70	peak	P	



Site

 Polarization: **Vertical**

Temperature: 25(°C)

Limit: FCC part 15.407 band edge (PK)

Power: DC 3.7 V


Humidity: 36 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	49.05	-8.04	41.01	74.00	-32.99	peak	P	
2	5350.000	47.04	-8.09	38.95	74.00	-35.05	peak	P	

Note: All modulation (802.11a, 802.11n, 802.11ac) have been tested, only the worst case in 802.11ac be reported.


5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205							
Test Method:	KDB 789033 D02 v02r01							
Frequency Range:	9kHz to 40GHz							
Measurement Distance:	3 m							
Antenna Polarization:	Horizontal & Vertical							
Operation mode:	Transmitting mode with modulation							
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark			
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value			
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value			
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value			
	Above 1GHz	Peak	1MHz	3MHz	Peak Value			
		Peak	1MHz	10Hz	Average Value			
Limit:	Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table, In restricted bands:							
	Frequency	Detector	Limit@3m					
	Above 1G	Peak	74dB μ V/m					
		AVG	54dB μ V/m					
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)					
	0.009-0.490	2400/F(KHz)	300					
	0.490-1.705	24000/F(KHz)	3					
	1.705-30	30	30					
	30-88	100	3					
	88-216	150	3					
	216-960	200	3					
	Above 960	500	3					
	In un-restricted bands: 68.2dB μ V/m							
Test setup:	For radiated emissions below 30MHz							
	 <p>Distance = 3m</p> <p>EUT</p> <p>Turn table</p> <p>Ground Plane</p> <p>Computer</p> <p>Pre -Amplifier</p> <p>Receiver</p> <p>30MHz to 1GHz</p>							



Above 1GHz



1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Procedure:

Test results:


PASS

5.8.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site #2 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 25.1(C) Humidity: 48 %

Limit: FCC Part 15C RE_3m

Power: DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	164.9075	17.80	12.90	30.70	43.50	-12.80	QP	P	
2	237.4760	19.58	12.62	32.20	46.00	-13.80	QP	P	
3	351.7079	16.04	15.56	31.60	46.00	-14.40	QP	P	
4	411.8240	16.79	17.51	34.30	46.00	-11.70	QP	P	
5	545.1826	12.56	20.24	32.80	46.00	-13.20	QP	P	
6 *	649.6597	15.15	22.05	37.20	46.00	-8.80	QP	P	

Vertical:



Site #2 3m Anechoic Chamber

 Polarization: **Vertical**

Temperature: 25.1(C) Humidity: 48 %

Limit: FCC Part 15C RE_3m

Power: DC 3.7 V

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	Remark
1	39.4371	13.28	13.92	27.20	40.00	-12.80	QP	P	
2	102.3597	13.23	10.57	23.80	43.50	-19.70	QP	P	
3	166.6514	22.58	12.72	35.30	43.50	-8.20	QP	P	
4	366.8231	13.70	16.10	29.80	46.00	-16.20	QP	P	
5	487.3151	10.78	19.12	29.90	46.00	-16.10	QP	P	
6 *	649.6597	23.05	22.05	45.10	46.00	-0.90	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80) and the worst case Mode (Highest channel and 802.11ac(VHT40)) was submitted only.

3. Measurement (dB μ V) = Reading level + Correction Factor , correction Factor= Antenna Factor + Cable loss - Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10360	H	38.06	---	8.02	46.08	---	74	54	-7.92
15540	H	38.88	---	9.87	48.75	---	74	54	-5.25
---	H	---	---	---	---	---	---	---	---
10360	V	36.72	---	8.02	44.74	---	74	54	-9.26
15540	V	39.36	---	9.87	49.23	---	74	54	-4.77
---	V	---	---	---	---	---	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10400	H	40.31	---	7.97	48.28	---	74	54	-5.72
15600	H	38.26	---	9.83	48.09	---	74	54	-5.91
---	H	---	---	---	---	---	---	---	---
10400	V	40.07	---	7.97	48.04	---	74	54	-5.96
15600	V	37.52	---	9.83	47.35	---	74	54	-6.65
---	V	---	---	---	---	---	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10480	H	37.94	---	7.97	45.91	---	74	54	-8.09
15720	H	38.38	---	9.83	48.21	---	74	54	-5.79
---	H	---	---	---	---	---	---	---	---
10480	V	38.89	---	7.97	46.86	---	74	54	-7.14
15720	V	36.63	---	9.83	46.46	---	74	54	-7.54
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10360	H	41.32	---	8.02	49.34	---	74	54	-4.66
15540	H	37.50	---	9.87	47.37	---	74	54	-6.63
---	H	---	---	---	---	---	---	---	---
10360	V	41.37	---	8.02	49.39	---	74	54	-4.61
15540	V	38.64	---	9.87	48.51	---	74	54	-5.49
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10400	H	41.29	---	7.97	49.26	---	74	54	-4.74
15600	H	37.87	---	9.83	47.70	---	74	54	-6.30
---	H	---	---	---	---	---	---	---	---
10400	V	41.12	---	7.97	49.09	---	74	54	-4.91
15600	V	38.09	---	9.83	47.92	---	74	54	-6.08
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH48: 5240MHz									

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10480	H	40.77	---	7.97	48.74	---	74	54	-5.26
15720	H	39.02	---	9.83	48.85	---	74	54	-5.15
---	H	---	---	---	---	---	---	---	---
10480	V	40.31	---	7.97	48.28	---	74	54	-5.72
15720	V	39.56	---	9.83	49.39	---	74	54	-4.61
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10380	H	40.07	---	7.75	47.82	---	74	54	-6.18
15570	H	37.32	---	9.87	47.19	---	74	54	-6.81
---	H	---	---	---	---	---	---	---	---
10380	V	40.27	---	7.75	48.02	---	74	54	-5.98
15570	V	38.01	---	9.87	47.88	---	74	54	-6.12
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10460	H	41.12	---	7.97	49.09	---	74	54	-4.91
15690	H	37.67	---	9.83	47.50	---	74	54	-6.50
---	H	---	---	---	---	---	---	---	---
10460	V	40.61	---	7.97	48.58	---	74	54	-5.42
15690	V	37.93	---	9.83	47.76	---	74	54	-6.24
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10360	H	41.30	---	8.02	49.32	---	74	54	-4.68
15540	H	37.79	---	9.87	47.66	---	74	54	-6.34
---	H	---	---	---	---	---	---	---	---
10360	V	38.46	---	8.02	46.48	---	74	54	-7.52
15540	V	38.58	---	9.87	48.45	---	74	54	-5.55
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10400	H	39.96	---	7.97	47.93	---	74	54	-6.07
15600	H	39.11	---	9.83	48.94	---	74	54	-5.06
---	H	---	---	---	---	---	---	---	---
10400	V	38.57	---	7.97	46.54	---	74	54	-7.46
15600	V	37.39	---	9.83	47.22	---	74	54	-6.78
---	V	---	---	---	---	---	---	---	---


11ac(VHT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10480	H	36.96	---	7.97	44.93	---	74	54	-9.07
15720	H	38.13	---	9.83	47.96	---	74	54	-6.04
---	H	---	---	---	---	---	---	---	---
10480	V	38.57	---	7.97	46.54	---	74	54	-7.46
15720	V	38.19	---	9.83	48.02	---	74	54	-5.98
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10380	H	40.38	---	7.75	48.13	---	74	54	-5.87
15570	H	38.69	---	9.87	48.56	---	74	54	-5.44
---	H	---	---	---	---	---	---	---	---
10380	V	38.97	---	7.75	46.72	---	74	54	-7.28
15570	V	38.24	---	9.87	48.11	---	74	54	-5.89
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10460	H	38.63	---	7.97	46.60	---	74	54	-7.40
15690	H	38.44	---	9.83	48.27	---	74	54	-5.73
---	H	---	---	---	---	---	---	---	---
10460	V	39.05	---	7.97	47.02	---	74	54	-6.98
15690	V	37.99	---	9.83	47.82	---	74	54	-6.18
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB μ V)	AV reading (dB μ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB μ V/m)	AV limit (dB μ V/m)	Margin (dB)
					Peak (dB μ V/m)	AV (dB μ V/m)			
10420	H	41.12	---	7.96	49.08	---	74	54	-4.92
15630	H	39.97	---	9.84	49.81	---	74	54	-4.19
---	H	---	---	---	---	---	---	---	---
10420	V	41.47	---	7.96	49.43	---	74	54	-4.57
15630	V	38.55	---	9.84	48.39	---	74	54	-5.61
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB μ V/m)-Average limit (dB μ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	 <pre> graph LR SA[Spectrum Analyzer] --- EUT[EUT] EUT --- ACDC[AC/DC Power supply] EUT --- TC[Temperature Chamber] </pre>
Test Procedure:	<p>The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage.</p> <ol style="list-style-type: none"> Turn the EUT on and couple its output to a spectrum analyzer. Turn the EUT off and set the chamber to the highest temperature specified. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at all models(11a,11n,11ac), the worst case (11ac) was found and test data was shown in this report.

Test plots as follows:

Test mode:		802.11ac(HT20)	Frequency(MHz):	5180
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.7V	5180.0091	9100	PASS
35		5180.0065	6500	PASS
25		5179.9877	-12300	PASS
15		5179.9983	-1700	PASS
5		5180.0038	3800	PASS
0		5180.0049	4900	PASS
20		5179.9832	-16800	PASS
	3.33V	5180.0034	3400	PASS
	4.07V	5179.9821	-17900	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5200
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.7V	5200.0097	9700	PASS
35		5200.0082	8200	PASS
25		5200.0076	7600	PASS
15		5200.0044	4400	PASS
5		5199.9982	-1800	PASS
0		5199.9873	-12700	PASS
20		5199.9955	-4500	PASS
	3.33V	5200.0036	3600	PASS
	4.07V	5200.0058	5800	PASS

Test mode:		802.11ac(HT20)	Frequency(MHz):	5240
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.7V	5240.0045	4500	PASS
35		5240.0021	2100	PASS
25		5240.0026	2600	PASS
15		5239.9993	-700	PASS
5		5239.9985	-1500	PASS
0		5239.9972	-2800	PASS
20		5240.0038	3800	PASS
	3.33V	5240.0019	1900	PASS
	4.07V	5239.9984	-1600	PASS


Test mode:		802.11ac(HT40)	Frequency(MHz):	5190
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.7V	5190.0128	12800	PASS
35		5190.0112	11200	PASS
25		5190.0101	10100	PASS
15		5190.0034	3400	PASS
5		5190.0066	6600	PASS
0		5190.0077	7700	PASS
20	3.33V	5189.9915	-8500	PASS
	3.7V	5189.9978	-2200	PASS
	4.07V	5190.0043	4300	PASS


Test mode:		802.11ac(HT40)	Frequency(MHz):	5230
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.7V	5230.0113	11300	PASS
35		5230.0122	12200	PASS
25		5230.0095	9500	PASS
15		5229.9984	-1600	PASS
5		5229.9982	-1800	PASS
0		5230.0051	5100	PASS
20	3.33V	5230.0048	4800	PASS
	3.7V	5230.0029	2900	PASS
	4.07V	5229.9976	-2400	PASS


Test mode:		802.11ac(VHT80)	Frequency(MHz):	5210
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.7V	5209.9806	-19400	PASS
35		5209.9842	-15800	PASS
25		5210.0044	4400	PASS
15		5210.0031	3100	PASS
5		5210.0025	2500	PASS
0		5210.0063	6300	PASS
20	3.33V	5210.0058	5800	PASS
	3.7V	5209.9987	-1300	PASS
	4.07V	5210.0089	8900	PASS


Appendix A: Test Result of Conducted Test**Duty Cycle**


Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	100	0	0
NVNT	a	5200	100	0	0
NVNT	a	5240	100	0	0
NVNT	n20	5180	100	0	0
NVNT	n20	5200	100	0	0
NVNT	n20	5240	100	0	0
NVNT	n40	5190	100	0	0
NVNT	n40	5230	100	0	0
NVNT	ac20	5180	100	0	0
NVNT	ac20	5200	100	0	0
NVNT	ac20	5240	100	0	0
NVNT	ac40	5190	100	0	0
NVNT	ac40	5230	100	0	0
NVNT	ac80	5210	100	0	0




















Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	6.49	24	Pass
NVNT	a	5200	6.45	24	Pass
NVNT	a	5240	6.68	24	Pass
NVNT	n20	5180	5.66	24	Pass
NVNT	n20	5200	5.92	24	Pass
NVNT	n20	5240	6.57	24	Pass
NVNT	n40	5190	6.08	24	Pass
NVNT	n40	5230	6.73	24	Pass
NVNT	ac20	5180	5.58	24	Pass
NVNT	ac20	5200	5.92	24	Pass
NVNT	ac20	5240	6.61	24	Pass
NVNT	ac40	5190	6.12	24	Pass
NVNT	ac40	5230	6.79	24	Pass
NVNT	ac80	5210	5.87	24	Pass




















-26dB Bandwidth


Condition	Mode	Frequency (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	21.294	Pass
NVNT	a	5200	21.445	Pass
NVNT	a	5240	21.345	Pass
NVNT	n20	5180	21.382	Pass
NVNT	n20	5200	21.485	Pass
NVNT	n20	5240	21.338	Pass
NVNT	n40	5190	42.245	Pass
NVNT	n40	5230	42.273	Pass
NVNT	ac20	5180	21.665	Pass
NVNT	ac20	5200	21.483	Pass
NVNT	ac20	5240	21.615	Pass
NVNT	ac40	5190	41.412	Pass
NVNT	ac40	5230	41.404	Pass
NVNT	ac80	5210	80.756	Pass





















Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	a	5180	16.604
NVNT	a	5200	16.627
NVNT	a	5240	16.629
NVNT	n20	5180	17.607
NVNT	n20	5200	17.608
NVNT	n20	5240	17.603
NVNT	n40	5190	36.413
NVNT	n40	5230	36.467
NVNT	ac20	5180	17.622
NVNT	ac20	5200	17.628
NVNT	ac20	5240	17.630
NVNT	ac40	5190	36.368
NVNT	ac40	5230	36.411
NVNT	ac80	5210	75.799





















Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	Conducted PSD (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	-4.85	11	Pass
NVNT	a	5200	-4.86	11	Pass
NVNT	a	5240	-4.6	11	Pass
NVNT	n20	5180	-5.53	11	Pass
NVNT	n20	5200	-5.36	11	Pass
NVNT	n20	5240	-4.68	11	Pass
NVNT	n40	5190	-8.23	11	Pass
NVNT	n40	5230	-7.43	11	Pass
NVNT	ac20	5180	-5.54	11	Pass
NVNT	ac20	5200	-5.41	11	Pass
NVNT	ac20	5240	-4.65	11	Pass
NVNT	ac40	5190	-8.12	11	Pass
NVNT	ac40	5230	-7.4	11	Pass
NVNT	ac80	5210	-11.31	11	Pass

















Appendix B: Photographs of Test Setup

Refer to the test report No. TCT220224E025

Appendix C: Photographs of EUT

Refer to the test report No. TCT220224E025

*****END OF REPORT*****