



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: AXEND,Inc.

Address: 12045 E.Waterfront Drive, Ste 450 Los Angeles CA 90094, Los Angeles, California, United States

FCC ID: 2A5R6AASW-2D

Product Name: Contactless Sleep Sensor

Model: AASW-2D, TASW-2D, TASW-2D/N, AASW-2D/N, TASW-2D/T, TASW-2D/TZ, TASW-1H, AASW-1H, TASW-1H/N, AASW-1H/N

Standard(s): 47 CFR Part 15, Subpart C(15.249)
ANSI C63.10-2013

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230418736-00A

Date Of Issue: 2023/5/23

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	6
1.2.2 Support Equipment List and Details	6
1.2.3 Support Cable List and Details	6
1.2.4 Block Diagram of Test Setup.....	7
1.3 FAR FIELD BOUNDARY CALCULATIONS	8
1.4 MEASUREMENT UNCERTAINTY	8
2. SUMMARY OF TEST RESULTS	9
3. REQUIREMENTS AND TEST PROCEDURES	10
3.1 AC LINE CONDUCTED EMISSIONS.....	10
3.1.1 Applicable Standard.....	10
3.1.2 EUT Setup.....	11
3.1.3 EMI Test Receiver Setup	11
3.1.4 Test Procedure	12
3.1.5 Corrected Amplitude & Margin Calculation.....	12
3.2 RADIATED EMISSIONS	13
3.2.1 Applicable Standard.....	13
3.2.2 EUT Setup.....	13
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	15
3.2.4 Test Procedure	15
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 20 dB EMISSION BANDWIDTH:	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 ANTENNA REQUIREMENT.....	18
3.4.1 Applicable Standard.....	18
3.4.2 Judgment.....	18
4. Test DATA AND RESULTS	19
4.1 AC LINE CONDUCTED EMISSIONS.....	19
4.2 RADIATION SPURIOUS EMISSIONS.....	22
4.3 20 dB EMISSION BANDWIDTH:	31

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230418736-00A	Original Report	2023/5/23

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Contactless Sleep Sensor
EUT Model:	AASW-2D
Multiple Model:	TASW-2D,TASW-2D/N,AASW-2D/N,TASW-2D/T,TASW-2D/TZ,TASW-1H,AASW-1H,TASW-1H/N,AASW-1H/N
Operation Frequency:	24002-24180MHz
Modulation Type:	FMCW
Rated Input Voltage:	DC 5V from adapter
Serial Number:	24IP_1
EUT Received Date:	2023/4/14
EUT Received Status:	Good
Note: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.	

Operation Frequency Detail:

Sweep Start Frequency (MHz)	Sweep Stop Frequency (MHz)
24002	24180
Per section 15.31(m), the below frequencies were performed the test as below:	
Test Frequency	Frequency (MHz)
Lowest	24002
Middle	24090
Highest	24180

Antenna Information Detail▲:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
PCB Antenna	50	6.9dBi/24~24.25GHz	Compliance
The Method of §15.203 Compliance: ☒ Antenna must be permanently attached to the unit. ☐ Antenna must use a unique type of connector to attach to the EUT. ☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.			

Accessory Information:

Accessory Description	Manufacturer	Model
Adapter	Shenzhen Sunshine Technological Co.,Ltd.	XSC-0502000SU

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer Transmitting
Equipment Modifications:	No
EUT Exercise Software:	No
The software was provided by manufacturer▲. The maximum power was configured default setting.	

1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.3 Support Cable List and Details


Cable Description	Shielding Cable	Ferrite Core	Length (m)	From Port	To
USB Cable	unshielded	Without ferrite core	2	Adapter	EUT

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



1.3 FAR Field Boundary Calculations

The far-field boundary is given in ANSI C63.10-2013:

$$R_m = 2D^2 / \lambda$$

Where:

D is the largest dimension of the antenna aperture in m and

λ is the free-space wavelength in m at the frequency of measurement.

The minimum test distance for the frequency range 40GHz-200GHz determine as below:

Model	Frequency Range (GHz)	Largest Dimension of the Horn Antenna (mm)	Minimum Test Distance R_m (m)
M19RH	40-60	46.3	0.57
861V/385	50-75	43.7	0.64
M12RH	60-90	30.02	0.36
M08RH	90-140	19.7	0.23

Note: The test distances used were 1.0 m from 40 GHz to 90 GHz, and 0.5 m from 90 GHz to 100 GHz, it can be seen that the EUT was always in the Far-field of the Receive Antenna during all Radiated Emissions Tests.

1.4 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 Db, 40~60G: 4.83dB, 60G~90G: 4.94dB, 90G-140G: 5.46dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s)/Rule(s)	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	Compliant
15.205, §15.209, §15.249	Radiated Emissions	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

During the conducted emission test, the EUT was connected to the outlet of the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiated Emissions

3.2.1 Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500




As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

3.2.2 EUT Setup

Below 1GHz:



1-26.5 GHz:**26.5-40 GHz:****40-90 GHz:**

90-100 GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.249 limits.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 100 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

According to C63.10, the 26.5- 100GHz test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 1.5m, 1m or 0.5m

For 26.5-40GHz

Distance extrapolation factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]}) \text{ dB} = 6.02 \text{ dB}$

For 40-90GHz

Distance extrapolation factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1m]})$ dB=9.54dB

For 90-100GHz

Distance extrapolation factor = $20 \log (\text{specific distance [3m]}/\text{test distance [0.5m]})$ dB=15.56dB

For above 40GHz, external harmonic mixers are utilized. The antenna is scanned around the entire perimeter surface of the EUT, in both horizontal and vertical polarizations. The Mixers and it's RF cables is compose a system for calibration, the conversion factor was added into the test Spectrum Analyzer in testing.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

For 30MHz-26.5GHz:

Result = Reading + Factor

For 26.5GHz-100GHz

Result = Reading + Factor-Distance extrapolation Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 20 dB Emission Bandwidth:

3.3.1 Applicable Standard

FCC §15.215

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

3.3.2 EUT Setup



3.3.3 Test Procedure

1. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
2. Repeat above procedures until all frequencies measured were complete.

3.4 Antenna Requirement

3.4.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

3.4.2 Judgment

Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	24IP_1	Test Date:	2023/4/25
Test Site:	CE	Test Mode:	Transmitting
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	23.5	Relative Humidity: (%)	63	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/03/31	2024/03/30
R&S	EMI Test Receiver	ESR3	102726	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2022/08/07	2023/08/06
Audix	Test Software	E3	190306 (V9)	N/A	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Mode: Transmitting
Port: Line
Note:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.155	13.74	9.61	23.35	55.74	32.39	Average
2	0.155	32.09	9.61	41.70	65.74	24.04	QP
3	0.228	12.63	9.61	22.24	52.50	30.26	Average
4	0.228	29.17	9.61	38.78	62.50	23.72	QP
5	0.449	11.54	9.61	21.15	46.90	25.75	Average
6	0.449	26.38	9.61	35.99	56.90	20.91	QP
7	0.554	18.79	9.62	28.41	46.00	17.59	Average
8	0.554	34.30	9.62	43.92	56.00	12.08	QP
9	1.070	7.48	9.62	17.10	46.00	28.90	Average
10	1.070	22.27	9.62	31.89	56.00	24.11	QP
11	1.520	6.47	9.63	16.10	46.00	29.90	Average
12	1.520	19.37	9.63	29.00	56.00	27.00	QP

Test Mode: Transmitting
Port: neutral
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.156	13.52	9.61	23.13	55.66	32.53	Average
2	0.156	30.68	9.61	40.29	65.66	25.37	QP
3	0.553	29.73	9.62	39.35	46.00	6.65	Average
4	0.553	38.49	9.62	48.11	56.00	7.89	QP
5	1.038	12.68	9.62	22.30	46.00	23.70	Average
6	1.038	21.90	9.62	31.52	56.00	24.48	QP
7	1.337	18.44	9.62	28.06	46.00	17.94	Average
8	1.337	26.70	9.62	36.32	56.00	19.68	QP
9	1.994	14.04	9.63	23.67	46.00	22.33	Average
10	1.994	23.88	9.63	33.51	56.00	22.49	QP
11	4.582	9.76	9.66	19.42	46.00	26.58	Average
12	4.582	22.74	9.66	32.40	56.00	23.60	QP

4.2 Radiation Spurious Emissions

Serial Number:	24IP_1		Test Date:	2023/4/24 ~2023/5/19	
Test Site:	966-1, 966-2		Test Mode:	Transmitting	
Tester:	Carl Xue, coco Tian		Test Result:	Pass	
Environmental Conditions:					
Temperature: (°C)	24.3~26.7	Relative Humidity: (%)	52~61	ATM Pressure: (kPa)	100.2~100.8
Test Equipment List and Details:					
Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2022/07/15	2023/07/14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022/07/17	2023/07/16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022/07/17	2023/07/16
Sonoma	Amplifier	310N	186165	2022/07/17	2023/07/16
Audix	Test Software	E3	201021 (V9)	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2022/07/15	2023/07/14
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2022/08/07	2023/08/06
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2022/08/07	2023/08/06
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/09	2023/11/08
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/02/05	2024/02/04
AH	Preamplifier	PAM-1840VH	190	2022/11/09	2023/11/08
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2022/08/07	2023/08/06
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2021/02/05	2024/02/04
OML	Harmonic Mixer	WR19/M19HWD	U60314-1	2020/10/16	2023/10/15
OML	Horn Antenna	M19RH	11648-03	2020/10/16	2023/10/15
OML	Harmonic Mixer	WR12/M12HWD	E60119-1	2020/10/17	2023/10/16
OML	Horn Antenna	M12RH	E60119-2	2020/10/18	2023/10/17
OML	Harmonic Mixer	WR08/M08HWD	F60315-1	2020/10/22	2023/10/21
OML	Horn Antenna	M08RH	F60315-2	2020/10/24	2023/10/23
* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).					


Test Data:

Please refer to the below table and plots.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.10 Figure 8, the worst orientation was photographed and it's data was recorded.


1) 30MHz-1GHz(High channel was the worst):

Test Mode: Transmitting
Polarization: horizontal
Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	150.011	41.49	-12.00	29.49	43.50	14.01	Peak
2	250.301	41.30	-13.08	28.22	46.00	17.78	Peak
3	300.367	41.21	-10.63	30.58	46.00	15.42	Peak
4	350.477	40.08	-10.03	30.05	46.00	15.95	Peak
5	451.135	36.21	-6.91	29.30	46.00	16.70	Peak
6	601.427	33.53	-5.03	28.50	46.00	17.50	Peak

Test Mode: Transmitting
Polarization: vertical
Note:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	33.562	35.23	-6.34	28.89	40.00	11.11	Peak
2	42.154	41.52	-12.54	28.98	40.00	11.02	Peak
3	99.528	39.02	-14.43	24.59	43.50	18.91	Peak
4	150.011	37.58	-12.00	25.58	43.50	17.92	Peak
5	350.477	37.03	-10.03	27.00	46.00	19.00	Peak
6	451.135	38.90	-6.91	31.99	46.00	14.01	Peak

2) 1GHz-40GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low channel				24002	MHz		
24002.000	75.32	PK	H	5.52	80.84	127.96	47.12
24002.000	69.27	AV	H	5.52	74.79	107.96	33.17
24002.000	72.11	PK	V	5.52	77.63	127.96	50.33
24002.000	66.26	AV	V	5.52	71.78	107.96	36.18
24000.000	45.35	PK	H	5.52	50.87	74.00	23.13
24000.000	35.45	AV	H	5.52	40.97	54.00	13.03
5812.50	35.64	PK	H	13.03	48.67	74.00	25.33
5812.50	22.38	AV	H	13.03	35.41	54.00	18.59
5812.50	34.98	PK	H	13.03	48.01	74.00	25.99
5812.50	21.88	AV	H	13.03	34.91	54.00	19.09
8029.60	43.02	PK	H	16.23	59.25	74.00	14.75
8029.60	36.35	AV	H	16.23	52.58	54.00	1.42
8029.60	41.12	PK	H	16.23	57.35	74.00	16.65
8029.60	34.67	AV	H	16.23	50.90	54.00	3.10
23353.00	50.80	PK	H	6.07	56.87	74.00	17.13
23353.00	38.29	AV	H	6.07	44.36	54.00	9.64
23353.00	50.66	PK	H	6.07	56.73	74.00	17.27
23353.00	37.51	AV	H	6.07	43.58	54.00	10.42
39305.20	51.29	PK	H	16.35	61.62	74.00	12.38
39305.20	38.29	AV	H	16.35	48.62	54.00	5.38
39305.20	52.04	PK	H	16.35	62.37	74.00	11.63
39305.20	38.91	AV	H	16.35	49.24	54.00	4.76
Middle channel				24090	MHz		
24090.000	75.68	PK	H	5.62	81.30	127.96	46.66
24090.000	69.54	AV	H	5.62	75.16	107.96	32.80
24090.000	72.35	PK	V	5.62	77.97	127.96	49.99
24090.000	66.73	AV	V	5.62	72.35	107.96	35.61
5874.00	34.56	PK	H	13.14	47.70	74.00	26.30
5874.00	21.38	AV	H	13.14	34.52	54.00	19.48
5874.00	34.13	PK	V	13.14	47.27	74.00	26.73
5874.00	21.09	AV	V	13.14	34.23	54.00	19.77
8029.60	43.47	PK	H	16.23	59.70	74.00	14.30
8029.60	36.68	AV	H	16.23	52.91	54.00	1.09
8029.60	40.56	PK	V	16.23	56.79	74.00	17.21
8029.60	33.37	AV	V	16.23	49.60	54.00	4.40
23376.50	51.24	PK	H	6.05	57.29	74.00	16.71
23376.50	38.64	AV	H	6.05	44.69	54.00	9.31
23376.50	50.98	PK	V	6.05	57.03	74.00	16.97
23376.50	37.94	AV	V	6.05	43.99	54.00	10.01
39308.60	51.64	PK	H	16.35	61.97	74.00	12.03

39308.60	38.67	AV	H	16.35	49.00	54.00	5.00
39762.40	53.12	PK	V	15.12	62.22	74.00	11.78
39762.40	40.16	AV	V	15.12	49.26	54.00	4.74

High channel 24180 MHz

24180.000	75.32	PK	H	5.72	81.04	127.96	46.92
24180.000	69.43	AV	H	5.72	75.15	107.96	32.81
24180.000	72.17	PK	V	5.72	77.89	127.96	50.07
24180.000	66.25	AV	V	5.72	71.97	107.96	35.99
24250.000	45.78	PK	H	5.80	51.58	74.00	22.42
24250.000	35.65	AV	H	5.80	41.45	54.00	12.55
1711.15	40.85	PK	H	0.78	41.63	74.00	32.37
1711.15	33.64	AV	H	0.78	34.42	54.00	19.58
1711.15	39.67	PK	H	0.78	40.45	74.00	33.55
1711.15	32.53	AV	H	0.78	33.31	54.00	20.69
8029.60	43.45	PK	H	16.23	59.68	74.00	14.32
8029.60	36.46	AV	H	16.23	52.69	54.00	1.31
8029.60	40.38	PK	H	16.23	56.61	74.00	17.39
8029.60	33.52	AV	H	16.23	49.75	54.00	4.25
23481.95	50.46	PK	H	5.99	56.45	74.00	17.55
23481.95	37.81	AV	H	5.99	43.80	54.00	10.20
23481.95	50.11	PK	H	5.99	56.10	74.00	17.90
23481.95	37.34	AV	H	5.99	43.33	54.00	10.67
39813.40	50.81	PK	H	14.92	59.71	74.00	14.29
39813.40	37.89	AV	H	14.92	46.79	54.00	7.21
39813.40	52.29	PK	H	14.92	61.19	74.00	12.81
39813.40	39.73	AV	H	14.92	48.63	54.00	5.37

Result = Reading + Factor- Distance extrapolation Factor

For 1-26.5GHz:

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [3m]})$ dB= 0 dB

For 26.5-40GHz:

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB= 6.02 dB

3) 40GHz-100GHz:

Frequency (GHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low channel 24.002 GHz							
48.004	23.83	PK	H	40.04	54.33	87.96	33.63
48.004	10.66	AV	H	40.04	41.16	67.96	26.80
48.004	23.71	PK	V	40.04	54.21	87.96	33.75
48.004	10.57	AV	V	40.04	41.07	67.96	26.89
72.006	35.11	PK	H	43.78	69.35	87.96	18.61
72.006	21.96	AV	H	43.78	56.20	67.96	11.76
72.006	34.66	PK	V	43.78	68.90	87.96	19.06
72.006	21.60	AV	V	43.78	55.84	67.96	12.12
96.008	30.20	PK	H	45.85	60.49	87.96	27.47
96.008	16.97	AV	H	45.85	47.26	67.96	20.70
96.008	30.05	PK	V	45.85	60.34	87.96	27.62
96.008	16.77	AV	V	45.85	47.06	67.96	20.90
Middle channel 24.09 GHz							
48.180	23.31	PK	H	40.07	53.84	87.96	34.12
48.180	10.50	AV	H	40.07	41.03	67.96	26.93
48.180	22.38	PK	V	40.07	52.91	87.96	35.05
48.180	9.57	AV	V	40.07	40.10	67.96	27.86
72.270	34.99	PK	H	43.82	69.27	87.96	18.69
72.270	21.79	AV	H	43.82	56.07	67.96	11.89
72.270	34.56	PK	V	43.82	68.84	87.96	19.12
72.270	21.43	AV	V	43.82	55.71	67.96	12.25
96.360	29.73	PK	H	45.89	60.06	87.96	27.90
96.360	16.60	AV	H	45.89	46.93	67.96	21.03
96.360	28.74	PK	V	45.89	59.07	87.96	28.89
96.360	15.60	AV	V	45.89	45.93	67.96	22.03
High channel 24.18 GHz							
48.360	24.32	PK	H	40.09	54.87	87.96	33.09
48.360	11.44	AV	H	40.09	41.99	67.96	25.97
48.360	23.23	PK	V	40.09	53.78	87.96	34.18
48.360	10.45	AV	V	40.09	41.00	67.96	26.96
72.540	35.22	PK	H	43.87	69.55	87.96	18.41
72.540	21.94	AV	H	43.87	56.27	67.96	11.69
72.540	35.10	PK	V	43.87	69.43	87.96	18.53
72.540	21.83	AV	V	43.87	56.16	67.96	11.80
96.720	30.25	PK	H	45.94	60.63	87.96	27.33
96.720	17.06	AV	H	45.94	47.44	67.96	20.52
96.720	29.11	PK	V	45.94	59.49	87.96	28.47
96.720	15.87	AV	V	45.94	46.25	67.96	21.71




Result = Reading + Factor- Distance extrapolation Factor




For 40-90GHz:



Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1m]})$ dB= 9.54 dB

For 90-100GHz:

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [0.5m]})$ dB= 15.56 dB

Test Plots(Worst for High Channel)1GHz-6GHz
Horizontal1GHz-6GHz
Vertical6GHz-18GHz
Horizontal

Test Plots(Worst for High Channel)6GHz-18GHz
Vertical18GHz-26.5GHz
Horizontal18GHz-26.5GHz
Vertical

Test Plots(Worst for High Channel)26.5GHz-40GHz
Horizontal26.5GHz-40GHz
Vertical

4.3 20 dB Emission Bandwidth:

Serial Number:	24IP_1	Test Date:	2023/5/17
Test Site:	966-1	Test Mode:	Transmitting
Tester:	coco Tian	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	24.3	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.2
----------------------	------	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101591	2022/07/15	2023/07/14
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/02/05	2024/02/04
AH	Preamplifier	PAM-1840VH	190	2022/11/09	2023/11/08
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2022/08/07	2023/08/06

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).



===== END OF REPORT =====