

**ATC**

# TEST REPORT

Applicant Name: Audfly Technology(Suzhou) Co., Ltd  
Address: No.78, Keling Road, SND Software Park, New District, Suzhou, Jiangsu Suzhou China  
Report Number: KS1220503-17661E-00B  
FCC ID: 2A5S9-AUD07FSMINI

**Test Standard (s)**  
FCC PART 15.247

**Sample Description**

Product Name: Audfly  
Trademark: N/A  
Tested Model: FS-Mini-B  
Series Model: FS-Mini-W  
Date Received: 2022-03-24  
Date of Test: 2022-03-28 to 2022-05-20  
Report Date: 2022-06-22

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

Ting Lü  
EMC Engineer

**Approved By:**

Candy Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “★”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**Shenzhen Accurate Technology Co., Ltd.**

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290      Fax: +86 755-26503396      Web: [www.atc-lab.com](http://www.atc-lab.com)

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS</b> .....	<b>8</b>
<b>TEST EQUIPMENT LIST</b> .....	<b>9</b>
<b>FCC §15.247 (i) &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b> .....	<b>10</b>
<b>FCC §15.203 – ANTENNA REQUIREMENT</b> .....	<b>12</b>
APPLICABLE STANDARD .....	12
ANTENNA CONNECTOR CONSTRUCTION .....	12
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS</b> .....	<b>13</b>
APPLICABLE STANDARD .....	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE .....	13
FACTOR & MARGIN CALCULATION .....	14
TEST DATA .....	14
<b>FCC §15.205, §15.209 &amp; §15.247(d) – RADIATED EMISSIONS</b> .....	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP .....	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	18
TEST PROCEDURE .....	18
FACTOR & MARGIN CALCULATION .....	18
TEST DATA .....	18
<b>FCC §15.247(a) (1)-CHANNEL SEPARATION TEST</b> .....	<b>24</b>
APPLICABLE STANDARD .....	24
TEST PROCEDURE .....	24
TEST DATA .....	24
<b>FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH</b> .....	<b>27</b>
APPLICABLE STANDARD .....	27
TEST PROCEDURE .....	27
TEST DATA .....	28
<b>FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST</b> .....	<b>34</b>
APPLICABLE STANDARD .....	34
TEST PROCEDURE .....	34

TEST DATA .....	34
<b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST DATA .....	37
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>48</b>
APPLICABLE STANDARD .....	48
TEST PROCEDURE .....	48
TEST DATA .....	48
<b>FCC §15.247(d) - BAND EDGES TESTING .....</b>	<b>54</b>
APPLICABLE STANDARD .....	54
TEST PROCEDURE .....	54
TEST DATA .....	54

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Product Name	Audfly
Trade Mark	N/A
Tested Model	FS-Mini-B
Series Model	FS-Mini-W
Frequency Range	2402~2480MHz
Maximum conducted Peak output power	1.84dBm
Modulation Technique	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification*	Internal PCB Antenna: 1.2dBi (provided by the applicant)
Voltage Range	DC 12V from adapter
Sample number	KS1220503-17661E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter Information:	Model: XSG1202000US Input: AC100-240V~50/60Hz, 0.6A, Max Output: 12V, 2.0A

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
AC Power Lines Conducted Emissions	2.72dB	
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
Temperature	1°C	
Humidity	6%	
Supply voltages	0.4%	

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2404	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

### EUT Exercise Software

Software “BT\_Tool”\* was used to test provided by manufacturer and power level was Default\*.

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
OPPO	Phone	Unknown	Unknown

### External I/O Cable


Cable Description	Length(m)	From Port	To
Power Cable	1.0	EUT	Adapter
Audio cable	1.5	EUT	Phone

### Block Diagram of Test Setup

For Conducted Emission:



For Radiated Emission:



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i), §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2022/02/03	2023/02/02
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/22	2022/12/21
Anritsu Corp	50Ω Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2021/12/25	2022/12/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2021/05/18	2022/05/17
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Radiated Emission Test Software: EZ EMC V 1.1.4.2					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV40	101495	2021/12/24	2022/12/23
WEINSCHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Cable	No.C01	C01	Each Time	

**\* Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

### **Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### **Result**

#### **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For worst case:

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402-2480	1.2	1.32	-1.0	0.79	20	0.0002	1
BT	2402-2480	1.2	1.32	2.0	1.58	20	0.0004	1

Note: 1. The tune up conducted power was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result:** Compliant.

## **FCC §15.203 – ANTENNA REQUIREMENT**

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has one Internal PCB Antenna arrangement, which was permanently attached and the antenna gain is 1.2dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207(a)

### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$


## Test Data

### Environmental Conditions

<b>Temperature:</b>	23 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.2 kPa


*The testing was performed by Jason Liu on 2022-05-13.*

*EUT operation mode: Transmitting in low channel of 8DPSK mode (Worst case as below)*

**AC 120V/60 Hz, Line**

Site : Shielding Room  
Condition: Line  
Job No. : KS1220503-17661E-RF  
Mode : BT Transmitting  
Power : AC 120V 60Hz

Freq	Factor	Read		Limit	Over	Remark
		MHz	dB	Level	Level	
1	0.155	9.80	31.25	41.05	55.70	-14.65 Average
2	0.155	9.80	40.45	50.25	65.70	-15.45 QP
3	0.222	9.80	23.46	33.26	52.74	-19.48 Average
4	0.222	9.80	33.11	42.91	62.74	-19.83 QP
5	0.324	9.80	25.16	34.96	49.59	-14.63 Average
6	0.324	9.80	30.92	40.72	59.59	-18.87 QP
7	0.504	9.80	23.24	33.04	46.00	-12.96 Average
8	0.504	9.80	32.16	41.96	56.00	-14.04 QP
9	3.426	9.83	18.24	28.07	46.00	-17.93 Average
10	3.426	9.83	25.05	34.88	56.00	-21.12 QP
11	5.429	9.85	17.34	27.19	50.00	-22.81 Average
12	5.429	9.85	23.84	33.69	60.00	-26.31 QP



**AC 120V/60 Hz, Neutral**

Site : Shielding Room  
Condition: Neutral  
Job No. : KS1220503-17661E-RF  
Mode : BT Transmitting  
Power : AC 120V 60Hz

Freq	Factor	Read		Limit	Over	Over	Remark
		MHz	dB	dBuV	dBuV	Line	Limit
1	0.160	9.80	29.72	39.52	55.49	-15.97	Average
2	0.160	9.80	38.40	48.20	65.49	-17.29	QP
3	0.258	9.80	27.14	36.94	51.51	-14.57	Average
4	0.258	9.80	33.29	43.09	61.51	-18.42	QP
5	0.321	9.80	22.22	32.02	49.69	-17.67	Average
6	0.321	9.80	30.12	39.92	59.69	-19.77	QP
7	0.640	9.81	13.56	23.37	46.00	-22.63	Average
8	0.640	9.81	22.24	32.05	56.00	-23.95	QP
9	4.949	9.89	12.79	22.68	46.00	-23.32	Average
10	4.949	9.89	20.75	30.64	56.00	-25.36	QP
11	5.058	9.89	12.84	22.73	50.00	-27.27	Average
12	5.058	9.89	19.19	29.08	60.00	-30.92	QP

**FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS****Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

**EUT Setup****Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

## Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

## Test Data

### Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Level Li on 2022-05-14.

EUT operation mode: Transmitting

(Pre-scan with GFSK, π/4-DQPSK, 8DPSK mode, the worst case is 8DPSK Mode)

**30MHz-1GHz: (8DPSK mode, Low Channel worst case)**

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded

**Horizontal**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : S1220503-17661E-RF

Test Mode: BT Transmitting

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
1	175.037	-13.12	50.20	37.08	43.50	-6.42 QP
2	215.551	-11.65	49.10	37.45	43.50	-6.05 Peak
3	295.018	-9.27	49.07	39.80	46.00	-6.20 Peak
4	307.292	-8.98	47.93	38.95	46.00	-7.05 QP
5	319.517	-8.48	44.93	36.45	46.00	-9.55 Peak
6	384.100	-7.08	37.52	30.44	46.00	-15.56 Peak

## Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : S1220503-17661E-RF  
Test Mode: BT Transmitting

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	52.460	-10.06	42.81	32.75	40.00	-7.25	QP
2	135.150	-15.03	45.85	30.82	43.50	-12.68	Peak
3	172.070	-13.37	49.17	35.80	43.50	-7.70	Peak
4	208.855	-11.86	43.44	31.58	43.50	-11.92	Peak
5	319.517	-8.48	33.59	25.11	46.00	-20.89	Peak
6	977.465	2.38	38.71	41.09	54.00	-12.91	Peak

**1-25 GHz (worst case):****BT:**

Frequency (MHz)	Receiver		Turtable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	
	Reading (dBuV)	PK/AV		Height (m)	Polar (H/V)					
BT 3DH1, Low Channel										
2310	55.54	PK	59	2.1	H	-7.23	48.31	74	-25.69	
2310	54.67	PK	14	1.9	V	-7.23	47.44	74	-26.56	
2390	53.33	PK	291	1.7	H	-7.21	46.12	74	-27.88	
2390	54.87	PK	33	1.4	V	-7.21	47.66	74	-26.34	
4804	51.7	PK	55	1.5	H	-3.52	48.18	74	-25.82	
4804	50.83	PK	281	1.8	V	-3.52	47.31	74	-26.69	
BT 3DH1, Middle Channel										
4882	50.62	PK	252	1.6	H	-3.37	47.25	74	-26.75	
4882	49.9	PK	151	2.0	V	-3.37	46.53	74	-27.47	
BT 3DH1, High Channel										
2483.5	53.57	PK	258	1.4	H	-7.2	46.37	74	-27.63	
2483.5	52.42	PK	69	1.8	V	-7.2	45.22	74	-28.78	
2500	53.55	PK	91	1.5	H	-7.18	46.37	74	-27.63	
2500	52.97	PK	184	1.6	V	-7.18	45.79	74	-28.21	
4960	49.76	PK	160	1.7	H	-3.01	46.75	74	-27.25	
4960	49.53	PK	56	1.8	V	-3.01	46.52	74	-27.48	

**Note:**

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading



Margin = Absolute Level - Limit

The other spurious emission which is in the noise floor level was not recorded.

For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


**1-18 GHz (Worst case):**

Pre-scan plots  
8DPSK mode Low Channel  
Horizontal




**18 -25GHz (Worst case):**

Pre-scan plots  
8DPSK mode Low Channel  
Horizontal



Vertical



## FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

### Test Data

#### Environmental Conditions

Temperature:	23 °C
Relative Humidity:	57 %
ATM Pressure:	101.2 kPa



The testing was performed by Paul Liu on 2022-03-29.


EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Result [MHz]	Limit [MHz]	Verdict
DH1	Ant1	Hop	0.999	>=0.925	PASS
2DH1	Ant1	Hop	1.003	>=0.863	PASS
3DH1	Ant1	Hop	0.999	>=0.865	PASS

Please refer to the below plots:





Date: 29 MAR 2022 11:44:35

## FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

### Applicable Standard


Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.



**Test Data****Environmental Conditions**

<b>Temperature:</b>	23°C
<b>Relative Humidity:</b>	56%
<b>ATM Pressure:</b>	101.0 kPa


The testing was performed by Paul Liu on 2022-03-28.


EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Antenna	Channel	20db EBW [MHz]	Limit [MHz]	Verdict
DH1	Ant1	2402	0.925	---	PASS
		2441	0.925	---	PASS
		2480	0.925	---	PASS
2DH1	Ant1	2402	1.289	---	PASS
		2441	1.294	---	PASS
		2480	1.294	---	PASS
3DH1	Ant1	2402	1.298	---	PASS
		2441	1.298	---	PASS
		2480	1.298	---	PASS

Please refer to the below plots:



**20 dB EMISSION BANDWIDTH**




Date: 28.MAR.2022 16:53:55




Date: 28.MAR.2022 16:48:09






Date: 28.MAR.2022 16:29:14



Date: 28.MAR.2022 16:31:27



Date: 28.MAR.2022 16:33:13

## FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

### Test Data

#### Environmental Conditions



Temperature:	23 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Paul Liu on 2022-03-28.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Result [Num]	Limit [Num]	Verdict
DH1	Ant1	Hop	79	>=15	PASS
2DH1	Ant1	Hop	79	>=15	PASS
3DH1	Ant1	Hop	79	>=15	PASS





## **FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**

### **Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **Test Procedure**

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW  $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	23.5 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.6 kPa

*The testing was performed by Paul Liu on 2022-05-20.*

*EUT operation mode: Transmitting*



Test Result: Compliant.


Test Mode	Antenna	Channel	Burst Width [ms]	Total Hops [Nun]	Results [s]	Limit [s]	Verdict
DH1	Ant1	Hop	0.41	330	0.135	<=0.4	PASS
DH3	Ant1	Hop	1.67	190	0.317	<=0.4	PASS
DH5	Ant1	Hop	2.94	110	0.323	<=0.4	PASS
2DH1	Ant1	Hop	0.42	330	0.139	<=0.4	PASS
2DH3	Ant1	Hop	1.70	150	0.255	<=0.4	PASS
2DH5	Ant1	Hop	2.95	130	0.384	<=0.4	PASS
3DH1	Ant1	Hop	0.43	330	0.142	<=0.4	PASS
3DH3	Ant1	Hop	1.69	180	0.304	<=0.4	PASS
3DH5	Ant1	Hop	2.98	130	0.387	<=0.4	PASS

Note 1: A period time=0.4\*79=31.6(s), Result=Burst Width\*Total Hops


Note 2: Total Hops =Hopping Number in 3.16s\*10

Note 3: Hoping Number in 3.16s=Total of highest signals in 3.16s (Second high signals were other channel)








Date: 20.MAY.2022 11:16:47




Date: 20.MAY.2022 11:28:28








Date: 20.MAY.2022 11:12:35




Date: 20.MAY.2022 11:31:13








Date: 20.MAY.2022 11:20:38




Date: 20.MAY.2022 11:27:24







Date: 20.MAY.2022 11:18:06



Date: 20.MAY.2022 11:29:59



Date: 20.MAY.2022 11:21:13



Date: 20.MAY.2022 15:22:59

## **FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**

### **Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### **Test Procedure**

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

### **Test Data**

#### **Environmental Conditions**



<b>Temperature:</b>	23 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa



*The testing was performed by Paul Liu on 2022-03-28.*


*EUT operation mode: Transmitting*

Test Result: Compliant.


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	-1.25	<=30	PASS
		2441	-2.06	<=30	PASS
		2480	-2.80	<=30	PASS
2DH1	Ant1	2402	1.25	<=20.97	PASS
		2441	0.44	<=20.97	PASS
		2480	-0.34	<=20.97	PASS
3DH1	Ant1	2402	1.84	<=20.97	PASS
		2441	1.06	<=20.97	PASS
		2480	0.20	<=20.97	PASS









Date: 28.MAR.2022 16:22:03




Date: 28.MAR.2022 16:23:08



Date: 28.MAR.2022 16:26:19



Date: 28.MAR.2022 16:25:48



Date: 28.MAR.2022 16:23:42

## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Data



#### Environmental Conditions



<b>Temperature:</b>	23 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.2 kPa


The testing was performed by Paul Liu from 2022-03-28 to 2022-03-29.

EUT operation mode: Transmitting


Test Result: Compliant.

**Conducted Band Edge Result:**







Date: 28.MAR.2022 17:00:38



Date: 28.MAR.2022 16:58:50




Date: 29.MAR.2022 11:35:40




Date: 29.MAR.2022 11:23:42

## 3DH1 Ant1 Low 2402





Date: 28.MAR.2022 17:01:38

## 3DH1 Ant1 High 2480



Date: 28.MAR.2022 17:03:31



\*\*\*\*\* END OF REPORT \*\*\*\*\*