

# Test Report

## 21-1-0167501T02a



**Number of pages:** 18 **Date of Report:** 2022-Jun-17

**Testing company:** CETECOM GmbH  
Im Teelbruch 116  
45219 Essen Germany  
Tel. + 49 (0) 20 54 / 95 19-0  
Fax: + 49 (0) 20 54 / 95 19-150 **Applicant:** UAB Pulsetto

**Test Object /  
Tested Device(s):** Nerve stimulator  
Pulsetto

**FCC ID:** 2A5T3-BXN-PU-22V001 **Contains IC:** --

**Testing has been  
carried out in  
accordance with:** **FCC Regulations:**  
Title 47 CFR, Chapter I  
FCC Regulations, Subchapter A  
Subpart B: §15.109 (Class B limits)

Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".

**Test Results:**  **The EUT complies with the requirements in respect of selected parameters subject to the test.**  
The test results relate only to devices specified in this document

**Signatures:**



Dipl.-Ing. Ninovic Perez  
Test Lab Manager  
Authorization of test report

B.Sc H.Laayouni  
Test manager  
Responsible of test report

## Table of Contents

Table of Annex.....	3
1.1    Disclaimer and Notes.....	4
1.1.1    Summary of Test Results .....	5
1.2.1    Summary of Test Methods .....	5
2.1    Identification of the Testing Laboratory.....	6
2.2    General limits for environmental conditions.....	6
2.3    Test Laboratories sub-contracted.....	6
2.4    Organizational Items .....	6
2.5    Applicant's details .....	6
2.6    Manufacturer's details .....	6
2.7    EUT: Type, S/N etc. and short descriptions used in this test report .....	7
2.8    Auxiliary Equipment (AE): Type, S/N etc. and short descriptions.....	7
2.9    Connected cables .....	7
2.10    Softwares .....	7
2.11    EUT set-ups .....	7
2.12    EUT operation modes.....	7
3.1    General Data of Main EUT as Declared by Applicant.....	8
3.2    Modifications on Test sample.....	8
4.1    DC-Power Lines Conducted Emissions.....	9
4.2    Radiated field strength emissions 30 MHz – 1 GHz.....	11
4.3    Radiated field strength emissions above 1 GHz .....	13
4.4    Results from external laboratory.....	16
4.5    Opinions and interpretations .....	16
4.6    List of abbreviations .....	16

**Table of Annex**

Annex No.	Contents	Reference Description	Total Pages
Annex 1	Test result diagrams	<b>CETECOM_TR21_1_0167501T02a_A1</b>	10
Annex 2	Internal photographs of EUT	--	--
Annex 3	External photographs of EUT	<b>CETECOM_TR21_1_0167501T02a_A3</b>	3
Annex 4	Test set-up photographs	<b>CETECOM_TR21_1_0167501T02a_A4</b>	3

The listed attachments are separate documents.

## 1 General information

### 1.1 Disclaimer and Notes

The test results of this test report relate exclusively to the test item specified in this test report as specified in chapter 2.7. CETECOM does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM.

The testing service provided by CETECOM has been rendered under the current "General Terms and Conditions for CETECOM". CETECOM will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM test report include or imply any product or service warranties from CETECOM, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM.

All rights and remedies regarding vendor's products and services for which CETECOM has prepared this test report shall be provided by the party offering such products or services and not by CETECOM.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at CETECOM.

Also we refer on special conditions which the applicant should fulfill according §2.927 to §2.948, special focus regarding modification of the equipment and availability of sample equipment for market surveillance tests.

## 1.1. Summary of Test Results

Test case	Reference in FCC <input checked="" type="checkbox"/>	Reference in ISED <input type="checkbox"/>	Reference in RSS-GEN <input type="checkbox"/>	Remark	Result
<a href="#">AC-Power Lines Conducted Emissions</a>	§15.107	ICES-003, Issue 7	RSS-Gen., Issue 5 Chapter 8.9, Chapter 7.3	--	PASSED
<a href="#">Radiated field strength emissions 30 MHz – 1 GHz</a>	§15.109 §15.33 §15.35	ICES-003, Issue 7	RSS-Gen., Issue 5 Chapter 8.9, Chapter 7.3	--	PASSED
<a href="#">Radiated field strength emissions above 1 GHz</a>	§15.109 §15.33 §15.35	ICES-003, Issue 7	RSS-Gen., Issue 5 Chapter 8.9, Chapter 7.3	--	PASSED

PASSED

The EUT complies with the essential requirements in the standard.

FAILED

The EUT does not comply with the essential requirements in the standard.

NP

The test was not performed by the CETECOM Laboratory.

\*The calculation of the measurement uncertainty shows compliance with the "maximum measurement uncertainties" of the tested standard and therefore for result evaluation the stated uncertainties will not be additionally added to the measured results.

## 1.2. Summary of Test Methods

Test case	Test method
AC-Power Lines Conducted Emissions	ANSI C63.4-2014 chapter 7
Radiated field strength emissions 30 MHz – 1 GHz	ANSI C63.4-2014 chapter 8.2.3
Radiated field strength emissions above 1 GHz	ANSI C63.4-2014 chapter 8.3

## 2 Administrative Data

### 2.1 Identification of the Testing Laboratory

Company name:	CETECOM GmbH
Address:	Im Teelbruch 116 45219 Essen - Kettwig Germany
Responsible for testing laboratory:	Dipl.-Ing. Ninovic Perez
Accreditation scope:	<a href="#">DAkkS Webpage</a>
Test location for Measurements above 18 GHz	CETECOM GmbH; Im Teelbruch 116; 45219 Essen - Kettwig

### 2.2 General limits for environmental conditions

Temperature:	22±2 °C
Relative. humidity:	45±15% rH

### 2.3 Test Laboratories sub-contracted

Company name:	--
---------------	----

### 2.4 Organizational Items

Order No.:	1
Responsible test manager:	B.Sc H.Laayouni
Receipt of EUT:	2022-Apr-21
Date(s) of test:	2022- Apr-22 ; 2022 Jun-06
Version of template:	14.3

### 2.5 Applicant's details

Applicant's name:	UAB Pulsetto
Address:	Babinių Sodų 18-oji g. 29 LT-08456, Vilnius
	Lithuania
Contact Person:	Vitalijus Majorovas
Contact Person's Email:	vitalijus.majorovas@gmail.com

### 2.6 Manufacturer's details

Applicant's name:	UAB Pulsetto
Address:	Babinių Sodų 18-oji g. 29 LT-08456, Vilnius
	Lithuania

## 2.7 EUT: Type, S/N etc. and short descriptions used in this test report

Short description*)	PMT Sample No.	Product	Model	Type	S/N	HW status	FW status
EUT 01	21-1-01675S02_C01	Nerve stimulator	Pulsetto	Pulsetto_ST	N/A	1.0.0	1.0.0
EUT 2	21-1-01675S08_C01	Nerve stimulator	Pulsetto	Pulsetto_ST	N/A	1.0.0	1.0.0

\*) EUT short description is used to simplify the identification of the EUT in this test report.

## 2.8 Auxiliary Equipment (AE): Type, S/N etc. and short descriptions

Short description*)	PMT Sample No.	Auxiliary Equipment	Model	Type	S/N	HW status	SW status
AE 01	--	Travel Adapter	ER-TA50EWE	--	SC2HB30DS/A-E	--	--

\*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

## 2.9 Connected cables

Short description*)	PMT Sample No.	Cable type	Connectors	Lenght
CAB 01	--	USB (flat cable)	Type C	100 cm

\*) CAB short description is used to simplify the identification of the connected cables in this test report.

## 2.10 Softwares

SW No.*)	Sample No.	SW Name	Description	SW Status
SW 1	21-1-01675S07_C01	YAT		2.4.1

\*) SW short description is used to simplify the identification of the used software in this test report. If the table above does not show any other line than the headline, no SW was used during testing nor was taken into account for evaluation.

## 2.11 EUT set-ups

set-up no.*)	Combination of EUT and AE	Description
1	EUTA + AE1 + CAB1	Used for Radiated measurements.

\*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

## 2.12 EUT operation modes

EUT operating mode no.*)	Operating modes	Additional information
Operating mode 1	Stimulation + Charging Mode	Stimulation active during the Measurements. Batterie charging during the Measurements

\*) EUT operating mode no. is used to simplify the test report.

### 3 Equipment under test (EUT)

#### 3.1 General Data of Main EUT as Declared by Applicant

Product name	Nerve stimulator		
Kind of product	Pulsetto		
Firmware	<input checked="" type="checkbox"/> for normal use	<input type="checkbox"/> Special version for test execution	
Power supply	<input type="checkbox"/> AC Mains	-	
	<input checked="" type="checkbox"/> DC Mains	5 VDC over the USB	
	<input checked="" type="checkbox"/> Battery	-	
Operational conditions	$T_{nom} = -40 \text{ }^{\circ}\text{C}$	$T_{min} = -40 \text{ }^{\circ}\text{C}$	$T_{max} = 80 \text{ }^{\circ}\text{C}$
EUT sample type	Pre-Production		
Weight	0,1Kg		
Size	11.0 x 10.0 x 4.0 cm		
Interfaces/Ports	USB-C		
For further details refer Applicants Declaration & following technical documents			

#### 3.2 Modifications on Test sample

Additions/deviations or exclusions	--
------------------------------------	----

## 4 Measurements

### 4.1 AC-Power Lines Conducted Emissions

#### 4.1.1 Description of the general test setup and methodology, see below example:

The radio frequency voltage conducted back into the AC power line in the frequency range 150 kHz to 30 MHz has to be investigated.

Compliance should be tested by measuring the radio frequency voltage between each power line and ground at the power terminals in the stated frequency range.

A 50 Ohm / 50  $\mu$ H line impedance stabilization network (LISN) is used coupling the interface to the measurement equipment.


The EUT power input leads are connected through the LISN to the AC-power source. The LISN enclosure is electrically connected to the ground plane. The measuring instrument is connected to the coaxial output of the LISN.

Tabletop devices were set-up on an 80 cm height above reference ground plane, floor standing equipment 10 cm raised above ground plane.

Measurements have been performed on each phase line and neutral line of the devices AC-power lines.

The EUT was power supplied with 120 V/60 Hz. The EUT was tested in the defined operating mode and installed (connected) to accessory equipment according the general description of use given by the applicant.

**Schematic:**



#### Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

#### Exploratory, preliminary measurements

As a first step, determines the worst-case phase line (neutral or phase) as well as the most critical operating mode of the equipment. A complete frequency-sweep with PK-Detector is performed on each current-carrying conductor.

#### Final measurement on critical frequencies

For power phases and critical frequencies (Margin to AV- or QP limit lower than 3 dB) as a second step includes measurements with receivers detector set to Quasi-Peak and Average.

**Formula:**

$$V_C = V_R + C_L \quad (1)$$

$$M = L_T - V_C \quad (2)$$

$V_C$  = measured Voltage –corrected value

$V_R$  = Receiver reading

$C_L$  = Cable loss

$M$  = Margin

$L_T$  = Limit

All units are dB-units, positive margin means value is below limit.

**4.1.2 Measurement Location**

Test site	120919 – Conducted Emission
-----------	-----------------------------

**4.1.3 Limit**

Frequency Range [MHz]	QUASI-Peak [dB $\mu$ V]	AVERAGE [dB $\mu$ V]
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**4.1.4 Result**

Diagram	Mode	Power Line	Max [dB $\mu$ V]	Detector	Result
1.01	OP mode 1	L1	45.28@3.98MHz	AVG	Passed


Remark: see more in diagrams in separate document **CETECOM\_TR21\_1\_0167501T02a\_A1**

## 4.2 Radiated field strength emissions 30 MHz – 1 GHz

### 4.2.1 Description of the general test setup and methodology, see below example:

Evaluating the field emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a NSA-compliant semi anechoic room (SAR) recognized by the regulatory commissions.

#### Schematic:



#### Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

##### Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 90°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

Measurement antenna: horizontal and vertical, heights: 1,0 m and 1,82 m as worst-case determined by an exploratory emission measurements. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

##### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by main-taining the EUT's worst-case operation mode, cable position, etc. either on 10m OATS or 3m semi-anechoic room.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position). The measurement antenna height between 1 m and 4 m.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out

### Formula:

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

AF = Antenna factor

C<sub>L</sub> = Cable loss

D<sub>F</sub> = Distance correction factor (if used)

E<sub>C</sub> = Electrical field – corrected value

E<sub>R</sub> = Receiver reading

G<sub>A</sub> = Gain of pre-amplifier (if used)

L<sub>T</sub> = Limit

M = Margin

All units are dB-units, positive margin means value is below limit.

### 4.2.2 Measurement Location

Test site	120901 - SAC - Radiated Emission <1GHz
-----------	--

### 4.2.3 Limit

Frequency Range [MHz]	Class B <input checked="" type="checkbox"/> (3 meters)		Class A <input type="checkbox"/> (10 meters)		Detector	RBW / VBW [kHz]
	Limit [μV/m]	Limit [dBμV/m]	Limit [μV/m]	Limit [dBμV/m]		
30 - 88	100	40.0	90	39.0	Quasi peak	100 / 300
88 - 216	150	43.5	150	43.5	Quasi peak	100 / 300
216 - 960	200	46.0	210	46.4	Quasi peak	100 / 300
960 - 1000	500	54.0	300	49.5	Quasi peak	100 / 300

### 4.2.4 Result

Diagram	Mode	Maximum Level [dBμV/m] Frequency Range 30 – 1000 MHz	Result
<a href="#">3.01_Laying</a>	Op mode 1	23.15 dBμV/m @ 189.84MHz	Passed
<a href="#">3.01_Standing</a>	Op. mode 1	30.31 dBμV/m @ 185.16MHz	Passed


Remark: for more informations and graphical plot see annex A1 [CETECOM\\_TR21\\_1\\_0167501T02a\\_A1](#)

## 4.3 Radiated field strength emissions above 1 GHz

### 4.3.1 Description of the general test setup and methodology, see below example:

Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 18-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT.

#### Schematic:



#### Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

#### Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 1.55 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 15°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

The measurements are performed in horizontal and vertical polarization of the measurement antennas. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

#### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself over 3-orthogonal axis and the height for EUT with large dimensions or three axis scan for portable/small equipment.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

### Formula:

$$E_C = E_R + A_F + C_L + D_F - G_A \quad (1)$$

$E_C$  = Electrical field – corrected value

$E_R$  = Receiver reading

$$M = L_T - E_C \quad (2)$$

$M$  = Margin

$L_T$  = Limit

$A_F$  = Antenna factor

$C_L$  = Cable loss

$D_F$  = Distance correction factor (if used)

$G_A$  = Gain of pre-amplifier (if used)

All units are dB-units, positive margin means value is below limit.

### 4.3.2 Measurement Location

Test site until 18GHz	12094 - FAC1 - Radiated Emissions
Test site above 18GHz	120907 -FAC2- Radiated Emission>18GHz

### 4.3.3 Limit

Radiated emissions limits (3 meters)				
Frequency Range [MHz]	Limit [ $\mu$ V/m]	Limit [ $\text{dB}\mu$ V/m]	Detector	RBW / VBW [kHz]
Above 1000	500	54	Average	1000 / 3000
Above 1000	5000	74	Peak	1000 / 3000

#### 4.3.4 Result

Diagram	Mode	Frequency Range 1 – 15 GHz Maximum LeveldB $\mu$ V/m]	Detector	Result
<a href="#">4.01</a>	OP. mode 1	58.49 dB $\mu$ V/m@2.75GHz	Peak	Passed

Remark: for more informations and graphical plot see annex A1 **CETECOM\_TR21\_1\_0167501T02a\_A1**

Diagram	Mode	Frequency Range 15 – 26,5 GHz Maximum LeveldB $\mu$ V/m]	Detector	Result
4.02_AntH 4.02_AntV	OP. mode 1	39.53 39.41	Average Average	Passed Passed
4.03_AntH 4.03_AntV	OP. mode 1	49.63 (Noise level) 49.62 (Noise level)	Average Average	Passed Passed

Remark: for more informations and graphical plot see annex A1 **CETECOM\_TR21\_1\_0167501T02a\_A1**

## 4.4 Results from external laboratory

None	-
------	---

## 4.5 Opinions and interpretations

None	-
------	---

## 4.6 List of abbreviations

None	-
------	---

# 5 Equipment lists

ID	Description	Manufacturer	SerNo	Cal due date
	<b>120919 - Conducted emission</b>			
20005	AC - LISN 50 Ohm/50µH ESH2-Z5	Rohde & Schwarz Messgerätebau GmbH	861741/005	2023-May-18
20007	Single-Line V-Network (50 Ohm/5µH) ESH3-Z6	Rohde & Schwarz Messgerätebau GmbH	892563/002	2023-May-17
20468	Digital Multimeter Fluke 112	Fluke Deutschland GmbH	90090455	2024-Jun-01
20556	Thermo-/Hygrometer WS-9400	Conrad Electronic GmbH	--	2023-Jul-15
20033	RF-current probe (100kHz-30MHz) ESH2-Z1	Rohde & Schwarz Messgerätebau GmbH	879581/18	2023-Jun-01
20377	EMI Test Receiver ESCS30	Rohde & Schwarz Messgerätebau GmbH	100160	2023-May-18
	<b>120901 - SAC - Radiated Emission &lt;1GHz</b>			
20574	Biconilog Hybrid Antenna BTA-L	Frankonia GmbH	980026L	03.05.2022
20620	EMI Test Receiver ESU26	Rohde & Schwarz Messgerätebau GmbH	100362	07.06.2023
20482	filter matrix Filter matrix SAR 1	CETECOM GmbH	-	
20885	Power Supply EA3632A	Agilent Technologies Deutschland GmbH	75305850	
20487	System CTC NSA-Verification SAR-EMI System EMI field (SAR) NSA	ETS-Lindgren GmbH	-	23.03.2022
	<b>120904 - FAC1 - Radiated Emissions</b>			
20341	Digital Multimeter Fluke 112	Fluke Deutschland GmbH	81650455	07.06.2023
20720	EMC32 [FAC]	Rohde & Schwarz Messgerätebau GmbH	V10.xx	
20489	EMI Test Receiver ESU40	Rohde & Schwarz Messgerätebau GmbH	1000-30	23.06.2023
20254	High Pass Filter 5HC 2600/12750-1.5KK (GSM1800/1900/DECT)	Trilithic	23042	
20868	High Pass Filter AFH-07000	AtlanTecRF	16071300004	
20291	High Pass Filter WHJ 2200-4EE (GSM 850/900)	Wainwright Instruments GmbH	14	
20020	Horn Antenna 3115	EMCO Elektronik GmbH	9012-3629	08.04.2023

ID	Description	Manufacturer	SerNo	Cal due date
20302	Horn Antenna BBHA9170 (Meas 1)	Schwarzbeck Mess-Elektronik OHG	155	15.04.2023
20512	Notch Filter WRCA 800/960-02/40-6EEK (GSM 850)	Wainwright Instruments GmbH	24	
20290	Notch Filter WRCA 901,9/903,1SS (GSM 900)	Wainwright Instruments GmbH	3RR	
20122	Notch Filter WRCB 1747/1748 (GSM 1800)	Wainwright Instruments GmbH	12	
20121	Notch Filter WRCB 1879,5/1880,5EE (GSM 1900)	Wainwright Instruments GmbH	15	
20448	Notch Filter WRCT 1850.0/2170.0-5/40-10SSK (WCDMA-FDD II)	Wainwright Instruments GmbH	5	
20066	Notch Filter WRCT 1900/2200-5/40-10EEK (WCDMA-FDDI)	Wainwright Instruments GmbH	5	
20449	Notch Filter WRCT 824.0/894.0-5/40-8SSK (WCDMA FDD V)	Wainwright Instruments GmbH	1	
20611	Power Supply E3632A	Agilent Technologies Deutschland GmbH	KR 75305854	
20338	Pre-Amplifier 100MHz - 26GHz JS4-00102600-38-5P	Miteq Inc.	838697	
20484	Pre-Amplifier 2,5GHz - 18GHz AMF-5D-02501800-25-10P	Miteq Inc.	1244554	
20287	Pre-Amplifier 25MHz - 4GHz AMF-2D-100M4G-35-10P	Miteq Inc.	379418	
20690	Spectrum Analyzer FSU	Rohde & Schwarz Messgerätebau GmbH	100302/026	07.06.2023
20439	UltraLog-Antenna HL 562	Rohde & Schwarz Messgerätebau GmbH	100248	10.03.2023
20828	Netgear Nighthawk x4S	NETGEAR Ireland International Ltd	5K5188590067B	
20732	Signal- and Spectrum Analyzer FSW67	Rohde & Schwarz Messgerätebau GmbH	104023	08.06.2023

## 6 Measurement Uncertainty valid for conducted/radiated measurements

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor  $k$ , such that a confidence level of approximately 95% is achieved. For uncertainty determination, each component used in the concrete measurement set-up was taken in account and its contribution to the overall uncertainty according its statistical distribution calculated.

RF-Measurement	Reference	Frequency range	Calculated uncertainty based on a confidence level of 95%							Remarks
Conducted emissions (U CISPR)	-	9 kHz - 150 kHz 150 kHz - 30 MHz	4.0 dB 3.6 dB							-
Power Output radiated	-	30 MHz - 4 GHz	3.17 dB							Substitution method
Power Output conducted	-	Set-up No.	Cel-C1	Cel-C2	BT1	W1	W2	--	--	-
		9 kHz - 12.75 GHz	N/A	0.60	0.7	0.25	N/A	--	--	
		12.75 - 26.5 GHz	N/A	0.82	--	N/A	N/A	--	--	
Conducted emissions on RF-port	-	9 kHz - 2.8 GHz	0.70	N/A	0.70	N/A	0.69	--	--	N/A - not applicable
		2.8 GHz - 12.75 GHz	1.48	N/A	1.51	N/A	1.43	--	--	
		12.75 GHz - 18 GHz	1.81	N/A	1.83	N/A	1.77	--	--	
		18 GHz - 26.5 GHz	1.83	N/A	1.85	N/A	1.79	--	--	
Occupied bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)							Frequency error
			1.0 dB							Power
Emission bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)							Frequency error
			See above: 0.70 dB							Power
Frequency stability	-	9 kHz - 20 GHz	0.0636 ppm							-
Radiated emissions Enclosure	-	150 kHz - 30 MHz	5.01 dB							Magnetic field strength
		30 MHz - 1 GHz	5.83 dB							Electrical Field strength
		1 GHz - 18 GHz	4.91 dB							
		18 GHz - 26.5 GHz	5.06 dB							

## 7 Versions of test reports (change history)

Version	Applied changes	Date of release
--	Initial release	2022-Apr-26
--	--	--
--	--	--

# End Of Test Report