

FCC Radio Test Report

FCC ID: 2A5TY-LLR068

Original Grant

Report No. : TBR-C-202202-0216-1
Applicant : Shenzhen Youwen Electronic Commerce Co., Ltd.

Equipment Under Test (EUT)

EUT Name : Wireless Charging Alarm Clock
Model No. : LLR068
Series Model No. : XKX068, VZ068, XZT068, XKXCHARGE1, T9
Brand Name : -----
Sample ID : 202202-0216_1-01
Receipt Date : 2022-02-25
Test Date : 2022-02-25 to 2023-03-23
Issue Date : 2022-03-23
Standards : FCC Part 15, Subpart C(15.209)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

Test/Witness Engineer : Camille Li

Engineer Supervisor : Ivan Su

Engineer Manager : Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

TB-RF-074-1.0

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	5
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test)	5
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units	6
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting	8
1.7 Measurement Uncertainty	8
1.8 Test Facility	9
2. TEST SUMMARY.....	10
3. TEST SOFTWARE.....	10
4. TEST EQUIPMENT.....	11
5. CONDUCTED EMISSION TEST	12
5.1 Test Standard and Limit.....	12
5.2 Test Setup.....	12
5.3 Test Procedure.....	13
5.4 Deviation From Test Standard.....	13
5.5 EUT Operating Mode	13
5.6 Test Data.....	13
6. RADIATED EMISSION TEST	14
6.1 Test Standard and Limit.....	14
6.2 Test Setup.....	15
6.3 Test Procedure.....	16
6.4 Deviation From Test Standard.....	16
6.5 EUT Operating Condition	16
6.6 Test Data.....	16
7. BANDWIDTH MEASUREMENT.....	17
7.1 Test Standard and Limit.....	17
7.2 Test Setup.....	17
7.3 Test Procedure.....	17
7.4 Deviation From Test Standard.....	17
7.5 EUT Operating Condition	17

7.6 Test Data.....	17
8. ANTENNA REQUIREMENT.....	18
8.1 Standard Requirement.....	18
8.2 Deviation From Test Standard.....	18
8.3 Antenna Connected Construction.....	18
8.4 Result.....	18
ATTACHMENT A--CONDUCTED EMISSION DATA (AC MAINS)	19
ATTACHMENT B-- RADIATED EMISSION TEST DATA	21
ATTACHMENT C-- BANDWIDTH MEASUREMENT DATA.....	27

Revision History

1. General Information about EUT

1.1 Client Information

Applicant	:	Shenzhen Youwen Electronic Commerce Co., Ltd.
Address	:	Room 401, Building 11, Shaxia Industrial Zone, Minzhi Community, Minzhi Street, Longhua District, Shenzhen, China.
Manufacturer	:	Shenzhen Dee Technology Co., Ltd.
Address	:	4D, Building 10, (Building 7-Building 11)City Pearl Garden, Donghuan 2nd Road, Sanlian Community, Longhua Street, Longhua District, Shenzhen.China.

1.2 General Description of EUT (Equipment Under Test)


EUT Name	:	Wireless Charging Alarm Clock
Model(s)	:	LLR068, XKX068, VZ068, XZT068, XKXCHARGE1, T9
Model Difference	:	All PCB boards and circuit diagrams are the same, the only difference is that different packaging.
Product Description	Operation Frequency:	110KHz-205KHz
	Modulation Type:	ASK
	Antenna:	Coil Antenna
Power Rating	:	Input: DC 5V, 2A/DC 9V, 2A Wireless Charge Output: 10W Max
Software Version	:	-----
Hardware Version	:	-----
Connecting I/O Port(S)	:	Please refer to the User's Manual

Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

1.3 Block Diagram Showing the Configuration of System Tested

Charging + TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	S/N	Manufacturer	Used "√"
Load	-----	-----	-----	√
Remark: The USB Cable, adapter provided and load by the Applicant,.				

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

Pretest Mode	
Final Test Mode	Description
Mode 1	Power + EUT + Full load
Mode 2	Power + EUT + Half load
Mode 3	Power + EUT + Empty load
For Conducted Test	
Final Test Mode	Description
Mode 1	Power + EUT + Full load
For Radiated Test	
Final Test Mode	Description
Mode 1	Power + EUT + Full load
For Bandwidth Test	
Final Test Mode	Description
Mode 1	Power + EUT + Full load

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.
According to ANSI C63.10 standards, All test modes were pre-tested, but we only recorded the worst case in this report.
- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software Version	N/A
Frequency	110-205KHz

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.

2. Test Summary

FCC Part 15 Subpart C(15.209)			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	N/A
15.207(a)	Conducted Emission	PASS	N/A
15.209(a)(f)	Radiated emissions	PASS	N/A
15.215	Bandwidth	PASS	N/A

Note: N/A is an abbreviation for Not Applicable.

3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE

4. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 02, 2021	Jul. 01, 2022
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 02, 2021	Jul. 01, 2022
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 02, 2021	Jul. 01, 2022
LISN	Rohde & Schwarz	ENV216	101131	Jul. 02, 2021	Jul. 01, 2022
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 02, 2021	Jul. 01, 2022
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 02, 2021	Jul. 01, 2022
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Feb. 28, 2022	Feb. 27, 2024
Horn Antenna	ETS-LINDGREN	3117	00143207	Feb. 28, 2022	Feb. 27, 2024
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 06, 2021	Jul. 05, 2022
Pre-amplifier	Sonoma	310N	185903	Feb. 24, 2022	Feb. 23, 2023
Pre-amplifier	HP	8449B	3008A00849	Feb. 24, 2022	Feb. 23, 2023
Cable	HUBER+SUHNER	100	SUCOFLEX	Feb. 24, 2022	Feb. 23, 2023
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 02, 2021	Jul. 01, 2022
Spectrum Analyzer	Rohde & Schwarz	ESPI	100010/007	Jul. 02, 2021	Jul. 01, 2022
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 10, 2021	Sep. 09, 2022
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 10, 2021	Sep. 09, 2022
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 10, 2021	Sep. 09, 2022
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 10, 2021	Sep. 09, 2022
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 10, 2021	Sep. 09, 2022
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 10, 2021	Sep. 09, 2022
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 10, 2021	Sep. 09, 2022

5. Conducted Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.207

5.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.2 Test Setup



5.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

5.4 Deviation From Test Standard

No deviation

5.5 EUT Operating Mode

Please refer to the description of test mode.

5.6 Test Data

Please refer to the Attachment A.

6. Radiated Emission Test

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.209(a)(f)

6.1.2 Test Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.



Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

6.2 Test Setup



6.3 Test Procedure

- (1) Measurements at frequency 9KHz~30MHz and Below 1GHz. The EUT was placed on a rotating 0.8m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) 9KHz~30MHz the test antenna 1m away from the ground, Both 0° and 90° antenna are set to make measurement.
Below 1GHz the test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW= 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.
For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW= 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple
- (8) For the actual test configuration, please see the test setup photo.

6.4 Deviation From Test Standard

No deviation

6.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

6.6 Test Data

Please refer to the Attachment B.


7. Bandwidth Measurement

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.215

7.2 Test Setup



7.3 Test Procedure

1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions;
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

7.4 Deviation From Test Standard

No deviation

7.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

7.6 Test Data

Please refer to the Attachment C.

8. Antenna Requirement

8.1 Standard Requirement

8.1.1 Standard

FCC Part 15.203

8.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8.2 Deviation From Test Standard

No deviation

8.3 Antenna Connected Construction


The antenna is Coil Antenna, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

8.4 Result

The EUT antenna is a Coil Antenna. It complies with the standard requirement.


Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

Attachment A--Conducted Emission Data (AC Mains)

Temperature:	22.4 °C	Relative Humidity:	43%					
Pressure:	1010 hPa							
Test Voltage:	AC 120V/60 Hz							
Terminal:	Line							
Test Mode:	Mode 1							
Remark:	Only showed test data of the worst mode							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1500	43.59	11.62	55.21	65.99	-10.78	QP
2		0.1500	25.40	11.62	37.02	55.99	-18.97	AVG
3		0.1700	39.16	11.63	50.79	64.96	-14.17	QP
4		0.1700	20.21	11.63	31.84	54.96	-23.12	AVG
5		0.1986	33.44	11.66	45.10	63.66	-18.56	QP
6		0.1986	15.59	11.66	27.25	53.66	-26.41	AVG
7		0.6020	22.98	11.45	34.43	56.00	-21.57	QP
8		0.6020	15.90	11.45	27.35	46.00	-18.65	AVG
9		1.3099	20.70	11.00	31.70	56.00	-24.30	QP
10		1.3099	18.99	11.00	29.99	46.00	-16.01	AVG
11		4.3220	20.87	10.12	30.99	56.00	-25.01	QP
12		4.3220	19.10	10.12	29.22	46.00	-16.78	AVG

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = QuasiPeak/Average (dBuV)-Limit (dBuV)

Temperature:	26°C	Relative Humidity:	54%				
Pressure:	1010 hPa						
Test Voltage:	AC 120V/60 Hz						
Terminal:	Neutral						
Test Mode:	Mode 1						
Remark:	Only showed test data of the worst mode						
							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV	dBuV	dB
1	*	0.1500	43.04	11.59	54.63	65.99	-11.36
2		0.1500	26.58	11.59	38.17	55.99	-17.82
3		0.1780	37.45	11.63	49.08	64.57	-15.49
4		0.1780	22.55	11.63	34.18	54.57	-20.39
5		0.2020	32.48	11.67	44.15	63.52	-19.37
6		0.2020	16.81	11.67	28.48	53.52	-25.04
7		0.2300	27.34	11.65	38.99	62.45	-23.46
8		0.2300	10.41	11.65	22.06	52.45	-30.39
9		0.5980	20.63	11.48	32.11	56.00	-23.89
10		0.5980	13.64	11.48	25.12	46.00	-20.88
11		3.6660	9.04	10.13	19.17	56.00	-36.83
12		3.6660	4.56	10.13	14.69	46.00	-31.31


Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = QuasiPeak/Average (dBuV)-Limit (dBuV)

Attachment B-- Radiated Emission Test Data

30MHz~1GHz

Temperature:	23.5 °C	Relative Humidity:	46%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Horizontal						
Test Mode:	Mode 1						
Remark:	Only worse case is reported						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		47.9940	43.73	-22.89	20.84	40.00	-19.16 peak
2		57.1914	48.75	-24.31	24.44	40.00	-15.56 peak
3		84.7019	41.02	-22.40	18.62	40.00	-21.38 peak
4	!	178.1327	59.38	-20.38	39.00	43.50	-4.50 QP
5	*	219.8449	63.89	-18.99	44.90	46.00	-1.10 QP
6		440.1963	43.83	-12.14	31.69	46.00	-14.31 peak
*:Maximum data x:Over limit !:over margin							
Remark:							
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)							
2. QuasiPeak (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)							
3. Margin (dB) = QuasiPeak (dB μ V/m)-Limit QPK(dB μ V/m)							


Temperature:	23.5 °C	Relative Humidity:	46%					
Test Voltage:	AC 120V/60 Hz							
Ant. Pol.	Vertical							
Test Mode:	Mode 1							
Remark:	Only worse case is reported							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	42.3022	55.45	-20.59	34.86	40.00	-5.14	peak
2	!	50.0566	58.36	-23.56	34.80	40.00	-5.20	QP
3		58.4074	56.42	-24.44	31.98	40.00	-8.02	peak
4		184.4898	55.06	-20.16	34.90	43.50	-8.60	QP
5	!	218.3085	59.72	-19.07	40.65	46.00	-5.35	QP
6		431.0316	39.52	-12.20	27.32	46.00	-18.68	peak


*:Maximum data x:Over limit !:over margin


Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = QuasiPeak (dB μ V/m)-Limit QPK(dB μ V/m)

9KHz-30MHz

Temperature:	23.5°C	Relative Humidity:	46%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Ant. 0°						
Test Mode:	Mode 1						
Remark:	N/A						
							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		0.0154	92.67	-9.09	83.58	124.21	-40.63
2		0.0200	71.64	-9.16	62.48	121.93	-59.45
3		0.0251	77.51	-9.24	68.27	119.95	-51.68
4		0.0352	75.87	-9.40	66.47	116.99	-50.52
5		0.0502	75.92	-9.70	66.22	113.89	-47.67
6	*	0.1307	92.32	-5.33	86.99	105.54	-18.55
Remark:							
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)							
2. QuasiPeak/AVG(dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)							
3. Margin (dB) = QuasiPeak/AVG (dB μ V/m)-Limit QPK/AVG(dB μ V/m)							


Temperature:	23.5 °C	Relative Humidity:	46%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Ant. 0°						
Test Mode:	Mode 1						
Remark:	N/A						
 <p>(RF) FCC 15C 9KHz-30MHz Margin -6 dB</p>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		0.2615	66.56	-9.54	57.02	99.48	-42.46
2		0.3914	71.20	-10.55	60.65	95.96	-35.31
3		0.5210	59.57	-11.11	48.46	73.46	-25.00
4	*	0.6508	62.93	-11.31	51.62	71.50	-19.88
5		1.8680	52.13	-11.84	40.29	70.00	-29.71
6		19.7397	38.07	-11.98	26.09	70.00	-43.91
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. QuasiPeak/AVG(dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = QuasiPeak/AVG (dB μ V/m)-Limit QPK/AVG(dB μ V/m)							

Temperature:	23.5°C	Relative Humidity:	46%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Ant. 90°						
Test Mode:	Mode 1						
Remark:	N/A						
							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		0.0154	93.21	-9.09	84.12	124.21	-40.09
2		0.0255	71.77	-9.24	62.53	119.81	-57.28
3		0.0353	75.90	-9.40	66.50	116.97	-50.47
4		0.0534	68.59	-9.66	58.93	113.35	-54.42
5		0.0808	66.39	-9.48	56.91	109.74	-52.83
6	*	0.1310	82.75	-5.34	77.41	105.52	-28.11
Remark:				1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. QuasiPeak/AVG(dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = QuasiPeak/AVG (dB μ V/m)-Limit QPK/AVG(dB μ V/m)			

Temperature:	23.5 °C	Relative Humidity:	46%				
Test Voltage:	AC 120V/60 Hz						
Ant. Pol.	Ant. 90°						
Test Mode:	Mode 1						
Remark:	N/A						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		0.3914	61.64	-10.55	51.09	95.96	-44.87 peak
2	*	0.6508	54.64	-11.31	43.33	71.50	-28.17 peak
3		1.1233	49.35	-11.72	37.63	66.68	-29.05 peak
4		1.8680	51.08	-11.84	39.24	70.00	-30.76 peak
5		3.4722	41.26	-11.98	29.28	70.00	-40.72 peak
6		9.0113	36.89	-11.71	25.18	70.00	-44.82 peak
Remark:				1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. QuasiPeak/AVG(dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = QuasiPeak/AVG (dB μ V/m)-Limit QPK/AVG(dB μ V/m)			

Attachment C-- Bandwidth Measurement Data

Frequency (KHz)	20 dBc Bandwidth (kHz)	99% OBW (kHz)	Result
121.4	3.855	23.8691	PASS



The screenshot shows a spectrum analysis interface with the following data:

- Ch Freq: 121.4 kHz
- Occupied Bandwidth: 23.8691 kHz
- Center: 121.400000 kHz
- Ref 0 dBm
- Atten 10 dB
- #Peak
- Log 10 dB/
- Center 121.4 kHz
- #Res BW 1 kHz
- #VBW 3 kHz
- Sweep 74.33 ms (401 pts)
- Span 30 kHz
- Occ BW % Pwr: 99.00 %
- x dB: -20.00 dB
- Transmit Freq Error: -92.527 Hz
- dB Bandwidth: 3.855 kHz

On the right, a sidebar lists the following parameters:

- Freq/Channel
- Center Freq: 121.400000 kHz
- Start Freq: 106.400000 kHz
- Stop Freq: 136.400000 kHz
- CF Step: 3.00000000 kHz
- Auto
- Man
- Freq Offset: 0.00000000 Hz
- Signal Track: On
- Off
- Scale Type: Log
- Lin

-----END OF REPORT-----