



Maximum Permissible Exposure Report

For Question,
Please Contact with WSCT
www.wsct-cert.com

Product Information

EUT

LCD monitors

Model Number

: BM5 III WR

Model Declaration

PT6L,LH5U,LH5W,BM5WR,BM5 IV WR ,BM5 V WR ,
LH5H II,LH5H III,LH5H V, LH5P II,LH5P III,BM7 II

Test Model

WR ,BM7 III WR ,

Power Supply

RH8,OEYEWWR,OEYEWWR II ,KEYGRIP II ,BKEY,BKEY II ,BKEY III ,

Hardware version

Shooter,Shooter II ,Shooter III ,LH7P,LH7P II ,LH7H,LH7H II ,LH8P,

Software version

LH8P II ,LH8H,LH8H II

Bluetooth

: PortKeys

Bluetooth Version

: N/A

Channel Number

: 40

Modulation Technology

: GFSK, $\pi/4$ -DQPSK, 8-DPSK for BR+EDR

Data Rates

: N/A

Antenna Type And Gain

: Internal Antenna 2.5dBi

WiFi

WLAN

: Supported IEEE 802.11a/b/g/n

IEEE 802.11b:2412-2462MHz

WLAN FCC Operation Frequency

IEEE 802.11g:2412-2462MHz

WLAN Channel Number

IEEE 802.11n HT20:2412-2462MHz

IEEE 802.11n HT40:2422-2452MHz

: 11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20)

: 7 Channels for 2422-2452MHz(IEEE 802.11n HT40)

WLAN Modulation Technology

IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)

Antenna Type And Gain

IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)

IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)

: Internal Antenna 0:

: 2.5dBi(Max.), for TX/RX (WLAN 2.4G Band),

Note: Antenna position refer to EUT Photos.



世标检测认证股份

World Standardization Certification & Testing Group (Shenzhen) Co.,Ltd.

ADD:Building A-B Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China

TEL:86-755-26996192 26992306 FAX:86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)



2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices





3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	W/f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

This Product can only use antennas certificated as follows provided by manufacturer;

Antenna Gain and type refer to Product information





Certificate Number 5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

6. Conducted Power

2.4G Band:

Bluetooth(BDR+EDR)

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)
GFSK	00	2402	4.69
	39	2441	5.56
	78	2480	5.72
$\pi/4$ -DQPSK	00	2402	6.51
	39	2441	6.94
	78	2480	7.04
8-DPSK	00	2402	6.53
	39	2441	7.28
	78	2480	7.41

Bluetooth(BLE)

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)
GFSK	00	2402	7.84
	39	2440	8.83
	78	2480	8.98

WiFi 2.4GHz Band

Test Mode	Channel	Frequency (MHz)	Antenna 0
			Antenna 1
IEEE 802.11b	1	2412	12.16
	6	2437	12.08
	11	2462	12.13
IEEE 802.11g	1	2412	11.18
	6	2437	11.19
	11	2462	11.23
IEEE 802.11n HT20	1	2412	11.41
	6	2437	11.40
	11	2462	11.33
IEEE 802.11n HT40	3	2422	10.26
	6	2437	10.31
	9	2452	10.29

7. Manufacturing Tolerance

Bluetooth(BDR+EDR)

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	4.0	5.0	5.0
Tolerance \pm (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6.0	6.0	7.0
Tolerance \pm (dB)	1.0	1.0	1.0
8-DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6.0	7.0	7.0
Tolerance \pm (dB)	1.0	1.0	1.0



世标检测认证股份

ADD:Building A-B Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China

TEL:86-755-26996192 26992306 FAX:86-755-86376605 E-mail:Fengbing.Wang@wsct-cert.com [Http://www.wsct-cert.com](http://www.wsct-cert.com)



Bluetooth(BLE)

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	7.0	8.0	8.0
Tolerance \pm (dB)	1.0	1.0	1.0

WiFi 2.4GHz Band – Antenna 0

IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.0	11.0	11.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	11.0	11.0	11.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	10.0	10.0	10.0
Tolerance \pm (dB)	1.0	1.0	1.0

8. Measurement Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20$ cm, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Bluetooth(BDR+EDR)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK	6.00	3.9811	2.5	1.7783	100%	0.0014	1.0000
$\pi/4$ -DQPSK	7.00	5.0119	2.5	1.7783	100%	0.0018	1.0000
8-DPSK	7.00	5.0119	2.5	1.7783	100%	0.0018	1.0000

Bluetooth(BLE)

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
GFSK	9.0	7.9433	2.5	1.7783	100%	0.0028	1.0000





WiFi 2.4GHz Band – Ant 0

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW					
IEEE 802.11b	12.0	15.8489	2.50	1.7783	100%	0.0056	1.0000
IEEE 802.11g	11.0	12.5893	2.50	1.7783	100%	0.0046	1.0000
IEEE 802.11n HT20	11.0	12.5893	2.50	1.7783	100%	0.0046	1.0000
IEEE 802.11n HT40	10.0	10.0000	2.50	1.7783	100%	0.0035	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

8.2 Simultaneous Transmission MPE

LTE + Bluetooth + Wi-Fi

Maximum MPE(mW/cm ²) BLE Ant.	Maximum MPE(mW/cm ²) BT Ant.	Maximum MPE(mW/cm ²) WIFI Ant.0	Σ MPE (mW/cm ²)	Limit (mW/cm ²)	Results
0.0018	0.0028	0.0056	0.0102	0.0330	PASS

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

