

# Armatura LLC

# RF TEST REPORT

**Report Type:**  
FCC Part 15.407

**Model:**  
OmniAC20

**REPORT NUMBER:**  
230402194SHA-003

**ISSUE DATE:**  
July 5, 2023

**DOCUMENT CONTROL NUMBER:**  
TTRF15.407\_V1 © 2018 Intertek





Total Quality. Assured.

## TEST REPORT

Intertek Testing Services Shanghai  
Building No.86, 1198 Qinzhou Road (North)  
Caohejing Development Zone  
Shanghai 200233, China

Telephone: 86 21 6127 8200  
[www.intertek.com](http://www.intertek.com)

Report no.: 230402194SHA-003

**Applicant:** Armatura LLC  
190 Bluegrass Valley Parkway Alpharetta, GA 30005

**Manufacturer:** Armatura LLC  
190 Bluegrass Valley Parkway Alpharetta, GA 30005

**FCC ID:** 2A5UQ-OMNIAC20W

### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 15 (2021):** Radio Frequency Devices (Subpart C)

**ANSI C63.10 (2013):** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

**PREPARED BY:**

---

Project Engineer  
Damon Ding

**REVIEWED BY:**

---

Reviewer  
Erick Liu

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****Content**

|   |           |
|---|-----------|
| <b>REVISION HISTORY</b> .....                           | <b>5</b>  |
| <b>MEASUREMENT RESULT SUMMARY</b> .....                 | <b>6</b>  |
| <b>1 GENERAL INFORMATION</b> .....                      | <b>7</b>  |
| 1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....     | 7         |
| 1.2 TECHNICAL SPECIFICATION .....                       | 7         |
| 1.3 ANTENNA INFORMATION.....                            | 7         |
| 1.4 DESCRIPTION OF TEST FACILITY .....                  | 8         |
| <b>2 TEST SPECIFICATIONS</b> .....                      | <b>9</b>  |
| 2.1 STANDARDS OR SPECIFICATION .....                    | 9         |
| 2.2 MODE OF OPERATION DURING THE TEST.....              | 9         |
| 2.3 TEST SOFTWARE LIST .....                            | 11        |
| 2.4 TEST PERIPHERALS LIST .....                         | 11        |
| 2.5 TEST ENVIRONMENT CONDITION:.....                    | 11        |
| 2.6 INSTRUMENT LIST .....                               | 12        |
| 2.7 MEASUREMENT UNCERTAINTY .....                       | 13        |
| 2.8 DUTY CYCLE.....                                     | 14        |
| <b>3 26 DB BANDWIDTH</b> .....                          | <b>16</b> |
| 3.1 LIMIT .....   | 16        |
| 3.2 MEASUREMENT PROCEDURE .....                         | 16        |
| 3.3 TEST CONFIGURATION .....                            | 17        |
| 3.4 THE RESULTS OF 26 DB BANDWIDTH .....                | 17        |
| <b>4 MINIMUM 6DB BANDWIDTH</b> .....                    | <b>18</b> |
| 4.1 LIMIT .....   | 18        |
| 4.2 MEASUREMENT PROCEDURE .....                         | 18        |
| 4.3 TEST CONFIGURATION .....                            | 18        |
| 4.4 THE RESULTS OF MINIMUM 6DB BANDWIDTH .....          | 18        |
| <b>5 MAXIMUM CONDUCTED OUTPUT POWER</b> .....           | <b>19</b> |
| 5.1 LIMIT .....   | 19        |
| 5.2 MEASUREMENT PROCEDURE .....                         | 20        |
| 5.3 TEST CONFIGURATION .....                            | 20        |
| 5.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER..... | 20        |
| <b>6 POWER SPECTRUM DENSITY</b> .....                   | <b>21</b> |
| 6.1 LIMIT .....   | 21        |
| 6.2 MEASUREMENT PROCEDURE .....                         | 22        |
| 6.3 TEST CONFIGURATION .....                            | 23        |
| 6.4 TEST RESULTS OF POWER SPECTRUM DENSITY .....        | 23        |
| <b>7 RADIATED EMISSIONS</b> .....                       | <b>24</b> |
| 7.1 LIMIT .....   | 24        |
| 7.2 MEASUREMENT PROCEDURE .....                         | 25        |
| 7.3 TEST CONFIGURATION .....                            | 26        |
| 7.4 TEST RESULTS OF RADIATED EMISSIONS .....            | 28        |
| <b>8 POWER LINE CONDUCTED EMISSION</b> .....            | <b>29</b> |
| 8.1 LIMIT .....   | 29        |

**TEST REPORT**

|   |           |
|---|-----------|
| 8.2 TEST CONFIGURATION .....                                | 29        |
| 8.3 MEASUREMENT PROCEDURE .....                             | 30        |
| 8.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....      | 31        |
| <b>9 DYNAMIC FREQUENCY SELECTION .....</b>                  | <b>32</b> |
| 9.1 LIMIT .....   | 32        |
| 9.2 TEST CONFIGURATION .....                                | 34        |
| 9.3 MEASUREMENT PROCEDURE .....                             | 35        |
| 9.4 TEST RESULTS OF DYNAMIC FREQUENCY SELECTION .....       | 35        |
| <b>10 FREQUENCY STABILITY .....</b>                         | <b>36</b> |
| 10.1 LIMIT .....  | 36        |
| 10.2 TEST RESULT.....                                       | 36        |
| <b>11 ANTENNA REQUIREMENT.....</b>                          | <b>37</b> |
| <b>APPENDIX I: PHOTOGRAPH OF TEST SETUP .....</b>           | <b>38</b> |
| <b>APPENDIX II: PHOTOGRAPH OF EQUIPMENT UNDER TEST.....</b> | <b>38</b> |

**TEST REPORT****Revision History**

| Report No.       | Version | Description             | Issued Date  |
|------------------|---------|-------------------------|--------------|
| 230402194SHA-003 | Rev. 01 | Initial issue of report | July 5, 2023 |
|                  |         |                         |              |
|                  |         |                         |              |

**TEST REPORT**

## Measurement result summary

| TEST ITEM                      | FCC REFERENCE                                      | RESULT |
|--------------------------------|--|--------|
| 26 dB Bandwidth                | 15.407(a)  | Pass   |
| Minimum 6dB Bandwidth          | 15.407(e)  | Pass   |
| Maximum Conducted Output Power | 15.407(a)  | Pass   |
| Power spectral density         | 15.407(a)  | Pass   |
| Radiated emission              | 15.407(b)<br>15.205<br>15.209                      | Pass   |
| Power line conducted emission  | 15.407(b)<br>15.207                                | Pass   |
| Dynamic Frequency Selection    | FCC 47 CFR Part 15 Subpart E<br>Section 15.407 (h) | Pass   |
| Frequency Stability            | 15.407(g)  | Pass   |
| Antenna requirement            | 15.203   | Pass   |

Notes: 1: NA =Not Applicable

2. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

4: This is a client device without radar detection capability and it does not support TPC function

**TEST REPORT**

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

|                       |   |
|-----------------------|---|
| Product name:         | Smart Access Control Terminal   |
| Type/Model:           | OmniAC20  |
| Description of EUT:   | Smart Access Control Terminal   |
| Rating:               | Powered from adapter:<br>Input: 100V-240~50/60Hz, 1.0A Max<br>Output: DC12V, 3.0A     |
| EUT type:             | <input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing |
| Software Version:     | Not provided  |
| Hardware Version:     | Not provided  |
| Normal Test Voltage:  | 120V ~60Hz  |
| Sample received date: | March 8, 2023   |
| Date of test:         | April 3, 2023 to June 07, 2023  |

### 1.2 Technical Specification

|                     |  |
|---------------------|--|
| Frequency Range:    | 5150 ~ 5250MHz<br>5250 ~ 5350MHz<br>5470 ~ 5725MHz<br>5725 ~ 5850MHz   |
| Support Standards:  | IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11n-HT40   |
| Type of Modulation: | OFDM (BPSK, QPSK, 16QAM, 64QAM)  |
| Channel Number:     | For 5150 ~ 5250MHz band: Channel 36 - 48<br>For 5250 ~ 5350MHz Band: Channel 52 - 64<br>For 5470 ~ 5725MHz Band: Channel 100 - 140<br>For 5725 ~ 5850MHz band: Channel 149 - 165 |

### 1.3 Antenna information

| Antenna information: |              |               |     |      |
|----------------------|--------------|---------------|-----|------|
| No.                  | Antenna Type | Gain (dBi)    |     | Note |
| 1                    | FPCB Antenna | 5150 -5350MHz | 3.7 | -    |
|                      |              | 5470-5725MHz  | 4.6 |      |
|                      |              | 5725-5850MHz  | 4.2 |      |

| Frequency Band | Tx/Rx Function | Beamforming function | CDD function | Directional gain (dBi) |
|----------------|----------------|----------------------|--------------|------------------------|
| 5150 -5350MHz  | 1Tx/1Rx        | NO                   | NO           | -                      |
| 5470-5725MHz   | 1Tx/1Rx        | NO                   | NO           | -                      |
| 5725-5850MHz   | 1Tx/1Rx        | NO                   | NO           | -                      |

**TEST REPORT****1.4 Description of Test Facility**

|            |  |
|------------|--|
| Name:      | Intertek Testing Services Shanghai                                     |
| Address:   | Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200   |
| Telefax:   | 86 21 54262353   |

|   |   |
|---|---|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab<br>Registration No. CNAS L0139   |
|   | FCC Accredited Lab<br>Designation Number: CN0175  |
|   | IC Registration Lab<br>CAB identifier.: CN0014  |
|   | VCCI Registration Lab<br>Member No: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252) |
|   | A2LA Accreditation Lab<br>Certificate Number: 3309.02   |

All tests were sub-contracted.

|            |   |
|------------|---|
| Name:      | Shenzhen UnionTrust Quality and Technology Co., Ltd.  |
| Address:   | Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng Science and Technology Park, Longhua District, Shenzhen, China |
| Telephone: | +86 (0) 755 2823 0888   |
| Telefax:   | +86 (0) 755 2823 0886   |

|   |   |
|---|---|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab<br>Registration No. CNAS L9069 |
|   | FCC Accredited Lab<br>Designation Number: CN1194      |
|   | A2LA Accreditation Lab<br>Certificate Number: 4312.01 |

**TEST REPORT****2 TEST SPECIFICATIONS****2.1 Standards or specification**

47CFR Part 15 (2021)

ANSI C63.10 (2013)

KDB 789033 D02 v02r01

**2.2 Mode of operation during the test**

While testing transmitting mode of EUT, the continuously transmission was applied by following software.

| Software name | Manufacturer | Version | Supplied by |
|---------------|--------------|---------|-------------|
| PUTTY.exe     | NA           | NA      | Client      |

The lowest, middle and highest channel for the following modes were tested as representatives.

| Frequency Band (MHz) | Mode          | Lowest (MHz) | Middle (MHz) | Highest (MHz) |
|----------------------|---------------|--------------|--------------|---------------|
| 5150 - 5250          | 802.11a       | 5180         | 5220         | 5240          |
|                      | 802.11n(HT20) | 5180         | 5220         | 5240          |
|                      | 802.11n(HT40) | 5190         | /            | 5230          |
| 5250 - 5350          | 802.11a       | 5260         | 5300         | 5320          |
|                      | 802.11n(HT20) | 5260         | 5300         | 5320          |
|                      | 802.11n(HT40) | 5270         | /            | 5310          |
| 5470 - 5725          | 802.11a       | 5500         | 5600         | 5700          |
|                      | 802.11n(HT20) | 5500         | 5600         | 5700          |
|                      | 802.11n(HT40) | 5510         | 5590         | 5670          |
| 5725 - 5850          | 802.11a       | 5745         | 5785         | 5825          |
|                      | 802.11n(HT20) | 5745         | 5785         | 5825          |
|                      | 802.11n(HT40) | 5755         | /            | 5795          |

**TEST REPORT****Data rate and Power setting:**

The pre-scan for the conducted power with all data rates in each modulation and band was used, and the worst case was found and used in all test cases. After this pre-scan, we choose the following table of the data rates as the worst case.

| Frequency Band (MHz) | Mode          | Worst case data rate |
|----------------------|---------------|----------------------|
| 5150 - 5250          | 802.11a       | 6Mbps                |
|                      | 802.11n(HT20) | MCS0                 |
|                      | 802.11n(HT40) | MCS0                 |
| 5250 - 5350          | 802.11a       | 6Mbps                |
|                      | 802.11n(HT20) | MCS0                 |
|                      | 802.11n(HT40) | MCS0                 |
| 5500 - 5725          | 802.11a       | 6Mbps                |
|                      | 802.11n(HT20) | MCS0                 |
|                      | 802.11n(HT40) | MCS0                 |
| 5725 - 5850          | 802.11a       | 6Mbps                |
|                      | 802.11n(HT20) | MCS0                 |
|                      | 802.11n(HT40) | MCS0                 |

**TEST REPORT**
**2.3 Test software list**

| Test Items         | Software | Manufacturer | Version    |
|--------------------|----------|--------------|------------|
| Conducted emission | e3       | Audix        | 920151119i |
| Radiated emission  | e3       | Audix        | 9.160323   |

**2.4 Test peripherals list**

| Item No. | Name            | Band and Model        | FCC ID      |
|----------|-----------------|-----------------------|-------------|
| 1        | Notebook        | DELL<br>Inspiron 5409 | NA          |
| 2        | Antenna Cable   | SMA                   | NA          |
| 3        | Advanced Look   | N/A, AL-280 (LED)     | N/A         |
| 4        | Card Reader     | ZKTeco, KR503E        | N/A         |
| 5        | Laptop          | Lenovo,E450           | N/A         |
| 6        | mouse           | DELL, MS111           | N/A         |
| 7        | Wireless Router | SAGEMCOM, RAC2V1S     | VW3FAST5280 |

**2.5 Test environment condition:**

| Test items                     | Temperature | Humidity |
|--------------------------------|-------------|----------|
| 26 dB Bandwidth                | 25.3 °C     | 49.6% RH |
| Minimum 6dB Bandwidth          |             |          |
| Maximum Conducted Output Power |             |          |
| Power spectral density         |             |          |
| Radiated Emissions             | 25.0 °C     | 61.9% RH |
| Power line conducted emission  | 24.4 °C     | 58.2% RH |

**TEST REPORT**
**2.6 Instrument list**

| Radiated Emission                   |  |                      |            |                                  |               |
|-------------------------------------|--|----------------------|------------|----------------------------------|---------------|
| Used                                | Equipment  | Manufacturer         | Type       | Internal no.                     | Cal. Due date |
| <input checked="" type="checkbox"/> | 3m Chamber SAC                                       | ETS-LINDGREN         | 3m         | NA                               | 21-Jan-2024   |
| <input checked="" type="checkbox"/> | Receiver   | R&S                  | ESIB26     | 100114                           | 2-Nov-2023    |
| <input checked="" type="checkbox"/> | Loop Antenna   | ETS-LINDGREN         | 6502       | 00202525                         | 20-Nov-2023   |
| <input checked="" type="checkbox"/> | Broadband Antenna                                    | ETS-LINDGREN         | 3142E      | 00201566                         | 12-Dec-2023   |
| <input checked="" type="checkbox"/> | 6dB Attenuator                                       | Talent               | RA6A5-N-18 | 18103001                         | 12-Dec-2023   |
| <input checked="" type="checkbox"/> | Preamplifier   | HP                   | 8447F      | 2805A02960                       | 31-Oct-2023   |
| <input checked="" type="checkbox"/> | Double-Ridged Waveguide Horn Antenna (Pre-amplifier) | ETS-Lindgren         | 3117-PA    | 00201541                         | 16-Apr-2024   |
| <input checked="" type="checkbox"/> | Pre-amplifier  | ETS-Lindgren         | 00118385   | 00201874                         | 31-Oct-2023   |
| <input checked="" type="checkbox"/> | Double-Ridged Waveguide Horn Antenna (Pre-amplifier) | ETS-LINDGREN         | 3116C-PA   | 00202652                         | 20-Nov-2023   |
| <input checked="" type="checkbox"/> | Pre-amplifier  | ETS-LINDGREN         | 00118384   | 00202652                         | 20-Nov-2023   |
| <input checked="" type="checkbox"/> | Band Reject Filter(2400MHz~2500MHz)                  | Micro-Tronics        | BRM50702   | G248                             | 1-Nov-2023    |
| <input checked="" type="checkbox"/> | Test Software  | Audix                | e3         | Software Version: 9.160323       |               |
| RF test                             |  |                      |            |                                  |               |
| Used                                | Equipment  | Manufacturer         | Type       | Internal no.                     | Cal. Due date |
| <input checked="" type="checkbox"/> | MXG X-Series RF Vector Signal Generator              | KEYSIGHT             | N5182B     | MY51350267                       | 31-Oct-2023   |
| <input checked="" type="checkbox"/> | EXA Signal Analyzer                                  | KEYSIGHT             | N9010A     | MY51440197                       | 13-Apr-2024   |
| <input checked="" type="checkbox"/> | USB Wideband Power Sensor                            | KEYSIGHT             | U2021XA    | MY55430035                       | 02-Nov-2023   |
| <input checked="" type="checkbox"/> | Test Software  | AutomationTestSystem | ECIT       | Software Version: 1.0.7515.16529 |               |

**TEST REPORT**

| Conducted Emission Test Equipment List |               |              |           |                              |               |
|--|---------------|--------------|-----------|------------------------------|---------------|
| Used                                   | Equipment     | Manufacturer | Model No. | Serial Number                | Cal. Due date |
| ☒                                      | Receiver      | R&S          | ESR7      | 1316.3003K07-101181-K3       | 31-Oct-2023   |
| ☒                                      | Pulse Limiter | R&S          | ESH3-Z2   | 0357.8810.54                 | 31-Oct-2023   |
| ☒                                      | LISN          | R&S          | ESH2-Z5   | 860014/024                   | 31-Oct-2023   |
| ☒                                      | LISN          | ETS-Lindgren | 3816/2SH  | 00201088                     | 31-Oct-2023   |
| ☒                                      | Test Software | Audix        | e3        | Software Version: 920151119i |               |

## 2.7 Measurement uncertainty


The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Test item   | Measurement uncertainty |
|---|-------------------------|
| Maximum peak output power                                   | ± 0.68 dB               |
| 26 dB Bandwidth   | ± 1.86 %                |
| Minimum 6dB Bandwidth                                       | ± 1.86 %                |
| Power spectral density                                      | ± 0.6 dB                |
| Radiated Emissions in restricted frequency bands below 1GHz | ± 4.6 dB                |
| Radiated Emissions in restricted frequency bands above 1GHz | ± 4.4 dB                |
| Emission outside the frequency band                         | ± 4.4 dB                |
| Power line conducted emission                               | ± 2.7 dB                |

## TEST REPORT


## 2.8 Duty cycle

| Test Mode         | Channel | ON Time [ms] | Period [ms] | Duty Cycle (%) | Duty Cycle Factor (dB) | Limit | Verdict |
|-------------------|---------|--------------|-------------|----------------|------------------------|-------|---------|
| IEEE 802.11a      | 5180    | 1.380        | 1.460       | 94.52          | 0.24                   | --    | N/A     |
| IEEE 802.11n-HT20 | 5180    | 5.060        | 5.160       | 98.06          | 0.00                   | --    | N/A     |
| IEEE 802.11n-HT40 | 5190    | 2.420        | 2.510       | 96.41          | 0.16                   | --    | N/A     |




## TEST REPORT

## IEEE 802.11n-HT20



## IEEE 802.11n-HT40



**TEST REPORT****3 26 dB Bandwidth**

Test result: Pass

**3.1 Limit**

None

**3.2 Measurement Procedure**

The EUT was tested according to test procedure of "KDB789033 D02 General UNII Test Procedures New Rules"


**26 dB Bandwidth**

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

**99% Occupied Bandwidth**

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW  $\geq 3 \cdot$  RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

**TEST REPORT****3.3 Test Configuration****3.4 The results of 26 dB Bandwidth**

Test data reference “Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix” Appendix A

**TEST REPORT****4 Minimum 6dB Bandwidth**

**Test result:** Pass

**4.1 Limit**


For systems using digital modulation techniques that may operate in the 5725 - 5850 MHz band, the minimum 6 dB bandwidth shall be at least 500 kHz.

**4.2 Measurement Procedure**

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

**4.3 Test Configuration****4.4 The results of Minimum 6dB Bandwidth**

Test data reference “Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix” Appendix B

**TEST REPORT****5 Maximum conducted output power****Test result:** Pass**5.1 Limit**

For an outdoor access point operating in the band 5.15-5.25GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W provided the maximum antenna gain does not exceed 6dBi.

The maximum e.i.r.p. at any elevation angle above 30 degrees from the horizon must not exceed 125mW (21 dBm).

For an indoor access point operating in the band 5.15-5.25GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6dBi.

For fixed point-to-point access points operating in the band 5.15-5.25GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W.

For client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. (FCC Limit)

For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or  $11\text{dBm} + 10\log B$ , where B is the 26dB emission bandwidth in megahertz. (FCC limit)

For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W. (FCC limit)

For Frequency Band 5150-5250 MHz, the maximum e.i.r.p. shall not exceed 200 mW or  $10 + 10\log_{10}B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. (IC limit)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 99% emission bandwidth in megahertz. (IC limit)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum e.i.r.p. shall not exceed 1.0 W or  $17 + 10 \log_{10}B$ , dBm, whichever is less. B is the 99% emission bandwidth in megahertz. (IC limit)


For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. (IC limit)

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

**TEST REPORT****5.2 Measurement Procedure**

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW  $\geq$  3 MHz.
- (iv) Number of points in sweep  $\geq 2 \times$  span / RBW. (This ensures that bin-to-bin spacing is  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle  $<$  98%, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq$  98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
- (viii) Trace average at least 100 traces in power averaging (rms) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

**5.3 Test Configuration****5.4 Test Results of Maximum conducted output power**

Test data reference “Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix” Appendix C

**TEST REPORT****6 Power spectrum density****Test result:** **Pass****6.1 Limit**

- For an outdoor access point operating in the band 5.15-5.25GHz, the maximum power spectral density shall not exceed 17dBm in any 1 megahertz band.
- For an indoor access point operating in the band 5.15-5.25GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.
- For client devices in the 5.15-5.25GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. (FCC limit)
- For the 5.25-5.35 GHz and 5.47-5.725GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. (FCC limit)
- For the band 5.725-5.85GHz, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. (FCC limit)
- For the 5.15-5.25GHz band, the e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band. (IC limit)
- For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. (IC limit)
- For the 5.725-5.85GHz band, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. (IC limit)


If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the less of original and original + (6 - antenna gain - beamforming gain).

**TEST REPORT****6.2 Measurement Procedure**

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

1. Create an average power spectrum for the EUT operating mode being tested by following the instructions in II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power....” (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
2. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
3. Make the following adjustments to the peak value of the spectrum, if applicable:
  - a) If Method SA-2 or SA-2 Alternative was used, add  $10 \log (1/x)$ , where x is the duty cycle, to the peak of the spectrum.
  - b) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
4. The result is the Maximum PSD over 1 MHz reference bandwidth.
5. For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in Section 15.407(a)(5). For devices operating in the band 5.725 - 5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
  - a) Set RBW  $\geq 1/T$ , where T is defined in II.B.I.a).
  - b) Set VBW  $\geq 3$  RBW.
  - c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10 \log (500 \text{ kHz}/\text{RBW})$  to the measured result, whereas RBW (<500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
  - d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add  $10 \log (1\text{MHz}/\text{RBW})$  to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
  - e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for steps 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

**TEST REPORT****6.3 Test Configuration****6.4 Test Results of Power spectrum density**

Test data reference "Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix" Appendix D

**TEST REPORT**

## 7 Radiated Emissions

 Test result: **Pass**

### 7.1 Limit

The radiated emissions which fall in the restricted bands, and the radiated emissions below 1GHz, must comply with the radiated emission limits specified showed as below:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

The radiated emissions which fall outside the restrict bands, should comply with the EIRP limit as below:

For transmitters operating in the 5.15 - 5.25 / 5.25 - 5.35 / 5.47 - 5.725GHz band:

| Frequency (MHz) | EIRP Limit (dBm) | Equivalent Field Strength (3m) (dB $\mu$ V/m) |
|-----------------|------------------|---|
| <5150           |                  |   |
| >5350           |                  |   |
| <5470           | -27              | 68.20   |
| >5725           |                  |   |

For transmitters operating in the 5.725 - 5.85GHz band:

| Frequency (MHz) | EIRP Limit (dBm/MHz) | Equivalent Field Strength (3m) (dB $\mu$ V/m) |
|-----------------|----------------------|---|
| <5650           | -27                  | 68.20   |
| 5650 ~ 5700     | -27 ~ 10             | 68.20 ~ 105.20                                |
| 5700 ~ 5720     | 10 ~ 15.6            | 105.20 ~ 110.80                               |
| 5720 ~ 5725     | 15.6 ~ 27            | 110.80 ~ 122.20                               |
| 5850 ~ 5855     | 27 ~ 15.6            | 122.20 ~ 110.80                               |
| 5855 ~ 5875     | 15.6 ~ 10            | 110.80 ~ 105.20                               |
| 5875 ~ 5925     | 10 ~ -27             | 105.20 ~ 68.20                                |
| >5925           | -27                  | 68.20   |

**TEST REPORT****7.2 Measurement Procedure****For Radiated emission below 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to peak or quasi-peak detect function and specified bandwidth with maximum hold mode.

**NOTE:**



1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.


**For Radiated emission above 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to peak or quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for peak or quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz at frequency above 1GHz for peak detection above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or  $3 \times RBW$  (Duty cycle  $\geq 98\%$ ) for average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

**TEST REPORT****7.3 Test Configuration****For Radiated emission below 30MHz:****For Radiated emission 30MHz to 1GHz:**

**TEST REPORT****For Radiated emission above 1GHz:**

**TEST REPORT**


**7.4 Test Results of Radiated Emissions**

Test data reference "Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix" Appendix E

**TEST REPORT****8 Power line conducted emission****Test result:** Pass**8.1 Limit**

| Frequency of Emission (MHz) | Conducted Limit (dBuV) |            |
|-----------------------------|------------------------|------------|
|                             | QP                     | AV         |
| 0.15-0.5                    | 66 to 56*              | 56 to 46 * |
| 0.5-5                       | 56                     | 46         |
| 5-30                        | 60                     | 50         |

\* Decreases with the logarithm of the frequency.

**8.2 Test Configuration**

## TEST REPORT

### 8.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

## TEST REPORT

### 8.4 Test Results of Power line conducted emission

Test data reference "Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix" Appendix F

**TEST REPORT**

## 9 Dynamic frequency selection

Test result: Pass

### 9.1 Limit

EUT Operating Mode:

| DFS Operational mode                                | Operating Frequency Range |                      |
|---|---------------------------|----------------------|
|   | 5250 MHz to 5350 MHz      | 5470 MHz to 5725 MHz |
| Slave without radar Interference detection function | ✓                         | ✓                    |

Applicability of DFS Requirements Prior to Use of a Channel:

| Requirement                     | Operational Mode |                                |                             |
|---------------------------------|------------------|--------------------------------|-----------------------------|
|                                 | Master           | Client Without Radar Detection | Client With Radar Detection |
| Non-Occupancy Period            | ✓                | Not required                   | Yes                         |
| DFS Detection Threshold         | ✓                | Not required                   | Yes                         |
| Channel Availability Check Time | ✓                | Not required                   | Not required                |
| U-NII Detection Bandwidth       | ✓                | Not required                   | Yes                         |

Applicability of DFS requirements during normal operation:

| Requirement                       | Operational Mode                             |                                |
|-----------------------------------|--|--------------------------------|
|                                   | Master Device or Client with Radar Detection | Client Without Radar Detection |
| DFS Detection Threshold           | Yes  | Not required                   |
| Channel Closing Transmission Time | Yes  | Yes                            |
| Channel Move Time                 | Yes  | Yes                            |
| U-NII Detection Bandwidth         | Yes  | Not required                   |

| Additional requirements for devices with multiple bandwidth modes  | Master Device or Client with Radar Detection | Client Without Radar Detection                       |
|--|--|--|
| U-NII Detection Bandwidth and Statistical Performance Check  | All BW modes must be tested                  | Not required   |
| Channel Move Time and Channel Closing Transmission Time  | Test using widest BW mode available          | Test using the widest BW mode available for the link |
| All other tests  | Any single BW mode                           | Not required   |
| <b>Note:</b> Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency. |  |  |

## TEST REPORT

### DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection:

| Maximum Transmit Power   | Value (See Notes 1, 2, and 3) |
|--|-------------------------------|
| EIRP $\geq$ 200 milliwatt  | -64 dBm                       |
| EIRP $<$ 200 milliwatt and power spectral density $<$ 10 dBm/MHz               | -62 dBm                       |
| EIRP $<$ 200 milliwatt that do not meet the power spectral density requirement | -64dBm                        |

**Note 1:** This is the level at the input of the receiver assuming a 0 dBi receive antenna.

**Note 2:** Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

**Note3:** EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

### DFS Radar Signal Parameter Values:

| Parameter                         | Value   |
|-----------------------------------|---|
| Non-occupancy period              | Minimum 30 minutes  |
| Channel Availability Check Time   | 60 seconds  |
| Channel Move Time                 | 10 seconds (See Note 1.)  |
| Channel Closing Transmission Time | 200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period.<br>(See Notes 1 and 2.) |
| U-NII Detection Bandwidth         | Minimum 100% of the U-NII 99% transmission power bandwidth. (See Note 3.)                                   |

**Note 1:** Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

**Note 2:** The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

**Note 3:** During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

### DFS Radar Signal Parameter:

Radar Type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time

## TEST REPORT

Table 1-Short Pulse Radar Test Waveforms

| Radar Type  | Pulse Width (μsec) | PRI (μsec)       | Number of Pulses  | Minimum Percentage of Successful Detection | Minimum Trials |
|---|--------------------|------------------|---|--|----------------|
| 0   | 1                  | 1428             | 18  | See Note 1.                                | See Note 1.    |
| 1   | 1                  | Test A<br>Test B | Roundup $\left\{ \left( \frac{1}{360} \right) \left( \frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$ | 60%  | 30             |
| 2   | 1-5                | 150-230          | 23-29   | 60%  | 30             |
| 3   | 6-10               | 200-500          | 16-18   | 60%  | 30             |
| 4   | 11-20              | 200-500          | 12-16   | 60%  | 30             |
| Aggregate (Radar Types 1-4)   |                    |                  |   | 80%  | 120            |
| <b>Note 1:</b> Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests. |                    |                  |   |  |                |


Table 2-Long Pulse Radar Test Waveform

| Radar Type | Pulse Width (μsec) | Chirp Width (MHz) | PRI (μsec) | Number of Pulses per Burst | Number of Bursts | Minimum Percentage of Successful Detection | Minimum Trials |
|------------|--------------------|-------------------|------------|----------------------------|------------------|--|----------------|
| 5          | 50-100             | 5-20              | 1000-2000  | 1-3                        | 8-20             | 80%  | 30             |

Table 3-Frequency Hopping Radar Test Waveform

| Radar Type | Pulse Width (μsec) | PRI (μsec) | Pulses per Hop | Hopping Rate (kHz) | Hopping Sequence Length (msec) | Minimum Percentage of Successful Detection | Minimum Trials |
|------------|--------------------|------------|----------------|--------------------|--------------------------------|--|----------------|
| 6          | 1                  | 333        | 9              | 0.333              | 300                            | 70%  | 30             |


## 9.2 Test Configuration



## TEST REPORT

### 9.3 Measurement Procedure

- a) One frequency will be chosen from the Operating Channels of the EUT within the 5250-5350 MHz or 5470-5725 MHz bands. For 802.11 devices, the test frequency must contain control signals. This can be verified by disabling channel loading and monitoring the spectrum analyzer. If no control signals are detected, another frequency must be selected within the emission bandwidth where control signals are detected.
- b) In case the EUT is a Master Device, a U-NII device operating as a Client Device will be used and it is assumed that the Client will associate with the EUT (Master). For radiated tests, the emissions of the Radar Waveform generator will be directed towards the Master Device. If the Master Device has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.
- c) The TCP protocol unicast data stream was generated by the iperf software command line with at least 17% activity ratio over any 100ms period.
- d) Timing plots are reported with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time).
- e) At time T0 the Radar Waveform generator sends a Burst of pulses for one of the Short Pulse Radar Types 1-4 at DFS Detection Threshold levels on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.
- f) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). Measure and record the Channel Move Time and Channel Closing Transmission Time if radar detection occurs.
- g) When operating as a Master Device, monitor the EUT for more than 30 minutes following instant T2 to verify that the EUT does not resume any transmissions on this Channel. Perform this test once and record the measurement result.



### 9.4 Test Results of Dynamic frequency selection

Test data reference "Appendix of 230402194SHA-003\_15.407-WIFI\_Appendix" Appendix G

**TEST REPORT****10 Frequency Stability****Test result:** Pass**10.1 Limit**

The frequency stability shall be sufficient to ensure that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

**10.2 Test Result**

Frequency Error - Temperature Variation

| Supply Voltage<br>DC (V) | Temperature<br>(°C) | Frequency Deviation (ppm) |
|--------------------------|---------------------|---------------------------|
|                          |                     | Channel<br>(5180MHz)      |
| 12                       | -20                 | 2.92                      |
|                          | -10                 | 2.92                      |
|                          | 0                   | 2.90                      |
|                          | 10                  | 2.90                      |
|                          | 20                  | 2.90                      |
|                          | 30                  | 2.92                      |
|                          | 40                  | 2.92                      |
|                          | 50                  | 3.07                      |

Frequency Error - Voltage Variation

| Supply Voltage<br>DC (V) | Temperature<br>(°C) | Frequency Deviation (ppm) |
|--------------------------|---------------------|---------------------------|
|                          |                     | Channel<br>(5180MHz)      |
| 10.2                     | 20                  | 2.92                      |
| 12.0                     |                     | 2.90                      |
| 13.8                     |                     | 2.90                      |

**TEST REPORT****11 Antenna requirement****Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT use of a permanently attached antenna and a unique coupling to the intentional radiator, so it can comply with the provisions of this section.

**TEST REPORT****Appendix I: Photograph of test setup**

See test photos attached in Appendix I for the actual connections between Product and support equipment.

**Appendix II: Photograph of equipment under test**

Refer to Appendix II for EUT external and internal photos.

\*\*\*\*\* END \*\*\*\*\*