



FCC TEST REPORT

FCC ID: 2A5WS-202202170224

Product	:	Robotic Vacuum Cleaner
Model Name	:	X500s, E50,E60,E50 Pro,E60 Pro,V50,V60,V70,M500
Brand	:	ROZI
Report No.	:	PTC22031802101E-FC02

Prepared for

Zaihong Trade (Shanghai)Co., Ltd.

Room 524,building 1, NO.8,Fuxing East Road, Tinglin Town jinshan,shanghai,China

Prepared by

Precise Testing & Certification Co., Ltd

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China



TEST RESULT CERTIFICATION

Applicant's name : Zaihong Trade (Shanghai)Co., Ltd.
Address : Room 524,building 1, NO.8,Fuxing East Road, Tinglin Town
jinshan,shanghai,China
Manufacture's name : Shenzhen Hua Xin Information Technology Co.,Ltd.
Address : B101-B801, building 4, No.7 Industrial Area, Heshuikou
Community, Matian Street, Guangming District, Shenzhen, China.
Product name : Robotic Vacuum Cleaner
Model name : X500s,
E50,E60,E50 Pro,E60 Pro,V50,V60,V70,M500
Test procedure : KDB 447498 D01 General RF Exposure Guidance v06
Test Date : Dec 08, 2020 to Mar 25 2022
Date of Issue : Mar 25 2022
Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads 'Abel Yu'.

Abel Yu / Engineer

Technical Manager:

A handwritten signature in black ink that reads 'Wu Weimin'.

Wu Weimin / Manager



Contents

	Page
2 TEST SUMMARY.....	4
3 GENERAL INFORMATION.....	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE.....	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT.....	6
4.3 MPE CALCULATION METHOD.....	7
4.4 TEST RESULT.....	7



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Robotic Vacuum Cleaner
Model Name	:	X500s,E50,E60,E50 Pro,E60 Pro,V50,V60,V70,M500 NOTE:(X500s is the main test model, other models and main test models have different appearance colors, others are the same)
Bluetooth Version	:	WiFi
Operating frequency	:	802.11b/g/n HT20: 2412-2462MHz
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation:	:	PCB
Antenna Gain:	:	3 dBi
Power supply	:	AC100-240V 50/60HZ 19V/0.6A(14.4V 2500mAh,battery)



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : FCC Part 2.1091

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
WIFI	2.00	18.06	63.97	0.0254	1	Pass

*****THE END REPORT*****