

RF Exposure Evaluation

FCC ID: 2A5XM-YS-203

1. Client Information

Applicant	:	Shenzhen Youshida High Technology Co., Ltd
Address	:	5/F Building A, Runchang Industrial Park, Xuexiang, Bantian Street, Longgang District, Shenzhen
Manufacturer	:	Shenzhen Youshida High Technology Co., Ltd
Address	:	5/F Building A, Runchang Industrial Park, Xuexiang, Bantian Street, Longgang District, Shenzhen

2. General Description of EUT

EUT Name	:	Karaoke speaker	
Model(s) No.	:	YS-203, YS-201, YS-202, YS-204, YS-205, YS-206, YS-207, YS-208, YS-209, YS-210, YS-211, YS-212, YS-213, YS-215, YS-216, YS-217, YS-218, YS-219, YS-220, YS-221, YS-222, YS-223, YS-224, YS-225, YS-226, YS-227, YS-228	
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is appearance.	
Sample ID	:	RW-C-202202-0171-1-1# & RW-C-202202-0171-1-2#	
Product Description	Operation Frequency:	Bluetooth 4.0: 2402MHz~2480MHz	
	Number of Channel:	Bluetooth 4.0: 79 channels	
	RF Output Power:	-2.24dBm	
	Antenna Gain:	-0.58dBi PCB Antenna	
Power Supply	:	USB Input: DC 5V/1A DC 3.7V by 3000mAh Li-ion battery	
Software Version	:	YSD2.0	
Hardware Version	:	YS1.3	
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.			

Note: More test information about the EUT please refer the RF Test Report.

The RF Exposure Evaluation for FCC:

SAR Test Exclusion Calculations

FCC: According to 447498 D04 Interim General RF Exposure Guidance v01.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Calculation:

Test separation: 5mm					
Bluetooth Mode (GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P _{th} (mW)
2.402	-3.96	-3±1	-2	0.631	3
2.441	-4.07	-4±1	-3	0.501	3
2.480	-4.54	-4±1	-3	0.501	3
Bluetooth Mode (π/4-DQPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Limit P _{th} (mW)
2.402	-2.68	-2±1	-1	0.794	3
2.441	-3.14	-3±1	-2	0.631	3
2.480	-3.61	-3±1	-2	0.631	3
Bluetooth Mode (8-DPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Limit P _{th} (mW)
2.402	-2.24	-2±1	-1	0.794	3
2.441	-2.72	-2±1	-1	0.794	3
2.480	-3.18	-3±1	-2	0.631	3

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D04, No SAR is required.

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 and the RSS-102§4 Table 4 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06, No SAR is required.

-----END OF REPORT-----