

FCC ID: 2A62SZY01FG

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHZ})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHZ})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	4.412	2.76	5 \pm 1	6.00	3.98	<5	1.23400	3.00	YES
	2.441	4.303	2.69	5 \pm 1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	4.566	2.86	5 \pm 1	6.00	3.98	<5	1.25388	3.00	YES
$\pi/4$ DQPSK	2.402	4.722	2.97	5 \pm 1	6.00	3.98	<5	1.23400	3.00	YES
	2.441	3.676	2.33	4 \pm 1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	3.82	2.41	4 \pm 1	5.00	3.16	<5	0.99599	3.00	YES
8DPSK	2.402	4.066	2.55	4 \pm 1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	3.85	2.43	4 \pm 1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	4.031	2.53	4 \pm 1	5.00	3.16	<5	0.99599	3.00	YES

Conclusion:

For the max result : 1.25388W/Kg \leq FCC Limit 3.0 for 1g SAR.