

	TEST REPOR	RT					
FCC ID:	2A6RZ-BLE01						
Test Report No::	TCT220329E030						
Date of issue::	May 07, 2022						
Testing laboratory:	SHENZHEN TONGCE TESTIN	G LAB					
Testing location/ address:	TCT Testing Industrial Park Fud Street, Bao'an District Shenzhe Republic of China						
Applicant's name:	Norsk Inc	(2)	(6)				
Address:	PO BOX 28488, MINNEAPOLIS United States	S, MINNESOTA, 5	55428 0488,				
Manufacturer's name:	SHENZHEN TAICO TECHNOL	SHENZHEN TAICO TECHNOLOGY CO., LTD					
Address::	Room 1035,1036,1038, Dongming Building, Minkang Road, Zhangkeng Community, Minzhi Street, Longhua District, Shenzhen, China						
Standard(s):	FCC CFR Title 47 Part 1.1307						
Product Name::	Bluetooth module						
Trade Mark::	N/A		<b>A</b>				
Model/Type reference:	VIP-BMS BLE01						
Rating(s)::	DC 3.3V						
Date of receipt of test item	Mar. 29, 2022		(0)				
Date (s) of performance of test:	Mar. 29, 2022 - May 07, 2022	). (					
Tested by (+signature) :	Onnado YE	Onnado Jano	CEZ				
Check by (+signature):	Beryl ZHAO	Boy Comp	OT) STING				
Approved by (+signature):	Tomsin	Tomsies	847				

#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





# **Table of Contents**

<ol> <li>2.</li> <li>3.</li> <li>4.</li> </ol>	1.1. 1.2. Ger 2.1. 2.2. Fac 3.1. 3.2.	EUT desc Model(s) neral Info Test envi Descripti ilities au Facilities Location	cription listormation fronment a on of Sup and Accre	and mode. port Units ditations	ent Data		
	) )	i Nosun		ousur Cink	(i)		



# 1. General Product Information

# 1.1. EUT description

Product Name:	Bluetooth module			(6)
Model/Type reference:	VIP-BMS BLE01			
Sample Number:	TCT220329E029-0101			
Operation Frequency:	2402MHz~2480MHz		(0)	
Modulation Type:	GFSK			
Antenna Type:	PCB Antenna	(C)		(C)
Antenna Gain:	0dBi			
Rating(s):	DC 3.3V			

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. N	arameter. <b>lodel(s) l</b> lone.	list			



# 2. General Information

#### 2.1. Test environment and mode

Item	Normal condition		
Temperature	+25°C		
Voltage	DC 3.3V		
Humidity	56%		
Atmospheric Pressure:	1008 mbar		
Test Mode:			
Engineering mode:	Keep the EUT in continuous transmitting by select channel		

# 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/		1	1	1

#### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



### 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an

District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





# 4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) The maximum output power for antenna is -0.23dBm (0.95mW) at 2440MHz, 0dBi antenna gain (with 1.00 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation

Given

$$E = \sqrt{\frac{30 \times P \times G}{d}} \quad \& \quad S = \frac{E^2}{3770}$$

Where

E = Field Strength in Volts / meter

P = Power in Watts

G=Numeric antenna gain

d=Distance in meters

S=Power Density in milliwatts / square centimeter

Maximum Permissible Exposure

output power= 0.95mW

Numeric Antenna gain= 1.00

Substituting the MPE safe distance using d=20cm into above equation.

Yields:

S=0.000199\*P\*G

Where  $P=Power\ in\ mW$ 

G=Numeric antenna gain

S=Power density in mW/cm2

Power density= 0.000189mW/cm2

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)

\*\*\*\*\*END OF REPORT\*\*\*\*

Page 6 of 6

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com