

# RF Exposure Requirements

---

## 1.1 Product Description for Equipment Under Test (EUT)

### Client Information

Applicant: Shenzhen Samying High Tech Co., LTD  
Address of applicant: 302, Block 5, Fulongte Industry Park, Huaxing Road, Dalang, Longhua, Shenzhen

Manufacturer: Shenzhen Samying High Tech Co., LTD  
Address of manufacturer: 302, Block 5, Fulongte Industry Park, Huaxing Road, Dalang, Longhua, Shenzhen

General Description of EUT	
Product Name:	Smart Night Light
Brand Name:	/
Model No.:	NL1800, NL1801, NL1802, NL1803
Adding Model(s):	/
Rated Voltage:	DC 4.5V
Power Adapter:	/
Software Version:	/
Hardware Version:	/
Serial Number:	/
FCC ID:	2A65ANL1800

Technical Characteristics of EUT	
Bluetooth Version:	V5.0 BLE
Frequency Range:	2402-2480MHz
RF Output Power:	4.367dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB
Antenna Gain:	0.5dBi

## 1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, the following RF exposure evaluation shall demonstrate RF exposure compliance.

**[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0**

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

### **1.3 Calculation Method**

#### **Bluetooth**

Tx frequency range: 2402~2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 4.367dBm

RF channel transmit frequency: 2440MHz

Result: 0.69

Limit: 3.0

So the transmitter complies with the RF exposure requirements and the SAR is not required.