

EUT Specification

FCC ID: 2A67RHMF-50

Characteristics	Description
Product Name	Magnetic Power Bank
Model number	HMF-50
Power Supply	AC 120V/60Hz for adapter
Operating Frequency Range	110-205KHz
Modulation Technique	ASK
Antenna Type	Induction coil
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Applicable Standard:

FCC Part 1(1.1310) ,Part 2(2.1091) and KDB 680106 D01 RF Exposure
Wireless Charging Apps v03

Applicable Requirement:

Three different categories of transmitters are defined by the FCC in OET Bulletin 65.

These categories are fixed installation, mobile, and portable and are defined as follows:

Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.

Mobile Devices: a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.

Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure.

These two categories are defined as follows:

Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. The phrase fully aware in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. Such training is not required for transient persons, but they must receive written and/or verbal information and notification (for example, using signs) concerning their exposure potential and appropriate means available to mitigate their exposure. The phrase exercise control means that an exposed person is allowed to and knows how to reduce or avoid exposure by administrative or engineering controls and work practices, such as use of personal protective equipment or time averaging of exposure.

General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the

potential for exposure or cannot exercise control over their exposure. Licensees and applicants are responsible for compliance with both the occupational/controlled exposure limits and the general population/uncontrolled exposure limits as they apply to transmitters under their jurisdiction. Licensees and applicants should be aware that the occupational/controlled exposure limits apply especially in situations where workers may have access to areas in very close proximity to antennas and access to the general public may be restricted.

In lieu of evaluation with the general population/uncontrolled exposure limits, amateur licensees authorized under part 97 of this chapter and members of his or her immediate household may be evaluated with respect to the occupational/controlled exposure limits in this section, provided appropriate training and information has been provided to the amateur licensee and members of his/her household. Other nearby persons who are not members of the amateur licensee's household must be evaluated with respect to the general population/uncontrolled exposure limits.

Test Procedure

- 1.EUT was placed on a table, and the measure probe was placed at a measurement distance of 0~10cm from the EUT to the center of the probe.
- 2.Power on the measuring probe, the EUT was set at the maximum field strength emission state.
- 3.The EUT was put in different directions (Left, Right, Front, Rear, Top and Bottom) toward to the measure probe.The distance from the EUT to the probe starts from 0cm, and measures every 2cm until the distance is 10cm.
- 4.Record the worst data of the different directions.

Measuring Device And Test Equipment

Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒	E-Field&H-Field Probe(9kHz-30MHz)	Narda	EHP-200A	180ZX11012	2022.03.06	1 Year

Description of Support Device

adapter	Model number: CD217
	: Input: AC 100-240V, 50/60Hz
	Output: DC 9V/3A,DC 12V/2.5A
iPhone	Manufacturer: Apple Inc.
	: M/N: A1524
	S/N: N/A
Wireless Charger Receiver	Manufacturer: Universal
Module	: M/N: N/A
	S/N: N/A
	Manufacturer: SAMSUNG
SAMSUNG S9	: M/N:Samsung Galaxy S9
	S/N: N/A

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Note: f denotes for frequency in MHz.

* denotes for plane-wave equivalent power density.

Measurement Result

We pretested three modes (max load, mid load, Standby) for EUT. The worst mode (max load) and worst test frequency(frequency: 127.7KHz)test data see the following.

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	10% Limit(A/m)
Measurement Point 1	Front	0	0.167	1.63	0.163
Measurement Point 2	Back	0	0.150		
Measurement Point 3	Left	0	0.149		
Measurement Point 4	Right	0	0.145		
Measurement Point 5	Bottom	0	0.138		
Measurement Point 6	Top	0	0.151		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	0	45.415	614	61.4
Measurement Point 2	Back	0	45.320		
Measurement Point 3	Left	0	45.258		
Measurement Point 4	Right	0	45.126		
Measurement Point 5	Bottom	0	45.337		
Measurement Point 6	Top	0	45.248		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	2	0.165	1.63	0.163
Measurement Point 2	Back	2	0.148		
Measurement Point 3	Left	2	0.146		
Measurement Point 4	Right	2	0.142		
Measurement Point 5	Bottom	2	0.136		
Measurement Point 6	Top	2	0.150		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	2	45.402	614	61.4
Measurement Point 2	Back	2	45.317		
Measurement Point 3	Left	2	45.247		
Measurement Point 4	Right	2	45.125		
Measurement Point 5	Bottom	2	45.329		
Measurement Point 6	Top	2	45.242		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	4	0.161	1.63	0.163
Measurement Point 2	Back	4	0.146		
Measurement Point 3	Left	4	0.144		
Measurement Point 4	Right	4	0.140		
Measurement Point 5	Bottom	4	0.134		
Measurement Point 6	Top	4	0.148		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	4	45.397	614	61.4
Measurement Point 2	Back	4	45.306		
Measurement Point 3	Left	4	45.241		
Measurement Point 4	Right	4	45.116		
Measurement Point 5	Bottom	4	45.322		
Measurement Point 6	Top	4	45.234		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	6	0.159	1.63	0.163
Measurement Point 2	Back	6	0.143		
Measurement Point 3	Left	6	0.141		
Measurement Point 4	Right	6	0.137		
Measurement Point 5	Bottom	6	0.131		
Measurement Point 6	Top	6	0.146		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	6	45.386	614	61.4
Measurement Point 2	Back	6	45.301		
Measurement Point 3	Left	6	45.233		
Measurement Point 4	Right	6	45.105		
Measurement Point 5	Bottom	6	45.312		
Measurement Point 6	Top	6	45.228		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	8	0.157	1.63	0.163
Measurement Point 2	Back	8	0.140		
Measurement Point 3	Left	8	0.139		
Measurement Point 4	Right	8	0.135		
Measurement Point 5	Bottom	8	0.130		
Measurement Point 6	Top	8	0.145		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	8	45.365	614	61.4
Measurement Point 2	Back	8	45.296		
Measurement Point 3	Left	8	45.225		
Measurement Point 4	Right	8	45.096		
Measurement Point 5	Bottom	8	45.303		
Measurement Point 6	Top	8	45.219		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	10	0.155	1.63	0.163
Measurement Point 2	Back	10	0.138		
Measurement Point 3	Left	10	0.137		
Measurement Point 4	Right	10	0.133		
Measurement Point 5	Bottom	10	0.128		
Measurement Point 6	Top	10	0.144		

Test Mode: Wireless Charging 5W use iPhone for 10% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	10	45.354	614	61.4
Measurement Point 2	Back	10	45.285		
Measurement Point 3	Left	10	45.211		
Measurement Point 4	Right	10	45.084		
Measurement Point 5	Bottom	10	45.297		
Measurement Point 6	Top	10	45.213		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	10% Limit(A/m)
Measurement Point 1	Front	0	0.168	1.63	0.163
Measurement Point 2	Back	0	0.151		
Measurement Point 3	Left	0	0.150		
Measurement Point 4	Right	0	0.146		
Measurement Point 5	Bottom	0	0.139		
Measurement Point 6	Top	0	0.152		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	0	45.417	614	61.4
Measurement Point 2	Back	0	45.321		
Measurement Point 3	Left	0	45.262		
Measurement Point 4	Right	0	45.129		
Measurement Point 5	Bottom	0	45.338		
Measurement Point 6	Top	0	45.249		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	2	0.165	1.63	0.163
Measurement Point 2	Back	2	0.147		
Measurement Point 3	Left	2	0.147		
Measurement Point 4	Right	2	0.143		
Measurement Point 5	Bottom	2	0.137		
Measurement Point 6	Top	2	0.151		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	2	45.406	614	61.4
Measurement Point 2	Back	2	45.322		
Measurement Point 3	Left	2	45.249		
Measurement Point 4	Right	2	45.126		
Measurement Point 5	Bottom	2	45.332		
Measurement Point 6	Top	2	45.244		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	4	0.162	1.63	0.163
Measurement Point 2	Back	4	0.147		
Measurement Point 3	Left	4	0.145		
Measurement Point 4	Right	4	0.141		
Measurement Point 5	Bottom	4	0.135		
Measurement Point 6	Top	4	0.149		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	4	45.399	614	61.4
Measurement Point 2	Back	4	45.307		
Measurement Point 3	Left	4	45.243		
Measurement Point 4	Right	4	45.118		
Measurement Point 5	Bottom	4	45.323		
Measurement Point 6	Top	4	45.236		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	6	0.160	1.63	0.163
Measurement Point 2	Back	6	0.144		
Measurement Point 3	Left	6	0.142		
Measurement Point 4	Right	6	0.138		
Measurement Point 5	Bottom	6	0.132		
Measurement Point 6	Top	6	0.147		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	6	45.389	614	61.4
Measurement Point 2	Back	6	45.306		
Measurement Point 3	Left	6	45.234		
Measurement Point 4	Right	6	45.108		
Measurement Point 5	Bottom	6	45.315		
Measurement Point 6	Top	6	45.229		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	8	0.158	1.63	0.163
Measurement Point 2	Back	8	0.141		
Measurement Point 3	Left	8	0.140		
Measurement Point 4	Right	8	0.136		
Measurement Point 5	Bottom	8	0.131		
Measurement Point 6	Top	8	0.146		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	8	45.366	614	61.4
Measurement Point 2	Back	8	45.299		
Measurement Point 3	Left	8	45.227		
Measurement Point 4	Right	8	45.098		
Measurement Point 5	Bottom	8	45.305		
Measurement Point 6	Top	8	45.217		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	10	0.156	1.63	0.163
Measurement Point 2	Back	10	0.139		
Measurement Point 3	Left	10	0.138		
Measurement Point 4	Right	10	0.134		
Measurement Point 5	Bottom	10	0.129		
Measurement Point 6	Top	10	0.145		

Test Mode: Wireless Charging 5W use iPhone for 50% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	10	45.357	614	61.4
Measurement Point 2	Back	10	45.288		
Measurement Point 3	Left	10	45.213		
Measurement Point 4	Right	10	45.086		
Measurement Point 5	Bottom	10	45.299		
Measurement Point 6	Top	10	45.215		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	10% Limit(A/m)
Measurement Point 1	Front	0	0.169	1.63	0.163
Measurement Point 2	Back	0	0.152		
Measurement Point 3	Left	0	0.151		
Measurement Point 4	Right	0	0.147		
Measurement Point 5	Bottom	0	0.140		
Measurement Point 6	Top	0	0.153		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	0	45.419	614	61.4
Measurement Point 2	Back	0	45.323		
Measurement Point 3	Left	0	45.263		
Measurement Point 4	Right	0	45.135		
Measurement Point 5	Bottom	0	45.340		
Measurement Point 6	Top	0	45.252		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	2	0.166	1.63	0.163
Measurement Point 2	Back	2	0.148		
Measurement Point 3	Left	2	0.147		
Measurement Point 4	Right	2	0.144		
Measurement Point 5	Bottom	2	0.138		
Measurement Point 6	Top	2	0.152		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	2	45.408	614	61.4
Measurement Point 2	Back	2	45.323		
Measurement Point 3	Left	2	45.253		
Measurement Point 4	Right	2	45.129		
Measurement Point 5	Bottom	2	45.334		
Measurement Point 6	Top	2	45.245		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	4	0.163	1.63	0.163
Measurement Point 2	Back	4	0.148		
Measurement Point 3	Left	4	0.146		
Measurement Point 4	Right	4	0.142		
Measurement Point 5	Bottom	4	0.135		
Measurement Point 6	Top	4	0.148		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	4	45.340	614	61.4
Measurement Point 2	Back	4	45.308		
Measurement Point 3	Left	4	45.246		
Measurement Point 4	Right	4	45.119		
Measurement Point 5	Bottom	4	45.325		
Measurement Point 6	Top	4	45.238		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	6	0.158	1.63	0.163
Measurement Point 2	Back	6	0.143		
Measurement Point 3	Left	6	0.141		
Measurement Point 4	Right	6	0.137		
Measurement Point 5	Bottom	6	0.132		
Measurement Point 6	Top	6	0.146		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	6	45.391	614	61.4
Measurement Point 2	Back	6	45.307		
Measurement Point 3	Left	6	45.238		
Measurement Point 4	Right	6	45.111		
Measurement Point 5	Bottom	6	45.316		
Measurement Point 6	Top	6	45.232		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	8	0.158	1.63	0.163
Measurement Point 2	Back	8	0.139		
Measurement Point 3	Left	8	0.140		
Measurement Point 4	Right	8	0.136		
Measurement Point 5	Bottom	8	0.131		
Measurement Point 6	Top	8	0.144		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	8	45.369	614	61.4
Measurement Point 2	Back	8	45.302		
Measurement Point 3	Left	8	45.229		
Measurement Point 4	Right	8	45.100		
Measurement Point 5	Bottom	8	45.308		
Measurement Point 6	Top	8	45.219		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	H- Field(A/m)	Limit(A/m)	50% Limit(A/m)
Measurement Point 1	Front	10	0.156	1.63	0.163
Measurement Point 2	Back	10	0.137		
Measurement Point 3	Left	10	0.138		
Measurement Point 4	Right	10	0.134		
Measurement Point 5	Bottom	10	0.130		
Measurement Point 6	Top	10	0.141		

Test Mode: Wireless Charging 5W use iPhone for 90% battery					
		Measuring Distance(cm)	E- Field(V/m)	Limit(V/m)	10% Limit(V/m)
Measurement Point 1	Front	10	45.359	614	61.4
Measurement Point 2	Back	10	45.290		
Measurement Point 3	Left	10	45.215		
Measurement Point 4	Right	10	45.088		
Measurement Point 5	Bottom	10	45.301		
Measurement Point 6	Top	10	45.218		

PHOTOGRAPHS OF TEST SETUP



Signature

Alan He

Alan He
Manager

Date: 2022-06-07