


	SPECIFICATION	
	Product Description	Model No.
	BXRFID254002	V2.0
Customer :		Page
Date : 2025-05-27		- 1 -

1、OVERALL PERFORMANCE(Antenna Element,&Cable)	
CHARACTERISTICS	SPEC
Center Frequency	920MHz~925MHz
Bandwidth	5MHz min
Polarization	R.H.C.P
Output VSWR	≤2.0 max
Output Impedance	50ohm
Dimensions	25mm(L)×25mm(W)×4mm(H) typ
Connector Type	NC
2、OPERRATING CONDITION	
Temperature	-35℃ to +75℃
Humidity	10% to 95% RH
3、STORAGE CONDITION	
Temperature	-40℃ to +85℃
Humidity	10% to 95% R H
4、Patch	
CHARACTERISTICS	SPEC
Dimensions	25mm(L)×25mm(W)×4.0mm(H) typ
Efficiency	≥15%
Peak Gain	≥-5.0 dB typ @GND 30*30mm
Axial ratio	≤3.0 dB
Circular polarization mode	One pin feed


	SPECIFICATION	
	Product Description	Model No.
	BXRFID254002	V2.0
Customer :		Page
Date : 2025-05-27		- 2 -

5、ANTENNA DIMENSIONS



Unmarked dimensional tolerance:±0.2mm

测试数据如下:




驻波

	SPECIFICATION	
	Product Description	Model No.
	BXRFID254002	V2.0
Customer：		Page
Date：2025-05-27		- 3 -

Frequency（Mhz）	Gain(dBi)	Efficiency
915	-7.80	4.30%
916	-6.92	4.93%
917	-6.06	6.12%
918	-5.26	7.69%
919	-4.55	9.87%
920	-4.13	12.98%
921	-3.03	17.43%
922	-1.92	22.03%
923	-1.78	24.03%
924	-2.59	22.46%
925	-3.87	18.89%
926	-5.31	14.99%
927	-6.90	10.96%
928	-8.41	7.91%
929	-9.83	5.76%
930	-11.10	4.26%

2D方向图



	SPECIFICATION	
	Product Description	Model No.
	BXRFID254002	V2.0
Customer：		Page
Date：2025-05-27		- 4 -

3D方向图

