

RF Exposure Requirements

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Guangzhoushi Desuo Dianzishangwu Youxiangongsi
Address of applicant: shundequ lunjiaojiedao lunjiao biguiyuan longwanyuan 8zuo220 foshanshi guangdongsheng, 528308

Manufacturer: ZHEJIANG PINXIN INTELLIGENT TECHNOLOGY CO.,LTD
Address of manufacturer: 1-4 FLOOR, WEST BUILDING 1, NO.59 BAIMU ROAD, ECONOMIC DEVELOPMENT ZONE, YONGKANG CITY, ZHEJIANG PROVINCE, CHINA

General Description of EUT	
Product Name:	BLUETOOTH BODY FAT SCALE
Brand Name:	/
Model No.:	EB8204
Adding Model(s):	/
Rated Voltage:	DC 3V
Power Adapter:	/
Software Version:	/
Hardware Version:	/
Serial Number:	2JDLP2033
FCC ID:	2A69FEB8204

Technical Characteristics of EUT	
Bluetooth Version:	V4.0 BLE
Frequency Range:	2402-2480MHz
RF Output Power:	-10.12dBm
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB
Antenna Gain:	0.5dBi

1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, the following RF exposure evaluation shall demonstrate RF exposure compliance.

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

1.3 Calculation Method

Bluetooth

Tx frequency range: 2402~2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: -10.12Bm

Maximum Tune-up Conducted Output Power: -9dBm

RF channel transmit frequency: 2440MHz

Result: 0.039

Limit: 3.0

So the transmitter complies with the RF exposure requirements and the SAR is not required.