

TEST REPORT

FCC PART 15.247

Report Reference No.: CTL2205193061-WF01

Compiled by: (position+printed name+signature)

Tested by: (position+printed name+signature)

Approved by: (position+printed name+signature)

Happy Guo (File administrators)

Gray Gao (Test Engineer)

> Ivan Xie (Manager)



Product Name : Smart watch

Model/Type reference..... C21

Trade Mark..... leete

FCC ID...... 2A69O-C21

Applicant's name...... Leete Technology(ShenZhen) Co., Ltd.

Room 605, Building B, Bantian International Center, Longgang, Address of applicant.....

Shenzhen, China

Shenzhen CTL Testing Technology Co., Ltd. Test Firm....:

Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Address of Test Firm.....

Nanshan District, Shenzhen, China 518055

Test specification....:

Standard....... FCC Part 15.247: Operation within the bands 902-928 MHz.

2400-2483.5 MHz and 5725-5850 MHz.

TRF Originator...... Shenzhen CTL Testing Technology Co., Ltd.

Master TRF...... Dated 2011-01

Date of receipt of test item..........: May. 25, 2022

Date of Test Date...... May. 25, 2022-Jun. 14, 2022

Result..... Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. : CTL2205193061-WF01

Jun. 15, 2022

Date of issue

Equipment under Test : Smart watch

Sample No : CTL220519306-1-S001

Model /Type : C21

Listed Models : C22, C23, C24, C25, C26, C27, C28, C29, C30

Applicant : Leete Technology(ShenZhen) Co., Ltd.

Address : Room 605, Building B, Bantian International Center,

Longgang, Shenzhen, China

Manufacturer : Leete Technology(ShenZhen) Co., Ltd.

Address : Room 605, Building B, Bantian International Center,

Longgang, Shenzhen, China

Test result	Pass *
-------------	--------

^{*}In the configuration tested, the EUT complied with the standards specified page 5.

The device (Product Name: Smart watch) Models Name: C21, C22, C23, C24, C25, C26, C27, C28, C29, C30 have same electrical, PCB and BOM, only the colour and model's names are different for marketing requirements.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

Report No.: CTL2205193061-WF01

Revisions	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2022-06-15	CTL2205193061-WF01	Tracy Qi
		The same of		
		NP.		
			Call C	170
				The sale
	0.70		-0 %	
	Daries Transport		13	

	Table of Contents	Page
1. SU	MMARY	
1.1.	TEST STANDARDS	
1.2.	TEST DESCRIPTION	
1.3.	TEST FACILITY	
1.4.	STATEMENT OF THE MEASUREMENT UNCERTAINTY	
2. GE	NERAL INFORMATION	
2.1.	ENVIRONMENTAL CONDITIONS	
2.2.	GENERAL DESCRIPTION OF EUT	
2.3.	DESCRIPTION OF TEST MODES AND TEST FREQUENCY	
2.4.	EQUIPMENTS USED DURING THE TEST	1
2.5.	RELATED SUBMITTAL(S) / GRANT (S)	
2.6.	MODIFICATIONS	1
3. TES	ST CONDITIONS AND RESULTS	1
3.1.	CONDUCTED EMISSIONS TEST.	1
3.2.	RADIATED EMISSIONS AND BAND EDGE	
3.3.	MAXIMUM PEAK OUTPUT POWER	2
3.4.	20dB Bandwidth	
3.5.	FREQUENCY SEPARATION	2
3.6.	NUMBER OF HOPPING FREQUENCY	2
3.7.	TIME OF OCCUPANCY (DWELL TIME)	
3.8.	OUT-OF-BAND EMISSIONS	
3.9.	PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	
3.10.	Antenna Requirement	
4. TES	ST SETUP PHOTOS OF THE EUT	2
5 PH	OTOS OF THE FUT	3

V1.0 Page 5 of 33 Report No.: CTL2205193061-WF01

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10: 2013: American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(1)(i)	20dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(b)	Pseudorandom Frequency Hopping Sequence	PASS
FCC Part 15.247(a)(1)(iii)	Number of hopping frequency& Time of Occupancy	PASS
FCC Part 15.247(a)(1)	Frequency Separation	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

V1.0 Page 6 of 33 Report No.: CTL2205193061-WF01

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.10 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods — Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±1.60 dB	(1)
Occupied Bandwidth	±0.20ppm	(1)
Radiated Emission 9KHz~30MHz	±3.40dB	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)

V1.0 Page 7 of 33 Report No.: CTL2205193061-WF01

Conducted Disturbance 0.15~30MHz	+3 304B	(1)
Conducted Disturbance 0.13 30M12	±3.200D	(' <i>)</i>

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	Smart watch
Model/Type reference:	C21
Power supply:	DC 3.8V from battery
Bluetooth:	
Version:	Supported BR/EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Wire Antenna
Antenna gain:	0.4dBi

Note 1: For more details, please refer to the user's manual of the EUT.

Note 2: Antenna gain provided by the applicant.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:

Channel	Frequency (MHz)
00	2402
01	2403
100	1 20
38	2440
39	2441
40	2442
	100
77	2479
78	2480

Preliminary tests were performed in each mode and packet length of BT, and found worst case as bellow, finally test were conducted at those mode and recorded in this report.

Test Items	Worst case		
Conducted Emissions	DH5 Middle channel		
Radiated Emissions and Band Edge	DH5		
Maximum Conducted Output Power	DH5/2DH5/3DH5		
20dB Bandwidth	DH5/2DH5/3DH5		
Frequency Separation	DH5/2DH5/3DH5 Middle channel		
Number of hopping frequency	DH5/2DH5/3DH5		
Time of Occupancy (Dwell Time)	DH1/DH3/DH5 Middle channel 2DH1/2DH3/2DH5 Middle channel 3DH1/3DH3/3DH5 Middle channel		
Out-of-band Emissions	DH5/2DH5/3DH5		

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.		Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ESH2-Z5		860014/010	2022/05/07	2023/05/06
Double cone logarithmic antenna	Schwarzbeck	VULB 9168		824	2020/04/07	2023/04/06
Horn Antenna	Ocean Microwave	OBH10	0400	26999002	2019/11/28	2022/11/27
EMI Test Receiver	R&S	ESC	CI	1166.5950.03	2022/05/07	2023/05/06
Spectrum Analyzer	Agilent	E440	7B	MY41440676	2022/05/07	2023/05/06
Spectrum Analyzer	Agilent	N902	20A	US46220290	2022/05/07	2023/05/06
Spectrum Analyzer	Keysight	N902	20A	MY53420874	2022/05/07	2023/05/06
Horn Antenna	Sunol Sciences Corp.	DRH-	118	A062013	2021/12/23	2024/12/22
Active Loop Antenna	Da Ze	ZN30900A		1	2021/05/13	2024/05/12
Amplifier	Agilent	8449	9B	3008A02306	2022/05/07	2023/05/06
Amplifier	Agilent	8447	7D	2944A10176	2022/05/06	2023/05/05
Amplifier	MRT	MRT-AP01M06		S-001	2022/05/07	2023/05/06
Amplifier	Brief&Smart	LNA-4018		2104197	2022/05/07	2023/05/06
Temperature/Humi dity Meter	Ji Yu	MC501		/	2022/05/07	2023/05/06
Power Sensor	Agilent	U202	1XA	MY55130004	2022/05/07	2023/05/06
Power Sensor	Agilent	U202	1XA	MY55130006	2022/05/07	2023/05/06
Power Sensor	Agilent	U202	1XA	MY54510008	2022/05/07	2023/05/06
Power Sensor	Agilent	U202	1XA	MY55060003	2022/05/07	2023/05/06
Spectrum Analyzer	RS	FS	Р	1164.4391.38	2022/05/07	2023/05/06
Test Software	.*					
Name	Name of Software Version					
TST-PASS V1.1.0						
EZ_EM	EZ_EMC(Below 1GHz) V1.1.4.2					
EZ_EMO	EZ_EMC((Above 1GHz)			V1.1.4.2		

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


<u>LIMIT</u>

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Fraguency range (MHz)	Limit (dBuV)			
Frequency range (MHz)	Quasi-peak	Average		
0.15-0.5	66 to 56*	56 to 46*		
0.5-5	56	46		
5-30	60	50		

^{*} Decreases with the logarithm of the frequency.

TEST CONFIGURATION





TEST PROCEDURE

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
- 2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
- 4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipments received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark: All modes of GFSK, Pi/4 DQPSK, and 8DPSK were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:





MEASUREMENT RESULT: "CTL220530106_fin"

V1.0

5/30/2022 10:	1.Z.AM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBuV	dB	dSpV	dB			
0.330000	31.70	10.0	60	27.8	QP	N	GND
0.375000	31.80	10.0	58	26.6	QP	N	GND
0.618000	33.70	10.1	56	22.3	QP	N	GND
0.640500	33.60	10.1	56	22.4	QP	N	GND

MEASUREMENT RESULT: "CTL220530106 fin2"

5/30/2022 10	:12AM						
Frequency MHz	Level dBuV	Transd dB	Limit	Margin dB	Detector	Line	PE
0.375000	21,70	10.0	48	26.7	AV	14	GND
0.622500	15.50	10.1	46	30.5	AV	11	GND
1.126500	20.20	10.2	46	25.8	AV	N	GND
3.385500	19.80	10.3	46	26.2	AV	N	GND
4.137000	18.30	10.3	46	27.7	AV.	N	GND
4.888500	18.60	10.4	46	27.4	AV	14	GND

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



V1.0 Page 15 of 33 Report No.: CTL2205193061-WF01

Ant. feed point

3 m

Ground Plane

Receiver Amp.

(C) Radiated Emission Test Set-Up, Frequency above 1000MHz

Test Procedure


- 1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measurements have been completed.
- 5. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.


TEST RESULTS


Remark:

- 1. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
- 2. For below 1GHz testing recorded worst at GFSK DH5 low channel.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, found the
 emission level are attenuated 20dB below the limits from 9 kHz to 30MHz, so it does not recorded
 in report.

For 30MHz-1GHz







For 1GHz to 25GHz

V1.0

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case GFSK is reported.

GFSK (above 1GHz)

Fred	Frequency(MHz):			2402		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)	
4804.00	56.27	PK	74.00	17.73	51.76	33.49	6.91	35.89	4.51	
4804.00	51.76	AV	54.00	2.24	47.25	33.49	6.91	35.89	4.51	
5320.00	49.23	PK	74.00	24.77	42.37	34.06	7.04	34.24	6.86	
5320.00	-	AV	54.00							
7206.00	47.66	PK	74.00	26.34	36.56	36.95	9.18	35.03	11.10	
7206.00	-	AV	54.00							

Fred	uency(MF	łz):	2402			Polarity:			VERTICAL			
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)			
4804.00	56.38	PK	74.00	17.62	51.87	33.49	6.91	35.89	4.51			
4804.00	52.65	AV	54.00	1.35	48.14	33.49	6.91	35.89	4.51			
5349.00	47.24	PK	74.00	26.76	40.38	34.06	7.04	34.24	6.86			
5349.00	-	AV	54.00				-					
7206.00	49.02	PK	74.00	24.98	37.92	36.95	9.18	35.03	11.10			
7206.00	-	AV	54.00									

Fred	Frequency(MHz): 2441			41		Polarity:	HORIZONTAL		
Frequency (MHz)	Le	ssion vel V/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4882.00	55.21	PK	74.00	18.79	48.85	33.60	6.95	34.19	6.36
4882.00	51.58	AV	54.00	2.42	45.22	33.60	6.95	34.19	6.36
5474.00	48.33	PK	74.00	25.67	40.73	34.56	7.15	34.11	7.60
5474.00		AV	54.00					-	
7323.00	50.26	PK	74.00	23.74	38.56	37.46	9.23	35.00	11.70
7323.00		AV	54.00	1			1	-	

Fred	Frequency(MHz):			2441 Polarity:			VERTICAL		
Frequency (MHz)	Le	ssion vel V/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre- amplifier (dB)	Correction Factor (dB/m)
4882.00	56.83	PK	74.00	17.17	50.47	33.60	6.95	34.19	6.36
4882.00	52.11	AV	54.00	1.89	45.75	33.60	6.95	34.19	6.36
5531.00	47.75	PK	74.00	26.25	40.15	34.56	7.15	34.11	7.60
5531.00	-	AV	54.00				1		
7323.00	48.59	PK	74.00	25.41	36.89	37.46	9.23	35.00	11.70
7323.00		AV	54.00				-		

Report No.: CTL2205193061-WF01

Fred	Frequency(MHz):			2480		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value	Antenna Factor	Cable Factor	Pre- amplifier	Correction Factor	
		,			(dBuV)	(dB/m)	(dB)	(dB)	(dB/m)	
4960.00	56.31	PK	74.00	17.69	51.39	33.84	7.00	35.92	4.92	
4960.00	51.79	AV	54.00	2.21	46.87	33.84	7.00	35.92	4.92	
5632.00	47.25	PK	74.00	26.75	39.97	34.45	7.12	34.29	7.28	
5632.00		AV	54.00							
7440.00	55.34	PK	74.00	18.66	43.39	37.64	9.28	34.97	11.95	
7440.00	49.22	AV	54.00	4.78	37.27	37.64	9.28	34.97	11.95	

REMARKS:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- 3. Margin value = Limit value- Emission level.
- 4. -- Mean the PK detector measured value is below average limit.
- 5. The other emission levels were very low against the limit.
- 6. RBW 1MHz VBW 3MHz Peak detector is for PK value; RBW 1MHz VBW 10Hz Peak detector is for AV value.

V1.0 Page 20 of 33 Report No.: CTL2205193061-WF01

Results of Band Edges Test (Radiated)

Note: All modulations have been tested, only worse case GFSK is reported.

Fred	quency(MH	lz):	2402		Polarity:			HORIZONTAL		
Frequency	Emission		Limit	Margin	Raw	Antenna	Cable	Pre-	Correction	
(MHz)	Le	vel	(dBuV/m)	(dB)	Value	Factor	Factor	amplifier	Factor	
	(dBu	V/m)			(dBuV)	(dB/m)	(dB)	(dB)	(dB/m)	
2402.00	95.51	PK		4	62.12	28.78	4.61	0.00	33.39	
2402.00	91.64	AV		-	58.25	28.78	4.61	0.00	33.39	
2377.00	47.31	PK	74.00	26.69	14.23	28.52	4.56	0.00	33.08	
2377.00		AV	54.00	-			-	-		
2390.00	58.27	PK	74.00	15.73	24.95	28.72	4.60	0.00	33.32	
2390.00	50.78	AV	54.00	3.22	17. 4 6	28.72	4.60	0.00	33.32	
2400.00		PK	54.00	-						
2400.00		AV	54.00	-			-			

Fred	Frequency(MHz): 2402			02	Polarity:				VERTICAL		
Frequency	Emission		Limit	Margin	Raw	Antenna	Cable	Pre-	Correction		
(MHz)	Le	vel	(dBuV/m)	(dB)	Value	Factor	Factor	amplifier	Factor		
	(dBu	V/m)			(dBuV)	(dB/m)	(dB)	(dB)	(dB/m)		
2402.00	96.32	PK		1	62.93	28.78	4.61	0.00	33.39		
2402.00	92.86	AV		1	59.47	28.78	4.61	0.00	33.39		
2352.00	46.77	PK	74.00	27.23	13.69	28.52	4.56	0.00	33.08		
2352.00	-	AV	54.00								
2390.00	59.32	PK	74.00	14.68	26	28.72	4.60	0.00	33.32		
2390.00	51.93	AV	54.00	2.07	18.61	28.72	4.60	0.00	33.32		
2400.00		PK	54.00	-							
2400.00	-	AV	54.00								

Fred	Frequency(MHz):		2480		Polarity:			HORIZONTAL		
Frequency	Emission		Limit	Margin	Raw	Antenna	Cable	Pre-	Correction	
(MHz)	Le	vel	(dBuV/m)	(dB)	Value	Factor	Factor	amplifier	Factor	
	(dBu	V/m)			(dBuV)	(dB/m)	(dB)	(dB)	(dB/m)	
2480.00	97.26	PK		-	63.64	28.92	4.70	0.00	33.62	
2480.00	93.63	AV		-	60.01	28.92	4.70	0.00	33.62	
2483.50	50.84	PK	74.00	23.16	17.21	28.93	4.70	0.00	33.63	
2483.50		AV	54.00	-						
2487.00	58.71	PK	74.00	15.29	25.05	28.95	4.71	0.00	33.66	
2487.00	49.22	AV	54.00	4.78	15.56	28.95	4.71	0.00	33.66	
2500.00	47.53	PK	74.00	26.47	13.85	28.96	4.72	0.00	33.68	
2500.00		AV	54.00							

Fred	quency(MF	lz):	2480		Polarity:			VERTICAL	
Frequency	Emission		Limit	Margin	Raw	Antenna	Cable	Pre-	Correction
(MHz)	Le	vel	(dBuV/m)	(dB)	Value	Factor	Factor	amplifier	Factor
	(dBu	V/m)			(dBuV)	(dB/m)	(dB)	(dB)	(dB/m)
2480.00	98.14	PK			64.52	28.92	4.70	0.00	33.62
2480.00	94.85	AV		-	61.23	28.92	4.70	0.00	33.62
2483.50	51.62	PK	74.00	22.38	17.99	28.93	4.70	0.00	33.63
2483.50		AV	54.00	1			-		
2492.00	58.36	PK	74.00	15.64	24.7	28.95	4.71	0.00	33.66
2492.00	51.75	AV	54.00	2.25	18.09	28.95	4.71	0.00	33.66
2500.00	49.62	PK	74.00	24.38	15.94	28.96	4.72	0.00	33.68
2500.00		AV	54.00	1	_	-	-		

REMARKS:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- 3. Margin value = Limit value- Emission level.
- 4. -- Mean the PK detector measured value is below average limit.
- 5. RBW 1MHz VBW 3MHz Peak detector is for PK value; RBW 1MHz VBW 10Hz Peak detector is for AV value.
- 6. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector is for PK Value; RMS detector is for AV value.
- 7. Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded in report.

V1.0 Page 21 of 33 Report No.: CTL2205193061-WF01

3.3. Maximum Peak Output Power

Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

Test Configuration



Test Results

Raw data reference to Section 2 from Appendix.

V1.0 Page 22 of 33 Report No.: CTL2205193061-WF01

3.4. 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

Raw data reference to Section 1 from Appendix.

V1.0 Page 23 of 33 Report No.: CTL2205193061-WF01

3.5. Frequency Separation

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

Raw data reference to Section 3 from Appendix.

V1.0 Page 24 of 33 Report No.: CTL2205193061-WF01

3.6. Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

Test Configuration



Test Results

Raw data reference to Section 4 from Appendix.

V1.0 Page 25 of 33 Report No.: CTL2205193061-WF01

3.7. Time of Occupancy (Dwell Time)

Limit

The average time of occupancy on any channel shall not be greater than 400 milliseconds within a period of 400 milliseconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 910KHz RBW and 910KHz VBW, Span 0Hz.

Test Configuration



Test Results

Raw data reference to Section 5 from Appendix.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF con-ducted or a radiated measurement, pro-vided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter com-plies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Report No.: CTL2205193061-WF01

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration



Test Results

Raw data reference to Section 6 from Appendix.

Report No.: CTL2205193061-WF01

3.9. Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

3.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The maximum gain of antenna was 0.4dBi



Report No.: CTL2205193061-WF01

4. Test Setup Photos of the EUT









5. Photos of the EUT


External Photos of EUT
















V1.0 Page 32 of 33 Report No.: CTL2205193061-WF01


Internal Photos of EUT






BT Antenna

BLE Antenna



V1.0 Page 33 of 33 Report No.: CTL2205193061-WF01



******************** End of Report *************