













NVNT_MIMO_TX_802_11n(HT20)_Power_Spectral_Density_5700**NVNT_MIMO_TX_802_11ac(VHT20)_Power_Spectral_Density_5500**

NVNT_MIMO_TX_802_11ac(VHT20)_Power_Spectral_Density_5600**NVNT_MIMO_TX_802_11ac(VHT20)_Power_Spectral_Density_5700**


NVNT_MIMO_TX_802_11n(HT40)_Power_Spectral_Density_5510**NVNT_MIMO_TX_802_11n(HT40)_Power_Spectral_Density_5590**

NVNT_MIMO_TX_802_11n(HT40)_Power_Spectral_Density_5670**NVNT_MIMO_TX_802_11ac(VHT40)_Power_Spectral_Density_5510**


NVNT_MIMO_TX_802_11ac(VHT40)_Power_Spectral_Density_5590**NVNT_MIMO_TX_802_11ac(VHT40)_Power_Spectral_Density_5670**



NVNT_MIMO_TX_802_11ac(VHT80) Power Spectral Density 5530**NVNT_MIMO_TX_802_11ac(VHT80) Power Spectral Density 5610**



NVNT_MIMO_TX_802_11ax(HE20)_Power_Spectral_Density_5500





NVNT_MIMO_TX_802_11ax(HE20)_Power_Spectral_Density_5600




NVNT_MIMO_TX_802_11ax(HE20)_Power_Spectral_Density_5700**NVNT_MIMO_TX_802_11ax(HE40)_Power_Spectral_Density_5510**


NVNT_MIMO_TX_802_11ax(HE40)_Power_Spectral_Density_5590**NVNT_MIMO_TX_802_11ax(HE40)_Power_Spectral_Density_5670**

NVNT_MIMO_TX_802_11ax(HE80)_Power_Spectral_Density_5530**NVNT_MIMO_TX_802_11ax(HE80)_Power_Spectral_Density_5610**

NVNT_MIMO_TX_802_11ac(VHT160)_Power_Spectral_Density_5570




NVNT_MIMO_TX_802_11ax(HE160)_Power_Spectral_Density_5570




Band 4 (5725 – 5850 MHz)

Condition	Antenna	Modulation	Frequency (MHz)	PSD_SA(dBm/RBW)	Duty factor(dB)	RB factor(dB)	PSD(dBm/500kHz)	limit(dBm/500kHz)	Result
NVNT	ANT1	802.11a	5745.00	-4.51	0.09	-0	-4.51	30	Pass
NVNT	ANT2	802.11a	5745.00	-4.85	0.09	-0	-4.85	30	Pass
NVNT	ANT1	802.11a	5785.00	-5.20	0.12	-0	-5.17	30	Pass
NVNT	ANT2	802.11a	5785.00	-4.76	0.12	-0	-4.72	30	Pass
NVNT	ANT1	802.11a	5825.00	-5.46	0.12	-0	-5.43	30	Pass
NVNT	ANT2	802.11a	5825.00	-6.40	0.12	-0	-6.36	30	Pass
NVNT	ANT1	802.11n(HT20)	5745.00	-4.34	0.12	-0	-4.31	30	Pass
NVNT	ANT2	802.11n(HT20)	5745.00	-4.50	0.12	-0	-4.47	30	Pass
NVNT	ANT1	802.11n(HT20)	5785.00	-5.05	0.12	-0	-5.01	30	Pass
NVNT	ANT2	802.11n(HT20)	5785.00	-5.14	0.09	-0	-5.13	30	Pass
NVNT	ANT1	802.11n(HT20)	5825.00	-5.04	0.12	-0	-5.01	30	Pass
NVNT	ANT2	802.11n(HT20)	5825.00	-5.85	0.12	-0	-5.82	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5745.00	-4.30	0.12	-0	-4.26	30	Pass
NVNT	ANT2	802.11ac(VHT20)	5745.00	-5.02	0.12	-0	-4.98	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5785.00	-5.01	0.12	-0	-4.98	30	Pass
NVNT	ANT2	802.11ac(VHT20)	5785.00	-4.70	0.12	-0	-4.66	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5825.00	-4.89	0.12	-0	-4.86	30	Pass
NVNT	ANT2	802.11ac(VHT20)	5825.00	-5.33	0.09	-0	-5.33	30	Pass
NVNT	ANT1	802.11ax(HE20)	5745.00	-3.93	0.12	-0	-3.90	30	Pass
NVNT	ANT2	802.11ax(HE20)	5745.00	-4.53	0.12	-0	-4.50	30	Pass
NVNT	ANT1	802.11ax(HE20)	5785.00	-4.76	0.12	-0	-4.73	30	Pass
NVNT	ANT2	802.11ax(HE20)	5785.00	-4.37	0.12	-0	-4.34	30	Pass
NVNT	ANT1	802.11ax(HE20)	5825.00	-5.33	0.12	-0	-5.30	30	Pass
NVNT	ANT2	802.11ax(HE20)	5825.00	-5.91	0.12	-0	-5.88	30	Pass
NVNT	ANT1	802.11n(HT40)	5755.00	-7.33	0.12	-0	-7.29	30	Pass
NVNT	ANT2	802.11n(HT40)	5755.00	-8.19	0.12	-0	-8.16	30	Pass
NVNT	ANT1	802.11n(HT40)	5795.00	-7.59	0.12	-0	-7.55	30	Pass
NVNT	ANT2	802.11n(HT40)	5795.00	-3.77	0.12	-0	-3.74	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5755.00	-6.69	0.00	-0	-6.77	30	Pass
NVNT	ANT2	802.11ac(VHT40)	5755.00	-4.83	0.12	-0	-4.80	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5795.00	-7.47	0.12	-0	-7.44	30	Pass
NVNT	ANT2	802.11ac(VHT40)	5795.00	-6.05	0.00	-0	-6.14	30	Pass
NVNT	ANT1	802.11ax(HE40)	5755.00	-6.74	0.12	-0	-6.70	30	Pass
NVNT	ANT2	802.11ax(HE40)	5755.00	-5.11	0.00	-0	-5.20	30	Pass
NVNT	ANT1	802.11ax(HE40)	5795.00	-7.47	0.12	-0	-7.44	30	Pass
NVNT	ANT2	802.11ax(HE40)	5795.00	-5.75	0.00	-0	-5.84	30	Pass
NVNT	ANT1	802.11ac(VHT80)	5775.00	-9.04	0.00	-0	-9.12	30	Pass
NVNT	ANT2	802.11ac(VHT80)	5775.00	-8.98	0.00	-0	-9.07	30	Pass
NVNT	ANT1	802.11ax(HE80)	5775.00	-9.56	0.12	-0	-9.53	30	Pass
NVNT	ANT2	802.11ax(HE80)	5775.00	-9.18	0.12	-0	-9.15	30	Pass


Power Spectral Density NVNT_ANT1_802_11a_5745




Power Spectral Density NVNT_ANT2_802_11a_5745




Power Spectral Density NVNT_ANT1_802_11a_5785




Power Spectral Density NVNT_ANT2_802_11a_5785




Power Spectral Density NVNT_ANT1_802_11a_5825




Power Spectral Density NVNT_ANT2_802_11a_5825




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5745




Power Spectral Density NVNT_ANT2_802_11n(HT20)_5745




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5785



Power Spectral Density NVNT_ANT2_802_11n(HT20)_5785




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5825




Power Spectral Density NVNT_ANT2_802_11n(HT20)_5825




Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5745




Power Spectral Density NVNT_ANT2_802_11ac(VHT20)_5745




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5785




Power Spectral Density_NVNT_ANT2_802_11ac(VHT20)_5785




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5825




Power Spectral Density_NVNT_ANT2_802_11ac(VHT20)_5825




Power Spectral Density NVNT_ANT1_802_11ax(HE20)_5745




Power Spectral Density NVNT_ANT2_802_11ax(HE20)_5745




Power Spectral Density NVNT_ANT1_802_11ax(HE20)_5785




Power Spectral Density NVNT_ANT2_802_11ax(HE20)_5785




Power Spectral Density NVNT_ANT1_802_11ax(HE20)_5825




Power Spectral Density NVNT_ANT2_802_11ax(HE20)_5825




Power Spectral Density NVNT_ANT1_802_11n(HT40)_5755




Power Spectral Density NVNT_ANT2_802_11n(HT40)_5755




Power Spectral Density NVNT_ANT1_802_11n(HT40)_5795




Power Spectral Density NVNT_ANT2_802_11n(HT40)_5795




Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5755




Power Spectral Density NVNT_ANT2_802_11ac(VHT40)_5755




Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5795




Power Spectral Density NVNT_ANT2_802_11ac(VHT40)_5795




Power Spectral Density NVNT_ANT1_802_11ax(HE40)_5755




Power Spectral Density NVNT_ANT2_802_11ax(HE40)_5755




Power Spectral Density NVNT_ANT1_802_11ax(HE40)_5795




Power Spectral Density NVNT_ANT2_802_11ax(HE40)_5795




Power Spectral Density NVNT_ANT1_802_11ac(VHT80)_5775




Power Spectral Density NVNT_ANT2_802_11ac(VHT80)_5775



Power Spectral Density NVNT_ANT1_802_11ax(HE80)_5775





Power Spectral Density NVNT_ANT2_802_11ax(HE80)_5775







Condition	Antenna	Mode	Frequency (MHz)	MIMO PSD(dBm/500kHz)	Limit(dBm/500kHz)	Result
NVNT	MIMO_TX	802.11n(HT20)	5745.00	-2.01	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	5785.00	-2.49	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	5825.00	-2.91	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5745.00	-2.04	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5785.00	-2.11	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5825.00	-2.53	30	Pass
NVNT	MIMO_TX	802.11ax(HE20)	5745.00	-1.62	30	Pass
NVNT	MIMO_TX	802.11ax(HE20)	5785.00	-1.97	30	Pass
NVNT	MIMO_TX	802.11ax(HE20)	5825.00	-2.77	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	5755.00	-5.21	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	5795.00	-2.55	30	Pass
NVNT	MIMO_TX	802.11ac(VHT40)	5755.00	-3.06	30	Pass
NVNT	MIMO_TX	802.11ac(VHT40)	5795.00	-4.24	30	Pass
NVNT	MIMO_TX	802.11ax(HE40)	5755.00	-3.74	30	Pass
NVNT	MIMO_TX	802.11ax(HE40)	5795.00	-4.14	30	Pass
NVNT	MIMO_TX	802.11ac(VHT80)	5775.00	-6.33	30	Pass
NVNT	MIMO_TX	802.11ax(HE80)	5775.00	-6.62	30	Pass

NVNT_MIMO_TX_802_11n(HT20)_Power Spectral Density 5745




NVNT_MIMO_TX_802_11n(HT20)_Power_Spectral_Density_5785**NVNT_MIMO_TX_802_11n(HT20)_Power_Spectral_Density_5825**


NVNT_MIMO_TX_802_11ac(VHT20) Power Spectral Density 5745**NVNT_MIMO_TX_802_11ac(VHT20) Power Spectral Density 5785**

NVNT_MIMO_TX_802_11ac(VHT20) Power Spectral Density 5825**NVNT_MIMO_TX_802_11ax(HE20) Power Spectral Density 5745**


NVNT_MIMO_TX_802_11ax(HE20)_Power_Spectral_Density_5785




NVNT_MIMO_TX_802_11ax(HE20)_Power_Spectral_Density_5825




NVNT_MIMO_TX_802_11n(HT40)_Power_Spectral_Density_5755



NVNT_MIMO_TX_802_11n(HT40)_Power_Spectral_Density_5795




NVNT_MIMO_TX_802_11ac(VHT40) Power Spectral Density 5755




NVNT_MIMO_TX_802_11ac(VHT40) Power Spectral Density 5795




NVNT_MIMO_TX_802_11ax(HE40)_Power_Spectral_Density_5755




NVNT_MIMO_TX_802_11ax(HE40)_Power_Spectral_Density_5795



NVNT_MIMO_TX_802_11ac(VHT80) Power Spectral Density 5775



NVNT_MIMO_TX_802_11ax(HE80) Power Spectral Density 5775



4.6 Band Edge

Test Requirement:	FCC Part15 E Section 15.407 and 15.205, RSS-Gen §8.9																								
Test Method:	ANSI C63.10:2013																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>AV</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	AV	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	AV	1MHz	3MHz	Average Value																					
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>68.2</td><td>Peak Value</td></tr></table> Undesirable emission limits: (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band. (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	68.2	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	68.2	Peak Value																							
Test Procedure:	a. The EUT was placed on the top of a rotating table 1.5 m above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.																								
Test setup:	Above 1GHz																								

Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remark:

According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:

$E[dBuV/m] = EIRP[dBm] + 95.2,$

For example, if $EIRP = -27dBm$

$E[dBuV/m] = -27 + 95.2 = 68.2dBuV/m.$

Measurement Data:**Band1**

Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.45	-13.16	43.29	68.20	-24.91	PK
V	5150.00	57.38	-13.16	44.22	68.20	-23.98	PK
Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.91	-13.16	33.75	54.00	-20.25	AV
V	5150.00	49.25	-13.16	36.09	54.00	-17.91	AV
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	57.46	-12.62	44.84	68.20	-23.36	PK
V	5350.00	56.15	-12.62	43.53	68.20	-24.67	PK
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.34	-12.62	33.72	54.00	-20.28	AV
V	5350.00	46.22	-12.62	33.60	54.00	-20.40	AV

Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.95	-13.16	41.79	68.20	-26.41	PK
V	5150.00	55.08	-13.16	41.92	68.20	-26.28	PK
Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.32	-13.16	34.16	54.00	-19.84	AV
V	5150.00	47.12	-13.16	33.96	54.00	-20.04	AV
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.21	-12.62	43.59	68.20	-24.61	PK
V	5350.00	60.65	-12.62	48.03	68.20	-20.17	PK
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.30	-12.62	32.68	54.00	-21.32	AV
V	5350.00	50.25	-12.62	37.63	54.00	-16.37	AV

Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	53.89	-13.16	40.73	68.20	-27.47	PK
V	5150.00	57.68	-13.16	44.52	68.20	-23.68	PK
Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.65	-13.16	32.49	54.00	-21.51	AV
V	5150.00	46.73	-13.16	33.57	54.00	-20.43	AV
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.58	-12.62	43.96	68.20	-24.24	PK
V	5350.00	54.80	-12.62	42.18	68.20	-26.02	PK
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.70	-12.62	35.08	54.00	-18.92	AV
V	5350.00	45.57	-12.62	32.95	54.00	-21.05	AV

Mode:		802.11ax(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.21	-13.16	43.05	68.20	-25.15	PK
V	5150.00	58.06	-13.16	44.90	68.20	-23.30	PK
Mode:		802.11ax(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.67	-13.16	34.51	54.00	-19.49	AV
V	5150.00	47.50	-13.16	34.34	54.00	-19.66	AV
Mode:		802.11ax(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.60	-12.62	42.98	68.20	-25.22	PK
V	5350.00	59.04	-12.62	46.42	68.20	-21.78	PK
Mode:		802.11ax(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.35	-12.62	33.73	54.00	-20.27	AV
V	5350.00	48.35	-12.62	35.73	54.00	-18.27	AV

Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	53.89	-13.16	40.73	68.20	-27.47	PK
V	5150.00	57.68	-13.16	44.52	68.20	-23.68	PK
Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.65	-13.16	32.49	54.00	-21.51	AV
V	5150.00	46.73	-13.16	33.57	54.00	-20.43	AV
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.58	-12.62	43.96	68.20	-24.24	PK
V	5350.00	54.80	-12.62	42.18	68.20	-26.02	PK
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.70	-12.62	35.08	54.00	-18.92	AV
V	5350.00	45.57	-12.62	32.95	54.00	-21.05	AV

Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.21	-13.16	43.05	68.20	-25.15	PK
V	5150.00	58.06	-13.16	44.90	68.20	-23.30	PK
Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.67	-13.16	34.51	54.00	-19.49	AV
V	5150.00	47.50	-13.16	34.34	54.00	-19.66	AV
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.60	-12.62	42.98	68.20	-25.22	PK
V	5350.00	59.04	-12.62	46.42	68.20	-21.78	PK
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.35	-12.62	33.73	54.00	-20.27	AV
V	5350.00	48.35	-12.62	35.73	54.00	-18.27	AV

Mode:		802.11ax(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	53.89	-13.16	40.73	68.20	-27.47	PK
V	5150.00	57.68	-13.16	44.52	68.20	-23.68	PK
Mode:		802.11ax(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.65	-13.16	32.49	54.00	-21.51	AV
V	5150.00	46.73	-13.16	33.57	54.00	-20.43	AV
Mode:		802.11ax(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.58	-12.62	43.96	68.20	-24.24	PK
V	5350.00	54.80	-12.62	42.18	68.20	-26.02	PK
Mode:		802.11ax(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.70	-12.62	35.08	54.00	-18.92	AV
V	5350.00	45.57	-12.62	32.95	54.00	-21.05	AV

Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.21	-13.16	43.05	68.20	-25.15	PK
V	5150.00	58.06	-13.16	44.90	68.20	-23.30	PK
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.67	-13.16	34.51	54.00	-19.49	AV
V	5150.00	47.50	-13.16	34.34	54.00	-19.66	AV
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.60	-12.62	42.98	68.20	-25.22	PK
V	5350.00	59.04	-12.62	46.42	68.20	-21.78	PK
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.35	-12.62	33.73	54.00	-20.27	AV
V	5350.00	48.35	-12.62	35.73	54.00	-18.27	AV

Mode:		802.11ax(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	57.18	-13.16	44.02	68.20	-24.18	PK
V	5150.00	58.53	-13.16	45.37	68.20	-22.83	PK
Mode:		802.11ax(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.64	-13.16	31.48	54.00	-22.52	AV
V	5150.00	46.46	-13.16	33.30	54.00	-20.70	AV
Mode:		802.11ax(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.13	-12.62	41.51	68.20	-26.69	PK
V	5350.00	56.29	-12.62	43.67	68.20	-24.53	PK
Mode:		802.11ax(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.39	-12.62	31.77	54.00	-22.23	AV
V	5350.00	49.11	-12.62	36.49	54.00	-17.51	AV

Band2

Mode:		802.11a		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.81	-13.16	43.65	68.20	-24.55	PK
V	5150.00	55.97	-13.16	42.81	68.20	-25.39	PK
Mode:		802.11a		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.16	-13.16	32.00	54.00	-22.00	AV
V	5150.00	47.08	-13.16	33.92	54.00	-20.08	AV
Mode:		802.11a		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	57.35	-12.62	44.73	68.20	-23.47	PK
V	5350.00	58.34	-12.62	45.72	68.20	-22.48	PK
Mode:		802.11a		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.58	-12.62	33.96	54.00	-20.04	AV
V	5350.00	46.56	-12.62	33.94	54.00	-20.06	AV

Mode:		802.11n(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	57.57	-13.16	44.41	68.20	-23.79	PK
V	5150.00	56.41	-13.16	43.25	68.20	-24.95	PK
Mode:		802.11n(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.87	-13.16	34.71	54.00	-19.29	AV
V	5150.00	48.41	-13.16	35.25	54.00	-18.75	AV
Mode:		802.11n(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	57.19	-12.62	44.57	68.20	-23.63	PK
V	5350.00	56.74	-12.62	44.12	68.20	-24.08	PK
Mode:		802.11n(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.07	-12.62	34.45	54.00	-19.55	AV
V	5350.00	46.57	-12.62	33.95	54.00	-20.05	AV

Mode:		802.11ac(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.41	-13.16	41.25	68.20	-26.95	PK
V	5150.00	55.00	-13.16	41.84	68.20	-26.36	PK
Mode:		802.11ac(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.28	-13.16	31.12	54.00	-22.88	AV
V	5150.00	46.64	-13.16	33.48	54.00	-20.52	AV
Mode:		802.11ac(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.84	-12.62	42.22	68.20	-25.98	PK
V	5350.00	56.37	-12.62	43.75	68.20	-24.45	PK
Mode:		802.11ac(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.86	-12.62	32.24	54.00	-21.76	AV
V	5350.00	46.83	-12.62	34.21	54.00	-19.79	AV

Mode:		802.11ax20		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBUV)	Factor (dB/m)	Measure Level (dBUV/m)	Limit (dBUV/m)	Over limit(dB)	Detector
H	5150.00	56.76	-13.16	43.60	68.20	-24.60	PK
V	5150.00	55.08	-13.16	41.92	68.20	-26.28	PK
Mode:		802.11ax20		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBUV)	Factor (dB/m)	Measure Level (dBUV/m)	Limit (dBUV/m)	Over limit(dB)	Detector
H	5150.00	47.56	-13.16	34.40	54.00	-19.60	AV
V	5150.00	47.32	-13.16	34.16	54.00	-19.84	AV
Mode:		802.11ax20		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBUV)	Factor (dB/m)	Measure Level (dBUV/m)	Limit (dBUV/m)	Over limit(dB)	Detector
H	5350.00	55.18	-12.62	42.56	68.20	-25.64	PK
V	5350.00	58.42	-12.62	45.80	68.20	-22.40	PK
Mode:		802.11ax20		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBUV)	Factor (dB/m)	Measure Level (dBUV/m)	Limit (dBUV/m)	Over limit(dB)	Detector
H	5350.00	47.85	-12.62	35.23	54.00	-18.77	AV
V	5350.00	46.63	-12.62	34.01	54.00	-19.99	AV

Mode:		802.11n(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.30	-13.16	42.14	68.20	-26.06	PK
V	5150.00	58.35	-13.16	45.19	68.20	-23.01	PK
Mode:		802.11n(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.26	-13.16	31.10	54.00	-22.90	AV
V	5150.00	46.20	-13.16	33.04	54.00	-20.96	AV
Mode:		802.11n(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	53.69	-12.62	41.07	68.20	-27.13	PK
V	5350.00	57.56	-12.62	44.94	68.20	-23.26	PK
Mode:		802.11n(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.72	-12.62	35.10	54.00	-18.90	AV
V	5350.00	47.98	-12.62	35.36	54.00	-18.64	AV

Mode:		802.11ac(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.98	-13.16	43.82	68.20	-24.38	PK
V	5150.00	55.81	-13.16	42.65	68.20	-25.55	PK
Mode:		802.11ac(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.04	-13.16	31.88	54.00	-22.12	AV
V	5150.00	47.75	-13.16	34.59	54.00	-19.41	AV
Mode:		802.11ac(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.97	-12.62	42.35	68.20	-25.85	PK
V	5350.00	59.55	-12.62	46.93	68.20	-21.27	PK
Mode:		802.11ac(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.45	-12.62	31.83	54.00	-22.17	AV
V	5350.00	50.32	-12.62	37.70	54.00	-16.30	AV

Mode:		802.11ax40		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.64	-13.16	42.48	68.20	-25.72	PK
V	5150.00	58.20	-13.16	45.04	68.20	-23.16	PK
Mode:		802.11ax40		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.87	-13.16	32.71	54.00	-21.29	AV
V	5150.00	45.92	-13.16	32.76	54.00	-21.24	AV
Mode:		802.11ax40		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.59	-12.62	42.97	68.20	-25.23	PK
V	5350.00	58.47	-12.62	45.85	68.20	-22.35	PK
Mode:		802.11ax40		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.62	-12.62	33.00	54.00	-21.00	AV
V	5350.00	46.87	-12.62	34.25	54.00	-19.75	AV

Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.79	-13.16	42.63	68.20	-25.57	PK
V	5150.00	54.76	-13.16	41.60	68.20	-26.60	PK
Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.46	-13.16	34.30	54.00	-19.70	AV
V	5150.00	48.06	-13.16	34.90	54.00	-19.10	AV
Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.68	-12.62	44.06	68.20	-24.14	PK
V	5350.00	58.17	-12.62	45.55	68.20	-22.65	PK
Mode:		802.11ac(HT80)		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.38	-12.62	33.76	54.00	-20.24	AV
V	5350.00	46.73	-12.62	34.11	54.00	-19.89	AV

Mode:		802.11ax80		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.62	-13.16	42.46	68.20	-25.74	PK
V	5150.00	57.97	-13.16	44.81	68.20	-23.39	PK
Mode:		802.11ax80		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.32	-13.16	31.16	54.00	-22.84	AV
V	5150.00	47.77	-13.16	34.61	54.00	-19.39	AV
Mode:		802.11ax80		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.39	-12.62	43.77	68.20	-24.43	PK
V	5350.00	58.42	-12.62	45.80	68.20	-22.40	PK
Mode:		802.11ax80		Frequency:		5290MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.59	-12.62	33.97	54.00	-20.03	AV
V	5350.00	46.12	-12.62	33.50	54.00	-20.50	AV

Band3

Mode:		802.11a		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	56.95	-12.29	44.66	68.20	-23.54	PK
V	5470.00	56.31	-12.29	44.02	68.20	-24.18	PK
Mode:		802.11a		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	47.76	-12.29	35.47	54.00	-18.53	AV
V	5470.00	46.29	-12.29	34.00	54.00	-20.00	AV
Mode:		802.11a		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	55.38	-11.60	43.78	68.20	-24.42	PK
V	5725.00	58.11	-11.60	46.51	68.20	-21.69	PK
Mode:		802.11a		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	46.74	-11.60	35.14	54.00	-18.86	AV
V	5725.00	46.17	-11.60	34.57	54.00	-19.43	AV

Mode:		802.11n(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	54.62	-12.29	42.33	68.20	-25.87	PK
V	5470.00	55.91	-12.29	43.62	68.20	-24.58	PK
Mode:		802.11n(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	44.29	-12.29	32.00	54.00	-22.00	AV
V	5470.00	45.68	-12.29	33.39	54.00	-20.61	AV
Mode:		802.11n(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	53.81	-11.60	42.21	68.20	-25.99	PK
V	5725.00	60.63	-11.60	49.03	68.20	-19.17	PK
Mode:		802.11n(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	46.05	-11.60	34.45	54.00	-19.55	AV
V	5725.00	49.78	-11.60	38.18	54.00	-15.82	AV

Mode:		802.11ac(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	54.63	-12.29	42.34	68.20	-25.86	PK
V	5470.00	57.11	-12.29	44.82	68.20	-23.38	PK
Mode:		802.11ac(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	47.84	-12.29	35.55	54.00	-18.45	AV
V	5470.00	47.81	-12.29	35.52	54.00	-18.48	AV
Mode:		802.11ac(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	54.74	-11.60	43.14	68.20	-25.06	PK
V	5725.00	56.29	-11.60	44.69	68.20	-23.51	PK
Mode:		802.11ac(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	44.52	-11.60	32.92	54.00	-21.08	AV
V	5725.00	45.45	-11.60	33.85	54.00	-20.15	AV

Mode:		802.11ax20		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	57.09	-12.29	44.80	68.20	-23.40	PK
V	5470.00	55.98	-12.29	43.69	68.20	-24.51	PK
Mode:		802.11ax20		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	45.82	-12.29	33.53	54.00	-20.47	AV
V	5470.00	48.47	-12.29	36.18	54.00	-17.82	AV
Mode:		802.11ax20		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	56.43	-11.60	44.83	68.20	-23.37	PK
V	5725.00	58.08	-11.60	46.48	68.20	-21.72	PK
Mode:		802.11ax20		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	47.44	-11.60	35.84	54.00	-18.16	AV
V	5725.00	48.56	-11.60	36.96	54.00	-17.04	AV

Mode:		802.11n(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	55.26	-12.29	42.97	68.20	-25.23	PK
V	5470.00	57.85	-12.29	45.56	68.20	-22.64	PK
Mode:		802.11n(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	45.48	-12.29	33.19	54.00	-20.81	AV
V	5470.00	45.52	-12.29	33.23	54.00	-20.77	AV
Mode:		802.11n(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	57.22	-11.60	45.62	68.20	-22.58	PK
V	5725.00	55.03	-11.60	43.43	68.20	-24.77	PK
Mode:		802.11n(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	44.71	-11.60	33.11	54.00	-20.89	AV
V	5725.00	48.27	-11.60	36.67	54.00	-17.33	AV


Mode:		802.11ac(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	56.56	-12.29	44.27	68.20	-23.93	PK
V	5470.00	57.86	-12.29	45.57	68.20	-22.63	PK
Mode:		802.11ac(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	45.30	-12.29	33.01	54.00	-20.99	AV
V	5470.00	47.64	-12.29	35.35	54.00	-18.65	AV
Mode:		802.11ac(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	54.32	-11.60	42.72	68.20	-25.48	PK
V	5725.00	57.99	-11.60	46.39	68.20	-21.81	PK
Mode:		802.11ac(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	45.31	-11.60	33.71	54.00	-20.29	AV
V	5725.00	46.53	-11.60	34.93	54.00	-19.07	AV

Mode:		802.11ax40		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	54.66	-12.29	42.37	68.20	-25.83	PK
V	5470.00	57.41	-12.29	45.12	68.20	-23.08	PK
Mode:		802.11ax40		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	46.53	-12.29	34.24	54.00	-19.76	AV
V	5470.00	45.34	-12.29	33.05	54.00	-20.95	AV
Mode:		802.11ax40		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	56.24	-11.60	44.64	68.20	-23.56	PK
V	5725.00	54.76	-11.60	43.16	68.20	-25.04	PK
Mode:		802.11ax40		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	46.27	-11.60	34.67	54.00	-19.33	AV
V	5725.00	47.99	-11.60	36.39	54.00	-17.61	AV


Mode:		802.11ac(HT80)		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	55.65	-12.29	43.36	68.20	-24.84	PK
V	5470.00	58.04	-12.29	45.75	68.20	-22.45	PK
Mode:		802.11ac(HT80)		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	47.43	-12.29	35.14	54.00	-18.86	AV
V	5470.00	47.53	-12.29	35.24	54.00	-18.76	AV
Mode:		802.11ac(HT80)		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	53.82	-11.60	42.22	68.20	-25.98	PK
V	5725.00	60.66	-11.60	49.06	68.20	-19.14	PK
Mode:		802.11ac(HT80)		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	44.80	-11.60	33.20	54.00	-20.80	AV
V	5725.00	48.81	-11.60	37.21	54.00	-16.79	AV

Mode:		802.11ax80		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)		
H	5470.00	54.04	-12.29	41.75	68.20	-26.45	PK
V	5470.00	58.47	-12.29	46.18	68.20	-22.02	PK
Mode:		802.11ax80		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)		
H	5470.00	44.72	-12.29	32.43	54.00	-21.57	AV
V	5470.00	45.37	-12.29	33.08	54.00	-20.92	AV
Mode:		802.11ax80		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)		
H	5725.00	54.16	-11.60	42.56	68.20	-25.64	PK
V	5725.00	55.81	-11.60	44.21	68.20	-23.99	PK
Mode:		802.11ax80		Frequency:		5530MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)		
H	5725.00	45.12	-11.60	33.52	54.00	-20.48	AV
V	5725.00	48.62	-11.60	37.02	54.00	-16.98	AV


Band4




Bandedge_NVNT_ANT1_802_11a_5825




Bandedge_NVNT_ANT2_802_11a_5825




Bandedge_NVNT_ANT1_802_11n(HT20)_5745




Bandedge_NVNT_ANT2_802_11n(HT20)_5745







Bandedge_NVNT_ANT1_802_11ac(VHT20)_5745




Bandedge_NVNT_ANT2_802_11ac(VHT20)_5745




Bandedge_NVNT_ANT1_802_11ac(VHT20)_5825




Bandedge_NVNT_ANT2_802_11ac(VHT20)_5825




Bandedge_NVNT_ANT1_802_11ax(HE20)_5745




Bandedge_NVNT_ANT2_802_11ax(HE20)_5745




Bandedge_NVNT_ANT1_802_11ax(HE20)_5825




Bandedge_NVNT_ANT2_802_11ax(HE20)_5825




Bandedge_NVNT_ANT1_802_11n(HT40)_5755




Bandedge_NVNT_ANT2_802_11n(HT40)_5755




Bandedge_NVNT_ANT1_802_11n(HT40)_5795




Bandedge_NVNT_ANT2_802_11n(HT40)_5795




Bandedge_NVNT_ANT1_802_11ac(VHT40)_5755



Bandedge_NVNT_ANT2_802_11ac(VHT40)_5755



Bandedge_NVNT_ANT1_802_11ac(VHT40)_5795



Bandedge_NVNT_ANT2_802_11ac(VHT40)_5795

