




Data rate: MCS11




Channel frequency:5180MHz@Chain1




Channel frequency:5240MHz@Chain1




Channel frequency:5320MHz@Chain1




Channel frequency:5500MHz@Chain1




Channel frequency:5600MHz@Chain1




Channel frequency:5700MHz@Chain1




Channel frequency:5745MHz@Chain1




Channel frequency:5825MHz@Chain1




Channel frequency:5180MHz@Chain2




Channel frequency:5240MHz@Chain2




Channel frequency:5320MHz@Chain2




Channel frequency:5500MHz@Chain2




Channel frequency:5600MHz@Chain2



Channel frequency:5700MHz@Chain2



Channel frequency:5745MHz@Chain2



Channel frequency:5825MHz@Chain2

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 53 von 129
Page 53 of 129


Modulation: 802.11ax-mode HE40MHz

Data Rate (Mbps)	Band	Channel Frequency (MHz)	Measured Average Power (dBm) Chain 1	Measured Average Power (dBm) Chain 2	Final Average output power (dBm)	Power Limit (dBm)
MCS0	UNII 1	5190	8.03	6.72	10.43	24
		5230	7.76	6.98	10.40	24
	UNII 2a	5270	9.46	8.98	12.24	24
		5510	7.72	7.01	10.39	24
	UNII 2c	5590	7.44	6.69	10.09	24
		5670	7.66	7.16	10.43	24
	UNII 3	5755	14.3	14.78	17.56	30
		5795	14.29	14.49	17.40	30
MCS11	UNII 1	5190	7.18	6.15	9.71	24
		5230	7.13	6.17	9.69	24
	UNII 2a	5270	8.45	8.12	11.30	24
		5510	-0.71	-2.15	1.64	24
	UNII 2c	5590	-0.59	-1.89	1.82	24
		5670	-0.99	-1.34	1.85	24
	UNII 3	5755	6.52	6.73	9.64	30
		5795	6.14	6.78	9.48	30


Note:

Total Average power (dBm): $10 \cdot \log\{10^{(\text{Ant0 of avg power}/10)} + 10^{(\text{Ant1 of avg power}/10)}\}$


Test Plots: MCS0




Channel frequency:5190MHz@Chain1




Channel frequency:5230MHz@Chain1




Channel frequency:5270MHz@Chain1




Channel frequency:5510MHz@Chain1




Channel frequency:5590MHz@Chain1




Channel frequency:5670MHz@Chain1




Channel frequency:5755MHz@Chain1




Channel frequency:5795MHz@Chain1




Channel frequency:5190MHz@Chain2




Channel frequency:5230MHz@Chain2




Channel frequency:5270MHz@Chain2




Channel frequency:5510MHz@Chain2




Channel frequency:5590MHz@Chain2



Channel frequency:5670MHz@Chain2




Channel frequency:5755MHz@Chain2




Channel frequency:5795MHz@Chain2


Data Rate: MCS11




Channel frequency:5190MHz@Chain1




Channel frequency:5230MHz@Chain1




Channel frequency:5270MHz@Chain1




Channel frequency:5510MHz@Chain1




Channel frequency:5590MHz@Chain1











Channel frequency:5670MHz@Chain1



Channel frequency:5755MHz@Chain1



Channel frequency:5795MHz@Chain1



Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 58 von 129
Page 58 of 129


Modulation: 802.11ax-mode HE80MHz

Data Rate (Mbps)	Band	Channel Frequency (MHz)	Measured Average Power (dBm) Chain 1	Measured Average Power (dBm) Chain 2	Final Average output power (dBm)	Power Limit (dBm)
MCS0	UNII 1	5210.00	4.41	3.64	7.05	24
	UNII 2a	5290.00	4.31	3.45	6.91	24
	UNII 2c	5530.00	4.17	3.69	6.95	24
		5690.00	3.94	3.42	6.70	24
	UNII 3	5775.00	11.85	12.68	15.30	30
MCS11	UNII 1	5210.00	5.27	5.03	8.16	24
	UNII 2a	5290.00	5.07	4.69	7.89	24
	UNII 2c	5530.00	-0.31	-1.03	2.36	24
		5690.00	-0.52	-0.83	2.34	24
	UNII 3	5775.00	7.14	7.16	10.16	30


Note:

Total Average power (dBm): $10 \cdot \log\{10^{(\text{Ant0 of avg power}/10)} + 10^{(\text{Ant1 of avg power}/10)}\}$


Test Plots: MCS0




Channel frequency: 5210 MHz @ Chain1




Channel frequency: 5290 MHz @ Chain1








Channel frequency: 5530 MHz @ Chain1



Channel frequency: 5690 MHz @ Chain1



Channel frequency: 5775 MHz @ Chain1



Prüfbericht - Nr.:


Test Report No.:

ULR-TC568822300000063F


Seite 61 von 129

Page 61 of 129


Test Plots: MCS11




Channel frequency:5210MHz@Chain1




Channel frequency:5290MHz@Chain1




Channel frequency:5530MHz@Chain1




Channel frequency:5690MHz@Chain1




Channel frequency:5775MHz@Chain1




Channel frequency:5210MHz@Chain2




Channel frequency:5290MHz@Chain2



Channel frequency:5530MHz@Chain2



Channel frequency:5690MHz@Chain2



Channel frequency:5775MHz@Chain2

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 63 von 129
Page 63 of 129

7.2 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C Section 15.407 (b) (15.205 & 15.209)
Test Method	ANSI C 63.10 – 2013
Measurement Bandwidth	100kHz for below 1GHz 1MHz for above 1GHz
Measurement Location	Semi Anechoic Chamber 30MHz - 1 GHz Fully Anechoic Chamber 1 GHz - 40GHz
Measuring Distance	3 m
Detector	Refer Remark
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

Limit:

Table 6: Undesirable emission limits

Frequency Band	Limit
5.15-5.25 GHz	e.i.r.p. -27dBm [68.2 dBuV/3m]
5.25-5.35 GHz	e.i.r.p. -27dBm [68.2 dBuV/3m]
5.47-5.725 GHz	e.i.r.p. -27dBm [68.2 dBuV/3m]
5.725-5.85 GHz	5.715 GHz to 5.725 GHz - e.i.r.p. -17dBm [78.2 dBuV/3m] 5.85 GHz to 5.86 GHz - e.i.r.p. -17dBm [78.2 dBuV/3m] other frequency range - e.i.r.p. -27dBm [68.2 dBuV/3m]

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 64 von 129
Page 64 of 129

Table 7: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Condition:

Normal Test Condition:

Temperature (Norm) = + 25 °C

Voltage = 12VDC through AC to DC Adapter

Relative humidity: 62 %

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 65 von 129
Page 65 of 129

Test results:


Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details

Test results for Frequency range : 9kHz – 30MHz

No Emissions found in the frequency range 9kHz – 30MHz

Test results for frequency range 30MHz – 1GHz

Antenna Polarization	Measured Frequency (MHz)	Measured Quasi peak value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	36.408	37.18	40.00	-2.82
	42.282	36.94	40.00	-3.06
	71.976	36.78	40.00	-3.22
	287.462	28.99	46.00	-17.01
	288.206	26.71	46.00	-19.29
	290.702	28.23	46.00	-17.77
	399.992	41.73	46.00	-4.27
	900.008	39.54	46.00	-6.46
Horizontal	78.564	32.93	40.00	-7.07
	287.618	35.33	46.00	-10.67
	291.134	32.65	46.00	-13.35
	296.102	34.54	46.00	-11.46
	399.956	42.21	46.00	-3.79
	528.014	33.67	46.00	-12.33
	599.978	39.16	46.00	-6.84
	899.966	44.48	46.00	-1.52




Channel Frequency 30MHz – 200MHz

Polarization Vertical

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568822300000063F

Seite 66 von 129
Page 66 of 129



Channel Frequency 30MHz – 200MHz

Polarization Horizontal




Channel Frequency 200MHz – 1GHz

Polarization Vertical

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 67 von 129
Page 67 of 129



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 68 von 129
Page 68 of 129

Test results for frequency range – 1GHz to 40 GHz

Modulation: 802.11a
Data rate: 6Mbps

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	100.71	-	-
		5180 (Av)		90.82	-	-
		5150 (Pk)		57.68	74*	-16.32
		5150 (Av)		35.96	54*	-18.04
		10360 (Pk)		52.57	68.23	-15.66
		10360 (Av)		39.56	54	-14.44
		15540 (Pk)		53.84	68.23	-14.39
		15540 (Av)		42.11	54	-11.89
		5180 (Pk)	Horizontal	108.03	-	-
		5180 (Av)		98.63	-	-
		5150 (Pk)		67.03	74*	-6.97
		5150 (Av)		42.36	54*	-11.64
		10360 (Pk)		51.63	68.23	-16.60
		10360 (Av)		39.61	54	-14.39
		15540 (Pk)		54.17	68.23	-14.06
		15540 (Av)		42.11	54	-11.89
	5240	5240 (Pk)	Vertical	97.89	-	-
		5240 (Av)		88.33	-	-
		5350 (Pk)		43.26	74*	-30.74
		5350 (Av)		30.90	54*	-23.10
		10480 (Pk)		52.80	68.23	-15.43
		10480 (Av)		40.58	54	-13.42
		15720 (Pk)		53.88	68.23	-14.35
		15720 (Av)		41.84	54	-12.16
		5240 (Pk)	Horizontal	106.26	-	-
		5240 (Av)		96.41	-	-
		5350 (Pk)		46.90	74*	-27.10
		5350 (Av)		35.03	54*	-18.97
		10480 (Pk)		53.36	68.23	-14.87
		10480 (Av)		40.55	54	-13.45
		15720 (Pk)		54.51	68.23	-13.72
		15720 (Av)		41.81	54	-12.19

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 69 von 129
Page 69 of 129

UNII 2a	5320	5320 (Pk)	Vertical	101.02	-	-
		5320 (Av)		91.17	-	-
		5350 (Pk)		57.25	74*	-16.75
		5350 (Av)		37.16	54*	-16.84
		10640 (Pk)		52.75	68.23	-15.48
		10640 (Av)		40.53	54	-13.47
		15960 (Pk)		53.82	68.23	-14.41
		15960 (Av)		42.05	54	-11.95
		5320 (Pk)	Horizontal	109.09	-	-
		5320 (Av)		99.21	-	-
		5350 (Pk)		65.79	74*	-8.21
		5350 (Av)		44.07	54*	-9.93
		10640 (Pk)		52.32	68.23	-15.91
		10640 (Av)		40.55	54	-13.45
		15960 (Pk)		54.45	68.23	-13.78
		15960 (Av)		42.09	54	-11.91
UNII 2c	5500	5500 (Pk)	Vertical	97.62	-	-
		5500 (Av)		87.63	-	-
		5460 (Pk)		44.61	74*	-29.39
		5460 (Av)		32.83	54*	-21.17
		11000 (Pk)		53.62	68.23	-14.61
		11000 (Av)		41.45	54	-12.55
		16500 (Pk)		55.98	68.23	-12.25
		16500 (Av)		43.94	54	-10.06
		5500 (Pk)	Horizontal	105.31	-	-
		5500 (Av)		95.82	-	-
		5460 (Pk)		50.03	74*	-23.97
		5460 (Av)		37.81	54*	-16.19
		11000 (Pk)		54.36	68.23	-13.87
		11000 (Av)		41.48	54	-12.52
		16500 (Pk)		56.32	68.23	-11.91
		16500 (Av)		43.92	54	-10.08
	5600	5600 (Pk)	Vertical	95.53	-	-
		5600 (Av)		85.63	-	-
		5460 (Pk)		42.37	74*	-31.63
		5460 (Av)		30.16	54*	-23.84
		11200 (Pk)		53.40	68.23	-14.83
		11200 (Av)		41.09	54	-12.91
		16800 (Pk)		56.14	68.23	-12.09
		16800 (Av)		43.73	54	-10.27
		5600 (Pk)	Horizontal	104.67	-	-
		5600 (Av)		94.52	-	-
		5460 (Pk)		43.87	74*	-30.13
		5460 (Av)		31.77	54*	-22.23
		11200 (Pk)		53.63	68.23	-14.60
		11200 (Av)		41.12	54	-12.88
		16800 (Pk)		56.30	68.23	-11.93
		16800 (Av)		43.76	54	-10.24

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 70 von 129
Page 70 of 129

	5700	5700 (Pk)	Vertical	95.71	-	-
		5700 (Av)		86.40	-	-
		5460 (Pk)		42.33	74*	-31.67
		5460 (Av)		29.73	54*	-24.27
		11400 (Pk)		53.97	68.23	-14.26
		11400 (Av)		41.86	54	-12.14
		17100 (Pk)		57.30	68.23	-10.93
		17100 (Av)		44.13	54	-9.87
		5700 (Pk)	Horizontal	105.42	-	-
		5700 (Av)		95.02	-	-
		5460 (Pk)		42.88	74*	-31.12
		5460 (Av)		30.71	54*	-23.29
		11400 (Pk)		53.41	68.23	-14.82
		11400 (Av)		42.04	54	-11.96
		17100 (Pk)		56.88	68.23	-11.35
		17100 (Av)		44.03	54	-9.97
UNII 3	5745	5745 (Pk)	Vertical	100.49	-	-
		5745 (Av)		91.27	-	-
		5715(Pk)		56.10	78.2*	-22.10
		5725(Pk)		65.36	78.2*	-12.84
		11490 (Pk)		55.33	68.23	-12.90
		11490 (Av)		43.52	54	-10.48
		17235 (Pk)		56.17	68.23	-12.06
		17235 (Av)		44.39	54	-9.61
		5745 (Pk)	Horizontal	109.04	-	-
		5745 (Av)		99.44	-	-
		5715(Pk)		66.60	78.2*	-11.6
		5725(Pk)		74.24	78.2*	-3.96
		11490 (Pk)		64.80	68.23	-3.43
		11490 (Av)		49.41	54	-4.59
		17235 (Pk)		56.51	68.23	-11.72
		17235 (Av)		44.30	54	-9.70
	5825	5825 (Pk)	Vertical	103.78	-	-
		5825 (Av)		93.94	-	-
		5850 (Pk)		60.69	78.2*	-17.51
		5860 (Pk)		53.86	78.2*	-24.34
		11650 (Pk)		54.99	68.23	-13.24
		11650 (Av)		42.85	54	-11.15
		17475 (Pk)		58.67	68.23	-9.56
		17475 (Av)		46.33	54	-7.67
		5825 (Pk)	Horizontal	110.42	-	-
		5825 (Av)		100.48	-	-
		5850 (Pk)		68.42	78.2*	-9.78
		5860 (Pk)		59.60	78.2*	-18.60
		11650 (Pk)		59.16	68.23	-9.07
		11650 (Av)		45.44	54	-8.56
		17475 (Pk)		58.38	68.23	-9.85
		17475 (Pk)		46.31	54	-7.69

Note:

* : Indicate restricted band frequency in 15.205

Pk: Peak Detector; Av: Average Detector

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 71 von 129
Page 71 of 129

Modulation: 802.11a
Data rate: 54Mbps

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	99.27	-	-
		5180 (Av)		85.26	-	-
		5150 (Pk)		48.29	74*	-25.71
		5150 (Av)		33.78	54*	-20.22
		10360 (Pk)		51.70	68.23	-16.53
		10360 (Av)		39.57	54	-14.43
		15540 (Pk)		54.55	68.23	-13.68
		15540 (Av)		42.14	54	-11.86
		5180 (Pk)	Horizontal	108.13	-	-
		5180 (Av)		94.27	-	-
		5150 (Pk)		55.25	74*	-18.75
		5150 (Av)		40.71	54*	-13.29
		10360 (Pk)		51.71	68.23	-16.52
		10360 (Av)		39.59	54	-14.41
		15540 (Pk)		54.61	68.23	-13.62
		15540 (Av)		42.16	54	-11.84
	5240	5240 (Pk)	Vertical	98.36	-	-
		5240 (Av)		84.51	-	-
		5350 (Pk)		43.88	74*	-30.12
		5350 (Av)		30.73	54*	-23.27
		10480 (Pk)		52.94	68.23	-15.29
		10480 (Av)		40.58	54	-13.42
		15720 (Pk)		53.84	68.23	-14.39
		15720 (Av)		41.88	54	-12.12
		5240 (Pk)	Horizontal	106.19	-	-
		5240 (Av)		92.07	-	-
		5350 (Pk)		46.82	74*	-27.18
		5350 (Av)		34.02	54*	-19.98
		10480 (Pk)		52.63	68.23	-15.60
		10480 (Av)		40.54	54	-13.46
		15720 (Pk)		54.09	68.23	-14.14
		15720 (Av)		41.85	54	-12.15

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 72 von 129
Page 72 of 129

UNII 2a	5320	5320 (Pk)	Vertical	101.90	-	-
		5320 (Av)		88.11	-	-
		5350 (Pk)		51.37	74*	-22.63
		5350 (Av)		34.56	54*	-19.44
		10640 (Pk)		53.02	68.23	-15.21
		10640 (Av)		40.41	54	-13.59
		15960 (Pk)		54.51	68.23	-13.72
		15960 (Av)		42.02	54	-11.98
		5320 (Pk)	Horizontal	109.26	-	-
		5320 (Av)		95.39	-	-
		5350 (Pk)		58.78	74*	-15.22
		5350 (Av)		40.89	54*	-13.11
		10640 (Pk)		53.41	68.23	-14.82
		10640 (Av)		40.40	54	-13.60
		15960 (Pk)		53.90	68.23	-14.33
		15960 (Av)		41.98	54	-12.02
UNII 2c	5500	5500 (Pk)	Vertical	97.78	-	-
		5500 (Av)		83.72	-	-
		5460 (Pk)		44.20	74*	-29.80
		5460 (Av)		32.24	54*	-21.76
		11000 (Pk)		53.54	68.23	-14.69
		11000 (Av)		41.35	54	-12.65
		16500 (Pk)		55.79	68.23	-12.44
		16500 (Av)		43.77	54	-10.23
		5500 (Pk)	Horizontal	104.70	-	-
		5500 (Av)		90.85	-	-
		5460 (Pk)		48.84	74*	-25.16
		5460 (Av)		36.14	54*	-17.86
		11000 (Pk)		53.58	68.23	-14.65
		11000 (Av)		41.35	54	-12.65
		16500 (Pk)		55.99	68.23	-12.24
		16500 (Av)		43.74	54	-10.26
	5600	5600 (Pk)	Vertical	96.60	-	-
		5600 (Av)		83.07	-	-
		5460 (Pk)		42.31	74*	-31.69
		5460 (Av)		29.99	54*	-24.01
		11200 (Pk)		52.93	68.23	-15.30
		11200 (Av)		41.00	54	-13.00
		16800 (Pk)		55.90	68.23	-12.33
		16800 (Av)		43.79	54	-10.21
		5600 (Pk)	Horizontal	105.94	-	-
		5600 (Av)		91.27	-	-
		5460 (Pk)		44.15	74*	-29.85
		5460 (Av)		31.25	54*	-22.75
		11200 (Pk)		53.84	68.23	-14.39
		11200 (Av)		40.97	54	-13.03
		16800 (Pk)		55.94	68.23	-12.29
		16800 (Av)		43.71	54	-10.29

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 73 von 129
Page 73 of 129

	5700	5700 (Pk)	Vertical	96.90	-	-
		5700 (Av)		82.70	-	-
		5460 (Pk)		42.25	74*	-31.75
		5460 (Av)		29.76	54*	-24.24
		11400 (Pk)		54.08	68.23	-14.15
		11400 (Av)		41.77	54	-12.23
		17100 (Pk)		56.29	68.23	-11.94
		17100 (Av)		44.08	54	-9.92
		5700 (Pk)	Horizontal	104.36	-	-
		5700 (Av)		90.57	-	-
		5460 (Pk)		42.44	74*	-31.56
		5460 (Av)		30.46	54*	-23.54
		11400 (Pk)		53.71	68.23	-14.52
		11400 (Av)		42.02	54	-11.98
		17100 (Pk)		56.25	68.23	-11.98
		17100 (Av)		44.13	54	-9.87
UNII 3	5745	5745 (Pk)	Vertical	101.39	-	-
		5745 (Av)		87.77	-	-
		5715(Pk)		53.47	78.2*	-24.73
		5725(Pk)		64.74	78.2*	-13.46
		11490 (Pk)		55.16	68.23	-13.07
		11490 (Av)		42.83	54	-11.17
		17235 (Pk)		56.59	68.23	-11.64
		17235 (Av)		43.92	54	-10.08
		5745 (Pk)	Horizontal	109.20	-	-
		5745 (Av)		95.03	-	-
		5715(Pk)		64.14	78.2*	-14.06
		5725(Pk)		73.62	78.2*	-4.58
		11490 (Pk)		58.64	68.23	-9.59
		11490 (Av)		44.37	54	-9.63
		17235 (Pk)		55.75	68.23	-12.48
		17235 (Av)		43.90	54	-10.10
	5825	5825 (Pk)	Vertical	102.04	-	-
		5825 (Av)		88.18	-	-
		5850 (Pk)		54.47	78.2*	-23.73
		5860 (Pk)		47.04	78.2*	-31.16
		11650 (Pk)		53.49	68.23	-14.74
		11650 (Av)		42.08	54	-11.92
		17475 (Pk)		57.52	68.23	-10.71
		17475 (Av)		46.07	54	-7.93
		5825 (Pk)	Horizontal	110.29	-	-
		5825 (Av)		95.67	-	-
		5850 (Pk)		61.70	78.2*	-16.50
		5860 (Pk)		54.19	78.2*	-24.01
		11650 (Pk)		64.69	68.23	-3.54
		11650 (Av)		48.46	54	-5.54
		17475 (Pk)		57.89	68.23	-10.34
		17475 (Pk)		46.01	54	-7.99

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 74 von 129
Page 74 of 129

Modulation: 802.11n-HT20
Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	100.43	-	-
		5180 (Av)		90.51	-	-
		5150 (Pk)		54.19	74*	-19.81
		5150 (Av)		35.28	54*	-18.72
		10360 (Pk)		51.82	68.23	-16.41
		10360 (Av)		39.56	54	-14.44
		15540 (Pk)		54.38	68.23	-13.85
		15540 (Av)		42.08	54	-11.92
		5180 (Pk)	Horizontal	105.26	-	-
		5180 (Av)		95.12	-	-
		5150 (Pk)		56.45	74*	-17.55
		5150 (Av)		40.44	54*	-13.56
		10360 (Pk)		51.96	68.23	-16.27
		10360 (Av)		39.52	54	-14.48
		15540 (Pk)		54.01	68.23	-14.22
		15540 (Av)		42.10	54	-11.90
	5240	5240 (Pk)	Vertical	96.54	-	-
		5240 (Av)		87.41	-	-
		5350 (Pk)		43.38	74*	-30.62
		5350 (Av)		30.92	54*	-23.08
		10480 (Pk)		52.99	68.23	-15.24
		10480 (Av)		40.52	54	-13.48
		15720 (Pk)		52.55	68.23	-15.68
		15720 (Av)		41.84	54	-12.16
		5240 (Pk)	Horizontal	105.00	-	-
		5240 (Av)		96.41	-	-
		5350 (Pk)		47.05	74*	-26.95
		5350 (Av)		35.35	54*	-18.65
		10480 (Pk)		52.32	68.23	-15.91
		10480 (Av)		40.51	54	-13.49
		15720 (Pk)		53.54	68.23	-14.69
		15720 (Av)		41.84	54	-12.16

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 75 von 129
Page 75 of 129

UNII 2a	5320	5320 (Pk)	Vertical	99.95	-	-
		5320 (Av)		90.10	-	-
		5350 (Pk)		59.07	74*	-14.93
		5350 (Av)		38.13	54*	-15.87
		10640 (Pk)		53.02	68.23	-15.21
		10640 (Av)		40.36	54	-13.64
		15960 (Pk)		53.93	68.23	-14.30
		15960 (Av)		42.09	54	-11.91
		5320 (Pk)	Horizontal	107.94	-	-
		5320 (Av)		98.09	-	-
		5350 (Pk)		65.86	74*	-8.14
		5350 (Av)		44.84	54*	-9.16
		10640 (Pk)		53.60	68.23	-14.63
		10640 (Av)		40.39	54	-13.61
		15960 (Pk)		54.86	68.23	-13.37
		15960 (Av)		42.07	54	-11.93
UNII 2c	5500	5500 (Pk)	Vertical	96.20	-	-
		5500 (Av)		86.58	-	-
		5460 (Pk)		45.48	74*	-28.52
		5460 (Av)		32.64	54*	-21.36
		11000 (Pk)		53.78	68.23	-14.45
		11000 (Av)		41.31	54	-12.69
		16500 (Pk)		56.22	68.23	-12.01
		16500 (Av)		43.81	54	-10.19
		5500 (Pk)	Horizontal	104.89	-	-
		5500 (Av)		94.89	-	-
		5460 (Pk)		49.29	74*	-24.71
		5460 (Av)		37.43	54*	-16.57
		11000 (Pk)		53.67	68.23	-14.56
		11000 (Av)		41.31	54	-12.69
		16500 (Pk)		56.35	68.23	-11.88
		16500 (Av)		43.78	54	-10.22
	5600	5600 (Pk)	Vertical	95.70	-	-
		5600 (Av)		86.21	-	-
		5460 (Pk)		42.43	74*	-31.57
		5460 (Av)		30.00	54*	-24.00
		11200 (Pk)		54.01	68.23	-14.22
		11200 (Av)		41.16	54	-12.84
		16800 (Pk)		56.57	68.23	-11.66
		16800 (Av)		44.08	54	-9.92
		5600 (Pk)	Horizontal	104.16	-	-
		5600 (Av)		94.28	-	-
		5460 (Pk)		44.37	74*	-29.63
		5460 (Av)		31.66	54*	-22.34
		11200 (Pk)		53.27	68.23	-14.96
		11200 (Av)		41.18	54	-12.82
		16800 (Pk)		56.86	68.23	-11.37
		16800 (Av)		44.07	54	-9.93

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 76 von 129
Page 76 of 129

5700	Vertical	5700 (Pk)	95.87	-	-
		5700 (Av)	85.60	-	-
		5460 (Pk)	42.53	74*	-31.47
		5460 (Av)	29.82	54*	-24.18
		11400 (Pk)	54.10	68.23	-14.13
		11400 (Av)	41.99	54	-12.01
		17100 (Pk)	56.41	68.23	-11.82
		17100 (Av)	44.68	54	-9.32
	Horizontal	5700 (Pk)	103.57	-	-
		5700 (Av)	94.03	-	-
		5460 (Pk)	43.25	74*	-30.75
		5460 (Av)	30.75	54*	-23.25
		11400 (Pk)	54.10	68.23	-14.13
		11400 (Av)	41.99	54	-12.01
		17100 (Pk)	56.41	68.23	-11.82
		17100 (Av)	44.68	54	-9.32
UNII 3	Vertical	5745 (Pk)	101.85	-	-
		5745 (Av)	92.52	-	-
		5715(Pk)	61.97	78.2*	-16.23
		5725(Pk)	71.02	78.2*	-7.18
		11490 (Pk)	57.01	68.23	-11.22
		11490 (Av)	43.67	54	-10.33
		17235 (Pk)	56.94	68.23	-11.29
		17235 (Av)	44.32	54	-9.68
	Horizontal	5745 (Pk)	109.52	-	-
		5745 (Av)	99.03	-	-
		5715(Pk)	68.25	78.2*	-9.95
		5725(Pk)	75.55	78.2*	-2.65
		11490 (Pk)	66.56	68.23	-1.67
		11490 (Av)	51.82	54	-2.18
		17235 (Pk)	56.26	68.23	-11.97
		17235 (Av)	44.28	54	-9.72
	Vertical	5825 (Pk)	104.13	-	-
		5825 (Av)	93.92	-	-
		5850 (Pk)	64.59	78.2*	-13.61
		5860 (Pk)	55.82	78.2*	-22.38
		11650 (Pk)	54.77	68.23	-13.46
		11650 (Av)	42.51	54	-11.49
		17475 (Pk)	58.56	68.23	-9.67
		17475 (Av)	46.32	54	-7.68
	Horizontal	5825 (Pk)	110.77	-	-
		5825 (Av)	100.99	-	-
		5850 (Pk)	73.83	78.2*	-4.37
		5860 (Pk)	65.02	78.2*	-13.18
		11650 (Pk)	61.30	68.23	-6.93
		11650 (Av)	47.20	54	-6.80
		17475 (Pk)	58.24	68.23	-9.99
		17475 (Pk)	46.39	54	-7.61

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 77 von 129

Page 77 of 129

Modulation: 802.11n-HT20

Data rate: MCS7

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	96.96	-	-
		5180 (Av)		83.37	-	-
		5150 (Pk)		46.25	74*	-27.75
		5150 (Av)		33.41	54*	-20.59
		10360 (Pk)		52.23	68.23	-16.00
		10360 (Av)		39.50	54	-14.50
		15540 (Pk)		54.06	68.23	-14.17
		15540 (Av)		41.90	54	-12.10
		5180 (Pk)	Horizontal	105.73	-	-
		5180 (Av)		92.01	-	-
		5150 (Pk)		54.54	74*	-19.46
		5150 (Av)		38.39	54*	-15.61
		10360 (Pk)		51.99	68.23	-16.24
		10360 (Av)		39.59	54	-14.41
		15540 (Pk)		54.01	68.23	-14.22
		15540 (Av)		41.96	54	-12.04
	5240	5240 (Pk)	Vertical	96.43	-	-
		5240 (Av)		82.45	-	-
		5350 (Pk)		43.04	74*	-30.96
		5350 (Av)		31.26	54*	-22.74
		10480 (Pk)		52.69	68.23	-15.54
		10480 (Av)		40.48	54	-13.52
		15720 (Pk)		54.12	68.23	-14.11
		15720 (Av)		41.61	54	-12.39
		5240 (Pk)	Horizontal	104.85	-	-
		5240 (Av)		91.24	-	-
		5350 (Pk)		47.21	74*	-26.79
		5350 (Av)		34.03	54*	-19.97
		10480 (Pk)		52.59	68.23	-15.64
		10480 (Av)		40.49	54	-13.51
		15720 (Pk)		53.87	68.23	-14.36
		15720 (Av)		41.64	54	-12.36

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 78 von 129
Page 78 of 129

UNII 2a	5320	5320 (Pk)	Vertical	99.69	-	-
		5320 (Av)		85.51	-	-
		5350 (Pk)		52.25	74*	-21.75
		5350 (Av)		35.22	54*	-18.78
		10640 (Pk)		53.36	68.23	-14.87
		10640 (Av)		40.42	54	-13.58
		15960 (Pk)		55.11	68.23	-13.12
		15960 (Av)		42.17	54	-11.83
		5320 (Pk)	Horizontal	107.86	-	-
		5320 (Av)		94.20	-	-
		5350 (Pk)		61.03	74*	-12.97
		5350 (Av)		41.12	54*	-12.88
		10640 (Pk)		53.19	68.23	-15.04
		10640 (Av)		40.37	54	-13.63
		15960 (Pk)		54.26	68.23	-13.97
		15960 (Av)		42.06	54	-11.94
UNII 2c	5500	5500 (Pk)	Vertical	93.41	-	-
		5500 (Av)		80.04	-	-
		5460 (Pk)		43.93	74*	-30.07
		5460 (Av)		31.03	54*	-22.97
		11000 (Pk)		53.99	68.23	-14.24
		11000 (Av)		41.32	54	-12.68
		16500 (Pk)		56.03	68.23	-12.20
		16500 (Av)		43.76	54	-10.24
		5500 (Pk)	Horizontal	101.99	-	-
		5500 (Av)		88.57	-	-
		5460 (Pk)		48.56	74*	-25.44
		5460 (Av)		35.62	54*	-18.38
		11000 (Pk)		53.60	68.23	-14.63
		11000 (Av)		41.33	54	-12.67
		16500 (Pk)		56.27	68.23	-11.96
		16500 (Av)		43.74	54	-10.26
	5600	5600 (Pk)	Vertical	92.62	-	-
		5600 (Av)		79.05	-	-
		5460 (Pk)		42.66	74*	-31.34
		5460 (Av)		30.04	54*	-23.96
		11200 (Pk)		53.85	68.23	-14.38
		11200 (Av)		41.15	54	-12.85
		16800 (Pk)		56.25	68.23	-11.98
		16800 (Av)		44.09	54	-9.91
		5600 (Pk)	Horizontal	93.05	-	-
		5600 (Av)		79.39	-	-
		5460 (Pk)		43.18	74*	-30.82
		5460 (Av)		30.02	54*	-23.98
		11200 (Pk)		53.68	68.23	-14.55
		11200 (Av)		41.10	54	-12.90
		16800 (Pk)		56.21	68.23	-12.02
		16800 (Av)		44.09	54	-9.91

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 79 von 129
Page 79 of 129

5700	Vertical	5700 (Pk)	95.87	-	-
		5700 (Av)	85.60	-	-
		5460 (Pk)	42.53	74*	-31.47
		5460 (Av)	29.82	54*	-24.18
		11400 (Pk)	54.29	68.23	-13.94
		11400 (Av)	41.95	54	-12.05
		17100 (Pk)	56.21	68.23	-12.02
		17100 (Av)	44.66	54	-9.34
	Horizontal	5700 (Pk)	101.19	-	-
		5700 (Av)	87.70	-	-
		5460 (Pk)	43.32	74*	-30.68
		5460 (Av)	30.51	54*	-23.49
		11400 (Pk)	54.27	68.23	-13.96
		11400 (Av)	41.98	54	-12.02
		17100 (Pk)	57.81	68.23	-10.42
		17100 (Av)	44.68	54	-9.32
UNII 3	Vertical	5745 (Pk)	99.19	-	-
		5745 (Av)	85.76	-	-
		5715(Pk)	57.47	78.2*	-20.73
		5725(Pk)	65.69	78.2*	-12.51
		11490 (Pk)	55.70	68.23	-12.53
		11490 (Av)	43.25	54	-10.75
		17235 (Pk)	57.28	68.23	-10.95
		17235 (Av)	45.08	54	-8.92
	Horizontal	5745 (Pk)	109.58	-	-
		5745 (Av)	95.35	-	-
		5715(Pk)	68.30	78.2*	-9.90
		5725(Pk)	76.25	78.2*	-1.95
		11490 (Pk)	57.86	68.23	-10.37
		11490 (Av)	44.10	54	-9.90
		17235 (Pk)	57.07	68.23	-11.16
		17235 (Av)	45.07	54	-8.93
	Vertical	5825 (Pk)	101.76	-	-
		5825 (Av)	88.21	-	-
		5850 (Pk)	59.14	78.2*	-19.06
		5860 (Pk)	48.31	78.2*	-29.89
		11650 (Pk)	53.88	68.23	-14.35
		11650 (Av)	42.16	54	-11.84
		17475 (Pk)	59.43	68.23	-8.80
		17475 (Av)	47.34	54	-6.66
	Horizontal	5825 (Pk)	108.88	-	-
		5825 (Av)	95.83	-	-
		5850 (Pk)	69.53	78.2*	-8.67
		5860 (Pk)	58.50	78.2*	-19.70
		11650 (Pk)	58.19	68.23	-10.04
		11650 (Av)	44.43	54	-9.57
		17475 (Pk)	60.16	68.23	-8.07
		17475 (Pk)	47.29	54	-6.71

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 80 von 129

Page 80 of 129

Modulation: 802.11ac-VHT20

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	100.76	-	-
		5180 (Av)		90.93	-	-
		5150 (Pk)		57.86	74*	-16.14
		5150 (Av)		36.10	54*	-17.90
		10360 (Pk)		51.93	68.23	-16.30
		10360 (Av)		39.27	54	-14.73
		15540 (Pk)		53.76	68.23	-14.47
		15540 (Av)		41.54	54	-12.46
		5180 (Pk)	Horizontal	108.00	-	-
		5180 (Av)		98.86	-	-
		5150 (Pk)		67.59	74*	-6.41
		5150 (Av)		42.92	54*	-11.08
		10360 (Pk)		51.09	68.23	-17.14
		10360 (Av)		39.20	54	-14.80
		15540 (Pk)		53.18	68.23	-15.05
		15540 (Av)		51.58	54	-2.42
	5240	5240 (Pk)	Vertical	98.04	-	-
		5240 (Av)		89.07	-	-
		5350 (Pk)		43.35	74*	-30.65
		5350 (Av)		31.01	54*	-22.99
		10480 (Pk)		52.95	68.23	-15.28
		10480 (Av)		40.28	54	-13.72
		15720 (Pk)		52.99	68.23	-15.24
		15720 (Av)		41.39	54	-12.61
		5240 (Pk)	Horizontal	105.61	-	-
		5240 (Av)		96.36	-	-
		5350 (Pk)		46.22	74*	-27.78
		5350 (Av)		34.85	54*	-19.15
		10480 (Pk)		52.22	68.23	-16.01
		10480 (Av)		40.26	54	-13.74
		15720 (Pk)		53.34	68.23	-14.89
		15720 (Av)		41.40	54	-12.60

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 81 von 129
Page 81 of 129

UNII 2a	5320	5320 (Pk)	Vertical	101.34	-	-
		5320 (Av)		92.00	-	-
		5350 (Pk)		58.78	74*	-15.22
		5350 (Av)		38.89	54*	-15.11
		10640 (Pk)		52.33	68.23	-15.90
		10640 (Av)		40.35	54	-13.65
		15960 (Pk)		54.90	68.23	-13.33
		15960 (Av)		42.02	54	-11.98
		5320 (Pk)	Horizontal	107.95	-	-
		5320 (Av)		99.06	-	-
		5350 (Pk)		67.18	74*	-6.82
		5350 (Av)		45.95	54*	-8.05
		10640 (Pk)		52.29	68.23	-15.94
		10640 (Av)		40.31	54	-13.69
		15960 (Pk)		54.13	68.23	-14.10
		15960 (Av)		41.97	54	-12.03
UNII 2c	5500	5500 (Pk)	Vertical	91.03	-	-
		5500 (Av)		77.36	-	-
		5460 (Pk)		44.59	74*	-29.41
		5460 (Av)		30.87	54*	-23.13
		11000 (Pk)		54.00	68.23	-14.23
		11000 (Av)		41.41	54	-12.59
		16500 (Pk)		56.03	68.23	-12.20
		16500 (Av)		43.81	54	-10.19
		5500 (Pk)	Horizontal	102.19	-	-
		5500 (Av)		88.49	-	-
		5460 (Pk)		48.72	74*	-25.28
		5460 (Av)		35.76	54*	-18.24
		11000 (Pk)		53.31	68.23	-14.92
		11000 (Av)		41.42	54	-12.58
		16500 (Pk)		56.21	68.23	-12.02
		16500 (Av)		43.83	54	-10.17
	5600	5600 (Pk)	Vertical	96.88	-	-
		5600 (Av)		87.62	-	-
		5460 (Pk)		42.92	74*	-31.08
		5460 (Av)		30.42	54*	-23.58
		11200 (Pk)		53.23	68.23	-15.00
		11200 (Av)		41.18	54	-12.82
		16800 (Pk)		55.78	68.23	-12.45
		16800 (Av)		44.16	54	-9.84
		5600 (Pk)	Horizontal	104.61	-	-
		5600 (Av)		95.20	-	-
		5460 (Pk)		43.94	74*	-30.06
		5460 (Av)		32.27	54*	-21.73
		11200 (Pk)		52.69	68.23	-15.54
		11200 (Av)		41.23	54	-12.77
		16800 (Pk)		56.72	68.23	-11.51
		16800 (Av)		44.10	54	-9.90

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 82 von 129
Page 82 of 129

5700	Vertical	5700 (Pk)	96.40	-	-
		5700 (Av)	87.12	-	-
		5460 (Pk)	43.17	74*	-30.83
		5460 (Av)	30.17	54*	-23.83
		11400 (Pk)	57.19	68.23	-11.04
		11400 (Av)	42.03	54	-11.97
		17100 (Pk)	57.43	68.23	-10.80
		17100 (Av)	44.79	54	-9.21
	Horizontal	5700 (Pk)	104.10	-	-
		5700 (Av)	95.17	-	-
		5460 (Pk)	43.39	74*	-30.61
		5460 (Av)	31.28	54*	-22.72
		11400 (Pk)	54.22	68.23	-14.01
		11400 (Av)	42.11	54	-11.89
		17100 (Pk)	56.45	68.23	-11.78
		17100 (Av)	44.80	54	-9.20
UNII 3	Vertical	5745 (Pk)	101.41	-	-
		5745 (Av)	91.75	-	-
		5715(Pk)	66.59	78.2*	-11.61
		5725(Pk)	57.39	78.2*	-20.81
		11490 (Pk)	56.18	68.23	-12.05
		11490 (Av)	43.06	54	-10.94
		17235 (Pk)	58.46	68.23	-9.77
		17235 (Av)	45.22	54	-8.78
	Horizontal	5745 (Pk)	108.63	-	-
		5745 (Av)	99.47	-	-
		5715(Pk)	75.91	78.2*	-2.29
		5725(Pk)	67.51	78.2*	-10.69
		11490 (Pk)	57.62	68.23	-10.61
		11490 (Av)	44.38	54	-9.62
		17235 (Pk)	57.76	68.23	-10.47
		17235 (Av)	45.22	54	-8.78
	Vertical	5825 (Pk)	101.65	-	-
		5825 (Av)	92.35	-	-
		5850 (Pk)	60.76	78.2*	-17.44
		5860 (Pk)	52.21	78.2*	-25.99
		11650 (Pk)	54.49	68.23	-13.74
		11650 (Av)	42.44	54	-11.56
		17475 (Pk)	59.91	68.23	-8.32
		17475 (Av)	47.41	54	-6.59
	Horizontal	5825 (Pk)	109.23	-	-
		5825 (Av)	99.49	-	-
		5850 (Pk)	70.59	78.2*	-7.61
		5860 (Pk)	60.40	78.2*	-17.80
		11650 (Pk)	65.35	68.23	-2.88
		11650 (Av)	50.57	54	-3.43
		17475 (Pk)	59.59	68.23	-8.64
		17475 (Pk)	47.42	54	-6.58

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 83 von 129

Page 83 of 129

Modulation: 802.11ac-VHT20

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	100.76	-	-
		5180 (Av)		90.93	-	-
		5150 (Pk)		57.86	74*	-16.14
		5150 (Av)		36.10	54*	-17.90
		10360 (Pk)		51.93	68.23	-16.30
		10360 (Av)		39.27	54	-14.73
		15540 (Pk)		53.76	68.23	-14.47
		15540 (Av)		41.54	54	-12.46
		5180 (Pk)	Horizontal	108.00	-	-
		5180 (Av)		98.86	-	-
		5150 (Pk)		67.59	74*	-6.41
		5150 (Av)		42.92	54*	-11.08
		10360 (Pk)		51.09	68.23	-17.14
		10360 (Av)		39.20	54	-14.80
		15540 (Pk)		53.18	68.23	-15.05
		15540 (Av)		51.58	54	-2.42
	5240	5240 (Pk)	Vertical	98.04	-	-
		5240 (Av)		89.07	-	-
		5350 (Pk)		43.35	74*	-30.65
		5350 (Av)		31.01	54*	-22.99
		10480 (Pk)		52.95	68.23	-15.28
		10480 (Av)		40.28	54	-13.72
		15720 (Pk)		52.99	68.23	-15.24
		15720 (Av)		41.39	54	-12.61
		5240 (Pk)	Horizontal	105.61	-	-
		5240 (Av)		96.36	-	-
		5350 (Pk)		46.22	74*	-27.78
		5350 (Av)		34.85	54*	-19.15
		10480 (Pk)		52.22	68.23	-16.01
		10480 (Av)		40.26	54	-13.74
		15720 (Pk)		53.34	68.23	-14.89
		15720 (Av)		41.40	54	-12.60

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 84 von 129
Page 84 of 129

UNII 2a	5320	5320 (Pk)	Vertical	101.34	-	-
		5320 (Av)		92.00	-	-
		5350 (Pk)		58.78	74*	-15.22
		5350 (Av)		38.89	54*	-15.11
		10640 (Pk)		52.33	68.23	-15.90
		10640 (Av)		40.35	54	-13.65
		15960 (Pk)		54.90	68.23	-13.33
		15960 (Av)		42.02	54	-11.98
		5320 (Pk)	Horizontal	107.95	-	-
		5320 (Av)		99.06	-	-
		5350 (Pk)		67.18	74*	-6.82
		5350 (Av)		45.95	54*	-8.05
		10640 (Pk)		52.29	68.23	-15.94
		10640 (Av)		40.31	54	-13.69
		15960 (Pk)		54.13	68.23	-14.10
		15960 (Av)		41.97	54	-12.03
UNII 2c	5500	5500 (Pk)	Vertical	91.03	-	-
		5500 (Av)		77.36	-	-
		5460 (Pk)		44.59	74*	-29.41
		5460 (Av)		30.87	54*	-23.13
		11000 (Pk)		54.00	68.23	-14.23
		11000 (Av)		41.41	54	-12.59
		16500 (Pk)		56.03	68.23	-12.20
		16500 (Av)		43.81	54	-10.19
		5500 (Pk)	Horizontal	102.19	-	-
		5500 (Av)		88.49	-	-
		5460 (Pk)		48.72	74*	-25.28
		5460 (Av)		35.76	54*	-18.24
		11000 (Pk)		53.31	68.23	-14.92
		11000 (Av)		41.42	54	-12.58
		16500 (Pk)		56.21	68.23	-12.02
		16500 (Av)		43.83	54	-10.17
	5600	5600 (Pk)	Vertical	96.88	-	-
		5600 (Av)		87.62	-	-
		5460 (Pk)		42.92	74*	-31.08
		5460 (Av)		30.42	54*	-23.58
		11200 (Pk)		53.23	68.23	-15.00
		11200 (Av)		41.18	54	-12.82
		16800 (Pk)		55.78	68.23	-12.45
		16800 (Av)		44.16	54	-9.84
		5600 (Pk)	Horizontal	104.61	-	-
		5600 (Av)		95.20	-	-
		5460 (Pk)		43.94	74*	-30.06
		5460 (Av)		32.27	54*	-21.73
		11200 (Pk)		52.69	68.23	-15.54
		11200 (Av)		41.23	54	-12.77
		16800 (Pk)		56.72	68.23	-11.51
		16800 (Av)		44.10	54	-9.90

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 85 von 129
Page 85 of 129

	5700	5700 (Pk)	Vertical	96.40	-	-
		5700 (Av)		87.12	-	-
		5460 (Pk)		43.17	74*	-30.83
		5460 (Av)		30.17	54*	-23.83
		11400 (Pk)		57.19	68.23	-11.04
		11400 (Av)		42.03	54	-11.97
		17100 (Pk)		57.43	68.23	-10.80
		17100 (Av)		44.79	54	-9.21
		5700 (Pk)	Horizontal	104.10	-	-
		5700 (Av)		95.17	-	-
		5460 (Pk)		43.39	74*	-30.61
		5460 (Av)		31.28	54*	-22.72
		11400 (Pk)		54.22	68.23	-14.01
		11400 (Av)		42.11	54	-11.89
		17100 (Pk)		56.45	68.23	-11.78
		17100 (Av)		44.80	54	-9.20
UNII 3	5745	5745 (Pk)	Vertical	101.41	-	-
		5745 (Av)		91.75	-	-
		5715(Pk)		66.59	78.2*	-11.61
		5725(Pk)		57.39	78.2*	-20.81
		11490 (Pk)		56.18	68.23	-12.05
		11490 (Av)		43.06	54	-10.94
		17235 (Pk)		58.46	68.23	-9.77
		17235 (Av)		45.22	54	-8.78
		5745 (Pk)	Horizontal	108.63	-	-
		5745 (Av)		99.47	-	-
		5715(Pk)		75.91	78.2*	-2.29
		5725(Pk)		67.51	78.2*	-10.69
		11490 (Pk)		57.62	68.23	-10.61
		11490 (Av)		44.38	54	-9.62
		17235 (Pk)		57.76	68.23	-10.47
		17235 (Av)		45.22	54	-8.78
	5825	5825 (Pk)	Vertical	101.65	-	-
		5825 (Av)		92.35	-	-
		5850 (Pk)		60.76	78.2*	-17.44
		5860 (Pk)		52.21	78.2*	-25.99
		11650 (Pk)		54.49	68.23	-13.74
		11650 (Av)		42.44	54	-11.56
		17475 (Pk)		59.91	68.23	-8.32
		17475 (Av)		47.41	54	-6.59
		5825 (Pk)	Horizontal	109.23	-	-
		5825 (Av)		99.49	-	-
		5850 (Pk)		70.59	78.2*	-7.61
		5860 (Pk)		60.40	78.2*	-17.80
		11650 (Pk)		65.35	68.23	-2.88
		11650 (Av)		50.57	54	-3.43
		17475 (Pk)		59.59	68.23	-8.64
		17475 (Pk)		47.42	54	-6.58

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 86 von 129
Page 86 of 129

Modulation: 802.11ac-VHT20
Data rate: MCS8

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	95.58	-	-
		5180 (Av)		84.49	-	-
		5150 (Pk)		46.23	74*	-27.77
		5150 (Av)		32.75	54*	-21.25
		10360 (Pk)		52.54	68.23	-15.69
		10360 (Av)		39.71	54	-14.29
		15540 (Pk)		54.49	68.23	-13.74
		15540 (Av)		42.10	54	-11.90
		5180 (Pk)	Horizontal	102.04	-	-
		5180 (Av)		91.10	-	-
		5150 (Pk)		51.91	74*	-22.09
		5150 (Av)		37.65	54*	-16.35
		10360 (Pk)		52.24	68.23	-15.99
		10360 (Av)		39.72	54	-14.28
		15540 (Pk)		53.93	68.23	-14.30
		15540 (Av)		42.10	54	-11.90
	5240	5240 (Pk)	Vertical	93.97	-	-
		5240 (Av)		83.14	-	-
		5350 (Pk)		42.87	74*	-31.13
		5350 (Av)		30.35	54*	-23.65
		10480 (Pk)		53.41	68.23	-14.82
		10480 (Av)		40.60	54	-13.40
		15720 (Pk)		53.99	68.23	-14.24
		15720 (Av)		41.88	54	-12.12
		5240 (Pk)	Horizontal	102.02	-	-
		5240 (Av)		91.20	-	-
		5350 (Pk)		44.99	74*	-29.01
		5350 (Av)		33.41	54*	-20.59
		10480 (Pk)		52.69	68.23	-15.54
		10480 (Av)		40.63	54	-13.37
		15720 (Pk)		53.94	68.23	-14.29
		15720 (Av)		41.93	54	-12.07

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 87 von 129
Page 87 of 129

UNII 2a	5320	5320 (Pk)	Vertical	100.32	-	-
		5320 (Av)		89.72	-	-
		5350 (Pk)		57.44	74*	-16.56
		5350 (Av)		38.48	54*	-15.52
		10640 (Pk)		52.56	68.23	-15.67
		10640 (Av)		40.59	54	-13.41
		15960 (Pk)		54.13	68.23	-14.10
		15960 (Av)		42.29	54	-11.71
		5320 (Pk)	Horizontal	108.03	-	-
		5320 (Av)		97.21	-	-
		5350 (Pk)		64.08	74*	-9.92
		5350 (Av)		44.57	54*	-9.43
		10640 (Pk)		52.37	68.23	-15.86
		10640 (Av)		40.60	54	-13.40
		15960 (Pk)		54.51	68.23	-13.72
		15960 (Av)		42.26	54	-11.74
UNII 2c	5500	5500 (Pk)	Vertical	92.08	-	-
		5500 (Av)		81.20	-	-
		5460 (Pk)		43.55	74*	-30.45
		5460 (Av)		31.29	54*	-22.71
		11000 (Pk)		53.55	68.23	-14.68
		11000 (Av)		41.59	54	-12.41
		16500 (Pk)		55.82	68.23	-12.41
		16500 (Av)		44.00	54	-10.00
		5500 (Pk)	Horizontal	98.90	-	-
		5500 (Av)		88.71	-	-
		5460 (Pk)		46.92	74*	-27.08
		5460 (Av)		34.14	54*	-19.86
		11000 (Pk)		53.65	68.23	-14.58
		11000 (Av)		41.57	54	-12.43
		16500 (Pk)		56.30	68.23	-11.93
		16500 (Av)		44.05	54	-9.95
	5600	5600 (Pk)	Vertical	50.56	-	-
		5600 (Av)		80.58	-	-
		5460 (Pk)		43.07	74*	-30.93
		5460 (Av)		30.24	54*	-23.76
		11200 (Pk)		53.65	68.23	-14.58
		11200 (Av)		41.37	54	-12.63
		16800 (Pk)		56.13	68.23	-12.10
		16800 (Av)		44.26	54	-9.74
		5600 (Pk)	Horizontal	99.91	-	-
		5600 (Av)		89.42	-	-
		5460 (Pk)		43.53	74*	-30.47
		5460 (Av)		31.36	54*	-22.64
		11200 (Pk)		52.92	68.23	-15.31
		11200 (Av)		41.33	54	-12.67
		16800 (Pk)		55.36	68.23	-12.87
		16800 (Av)		44.25	54	-9.75

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 88 von 129
Page 88 of 129

	5700	5700 (Pk)	Vertical	92.30	-	-
		5700 (Av)		81.06	-	-
		5460 (Pk)		43.11	74*	-30.89
		5460 (Av)		30.21	54*	-23.79
		11400 (Pk)		53.75	68.23	-14.48
		11400 (Av)		42.12	54	-11.88
		17100 (Pk)		57.80	68.23	-10.43
		17100 (Av)		44.90	54	-9.10
		5700 (Pk)	Horizontal	100.03	-	-
		5700 (Av)		88.84	-	-
		5460 (Pk)		42.70	74*	-31.30
		5460 (Av)		30.87	54*	-23.13
		11400 (Pk)		54.12	68.23	-14.11
		11400 (Av)		42.14	54	-11.86
		17100 (Pk)		56.49	68.23	-11.74
		17100 (Av)		44.93	54	-9.07
UNII 3	5745	5745 (Pk)	Vertical	100.09	-	-
		5745 (Av)		89.74	-	-
		5715(Pk)		54.70	78.2*	-23.50
		5725(Pk)		65.40	78.2*	-12.80
		11490 (Pk)		56.65	68.23	-11.58
		11490 (Av)		43.02	54	-10.98
		17235 (Pk)		57.68	68.23	-10.55
		17235 (Av)		45.38	54	-8.62
		5745 (Pk)	Horizontal	107.85	-	-
		5745 (Av)		97.03	-	-
		5715(Pk)		65.20	78.2*	-13.00
		5725(Pk)		75.42	78.2*	-2.78
		11490 (Pk)		60.24	68.23	-7.99
		11490 (Av)		46.86	54	-7.14
		17235 (Pk)		57.90	68.23	-10.33
		17235 (Av)		45.40	54	-8.60
	5825	5825 (Pk)	Vertical	101.07	-	-
		5825 (Av)		90.06	-	-
		5850 (Pk)		60.38	78.2*	-17.82
		5860 (Pk)		35.93	78.2*	-42.27
		11650 (Pk)		54.22	68.23	-14.01
		11650 (Av)		41.88	54	-12.12
		17475 (Pk)		59.47	68.23	-8.76
		17475 (Av)		46.93	54	-7.07
		5825 (Pk)	Horizontal	108.32	-	-
		5825 (Av)		97.57	-	-
		5850 (Pk)		69.22	78.2*	-8.98
		5860 (Pk)		60.04	78.2*	-18.16
		11650 (Pk)		56.66	68.23	-11.57
		11650 (Av)		43.36	54	-10.64
		17475 (Pk)		58.92	68.23	-9.31
		17475 (Pk)		46.98	54	-7.02

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 89 von 129
Page 89 of 129

Modulation: 802.11ax-HE20
Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	98.08	-	-
		5180 (Av)		85.83	-	-
		5150 (Pk)		52.25	74*	-21.75
		5150 (Av)		33.27	54*	-20.73
		10360 (Pk)		52.14	68.23	-16.09
		10360 (Av)		39.43	54	-14.57
		15540 (Pk)		53.66	68.23	-14.57
		15540 (Av)		41.28	54	-12.72
		5180 (Pk)	Horizontal	109.80	-	-
		5180 (Av)		97.95	-	-
		5150 (Pk)		60.08	74*	-13.92
		5150 (Av)		42.37	54*	-11.63
		10360 (Pk)		50.86	68.23	-17.37
		10360 (Av)		39.38	54	-14.62
		15540 (Pk)		53.01	68.23	-15.22
		15540 (Av)		41.30	54	-12.70
	5240	5240 (Pk)	Vertical	98.96	-	-
		5240 (Av)		86.52	-	-
		5350 (Pk)		43.33	74*	-30.67
		5350 (Av)		31.71	54*	-22.29
		10480 (Pk)		51.91	68.23	-16.32
		10480 (Av)		40.32	54	-13.68
		15720 (Pk)		52.99	68.23	-15.24
		15720 (Av)		41.64	54	-12.36
		5240 (Pk)	Horizontal	109.49	-	-
		5240 (Av)		96.62	-	-
		5350 (Pk)		50.42	74*	-23.58
		5350 (Av)		36.87	54*	-17.13
		10480 (Pk)		51.89	68.23	-16.34
		10480 (Av)		40.38	54	-13.62
		15720 (Pk)		53.22	68.23	-15.01
		15720 (Av)		41.68	54	-12.32

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 90 von 129
Page 90 of 129

UNII 2a	5320	5320 (Pk)	Vertical	98.88	-	-
		5320 (Av)		86.55	-	-
		5350 (Pk)		55.62	74*	-18.38
		5350 (Av)		34.80	54*	-19.20
		10640 (Pk)		52.04	68.23	-16.19
		10640 (Av)		40.27	54	-13.73
		15960 (Pk)		53.90	68.23	-14.33
		15960 (Av)		41.93	54	-12.07
		5320 (Pk)	Horizontal	111.67	-	-
		5320 (Av)		99.76	-	-
		5350 (Pk)		67.06	74*	-6.94
		5350 (Av)		46.00	54*	-8.00
		10640 (Pk)		51.82	68.23	-16.41
		10640 (Av)		40.24	54	-13.76
		15960 (Pk)		53.37	68.23	-14.86
		15960 (Av)		41.84	54	-12.16
UNII 2c	5500	5500 (Pk)	Vertical	96.97	-	-
		5500 (Av)		84.70	-	-
		5460 (Pk)		43.42	74*	-30.58
		5460 (Av)		31.33	54*	-22.67
		11000 (Pk)		53.64	68.23	-14.59
		11000 (Av)		41.31	54	-12.69
		16500 (Pk)		55.50	68.23	-12.73
		16500 (Av)		43.91	54	-10.09
		5500 (Pk)	Horizontal	108.73	-	-
		5500 (Av)		96.76	-	-
		5460 (Pk)		51.76	74*	-22.24
		5460 (Av)		40.00	54*	-14.00
		11000 (Pk)		52.76	68.23	-15.47
		11000 (Av)		41.37	54	-12.63
		16500 (Pk)		55.61	68.23	-12.62
		16500 (Av)		43.87	54	-10.13
	5600	5600 (Pk)	Vertical	97.61	-	-
		5600 (Av)		85.72	-	-
		5460 (Pk)		43.24	74*	-30.76
		5460 (Av)		30.09	54*	-23.91
		11200 (Pk)		53.71	68.23	-14.52
		11200 (Av)		41.14	54	-12.86
		16800 (Pk)		55.23	68.23	-13.00
		16800 (Av)		44.17	54	-9.83
		5600 (Pk)	Horizontal	108.23	-	-
		5600 (Av)		96.49	-	-
		5460 (Pk)		44.50	74*	-29.50
		5460 (Av)		33.23	54*	-20.77
		11200 (Pk)		52.60	68.23	-15.63
		11200 (Av)		41.15	54	-12.85
		16800 (Pk)		55.44	68.23	-12.79
		16800 (Av)		44.10	54	-9.90

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 91 von 129
Page 91 of 129

	5700	5700 (Pk)	Vertical	94.37	-	-
		5700 (Av)		82.36	-	-
		5460 (Pk)		42.86	74*	-31.14
		5460 (Av)		29.80	54*	-24.20
		11400 (Pk)		53.10	68.23	-15.13
		11400 (Av)		41.98	54	-12.02
		17100 (Pk)		56.58	68.23	-11.65
		17100 (Av)		44.73	54	-9.27
		5700 (Pk)	Horizontal	106.80	-	-
		5700 (Av)		94.87	-	-
		5460 (Pk)		43.06	74*	-30.94
		5460 (Av)		31.03	54*	-22.97
		11400 (Pk)		53.24	68.23	-14.99
		11400 (Av)		41.98	54	-12.02
		17100 (Pk)		57.17	68.23	-11.06
		17100 (Av)		44.78	54	-9.22
UNII 3	5745	5745 (Pk)	Vertical	101.89	-	-
		5745 (Av)		88.96	-	-
		5715(Pk)		67.67	78.2*	-10.53
		5725(Pk)		57.89	78.2*	-20.31
		11490 (Pk)		55.43	68.23	-12.80
		11490 (Av)		42.99	54	-11.01
		17235 (Pk)		56.25	68.23	-11.98
		17235 (Av)		45.02	54	-8.98
		5745 (Pk)	Horizontal	111.50	-	-
		5745 (Av)		99.32	-	-
		5715(Pk)		65.01	78.2*	-13.19
		5725(Pk)		55.56	78.2*	-22.64
		11490 (Pk)		55.14	68.23	-13.09
		11490 (Av)		42.92	54	-11.08
		17235 (Pk)		56.51	68.23	-11.72
		17235 (Av)		44.95	54	-9.05
	5825	5825 (Pk)	Vertical	104.13	-	-
		5825 (Av)		91.17	-	-
		5850 (Pk)		61.74	78.2*	-16.46
		5860 (Pk)		54.44	78.2*	-23.76
		11650 (Pk)		54.02	68.23	-14.21
		11650 (Av)		41.87	54	-12.13
		17475 (Pk)		58.80	68.23	-9.43
		17475 (Av)		46.90	54	-7.10
		5825 (Pk)	Horizontal	111.75	-	-
		5825 (Av)		99.02	-	-
		5850 (Pk)		67.68	78.2*	-10.52
		5860 (Pk)		59.04	78.2*	-19.16
		11650 (Pk)		58.41	68.23	-9.82
		11650 (Av)		44.87	54	-9.13
		17475 (Pk)		59.19	68.23	-9.04
		17475 (Pk)		46.90	54	-7.10

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 92 von 129
Page 92 of 129

Modulation: 802.11ax-HE20
Data rate: MCS11

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5180	5180 (Pk)	Vertical	96.28	-	-
		5180 (Av)		83.48	-	-
		5150 (Pk)		45.38	74*	-28.62
		5150 (Av)		32.66	54*	-21.34
		10360 (Pk)		51.76	68.23	-16.47
		10360 (Av)		39.37	54	-14.63
		15540 (Pk)		53.87	68.23	-14.36
		15540 (Av)		42.01	54	-11.99
		5180 (Pk)	Horizontal	101.31	-	-
		5180 (Av)		88.25	-	-
		5150 (Pk)		50.60	74*	-23.40
		5150 (Av)		35.97	54*	-18.03
		10360 (Pk)		52.10	68.23	-16.13
		10360 (Av)		39.65	54	-14.35
		15540 (Pk)		53.10	68.23	-15.13
		15540 (Av)		41.92	54	-12.08
	5240	5240 (Pk)	Vertical	95.25	-	-
		5240 (Av)		82.31	-	-
		5350 (Pk)		43.08	74*	-30.92
		5350 (Av)		30.59	54*	-23.41
		10480 (Pk)		52.07	68.23	-16.16
		10480 (Av)		40.35	54	-13.65
		15720 (Pk)		54.05	68.23	-14.18
		15720 (Av)		41.71	54	-12.29
		5240 (Pk)	Horizontal	100.50	-	-
		5240 (Av)		87.41	-	-
		5350 (Pk)		44.01	74*	-29.99
		5350(Av)		31.85	54*	-22.15
		10480 (Pk)		52.71	68.23	-15.52
		10480 (Av)		40.41	54	-13.59
		15720 (Pk)		53.14	68.23	-15.09
		15720 (Av)		41.68	54	-12.32

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 93 von 129
Page 93 of 129

UNII 2a	5320	5320 (Pk)	Vertical	97.39	-	-
		5320 (Av)		84.00	-	-
		5350 (Pk)		49.07	74*	-24.93
		5350 (Av)		32.70	54*	-21.30
		10640 (Pk)		53.24	68.23	-14.99
		10640 (Av)		40.37	54	-13.63
		15960 (Pk)		53.94	68.23	-14.29
		15960 (Av)		41.91	54	-12.09
		5320 (Pk)	Horizontal	109.38	-	-
		5320 (Av)		96.59	-	-
		5350 (Pk)		60.86	74*	-13.14
		5350 (Av)		42.48	54*	-11.52
		10640 (Pk)		51.67	68.23	-16.56
		10640 (Av)		40.33	54	-13.67
		15960 (Pk)		54.26	68.23	-13.97
		15960 (Av)		41.85	54	-12.15
UNII 2c	5500	5500 (Pk)	Vertical	90.75	-	-
		5500 (Av)		77.39	-	-
		5460 (Pk)		42.45	74*	-31.55
		5460 (Av)		30.31	54*	-23.69
		11000 (Pk)		53.08	68.23	-15.15
		11000 (Av)		41.29	54	-12.71
		16500 (Pk)		55.54	68.23	-12.69
		16500 (Av)		43.93	54	-10.07
		5500 (Pk)	Horizontal	99.53	-	-
		5500 (Av)		87.19	-	-
		5460 (Pk)		45.59	74*	-28.41
		5460 (Av)		33.69	54*	-20.31
		11000 (Pk)		53.15	68.23	-15.08
		11000 (Av)		41.33	54	-12.67
		16500 (Pk)		55.79	68.23	-12.44
		16500 (Av)		43.99	54	-10.01
	5600	5600 (Pk)	Vertical	89.10	-	-
		5600 (Av)		76.60	-	-
		5460 (Pk)		42.84	74*	-31.16
		5460 (Av)		29.81	54*	-24.19
		11200 (Pk)		52.73	68.23	-15.50
		11200 (Av)		41.11	54	-12.89
		16800 (Pk)		55.58	68.23	-12.65
		16800 (Av)		44.11	54	-9.89
		5600 (Pk)	Horizontal	99.56	-	-
		5600 (Av)		86.24	-	-
		5460 (Pk)		42.88	74*	-31.12
		5460 (Av)		31.10	54*	-22.90
		11200 (Pk)		52.52	68.23	-15.71
		11200 (Av)		41.09	54	-12.91
		16800 (Pk)		55.58	68.23	-12.65
		16800 (Av)		44.13	54	-9.87

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 94 von 129
Page 94 of 129

5700	Vertical	5700 (Pk)	88.88	-	-
		5700 (Av)	76.24	-	-
		5460 (Pk)	42.77	74*	-31.23
		5460 (Av)	29.85	54*	-24.15
		11400 (Pk)	53.58	68.23	-14.65
		11400 (Av)	41.89	54	-12.11
		17100 (Pk)	57.08	68.23	-11.15
		17100 (Av)	44.72	54	-9.28
	Horizontal	5700 (Pk)	96.26	-	-
		5700 (Av)	83.52	-	-
		5460 (Pk)	42.73	74*	-31.27
		5460 (Av)	30.07	54*	-23.93
		11400 (Pk)	54.10	68.23	-14.13
		11400 (Av)	41.89	54	-12.11
		17100 (Pk)	56.26	68.23	-11.97
		17100 (Av)	44.70	54	-9.30
UNII 3	5745	5745 (Pk)	96.07	-	-
		5745 (Av)	82.95	-	-
		5715(Pk)	47.32	78.2*	-30.88
		5725(Pk)	58.10	78.2*	-20.10
		11490 (Pk)	54.83	68.23	-13.40
		11490 (Av)	42.95	54	-11.05
		17235 (Pk)	57.18	68.23	-11.05
		17235 (Av)	45.01	54	-8.99
	Horizontal	5745 (Pk)	103.48	-	-
		5745 (Av)	89.72	-	-
		5715(Pk)	51.03	78.2*	-27.17
		5725(Pk)	63.50	78.2*	-14.70
		11490 (Pk)	59.47	68.23	-8.76
		11490 (Av)	46.20	54	-7.80
		17235 (Pk)	56.40	68.23	-11.83
		17235 (Av)	44.98	54	-9.02
	5825	5825 (Pk)	95.77	-	-
		5825 (Av)	82.95	-	-
		5850 (Pk)	54.82	78.2*	-23.38
		5860 (Pk)	46.32	78.2*	-31.88
		11650 (Pk)	54.21	68.23	-14.02
		11650 (Av)	41.91	54	-12.09
		17475 (Pk)	59.21	68.23	-9.02
		17475 (Av)	46.98	54	-7.02
	Horizontal	5825 (Pk)	103.08	-	-
		5825 (Av)	89.41	-	-
		5850 (Pk)	58.65	78.2*	-19.55
		5860 (Pk)	51.90	78.2*	-26.30
		11650 (Pk)	59.38	68.23	-8.85
		11650 (Av)	45.74	54	-8.26
		17475 (Pk)	58.82	68.23	-9.41
		17475 (Pk)	46.87	54	-7.13

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 95 von 129

Page 95 of 129

Modulation: 802.11n-HT40

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5190	5190 (Pk)	Vertical	94.15	-	-
		5190 (Av)		83.81	-	-
		5150 (Pk)		58.03	74*	-15.97
		5150 (Av)		38.20	54*	-15.80
		10380 (Pk)		51.78	68.23	-16.45
		10380 (Av)		39.76	54	-14.24
		15570 (Pk)		53.15	68.23	-15.08
		15570 (Av)		41.28	54	-12.72
		5190 (Pk)	Horizontal	102.82	-	-
		5190 (Av)		92.32	-	-
		5150 (Pk)		64.82	74*	-9.18
		5150 (Av)		44.84	54*	-9.16
		10380 (Pk)		50.96	68.23	-17.27
		10380 (Av)		39.68	54	-14.32
		15570 (Pk)		54.05	68.23	-14.18
		15570 (Av)		41.20	54	-12.80
	5230	5230 (Pk)	Vertical	95.48	-	-
		5230 (Av)		84.92	-	-
		5150 (Pk)		44.03	74*	-29.97
		5150 (Av)		31.86	54*	-22.14
		10460 (Pk)		52.82	68.23	-15.41
		10460 (Av)		40.13	54	-13.87
		15690 (Pk)		53.69	68.23	-14.54
		15690 (Av)		41.17	54	-12.83
		5230 (Pk)	Horizontal	101.61	-	-
		5230 (Av)		91.38	-	-
		5150 (Pk)		49.37	74*	-24.63
		5150 (Av)		36.75	54*	-17.25
		10460 (Pk)		56.57	68.23	-11.66
		10460 (Av)		40.14	54	-13.86
		15690 (Pk)		53.63	68.23	-14.60
		15690 (Av)		41.16	54	-12.84

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 96 von 129
Page 96 of 129

UNII 2a	5270	5270 (Pk)	Vertical	95.47	-	-
		5270 (Av)		85.12	-	-
		5350 (Pk)		48.59	74*	-25.41
		5350 (Av)		33.74	54*	-20.26
		10540 (Pk)		52.52	68.23	-15.71
		10540 (Av)		40.16	54	-13.84
		15810 (Pk)		53.77	68.23	-14.46
		15810 (Av)		40.96	54	-13.04
		5270 (Pk)	Horizontal	103.29	-	-
		5270 (Av)		93.23	-	-
		5350 (Pk)		53.69	74*	-20.31
		5350 (Av)		39.40	54*	-14.60
		10540 (Pk)		52.62	68.23	-15.61
		10540 (Av)		40.12	54	-13.88
		15810 (Pk)		53.07	68.23	-15.16
		15810 (Av)		40.96	54	-13.04
UNII 2c	5510	5510 (Pk)	Vertical	92.89	-	-
		5510 (Av)		82.43	-	-
		5460 (Pk)		49.83	74*	-24.17
		5460 (Av)		33.79	54*	-20.21
		11020 (Pk)		52.93	68.23	-15.30
		11020 (Av)		41.15	54	-12.85
		16530 (Pk)		54.63	68.23	-13.60
		16530 (Av)		43.05	54	-10.95
		5510 (Pk)	Horizontal	100.65	-	-
		5510 (Av)		90.28	-	-
		5460 (Pk)		56.40	74*	-17.60
		5460 (Av)		41.22	54*	-12.78
		11020 (Pk)		54.31	68.23	-13.92
		11020 (Av)		41.12	54	-12.88
		16530 (Pk)		55.70	68.23	-12.53
		16530 (Av)		43.05	54	-10.95
	5590	5590 (Pk)	Vertical	91.90	-	-
		5590 (Av)		81.22	-	-
		5460 (Pk)		44.16	74*	-29.84
		5460 (Av)		30.83	54*	-23.17
		11180 (Pk)		54.03	68.23	-14.20
		11180 (Av)		40.76	54	-13.24
		16770 (Pk)		56.35	68.23	-11.88
		16770 (Av)		43.75	54	-10.25
		5590 (Pk)	Horizontal	99.99	-	-
		5590(Av)		89.56	-	-
		5460 (pk)		46.68	74*	-27.32
		5460(Av)		34.12	54*	-19.88
		11180 (Pk)		52.84	68.23	-15.39
		11180(Av)		40.72	54	-13.28
		16770 (Pk)		56.04	68.23	-12.19
		16770 (Av)		43.73	54	-10.27

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 97 von 129
Page 97 of 129

5670	Vertical	5670 (Pk)	93.45	-	-
		5670 (Av)	82.94	-	-
		5460 (Pk)	43.47	74*	-30.53
		5460 (Av)	30.17	54*	-23.83
		11340 (Pk)	53.40	68.23	-14.83
		11340 (Av)	41.35	54	-12.65
		17010 (Pk)	55.99	68.23	-12.24
		17010 (Av)	43.73	54	-10.27
	Horizontal	5670 (Pk)	100.90	-	-
		5670 (Av)	90.39	-	-
		5460 (Pk)	44.15	74*	-29.85
		5460 (Av)	31.78	54*	-22.22
		11340 (Pk)	53.49	68.23	-14.74
		11340 (Av)	41.33	54	-12.67
		17010 (Pk)	55.82	68.23	-12.41
		17010 (Av)	43.75	54	-10.25
UNII 3	5755	5755 (Pk)	93.03	-	-
		5755 (Av)	81.99	-	-
		5715(Pk)	61.49	78.2*	-16.71
		5725(Pk)	62.76	78.2*	-15.44
		11510 (Pk)	54.10	68.23	-14.13
		11510 (Av)	42.81	54	-11.19
		17265 (Pk)	57.39	68.23	-10.84
		17265 (Av)	44.76	54	-9.24
	Horizontal	5755 (Pk)	103.09	-	-
		5755 (Av)	93.77	-	-
		5715(Pk)	70.58	78.2*	-7.62
		5725(Pk)	73.11	78.2*	-5.09
		11510 (Pk)	55.06	68.23	-13.17
		11510 (Av)	42.64	54	-11.36
		17265 (Pk)	57.68	68.23	-10.55
		17265 (Av)	44.69	54	-9.31
	5795	5795 (Pk)	100.44	-	-
		5795 (Av)	89.75	-	-
		5850 (Pk)	62.45	78.2*	-15.75
		5860 (Pk)	61.83	78.2*	-16.37
		11590 (Pk)	54.33	68.23	-13.90
		11590 (Av)	42.41	54	-11.59
		17385 (Pk)	57.90	68.23	-10.33
		17385 (Av)	45.79	54	-8.21
	Horizontal	5795 (Pk)	97.33	-	-
		5795 (Av)	86.75	-	-
		5850 (Pk)	62.97	78.2*	-15.23
		5860 (Pk)	60.73	78.2*	-17.47
		11590 (Pk)	61.03	68.23	-7.20
		11590 (Av)	46.96	54	-7.04
		17385 (Pk)	57.41	68.23	-10.82
		17385 (Av)	45.54	54	-8.46

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 98 von 129

Page 98 of 129

Modulation: 802.11n-HT40

Data rate: MCS7

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
UNII 1	5190	5190 (Pk)	Vertical	91.77	-	-
		5190 (Av)		76.72	-	-
		5150 (Pk)		51.22	74*	-22.78
		5150 (Av)		33.58	54*	-20.42
		10380 (Pk)		51.57	68.23	-16.66
		10380 (Av)		39.61	54	-14.39
		15570 (Pk)		53.15	68.23	-15.08
		15570 (Av)		41.33	54	-12.67
		5190 (Pk)	Horizontal	102.33	-	-
		5190 (Av)		87.10	-	-
		5150 (Pk)		59.42	74*	-14.58
		5150 (Av)		39.76	54*	-14.24
		10380 (Pk)		51.44	68.23	-16.79
		10380 (Av)		39.54	54	-14.46
		15570 (Pk)		53.81	68.23	-14.42
		15570 (Av)		41.34	54	-12.66
	5230	5230 (Pk)	Vertical	95.94	-	-
		5230 (Av)		80.75	-	-
		5150 (Pk)		45.05	74*	-28.95
		5150 (Av)		31.57	54*	-22.43
		10460 (Pk)		51.70	68.23	-16.53
		10460 (Av)		40.22	54	-13.78
		15690 (Pk)		54.03	68.23	-14.20
		15690 (Av)		41.36	54	-12.64
		5230 (Pk)	Horizontal	102.74	-	-
		5230 (Av)		86.95	-	-
		5150 (Pk)		50.27	74*	-23.73
		5150 (Av)		35.37	54*	-18.63
		10460 (Pk)		53.12	68.23	-15.11
		10460 (Av)		40.20	54	-13.80
		15690 (Pk)		53.78	68.23	-14.45
		15690 (Av)		41.35	54	-12.65

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 99 von 129
Page 99 of 129

UNII 2a	5270	5270 (Pk)	Vertical	94.83	-	-
		5270 (Av)		79.64	-	-
		5350 (Pk)		45.33	74*	-28.67
		5350 (Av)		31.55	54*	-22.45
		10540 (Pk)		52.51	68.23	-15.72
		10540 (Av)		40.38	54	-13.62
		15810 (Pk)		52.66	68.23	-15.57
		15810 (Av)		41.15	54	-12.85
		5270 (Pk)	Horizontal	98.23	-	-
		5270 (Av)		83.57	-	-
		5350 (Pk)		48.24	74*	-25.76
		5350 (Av)		33.50	54*	-20.50
		10540 (Pk)		52.91	68.23	-15.32
		10540 (Av)		40.40	54	-13.60
		15810 (Pk)		52.95	68.23	-15.28
		15810 (Av)		41.19	54	-12.81
UNII 2c	5510	5510 (Pk)	Vertical	91.97	-	-
		5510 (Av)		76.34	-	-
		5460 (Pk)		47.06	74*	-26.94
		5460 (Av)		31.67	54*	-22.33
		11020 (Pk)		53.51	68.23	-14.72
		11020 (Av)		41.38	54	-12.62
		16530 (Pk)		54.67	68.23	-13.56
		16530 (Av)		43.28	54	-10.72
		5510 (Pk)	Horizontal	99.11	-	-
		5510 (Av)		83.95	-	-
		5460 (Pk)		55.30	74*	-18.70
		5460 (Av)		36.54	54*	-17.46
		11020 (Pk)		53.35	68.23	-14.88
		11020 (Av)		41.40	54	-12.60
		16530 (Pk)		55.27	68.23	-12.96
		16530 (Av)		43.25	54	-10.75
	5590	5590 (Pk)	Vertical	90.51	-	-
		5590 (Av)		75.10	-	-
		5460 (Pk)		43.31	74*	-30.69
		5460 (Av)		30.48	54*	-23.52
		11180 (Pk)		52.62	68.23	-15.61
		11180 (Av)		40.99	54	-13.01
		16770 (Pk)		56.29	68.23	-11.94
		16770 (Pk)		44.09	54	-9.91
		5590 (Pk)	Horizontal	98.23	-	-
		5590 (Av)		84.40	-	-
		5460 (Pk)		44.85	74*	-29.15
		5460 (Av)		31.84	54*	-22.16
		11180 (Pk)		53.28	68.23	-14.95
		11180 (Av)		41.05	54	-12.95
		16770 (Pk)		55.38	68.23	-12.85
		16770 (Pk)		44.04	54	-9.96

	5670	5670 (Pk)	Vertical	89.54	-	-
		5670 (Av)		74.34	-	-
		5460 (Pk)		43.06	74*	-30.94
		5460 (Av)		30.14	54*	-23.86
		11340 (Pk)		53.33	68.23	-14.90
		11340 (Av)		40.71	54	-13.29
		17010 (Pk)		55.61	68.23	-12.62
		17010 (Av)		42.89	54	-11.11
		5670 (Pk)	Horizontal	99.93	-	-
		5670 (Av)		85.01	-	-
		5460 (Pk)		42.84	74*	-31.16
		5460 (Av)		30.90	54*	-23.10
		11340 (Pk)		52.31	68.23	-15.92
		11340 (Av)		40.70	54	-13.30
		17010 (Pk)		54.86	68.23	-13.37
		17010 (Av)		42.89	54	-11.11
UNII 3	5755	5755 (Pk)	Vertical	96.60	-	-
		5755 (Av)		80.87	-	-
		5715(Pk)		66.47	78.2*	-11.73
		5725(Pk)		64.05	78.2*	-14.15
		11510 (Pk)		53.90	68.23	-14.33
		11510 (Av)		41.83	54	-12.17
		17265 (Pk)		55.40	68.23	-12.83
		17265 (Av)		43.34	54	-10.66
		5755 (Pk)	Horizontal	103.65	-	-
		5755 (Av)		89.95	-	-
		5715(Pk)		70.84	78.2*	-7.36
		5725(Pk)		73.70	78.2*	-4.50
		11510 (Pk)		53.65	68.23	-14.58
		11510 (Av)		41.84	54	-12.16
		17265 (Pk)		55.15	68.23	-13.08
		17265 (Av)		43.33	54	-10.67
	5795	5795 (Pk)	Vertical	96.13	-	-
		5795 (Av)		80.56	-	-
		5850 (Pk)		53.61	78.2*	-24.59
		5860 (Pk)		49.79	78.2*	-28.41
		11590 (Pk)		54.97	68.23	-13.26
		11590 (Av)		42.32	54	-11.68
		17385 (Pk)		58.64	68.23	-9.59
		17385 (Av)		45.79	54	-8.21
		5795 (Pk)	Horizontal	101.00	-	-
		5795 (Av)		85.14	-	-
		5850 (Pk)		59.63	78.2*	-18.57
		5860 (Pk)		58.19	78.2*	-20.01
		11590 (Pk)		56.91	68.23	-11.32
		11590 (Av)		43.54	54	-10.46
		17385 (Pk)		58.34	68.23	-9.89
		17385 (Av)		45.76	54	-8.24

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 101 von 129

Page 101 of 129

Modulation: 802.11ac-VHT40

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5190	5190 (Pk)	Vertical	90.08	-	-
		5190 (Av)		80.27	-	-
		5150 (Pk)		54.90	74*	-19.10
		5150 (Av)		35.82	54*	-18.18
		10380 (Pk)		53.42	68.23	-14.81
		10380 (Av)		41.17	54	-12.83
		15570 (Pk)		52.88	68.23	-15.35
		15570 (Av)		40.68	54	-13.32
		5190 (Pk)	Horizontal	98.50	-	-
		5190 (Av)		88.58	-	-
		5150 (Pk)		63.85	74*	-10.15
		5150 (Av)		44.30	54*	-9.70
		10380 (Pk)		53.01	68.23	-15.22
		10380 (Av)		41.10	54	-12.90
		15570 (Pk)		51.66	68.23	-16.57
		15570 (Av)		40.69	54	-13.31
	5230	5230 (Pk)	Vertical	90.08	-	-
		5230 (Av)		80.83	-	-
		5150 (Pk)		42.38	74*	-31.62
		5150 (Av)		30.58	54*	-23.42
		10460 (Pk)		52.25	68.23	-15.98
		10460 (Av)		40.05	54	-13.95
		15690 (Pk)		52.85	68.23	-15.38
		15690 (Av)		40.62	54	-13.38
		5230 (Pk)	Horizontal	95.04	-	-
		5230 (Av)		85.28	-	-
		5150 (Pk)		44.50	74*	-29.50
		5150 (Av)		32.12	54*	-21.88
		10460 (Pk)		51.59	68.23	-16.64
		10460 (Av)		40.03	54	-13.97
		15690 (Pk)		52.45	68.23	-15.78
		15690 (Av)		40.61	54	-13.39

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 102 von 129
Page 102 of 129

UNII 2a	5270	5270 (Pk)	Vertical	90.87	-	-
		5270 (Av)		81.07	-	-
		5350 (Pk)		42.41	74*	-31.59
		5350 (Av)		30.95	54*	-23.05
		10540 (Pk)		52.89	68.23	-15.34
		10540 (Av)		40.21	54	-13.79
		15810 (Pk)		52.46	68.23	-15.77
		15810 (Av)		40.72	54	-13.28
		5270 (Pk)	Horizontal	103.41	-	-
		5270 (Av)		93.65	-	-
		5350 (Pk)		51.33	74*	-22.67
		5350 (Av)		39.51	54*	-14.49
		10540 (Pk)		51.86	68.23	-16.37
		10540 (Av)		40.18	54	-13.82
		15810 (Pk)		52.63	68.23	-15.60
		15810 (Av)		40.74	54	-13.26
UNII 2c	5510	5510 (Pk)	Vertical	89.91	-	-
		5510 (Av)		80.84	-	-
		5460 (Pk)		50.67	74*	-23.33
		5460 (Av)		33.24	54*	-20.76
		11020 (Pk)		52.35	68.23	-15.88
		11020 (Av)		40.88	54	-13.12
		16530 (Pk)		53.88	68.23	-14.35
		16530 (Av)		42.44	54	-11.56
		5510 (Pk)	Horizontal	94.65	-	-
		5510 (Av)		85.29	-	-
		5460 (Pk)		52.45	74*	-21.55
		5460 (Av)		36.13	54*	-17.87
		11020 (Pk)		52.56	68.23	-15.67
		11020 (Av)		40.83	54	-13.17
		16530 (Pk)		53.47	68.23	-14.76
		16530 (Av)		42.39	54	-11.61
	5590	5590 (Pk)	Vertical	91.05	-	-
		5590 (Av)		81.34	-	-
		5460 (Pk)		42.19	74*	-31.81
		5460 (Av)		30.52	54*	-23.48
		11180 (Pk)		51.81	68.23	-16.42
		11180 (Av)		40.38	54	-13.62
		16770 (Pk)		55.26	68.23	-12.97
		16770 (Av)		43.29	54	-10.71
		5590 (Pk)	Horizontal	101.27	-	-
		5590 (Av)		91.74	-	-
		5460 (Pk)		45.97	74*	-28.03
		5460 (Av)		34.86	54*	-19.14
		11180 (Pk)		53.17	68.23	-15.06
		11180 (Av)		40.42	54	-13.58
		16770 (Pk)		55.44	68.23	-12.79
		16770 (Av)		43.27	54	-10.73

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 103 von 129
Page 103 of 129

5670	Vertical	5670 (Pk)	87.35	-	-
		5670 (Av)	78.42	-	-
		5460 (Pk)	42.56	74*	-31.44
		5460 (Av)	30.06	54*	-23.94
		11340 (Pk)	52.30	68.23	-15.93
		11340 (Av)	40.76	54	-13.24
		17010 (Pk)	54.30	68.23	-13.93
		17010 (Av)	42.96	54	-11.04
	Horizontal	5670 (Pk)	99.43	-	-
		5670 (Av)	89.77	-	-
		5460 (Pk)	43.66	74*	-30.34
		5460 (Av)	31.44	54*	-22.56
		11340 (Pk)	52.19	68.23	-16.04
		11340 (Av)	40.71	54	-13.29
		17010 (Pk)	55.02	68.23	-13.21
		17010 (Av)	42.88	54	-11.12
UNII 3	Vertical	5755 (Pk)	95.72	-	-
		5755 (Av)	84.76	-	-
		5715(Pk)	67.88	78.2*	-10.32
		5725(Pk)	69.16	78.2*	-9.04
		11510 (Pk)	56.67	68.23	-11.56
		11510 (Av)	42.00	54	-12.00
		17265 (Pk)	55.34	68.23	-12.89
		17265 (Av)	43.38	54	-10.62
	Horizontal	5755 (Pk)	107.60	-	-
		5755 (Av)	94.76	-	-
		5715(Pk)	73.42	78.2*	-4.78
		5725(Pk)	75.60	78.2*	-2.60
		11510 (Pk)	53.97	68.23	-14.26
		11510 (Av)	41.91	54	-12.09
		17265 (Pk)	54.71	68.23	-13.52
		17265 (Av)	43.37	54	-10.63
	Vertical	5795 (Pk)	99.05	-	-
		5795 (Av)	89.03	-	-
		5850 (Pk)	61.58	78.2*	-16.62
		5860 (Pk)	58.77	78.2*	-19.43
		11590 (Pk)	55.01	68.23	-13.22
		11590 (Av)	42.36	54	-11.64
		17385 (Pk)	57.18	68.23	-11.05
		17385 (Av)	45.81	54	-8.19
	Horizontal	5795 (Pk)	97.29	-	-
		5795 (Av)	87.55	-	-
		5850 (Pk)	60.09	78.2*	-18.11
		5860 (Pk)	59.00	78.2*	-19.20
		11590 (Pk)	66.21	68.23	-2.02
		11590 (Av)	52.02	54	-1.98
		17385 (Pk)	57.85	68.23	-10.38
		17385 (Av)	45.79	54	-8.21

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 104 von 129

Page 104 of 129

Modulation: 802.11ac-VHT40

Data rate: MCS9

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5190	5190 (Pk)	Vertical	87.37	-	-
		5190 (Av)		72.40	-	-
		5150 (Pk)		47.36	74*	-26.64
		5150 (Av)		31.52	54*	-22.48
		10380 (Pk)		52.84	68.23	-15.39
		10380 (Av)		39.51	54	-14.49
		15570 (Pk)		52.93	68.23	-15.30
		15570 (Av)		40.68	54	-13.32
		5190 (Pk)	Horizontal	95.32	-	-
		5190 (Av)		79.84	-	-
		5150 (Pk)		49.83	74*	-24.17
		5150 (Av)		34.34	54*	-19.66
		10380 (Pk)		51.75	68.23	-16.48
		10380 (Av)		39.47	54	-14.53
		15570 (Pk)		52.42	68.23	-15.81
		15570 (Av)		40.71	54	-13.29
	5230	5230 (Pk)	Vertical	89.64	-	-
		5230 (Av)		75.20	-	-
		5150 (Pk)		42.44	74*	-31.56
		5150 (Av)		30.73	54*	-23.27
		10460 (Pk)		52.01	68.23	-16.22
		10460 (Av)		40.02	54	-13.98
		15690 (Pk)		52.07	68.23	-16.16
		15690 (Av)		40.56	54	-13.44
		5230 (Pk)	Horizontal	101.41	-	-
		5230 (Av)		87.96	-	-
		5150 (Pk)		49.17	74*	-24.83
		5150 (Av)		35.98	54*	-18.02
		10460 (Pk)		51.57	68.23	-16.66
		10460 (Av)		39.99	54	-14.01
		15690 (Pk)		52.20	68.23	-16.03
		15690 (Av)		40.60	54	-13.40

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 105 von 129
Page 105 of 129

UNII 2a	5270	5270 (Pk)	Vertical	91.26	-	-
		5270 (Av)		77.13	-	-
		5350 (Pk)		43.82	74*	-30.18
		5350 (Av)		30.96	54*	-23.04
		10540 (Pk)		51.83	68.23	-16.40
		10540 (Av)		40.23	54	-13.77
		15810 (Pk)		52.49	68.23	-15.74
		15810 (Av)		40.82	54	-13.18
		5270 (Pk)	Horizontal	97.37	-	-
		5270 (Av)		82.88	-	-
		5350 (Pk)		46.21	74*	-27.79
		5350 (Av)		32.97	54*	-21.03
		10540 (Pk)		52.12	68.23	-16.11
		10540 (Av)		40.26	54	-13.74
		15810 (Pk)		52.90	68.23	-15.33
		15810 (Av)		40.83	54	-13.17
UNII 2c	5510	5510 (Pk)	Vertical	90.25	-	-
		5510 (Av)		75.94	-	-
		5460 (Pk)		47.62	74*	-26.38
		5460 (Av)		32.52	54*	-21.48
		11020 (Pk)		52.36	68.23	-15.87
		11020 (Av)		40.80	54	-13.20
		16530 (Pk)		53.81	68.23	-14.42
		16530 (Av)		42.26	54	-11.74
		5510 (Pk)	Horizontal	96.92	-	-
		5510 (Av)		81.83	-	-
		5460 (Pk)		52.48	74*	-21.52
		5460 (Av)		36.03	54*	-17.97
		11020 (Pk)		52.48	68.23	-15.75
		11020 (Av)		40.79	54	-13.21
		16530 (Pk)		53.71	68.23	-14.52
		16530 (Av)		42.33	54	-11.67
	5590	5590 (Pk)	Vertical	88.98	-	-
		5590 (Av)		74.76	-	-
		5460 (Pk)		42.71	74*	-31.29
		5460 (Av)		30.43	54*	-23.57
		11180 (Pk)		51.73	68.23	-16.50
		11180 (Av)		40.33	54	-13.67
		16770 (Pk)		55.91	68.23	-12.32
		16770 (Av)		43.25	54	-10.75
		5590 (Pk)	Horizontal	98.23	-	-
		5590 (Av)		83.84	-	-
		5460 (Pk)		44.42	74*	-29.58
		5460 (Av)		32.30	54*	-21.70
		11180 (Pk)		51.47	68.23	-16.76
		11180 (Av)		40.39	54	-13.61
		16770 (Pk)		55.36	68.23	-12.87
		16770 (Av)		43.27	54	-10.73

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 106 von 129
Page 106 of 129

5670	Vertical	5670 (Pk)	90.34	-	-
		5670 (Av)	76.46	-	-
		5460 (Pk)	43.09	74*	-30.91
		5460 (Av)	30.11	54*	-23.89
		11340 (Pk)	52.56	68.23	-15.67
		11340 (Av)	40.77	54	-13.23
		17010 (Pk)	53.75	68.23	-14.48
		17010 (Av)	42.71	54	-11.29
	Horizontal	5670 (Pk)	99.53	-	-
		5670 (Av)	86.03	-	-
		5460 (Pk)	43.98	74*	-30.02
		5460 (Av)	31.13	54*	-22.87
		11340 (Pk)	52.14	68.23	-16.09
		11340 (Av)	40.78	54	-13.22
		17010 (Pk)	54.96	68.23	-13.27
		17010 (Av)	42.75	54	-11.25
UNII 3	5755	5755 (Pk)	94.18	-	-
		5755 (Av)	82.60	-	-
		5715(Pk)	62.43	78.2*	-15.77
		5725(Pk)	65.43	78.2*	-12.77
		11510 (Pk)	53.43	68.23	-14.80
		11510 (Av)	41.89	54	-12.11
		17265 (Pk)	54.23	68.23	-14.00
		17265 (Av)	43.03	54	-10.97
	Horizontal	5755 (Pk)	105.33	-	-
		5755 (Av)	94.29	-	-
		5715(Pk)	71.68	78.2*	-6.52
		5725(Pk)	74.99	78.2*	-3.21
		11510 (Pk)	53.79	68.23	-14.44
		11510 (Av)	41.99	54	-12.01
		17265 (Pk)	54.97	68.23	-13.26
		17265 (Av)	43.08	54	-10.92
	5795	5795 (Pk)	98.61	-	-
		5795 (Av)	82.98	-	-
		5850 (Pk)	60.49	78.2*	-17.71
		5860 (Pk)	54.45	78.2*	-23.75
		11590 (Pk)	54.54	68.23	-13.69
		11590 (Av)	42.34	54	-11.66
		17385 (Pk)	57.38	68.23	-10.85
		17385 (Av)	45.79	54	-8.21
	Horizontal	5795 (Pk)	108.63	-	-
		5795 (Av)	93.62	-	-
		5850 (Pk)	70.18	78.2*	-8.02
		5860 (Pk)	63.45	78.2*	-14.75
		11590 (Pk)	54.91	68.23	-13.32
		11590 (Av)	42.73	54	-11.27
		17385 (Pk)	58.09	68.23	-10.14
		17385 (Av)	45.79	54	-8.21

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 107 von 129

Page 107 of 129

Modulation: 802.11ax-HE40

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5190	5190 (Pk)	Vertical	93.96	-	-
		5190 (Av)		81.73	-	-
		5150 (Pk)		53.19	74*	-20.81
		5150 (Av)		37.19	54*	-16.81
		10380 (Pk)		50.77	68.23	-17.46
		10380 (Av)		39.27	54	-14.73
		15570 (Pk)		52.89	68.23	-15.34
		15570 (Av)		40.86	54	-13.14
		5190 (Pk)	Horizontal	104.99	-	-
		5190 (Av)		92.49	-	-
		5150 (Pk)		61.93	74*	-12.07
		5150 (Av)		46.57	54*	-7.43
		10380 (Pk)		51.20	68.23	-17.03
		10380 (Av)		39.32	54	-14.68
		15570 (Pk)		53.52	68.23	-14.71
		15570 (Av)		40.84	54	-13.16
	5230	5230 (Pk)	Vertical	92.89	-	-
		5230 (Av)		80.46	-	-
		5150 (Pk)		43.31	74*	-30.69
		5150 (Av)		31.17	54*	-22.83
		10460 (Pk)		52.04	68.23	-16.19
		10460 (Av)		40.16	54	-13.84
		15690 (Pk)		52.66	68.23	-15.57
		15690 (Av)		41.20	54	-12.80
		5230 (Pk)	Horizontal	97.61	-	-
		5230 (Av)		85.17	-	-
		5150 (Pk)		44.08	74*	-29.92
		5150 (Av)		32.13	54*	-21.87
		10460 (Pk)		51.89	68.23	-16.34
		10460 (Av)		40.23	54	-13.77
		15690 (Pk)		52.36	68.23	-15.87
		15690 (Av)		41.21	54	-12.79

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 108 von 129
Page 108 of 129

UNII 2a	5270	5270 (Pk)	Vertical	94.78	-	-
		5270 (Av)		82.06	-	-
		5350 (Pk)		45.73	74*	-28.27
		5350 (Av)		31.85	54*	-22.15
		10540 (Pk)		51.98	68.23	-16.25
		10540 (Av)		40.24	54	-13.76
		15810 (Pk)		53.02	68.23	-15.21
		15810 (Av)		41.16	54	-12.84
		5270 (Pk)	Horizontal	106.33	-	-
		5270 (Av)		93.50	-	-
		5350 (Pk)		52.84	74*	-21.16
		5350 (Av)		39.85	54*	-14.15
		10540 (Pk)		52.25	68.23	-15.98
		10540 (Av)		40.22	54	-13.78
		15810 (Pk)		52.71	68.23	-15.52
		15810 (Av)		41.13	54	-12.87
UNII 2c	5510	5510 (Pk)	Vertical	93.57	-	-
		5510 (Av)		81.04	-	-
		5460 (Pk)		47.33	74*	-26.67
		5460 (Av)		33.71	54*	-20.29
		11020 (Pk)		52.23	68.23	-16.00
		11020 (Av)		40.88	54	-13.12
		16530 (Pk)		54.38	68.23	-13.85
		16530 (Av)		42.50	54	-11.50
		5510 (Pk)	Horizontal	98.10	-	-
		5510 (Av)		85.77	-	-
		5460 (Pk)		53.44	74*	-20.56
		5460 (Av)		36.75	54*	-17.25
		11020 (Pk)		52.79	68.23	-15.44
		11020 (Av)		40.92	54	-13.08
		16530 (Pk)		54.48	68.23	-13.75
		16530 (Av)		42.56	54	-11.44
	5590	5590 (Pk)	Vertical	93.26	-	-
		5590 (Av)		80.39	-	-
		5460 (Pk)		42.63	74*	-31.37
		5460 (Av)		30.43	54*	-23.57
		11180 (Pk)		52.34	68.23	-15.89
		11180 (Av)		40.51	54	-13.49
		16770 (Pk)		55.52	68.23	-12.71
		5590 (Pk)		43.46	54	-10.54
		5590 (Pk)	Horizontal	104.67	-	-
		5590 (Av)		91.84	-	-
		5460 (Pk)		47.33	74*	-26.67
		5460 (Av)		35.35	54*	-18.65
		11180 (Pk)		53.30	68.23	-14.93
		11180 (Av)		40.57	54	-13.43
		16770 (Pk)		54.40	68.23	-13.83
		16770 (Av)		42.55	54	-11.45

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 109 von 129
Page 109 of 129

	5670	5670 (Pk)	Vertical	91.86	-	-
		5670 (Av)		79.11	-	-
		5460 (Pk)		42.05	74*	-31.95
		5460 (Av)		29.91	54*	-24.09
		11340 (Pk)		53.10	68.23	-15.13
		11340 (Av)		41.10	54	-12.90
		17010 (Pk)		55.06	68.23	-13.17
		17010 (Av)		42.77	54	-11.23
		5670 (Pk)	Horizontal	100.78	-	-
		5670 (Av)		88.10	-	-
		5460 (Pk)		42.46	74*	-31.54
		5460 (Av)		31.45	54*	-22.55
		11340 (Pk)		52.79	68.23	-15.44
		11340 (Av)		40.97	54	-13.03
		17010 (Pk)		54.80	68.23	-13.43
		17010 (Av)		42.86	54	-11.14
UNII 3	5755	5755 (Pk)	Vertical	93.29	-	-
		5755 (Av)		81.82	-	-
		5715(Pk)		61.33	78.2*	-16.87
		5725(Pk)		63.60	78.2*	-14.60
		11510 (Pk)		54.66	68.23	-13.57
		11510 (Av)		42.67	54	-11.33
		17265 (Pk)		55.56	68.23	-12.67
		17265 (Av)		43.95	54	-10.05
		5755 (Pk)	Horizontal	105.86	-	-
		5755 (Av)		94.34	-	-
		5715(Pk)		68.83	78.2*	-9.37
		5725(Pk)		72.39	78.2*	-5.81
		11510 (Pk)		54.24	68.23	-13.99
		11510 (Av)		42.66	54	-11.34
		17265 (Pk)		55.63	68.23	-12.60
		17265 (Av)		43.91	54	-10.09
	5795	5795 (Pk)	Vertical	97.17	-	-
		5795 (Av)		83.74	-	-
		5850 (Pk)		57.33	78.2*	-20.87
		5860 (Pk)		54.85	78.2*	-23.35
		11590 (Pk)		56.18	68.23	-12.05
		11590 (Av)		43.38	54	-10.62
		17385 (Pk)		57.90	68.23	-10.33
		17385 (Av)		45.80	54	-8.20
		5795 (Pk)	Horizontal	110.75	-	-
		5795 (Av)		97.37	-	-
		5850 (Pk)		71.12	78.2*	-7.08
		5860 (Pk)		67.61	78.2*	-10.59
		11590 (Pk)		58.60	68.23	-9.63
		11590 (Av)		45.14	54	-8.86
		17385 (Pk)		57.71	68.23	-10.52
		17385 (Av)		45.84	54	-8.16

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 110 von 129

Page 110 of 129

Modulation: 802.11ax-HE40

Data rate: MCS11

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5190	5190 (Pk)	Vertical	93.05	-	-
		5190 (Av)		79.99	-	-
		5150 (Pk)		51.46	74*	-22.54
		5150 (Av)		35.67	54*	-18.33
		10380 (Pk)		51.39	68.23	-16.84
		10380 (Av)		39.27	54	-14.73
		15570 (Pk)		52.71	68.23	-15.52
		15570 (Av)		40.64	54	-13.36
		5190 (Pk)	Horizontal	104.27	-	-
		5190 (Av)		90.55	-	-
		5150 (Pk)		59.49	74*	-14.51
		5150 (Av)		43.67	54*	-10.33
		10380 (Pk)		50.49	68.23	-17.74
		10380 (Av)		39.25	54	-14.75
		15570 (Pk)		52.47	68.23	-15.76
		15570 (Av)		40.44	54	-13.56
	5230	5230 (Pk)	Vertical	92.93	-	-
		5230 (Av)		79.46	-	-
		5150 (Pk)		43.87	74*	-30.13
		5150 (Av)		30.88	54*	-23.12
		10460 (Pk)		51.27	68.23	-16.96
		10460 (Av)		39.87	54	-14.13
		15690 (Pk)		51.66	68.23	-16.57
		15690 (Av)		40.54	54	-13.46
		5230 (Pk)	Horizontal	101.46	-	-
		5230 (Av)		88.81	-	-
		5150 (Pk)		46.19	74*	-27.81
		5150 (Av)		34.33	54*	-19.67
		10460 (Pk)		51.31	68.23	-16.92
		10460 (Av)		39.81	54	-14.19
		15690 (Pk)		51.85	68.23	-16.38
		15690 (Av)		40.52	54	-13.48

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 111 von 129
Page 111 of 129

UNII 2a	5270	5270 (Pk)	Vertical	94.88	-	-
		5270 (Av)		81.56	-	-
		5350 (Pk)		45.31	74*	-28.69
		5350 (Av)		32.23	54*	-21.77
		10540 (Pk)		51.37	68.23	-16.86
		10540 (Av)		40.15	54	-13.85
		15810 (Pk)		52.64	68.23	-15.59
		15810 (Av)		41.14	54	-12.86
		5270 (Pk)	Horizontal	106.39	-	-
		5270 (Av)		92.92	-	-
		5350 (Pk)		51.64	74*	-22.36
		5350 (Av)		38.22	54*	-15.78
		10540 (Pk)		52.17	68.23	-16.06
		10540 (Av)		40.17	54	-13.83
		15810 (Pk)		53.56	68.23	-14.67
		15810 (Av)		41.16	54	-12.84
UNII 2c	5510	5510 (Pk)	Vertical	84.52	-	-
		5510 (Av)		70.67	-	-
		5460 (Pk)		42.63	74*	-31.37
		5460 (Av)		30.06	54*	-23.94
		11020 (Pk)		52.76	68.23	-15.47
		11020 (Av)		41.05	54	-12.95
		16530 (Pk)		55.29	68.23	-12.94
		16530 (Av)		43.23	54	-10.77
		5510 (Pk)	Horizontal	94.86	-	-
		5510 (Av)		81.62	-	-
		5460 (Pk)		44.70	74*	-29.30
		5460 (Av)		32.74	54*	-21.26
		11020 (Pk)		52.52	68.23	-15.71
		11020 (Av)		41.12	54	-12.88
		16530 (Pk)		55.88	68.23	-12.35
		16530 (Av)		43.23	54	-10.77
	5590	5590 (Pk)	Vertical	84.71	-	-
		5590 (Av)		70.90	-	-
		5460 (Pk)		41.94	74*	-32.06
		5460 (Av)		29.94	54*	-24.06
		11180 (Pk)		52.40	68.23	-15.83
		11180 (Av)		40.64	54	-13.36
		16770 (Pk)		55.20	68.23	-13.03
		16770 (Av)		43.58	54	-10.42
		5590 (Pk)	Horizontal	92.19	-	-
		5590 (Av)		79.11	-	-
		5460 (Pk)		42.90	74*	-31.10
		5460 (Av)		30.59	54*	-23.41
		11180 (Pk)		52.35	68.23	-15.88
		11180 (Av)		40.68	54	-13.32
		16770 (Pk)		55.87	68.23	-12.36
		16770 (Av)		43.65	54	-10.35

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 112 von 129
Page 112 of 129

	5670	5670 (Pk)	Vertical	82.84	-	-
		5670 (Av)		69.42	-	-
		5460 (Pk)		42.65	74*	-31.35
		5460 (Av)		30.06	54*	-23.94
		11340 (Pk)		52.61	68.23	-15.62
		11340 (Av)		41.06	54	-12.94
		17010 (Pk)		55.13	68.23	-13.10
		17010 (Av)		43.02	54	-10.98
		5670 (Pk)	Horizontal	95.90	-	-
		5670 (Av)		81.99	-	-
		5460 (Pk)		43.01	74*	-30.99
		5460 (Av)		31.04	54*	-22.96
		11340 (Pk)		52.81	68.23	-15.42
		11340 (Av)		41.11	54	-12.89
		17010 (Pk)		54.60	68.23	-13.63
		17010 (Av)		42.96	54	-11.04
UNII 3	5755	5755 (Pk)	Vertical	94.42	-	-
		5755 (Av)		80.65	-	-
		5715(Pk)		52.62	78.2*	-25.58
		5725(Pk)		55.58	78.2*	-22.62
		11510 (Pk)		55.01	68.23	-13.22
		11510 (Av)		42.76	54	-11.24
		17265 (Pk)		56.53	68.23	-11.70
		17265 (Av)		43.75	54	-10.25
		5755 (Pk)	Horizontal	103.81	-	-
		5755 (Av)		89.93	-	-
		5715(Pk)		61.17	78.2*	-17.03
		5725(Pk)		65.36	78.2*	-12.84
		11510 (Pk)		54.53	68.23	-13.70
		11510 (Av)		42.73	54	-11.27
		17265 (Pk)		55.80	68.23	-12.43
		17265 (Av)		43.77	54	-10.23
	5795	5795 (Pk)	Vertical	91.80	-	-
		5795 (Av)		77.92	-	-
		5850 (Pk)		43.81	78.2*	-34.39
		5860 (Pk)		44.33	78.2*	-33.87
		11590 (Pk)		55.01	68.23	-13.22
		11590 (Av)		42.36	54	-11.64
		17385 (Pk)		58.13	68.23	-10.10
		17385 (Av)		45.82	54	-8.18
		5795 (Pk)	Horizontal	93.04	-	-
		5795 (Av)		79.08	-	-
		5850 (Pk)		44.57	78.2*	-33.63
		5860 (Pk)		43.97	78.2*	-34.23
		11590 (Pk)		54.64	68.23	-13.59
		11590 (Av)		42.49	54	-11.51
		17385 (Pk)		57.72	68.23	-10.51
		17385 (Av)		45.82	54	-8.18

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 113 von 129

Page 113 of 129

Modulation: 802.11ac-VHT80

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5210	5210 (Pk)	Vertical	82.48	-	-
		5210 (Av)		72.01	-	-
		5150 (Pk)		47.48	74*	-26.52
		5150 (Av)		35.34	54*	-18.66
		10420 (Pk)		52.68	68.23	-15.55
		10420 (Av)		39.67	54	-14.33
		15630 (Pk)		53.33	68.23	-14.90
		15630 (Av)		41.05	54	-12.95
		5210 (Pk)	Horizontal	81.81	-	-
		5210 (Av)		81.18	-	-
		5150 (Pk)		53.41	74*	-20.59
		5150 (Av)		41.00	54*	-13.00
		10420 (Pk)		52.19	68.23	-16.04
		10420 (Av)		39.67	54	-14.33
		15630 (Pk)		53.08	68.23	-15.15
		15630 (Av)		41.14	54	-12.86
UNII 2a	5290	5290 (Pk)	Vertical	81.85	-	-
		5290 (Av)		72.00	-	-
		5350 (Pk)		46.56	74*	-27.44
		5350 (Av)		33.34	54*	-20.66
		10580 (Pk)		52.45	68.23	-15.78
		10580 (Av)		40.17	54	-13.83
		15870 (Pk)		53.37	68.23	-14.86
		15870 (Av)		41.33	54	-12.67
		5290 (Pk)	Horizontal	93.62	-	-
		5290 (Av)		83.81	-	-
		5350 (Pk)		55.76	74*	-18.24
		5350 (Av)		43.39	54*	-10.61
		10580 (Pk)		52.10	68.23	-16.13
		10580 (Av)		40.09	54	-13.91
		15870 (Pk)		53.28	68.23	-14.95
		15870 (Av)		41.37	54	-12.63

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 114 von 129
Page 114 of 129

UNII 2c	5530	5530 (Pk)	Vertical	85.92	-	-
		5530 (Av)		74.75	-	-
		5460 (Pk)		48.72	74*	-25.28
		5460 (Av)		33.14	54*	-20.86
		11060 (Pk)		52.79	68.23	-15.44
		11060 (Av)		40.83	54	-13.17
		16590 (Pk)		54.86	68.23	-13.37
		16590 (Av)		42.73	54	-11.27
		5530 (Pk)	Horizontal	93.10	-	-
		5530 (Av)		83.52	-	-
		5460 (Pk)		56.62	74*	-17.38
		5460 (Av)		43.23	54*	-10.77
		11060 (Pk)		52.46	68.23	-15.77
		11060 (Av)		40.83	54	-13.17
		16590 (Pk)		54.54	68.23	-13.69
		16590 (Av)		42.74	54	-11.26
	5690	5690 (Pk)	Vertical	82.34	-	-
		5690 (Av)		73.12	-	-
		5460 (Pk)		42.70	74*	-31.30
		5460 (Av)		29.78	54*	-24.22
		11380 (Pk)		53.07	68.23	-15.16
		11380 (Av)		41.53	54	-12.47
		17070 (Pk)		55.52	68.23	-12.71
		17070 (Av)		43.50	54	-10.50
		5690 (Pk)	Horizontal	92.87	-	-
		5690 (Av)		83.51	-	-
		5460 (Pk)		44.71	74*	-29.29
		5460 (Av)		32.68	54*	-21.32
		11380 (Pk)		53.43	68.23	-14.80
		11380 (Av)		41.53	54	-12.47
		17070 (Pk)		55.99	68.23	-12.24
		17070 (Av)		43.62	54	-10.38
UNII 3	5775	5775 (Pk)	Vertical	91.68	-	-
		5775 (Av)		80.99	-	-
		11550 (Pk)		54.61	68.23	-13.62
		11550 (Av)		42.36	54	-11.64
		17325 (Pk)		55.51	68.23	-12.72
		17325 (Av)		44.63	54	-9.37
		5775 (Pk)	Horizontal	102.80	-	-
		5775 (Av)		92.33	-	-
		11550 (Pk)		53.97	68.23	-14.26
		11550 (Av)		42.70	54	-11.30
		17325 (Pk)		56.57	68.23	-11.66
		17325 (Av)		44.61	54	-9.39

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 115 von 129

Page 115 of 129

Modulation: 802.11ac-VHT80

Data rate: MCS9

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5210	5210 (Pk)	Vertical	85.37	-	-
		5210 (Av)		74.68	-	-
		5150 (Pk)		46.63	74*	-27.37
		5150 (Av)		34.49	54*	-19.51
		10420 (Pk)		51.67	68.23	-16.56
		10420 (Av)		39.59	54	-14.41
		15630 (Pk)		52.98	68.23	-15.25
		15630 (Av)		40.85	54	-13.15
		5210 (Pk)	Horizontal	95.11	-	-
		5210 (Av)		84.49	-	-
		5150 (Pk)		55.97	74*	-18.03
		5150 (Av)		43.18	54*	-10.82
		10420 (Pk)		51.91	68.23	-16.32
		10420 (Av)		39.63	54	-14.37
		15630 (Pk)		53.68	68.23	-14.55
		15630 (Av)		40.83	54	-13.17
UNII 2a	5290	5290 (Pk)	Vertical	85.98	-	-
		5290 (Av)		75.03	-	-
		5350 (Pk)		44.76	74*	-29.24
		5350 (Av)		32.88	54*	-21.12
		10580 (Pk)		51.93	68.23	-16.30
		10580 (Av)		40.12	54	-13.88
		15870 (Pk)		54.13	68.23	-14.10
		15870 (Av)		41.27	54	-12.73
		5290 (Pk)	Horizontal	94.84	-	-
		5290 (Av)		84.26	-	-
		5350 (Pk)		54.32	74*	-19.68
		5350 (Av)		41.47	54*	-12.53
		10580 (Pk)		52.96	68.23	-15.27
		10580 (Av)		40.05	54	-13.95
		15870 (Pk)		53.45	68.23	-14.78
		15870 (Av)		41.24	54	-12.76

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 116 von 129
Page 116 of 129

UNII 2c	5530	5530 (Pk)	Vertical	80.41	-	-
		5530 (Av)		69.59	-	-
		5460 (Pk)		41.93	74*	-32.07
		5460 (Av)		30.22	54*	-23.78
		11060 (Pk)		53.16	68.23	-15.07
		11060 (Av)		40.83	54	-13.17
		16590 (Pk)		54.74	68.23	-13.49
		16590 (Av)		42.90	54	-11.10
		5530 (Pk)	Horizontal	88.87	-	-
		5530 (Av)		78.08	-	-
		5460 (Pk)		47.41	74*	-26.59
		5460 (Av)		34.60	54*	-19.40
		11060 (Pk)		53.02	68.23	-15.21
		11060 (Av)		40.85	54	-13.15
		16590 (Pk)		55.44	68.23	-12.79
		16590 (Av)		42.92	54	-11.08
	5690	5690 (Pk)	Vertical	78.31	-	-
		5690 (Av)		67.39	-	-
		5460 (Pk)		42.92	74*	-31.08
		5460 (Av)		29.64	54*	-24.36
		11380 (Pk)		53.15	68.23	-15.08
		11380 (Av)		41.69	54	-12.31
		17070 (Pk)		55.23	68.23	-13.00
		17070 (Av)		43.82	54	-10.18
		5690 (Pk)	Horizontal	89.66	-	-
		5690 (Av)		78.67	-	-
		5460 (Pk)		43.23	74*	-30.77
		5460 (Av)		31.36	54*	-22.64
		11380 (Pk)		54.31	68.23	-13.92
		11380 (Av)		41.65	54	-12.35
		17070 (Pk)		55.43	68.23	-12.80
		17070 (Av)		43.79	54	-10.21
UNII 3	5775	5775 (Pk)	Vertical	89.65	-	-
		5775 (Ak)		78.14	-	-
		11550 (Pk)		55.03	68.23	-13.20
		11550 (Av)		42.47	54	-11.53
		17325 (Pk)		56.37	68.23	-11.86
		17325 (Av)		44.81	54	-9.19
		5775 (Pk)	Horizontal	95.38	-	-
		5775 (Av)		84.60	-	-
		11550 (Pk)		53.96	68.23	-14.27
		11550 (Av)		42.47	54	-11.53
		17325 (Pk)		56.97	68.23	-11.26
		17325 (Av)		44.92	54	-9.08

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 117 von 129

Page 117 of 129

Modulation: 802.11ax-HE80

Data rate: MCS0

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
UNII 1	5210	5210 (Pk)	Vertical	85.89	-	-
		5210 (Av)		73.26	-	-
		5150 (Pk)		46.72	74*	-27.28
		5150 (Av)		33.83	54*	-20.17
		10420 (Pk)		52.12	68.23	-16.11
		10420 (Av)		39.70	54	-14.30
		15630 (Pk)		53.05	68.23	-15.18
		15630 (Av)		41.01	54	-12.99
		5210 (Pk)	Horizontal	98.15	-	-
		5210 (Av)		85.52	-	-
		5150 (Pk)		55.44	74*	-18.56
		5150 (Av)		42.77	54*	-11.23
		10420 (Pk)		51.69	68.23	-16.54
		10420 (Av)		39.64	54	-14.36
		15630 (Pk)		52.87	68.23	-15.36
		15630 (Av)		41.02	54	-12.98
UNII 2a	5290	5290 (Pk)	Vertical	86.68	-	-
		5290 (Av)		73.31	-	-
		5350 (Pk)		47.94	74*	-26.06
		5350 (Av)		34.40	54*	-19.60
		10580 (Pk)		51.71	68.23	-16.52
		10580 (Av)		40.24	54	-13.76
		15870 (Pk)		54.39	68.23	-13.84
		15870 (Av)		41.48	54	-12.52
		5290 (Pk)	Horizontal	95.95	-	-
		5290 (Av)		82.24	-	-
		5350 (Pk)		55.43	74*	-18.57
		5350 (Av)		41.39	54*	-12.61
		10580 (Pk)		52.61	68.23	-15.62
		10580 (Av)		40.19	54	-13.81
		15870 (Pk)		53.72	68.23	-14.51
		15870 (Av)		41.35	54	-12.65

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 118 von 129
Page 118 of 129

UNII 2c	5530	5530 (Pk)	Vertical	85.96	-	-
		5530 (Av)		73.09	-	-
		5460 (Pk)		46.75	74*	-27.25
		5460 (Av)		33.47	54*	-20.53
		11060 (Pk)		52.66	68.23	-15.57
		11060 (Av)		40.86	54	-13.14
		16590 (Pk)		54.37	68.23	-13.86
		16590 (Av)		42.94	54	-11.06
		5530 (Pk)	Horizontal	93.97	-	-
		5530 (Av)		81.11	-	-
		5460 (Pk)		53.12	74*	-20.88
		5460 (Av)		40.12	54*	-13.88
		11060 (Pk)		53.26	68.23	-14.97
		11060 (Av)		40.89	54	-13.11
		16590 (Pk)		54.61	68.23	-13.62
		16590 (Av)		42.94	54	-11.06
	5690	5690 (Pk)	Vertical	87.00	-	-
		5690 (Av)		74.08	-	-
		5460 (Pk)		41.67	74*	-32.33
		5460 (Av)		29.52	54*	-24.48
		11380 (Pk)		53.05	68.23	-15.18
		11380 (Av)		41.68	54	-12.32
		17070 (Pk)		56.43	68.23	-11.80
		17070 (Av)		43.55	54	-10.45
		5690 (Pk)	Horizontal	96.67	-	-
		5690 (Av)		83.98	-	-
		5460 (Pk)		44.74	74*	-29.26
		5460 (Av)		32.62	54*	-21.38
		11380 (Pk)		53.54	68.23	-14.69
		11380 (Av)		41.69	54	-12.31
		17070 (Pk)		55.34	68.23	-12.89
		17070 (Av)		43.59	54	-10.41
UNII 3	5775	5775 (Pk)	Vertical	95.60	-	-
		5775 (Av)		82.15	-	-
		11550 (Pk)		54.80	68.23	-13.43
		11550 (Av)		42.48	54	-11.52
		17325 (Pk)		57.22	68.23	-11.01
		17325 (Av)		45.11	54	-8.89
		5775 (Pk)	Horizontal	105.36	-	-
		5775 (Av)		92.14	-	-
		11550 (Pk)		55.03	68.23	-13.20
		11550 (Av)		43.66	54	-10.34
		17325 (Pk)		56.66	68.23	-11.57
		17325 (Av)		45.09	54	-8.91

Prüfbericht - Nr.:

Test Report No.:

ULR-TC568822300000063F

Seite 119 von 129

Page 119 of 129

Modulation: 802.11ax-HE80

Data rate: MCS11

UNII Bands	Channel Frequency (MHz)	Frequency (MHz)	Polarization	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
UNII 1	5210	5210 (Pk)	Vertical	88.29	-	-
		5210 (Av)		75.23	-	-
		5150 (Pk)		49.32	74*	-24.68
		5150 (Av)		33.85	54*	-20.15
		10420 (Pk)		51.98	68.23	-16.25
		10420 (Av)		39.69	54	-14.31
		15630 (Pk)		52.67	68.23	-15.56
		15630 (Av)		40.87	54	-13.13
		5210 (Pk)	Horizontal	97.68	-	-
		5210 (Av)		86.21	-	-
		5150 (Pk)		58.78	74*	-15.22
		5150 (Av)		43.05	54*	-10.95
		10420 (Pk)		51.74	68.23	-16.49
		10420 (Av)		39.70	54	-14.30
		15630 (Pk)		53.45	68.23	-14.78
		15630 (Av)		40.88	54	-13.12
UNII 2a	5290	5290 (Pk)	Vertical	88.75	-	-
		5290 (Av)		75.32	-	-
		5350 (Pk)		49.68	74*	-24.32
		5350 (Av)		34.59	54*	-19.41
		10580 (Pk)		52.48	68.23	-15.75
		10580 (Av)		40.20	54	-13.80
		15870 (Pk)		53.63	68.23	-14.60
		15870 (Av)		41.34	54	-12.66
		5290 (Pk)	Horizontal	99.22	-	-
		5290 (Av)		86.03	-	-
		5350 (Pk)		60.31	74*	-13.69
		5350 (Av)		44.39	54*	-9.61
		10580 (Pk)		52.20	68.23	-16.03
		10580 (Av)		40.18	54	-13.82
		15870 (Pk)		53.11	68.23	-15.12
		15870 (Av)		41.33	54	-12.67

Prüfbericht - Nr.:
Test Report No.:


ULR-TC568822300000063F

Seite 120 von 129
Page 120 of 129

UNII 2c	5530	5530 (Pk)	Vertical	81.16	-	-
		5530 (Av)		68.22	-	-
		5460 (Pk)		42.78	74*	-31.22
		5460 (Av)		30.07	54*	-23.93
		11060 (Pk)		52.48	68.23	-15.75
		11060 (Av)		41.06	54	-12.94
		16590 (Pk)		54.57	68.23	-13.66
		16590 (Av)		43.15	54	-10.85
		5530 (Pk)	Horizontal	92.64	-	-
		5530 (Av)		79.08	-	-
		5460 (Pk)		48.41	74*	-25.59
		5460 (Av)		34.30	54*	-19.70
		11060 (Pk)		52.35	68.23	-15.88
		11060 (Av)		41.11	54	-12.89
		16590 (Pk)		54.67	68.23	-13.56
		16590 (Av)		43.11	54	-10.89
	5690	5690 (Pk)	Vertical	82.36	-	-
		5690 (Av)		68.61	-	-
		5460 (Pk)		41.33	74*	-32.67
		5460 (Av)		29.41	54*	-24.59
		11380 (Pk)		54.00	68.23	-14.23
		11380 (Av)		41.76	54	-12.24
		17070 (Pk)		56.06	68.23	-12.17
		17070 (Av)		43.86	54	-10.14
		5690 (Pk)	Horizontal	92.12	-	-
		5690 (Av)		78.58	-	-
		5460 (Pk)		43.59	74*	-30.41
		5460 (Av)		31.28	54*	-22.72
		11380 (Pk)		53.12	68.23	-15.11
		11380 (Av)		41.72	54	-12.28
		17070 (Pk)		56.05	68.23	-12.18
		17070 (Av)		43.84	54	-10.16
UNII 3	5775	5775 (Pk)	Vertical	90.16	-	-
		5775 (Av)		75.73	-	-
		11550 (Pk)		54.56	68.23	-13.67
		11550 (Av)		42.35	54	-11.65
		17325 (Pk)		56.43	68.23	-11.80
		17325 (Av)		44.74	54	-9.26
		5775 (Pk)	Horizontal	99.63	-	-
		5775 (Av)		85.66	-	-
		11550 (Pk)		54.17	68.23	-14.06
		11550 (Av)		42.45	54	-11.55
		17325 (Pk)		57.64	68.23	-10.59
		17325 (Av)		44.74	54	-9.26


Test Plots:

Modulation 802.11ax-20MHz



Channel frequency: 5825MHz


Polarization: Vertical



Channel frequency: 5825MHz


Polarization: Horizontal

Channel Frequency: 5825MHz




Frequency range: 1GHz-18GHz

Polarization: Vertical




Frequency range: 1GHz-18GHz

Polarization: Horizontal



Frequency range: 18GHz-40GHz

Polarization: Vertical



Frequency range: 18GHz-40GHz

Polarization: Horizontal

8 Conducted Spurious Emission test on AC Power Line

Result

Pass

Test Specification : FCC Part 15 Section 15.207
Test Method : ANSI C 63.10-2013
Testing Location : Screened room
Measurement Bandwidth : 9kHz
Frequency Range : 150kHz – 30MHz
Supply Voltage : 110VAC,60Hz
Test Method : Refer TEST METHODOLOGY

Limits of section 15.207

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak (dBμV)	Average (dBμV)
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency

Test Conditions:

Normal Temperature = +24°C Voltage (V norm) = 110V AC (Through AC to DC Adapter)
RH = 64 %


Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 125 von 129
Page 125 of 129

Test result:

Power: 110V 60Hz_LINE



Line Graph

Quasipeak:-

Frequency (MHz)	Correction (dB)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
1.53175	19.69	47.25	56	-8.75	Pass
2.2998	19.69	46.63	56	-9.37	Pass
3.63845	19.7	46.53	56	-9.47	Pass
4.02155	19.71	46.1	56	-9.9	Pass
4.7873	19.7	44.72	56	-11.28	Pass
3.0624	19.7	44.48	56	-11.52	Pass
0.76645	19.66	42.49	56	-13.51	Pass
2.48955	19.69	40.37	56	-15.63	Pass
0.2273	19.56	36.83	62.6	-25.77	Pass

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F


Seite 126 von 129
Page 126 of 129

Average:-

Frequency (MHz)	Correction (dB)	Level (dBµV)	Limit (dBµV)	Margin (dB)	Comments
1.53175	19.69	45.9	46	-0.1	Pass
2.2998	19.69	45.04	46	-0.96	Pass
3.63845	19.7	44.32	46	-1.68	Pass
4.02155	19.71	43.9	46	-2.1	Pass
4.7873	19.7	41.57	46	-4.43	Pass
3.0624	19.7	41.5	46	-4.5	Pass
0.76645	19.66	40.76	46	-5.24	Pass
2.48955	19.69	37.99	46	-8.01	Pass
0.2273	19.56	29.46	52.6	-23.13	Pass

Line Table

Power: 110V60Hz_NEUTRAL



Neutral Graph

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 127 von 129
Page 127 of 129

Quasipeak:-

Frequency (MHz)	Correction (dB)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
1.5331	19.7	46.96	56	-9.04	Pass
2.29665	19.69	46.4	56	-9.6	Pass
3.6398	19.71	46.4	56	-9.6	Pass
4.0229	19.71	45.98	56	-10.02	Pass
3.0651	19.7	44.94	56	-11.06	Pass
4.7855	19.71	43.87	56	-12.13	Pass
0.76645	19.67	42.19	56	-13.81	Pass
4.4105	19.71	41.11	56	-14.89	Pass
0.20975	19.55	33.68	63.21	-29.52	Pass
0.17195	19.55	35.16	64.96	-29.8	Pass

Average:-

Frequency (MHz)	Correction (dB)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Comments
1.5331	19.7	45.72	46	-0.28	Pass
2.29665	19.69	44.75	46	-1.25	Pass
3.6398	19.71	44.15	46	-1.85	Pass
4.0229	19.71	43.82	46	-2.18	Pass
3.0651	19.7	42.39	46	-3.61	Pass
0.76645	19.67	40.71	46	-5.29	Pass
4.7855	19.71	40	46	-6	Pass
4.4105	19.71	35.75	46	-10.25	Pass
0.20975	19.55	22.99	53.21	-30.22	Pass
0.17195	19.55	22.79	54.96	-32.17	Pass

Neutral Table

9 LIST OF TABLES

Table 1: List of test and measurement instruments	6
Table 2: Instrument application Software versions	7
Table 3: Ratings and System Details as declared by the Client*	8
Table 4: Measurement Uncertainty	9
Table 5: List of Wi-Fi center Frequencies	11
Table 6: Undesirable emission limits	63
Table 7: Transmitter limits for Radiated emission	64

10 Power level used for testing

a-mode 6Mbps		n-mode HT20_MCS0		ac-mode VHT40_MCS0	
5180	10	5180	10	5190	10
5240	10	5240	10	5230	10
5260	12	5260	12	5270	11
5320	12	5320	12	5510	11
5500	9	5500	5	5590	8
5700	9	5700	5	5670	8
5745	13	5745	13	5755	12
5825	13	5825	13	5795	12
a-mode 54Mbps		n-mode HT20_MCS7		ac-mode VHT40_MCS9	
5180	9	5180	10	5190	9
5240	9	5240	10	5230	9
5260	12	5260	12	5270	11
5320	12	5320	12	5510	11
5500	8	5500	7	5590	6
5700	8	5700	7	5670	6
5745	13	5745	14	5755	10
5825	13	5825	14	5795	10
ac-mode VHT20_MCS0		n-mode HT40_MCS0		ac_VHT80_MCS0	
5180	10	5190	10	5210	8
5240	10	5230	10	5290	8
5260	12	5270	12	5530	8
5320	12	5510	12	5690	8
5500	9	5590	9	5755	15
5700	9	5670	9	ac_VHT80_MCS9	
5745	13	5755	12	5210	7
5825	13	5795	12	5290	7
ac-mode VHT20_MCS8		n-mode HT40_MCS7		5530	7
5180	10	5190	10	5690	7
5240	10	5230	10	5755	10
5260	12	5270	12		
5320	12	5510	12		
5500	9	5590	12		
5700	9	5670	12		
5745	12	5755	12		
5825	12	5795	12		

Prüfbericht - Nr.:
Test Report No.:

ULR-TC568822300000063F

Seite 129 von 129
Page 129 of 129

ax-mode HE20_HE0		ax-mode HE40_HE0		ax-mode HE80_HE0	
5180	10	5190	9	5190	8
5240	10	5230	9	5230	8
5320	13	5270	11	5270	8
5500	8	5510	9	5510	8
5600	8	5590	9	5590	8
5700	8	5670	9	5670	8
5745	13	5755	12	5755	13
5825	13	5795	12	5795	13
ax-mode HE20_HE11		ax-mode HE40_HE11		ax-mode HE80_HE11	
5180	9	5190	9	5190	8
5240	9	5230	9	5230	8
5320	10	5270	9	5270	8
5500	7	5510	6	5510	8
5600	7	5590	6	5590	8
5700	7	5670	6	5670	8
5745	10	5755	8	5755	9
5825	10	5795	8	5795	9

*****END OF TEST REPORT*****