



RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

BLE						
Test Mode	Frequency (MHz)	Max Power (dBm)	Max Power (mW)	Min. Distance (mm)	Calc. thresholds	limit
GFSK	2440	-0.357	0.92	5	0.29011	3.0

BT						
Test Mode	Frequency (MHz)	Max Power (dBm)	Max Power (mW)	Min. Distance (mm)	Calc. thresholds	limit
GFSK	2402	-0.714	0.85	5	0.26721	3.0
$\pi/4$ -DQPSK	2440	-0.711	0.85	5	0.26696	3.0
8-DPSK	2402	-0.687	0.85	5	0.26790	3.0

So a SAR test is not required