

# TEST REPORT

Applicant Name : Shenzhen Yinai Intelligent Manufacturing Technology Co., Ltd  
Address : 6 Floor, D Building, Huamingcheng High-Tech Park, Matian Street, Guangming Dist, Shenzhen, Guangdong, China  
Report Number : SZNS1220414-14123E-RF  
FCC ID: 2A6HHCCL-001

## Test Standard (s)

FCC Part 15C

## Sample Description

Product Type: WATCH WIRELESS CHARGER  
Model No.: CCL-001  
Multiple Model(s) No.: CCL-002, YPF-001, YPF-002, HREOYY-0125, WYM-001, WYM-002, EN-W12, W12, W12-1  
Date Received: 2022-04-14  
Date of Test: 2022-04-20 to 2022-04-21  
Report Date: 2022-04-21

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:



Black Ding  
EMC Engineer

## Approved By:



Robert Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk ★.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk \*\*. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290 Fax: +86 755-26503396 Web: [www.atc-lab.com](http://www.atc-lab.com)

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE .....	3
TEST METHODOLOGY .....	3
MEASUREMENT UNCERTAINTY.....	3
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EUT EXERCISE SOFTWARE .....	5
LOCAL SUPPORT EQUIPMENT.....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>8</b>
<b>FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
BLOCK DIAGRAM OF TEST SETUP .....	10
TEST DATA .....	10
<b>FCC§15.203 – ANTENNA REQUIREMENT .....</b>	<b>12</b>
APPLICABLE STANDARD .....	12
ANTENNA CONNECTED CONSTRUCTION .....	12
<b>FCC §15.207 – AC LINE CONDUCTED EMISSION .....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
EUT SETUP .....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE .....	13
CORRECTED FACTOR & MARGIN CALCULATION .....	14
TEST DATA .....	14
<b>FCC §15.205 &amp; §15.209 - RADIATED EMISSIONS TEST .....</b>	<b>17</b>
APPLICABLE STANDARD .....	17
EUT SETUP .....	17
EMI TEST RECEIVER SETUP.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	18
TEST DATA .....	18

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Product Type	WATCH WIRELESS CHARGER
Test Model	CCL-001
Multiple Model(s) No.	CCL-002, YPF-001, YPF-002, HREOYY-0125, WYM-001, WYM-002, EN-W12, W12, W12-1
Model Different	Please refer to DOS
Frequency Range	0.320-0.325MHz
Antenna Type	Coil
Input Voltage	DC5V from adapter
Sample serial number	SZNS1220414-14123E-RF-S1
Sample/EUT Status	Good condition

### Objective

This test report is in accordance with Part 2, Subpart J, and Part 15, Subparts A and C of the Federal Communications Commission's rules.

The objective is to determine the compliance of EUT with FCC rules, section 15.203, 15.205, 15.207 and 15.209.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Measurement Uncertainty

Parameter	Uncertainty
AC Power Lines Conducted Emissions	2.72dB
Emissions, Radiated	9kHz – 30MHz
	30MHz - 1GHz
Temperature	1 °C
Humidity	6%
Supply voltages	0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## **Test Facility**

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## **SYSTEM TEST CONFIGURATION**

### **Justification**

The system was configured for testing in a test mode

### **EUT Exercise Software**

No software used in test.

### **Local Support Equipment**


Manufacturer	Description	Model	Serial Number
Dongguan Aohai Power Technology Co.,Ltd.	Adapter	A8-501000	A1906034835
Apple Inc.	Apple Watch	55783	A33

### **External I/O Cable**


Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

## Block Diagram of Test Setup

For conducted emission:



For Radiated Emission



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§1.1310 & §2.1091	Maximum Permissible Exposure(MPE)	Compliant
FCC§15.203	Antenna Requirement	Compliant
FCC§15.207	AC Line Conducted Emission	Compliant
§15.209 §15.205	Radiated Emission Test	Compliant

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emissions Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
R & S	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50ΩCoaxial Switch	MP59B	6200506474	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
<b>RF Radiated test</b>					
Rohde & Schwarz	Test Receiver	ESR	101817	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
SCHWARZBECK	LOOP ANTENNA	FMZB1516	1516131	2021/12/22	2024/12/21
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Radiated Emission Test Software: e3 19821b (V9) & EZ_EMC V 1.1.4.2					
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
<b>RF Exposure Test (MPE)</b>					
Narda	Electric and Magnetic Field Analyzer	EHP-200AC	180ZX10204	2021/06/07	2024/06/06
Narda	USB-RS232 Converter	Unknown	20042558	/	/
Narda	Software	EHP200-TS	Unknown	/	/

**\* Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §1.1310, §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According with KDB 680106 D01 RF Exposure Wireless Charging Apps v03r01 clause 3 c)


- c) For devices designed for typical desktop applications, such as wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

According to KDB 680106 D01 RF Exposure Wireless Charging App v03r01 clause 5 b)

- b) Inductive wireless power transfer applications with supporting field strength results and meeting all of the following requirements are not required to submit a KDB inquiry for devices approved using SDoC<sup>2</sup> or a PAG<sup>3</sup> for equipment approved using certification to address RF exposure compliance. However, the responsible party is required to keep a copy of the test report in accordance with KDB 865664 D02. A copy of the test report is to be submitted with the application if the device is approved using certification.

- (1) Power transfer frequency is less than 1 MHz
- (2) Output power from each primary coil is less than or equal to 15 watts.
- (3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
- (4) Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- (6) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.

## Block Diagram of Test Setup



Note: 20 cm for Top test.

## Test Data

### Environmental Conditions

Temperature:	24 °C
Relative Humidity:	51 %
ATM Pressure:	101.1 kPa

The testing was performed by Nick Fang on 2022-04-20.

Test Mode: Wireless Charging (Worst case)

**H-Field Strength**

Frequency Range (kHz)	Position A (A/m)	Position B (A/m)	Position C (A/m)	Position D (A/m)	Position E (A/m)	50% Limit (A/m)	Limit (A/m)
320-325	0.275	0.281	0.297	0.295	0.426	0.815	1.63

**E-Field Strength**

Frequency Range (kHz)	Position A (V/m)	Position B (V/m)	Position C (V/m)	Position D (V/m)	Position E (V/m)	50% Limit (V/m)	Limit (V/m)
320-325	4.567	4.649	4.738	4.721	6.794	307	614

Note: Test with 15cm distance from the center of the probe(s) to the edge of the device, 20cm from the center of the probe(s) to the top of the device.

**Result: Pass****Considerations of compliance 680106 D01 RF Exposure Wireless Charging App v03r01 clause 5 b:**

**(1)** Power transfer frequency is less than 1 MHz.

Yes, the operation frequency is 320-325kHz.

**(2)** Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of primary coil is 10Watts.

**(3)** The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.

The transfer system includes one primary coil to detect and allow coupling only between individual pairs of coils.

**(4)** Client device is placed directly in contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter

**(5)** Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, mobile exposure conditions only

**(6)** The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.

Yes, the test result for H and E-Field strength less than 50% of the MPE limit.

## **FCC§15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **Antenna Connected Construction**

The EUT has one coil antenna arrangement which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


**Result: Compliant.**

## FCC §15.207 – AC LINE CONDUCTED EMISSION

### Applicable Standard

FCC§15.207

### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$


## Test Data

### Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.1 kPa


*The testing was performed by Caro Hu on 2022-04-20.*

*Test Mode: Transmitting*

**AC 120 V/60 Hz, Line:**

Site : Shielding Room  
Condition: Line  
Job No. : SZNS1220414-14123E-RF  
Mode : Transmitting  
Model : CCL-001  
Power : AC 120V 60Hz

Freq	Factor	Read		Limit		Over Limit	Remark
		MHz	dB	dBuV	dBuV		
1	0.180	9.80	20.18	29.98	54.48	-24.50	Average
2	0.180	9.80	32.04	41.84	64.48	-22.64	QP
3	0.202	9.80	16.95	26.75	53.51	-26.76	Average
4	0.202	9.80	27.35	37.15	63.51	-26.36	QP
5	0.303	9.80	16.45	26.25	50.15	-23.90	Average
6	0.303	9.80	23.73	33.53	60.15	-26.62	QP
7	0.580	9.81	21.24	31.05	46.00	-14.95	Average
8	0.580	9.81	27.59	37.40	56.00	-18.60	QP
9	2.265	9.82	18.41	28.23	46.00	-17.77	Average
10	2.265	9.82	21.04	30.86	56.00	-25.14	QP
11	22.313	10.02	25.64	35.66	50.00	-14.34	Average
12	22.313	10.02	27.30	37.32	60.00	-22.68	QP

**AC 120V/ 60 Hz, Neutral:**

Site : Shielding Room  
Condition: Neutral  
Job No. : SZNS1220414-14123E-RF  
Mode : Transmitting  
Model : CCL-001  
Power : AC 120V 60Hz

Freq	Factor	Read		Limit Line	Over Limit	Remark
		MHz	dB	dBuV	dBuV	dB
1	0.184	9.80	23.54	33.34	54.29	-20.95 Average
2	0.184	9.80	32.30	42.10	64.29	-22.19 QP
3	0.210	9.80	20.99	30.79	53.19	-22.40 Average
4	0.210	9.80	29.42	39.22	63.19	-23.97 QP
5	0.376	9.80	20.94	30.74	48.36	-17.62 Average
6	0.376	9.80	26.02	35.82	58.36	-22.54 QP
7	0.572	9.81	25.22	35.03	46.00	-10.97 Average
8	0.572	9.81	30.87	40.68	56.00	-15.32 QP
9	3.554	9.84	22.08	31.92	46.00	-14.08 Average
10	3.554	9.84	26.42	36.26	56.00	-19.74 QP
11	21.744	10.12	23.74	33.86	50.00	-16.14 Average
12	21.744	10.12	25.86	35.98	60.00	-24.02 QP

## FCC §15.205 & §15.209 - RADIATED EMISSIONS TEST

### Applicable Standard


As per FCC Part 15.209

(a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

### EUT Setup



The radiated emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Measurement
9 kHz – 150 kHz	300 Hz	1 kHz	PK
150 kHz – 30 MHz	10 kHz	30 kHz	PK
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level/Result} - \text{Limit.} \\ \text{Level/Result} &= \text{Reading level} + \text{Factor} \end{aligned}$$

## Test Data

### Environmental Conditions


Temperature:	24°C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

*The testing was performed by Nick Fang on 2022-04-21.*

*Test mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)*

9 kHz~150kHz:


Parallel



Site : chamber  
Condition: 3m  
Job No. : SZNS1220414-14123E-RF  
Test Mode: Transmitting  
: Parallel

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.013	-11.46	53.22	41.76	125.32	-83.56	Peak
2	0.030	-11.64	50.05	38.41	118.18	-79.77	Peak
3	0.135	-11.95	45.14	33.19	105.01	-71.82	Peak

Perpendicular



Site : chamber

Condition: 3m


Job No. : SZNS1220414-14123E-RF

Test Mode: Transmitting

: Perpendicular


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1		0.025	-11.66	50.56	38.90	119.60	-80.70 Peak
2		0.063	-11.56	50.96	39.40	111.61	-72.21 Peak
3		0.099	-11.55	42.86	31.31	107.65	-76.34 Peak

## Ground-parallel



Site : chamber  
Condition: 3m  
Job No. : SZNS1220414-14123E-RF  
Test Mode: Transmitting  
: Ground-parallel


Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	0.009	-11.35	51.43	40.08	128.32	-88.24	Peak
2	0.041	-11.57	47.34	35.77	115.42	-79.65	Peak
3	0.064	-11.57	46.58	35.01	111.41	-76.40	Peak

150 kHz~30 MHz  
Parallel

Site : chamber  
Condition: 3m  
Job No. : SZNS1220414-14123E-RF  
Test Mode: Transmitting  
Note : Parallel

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2.678	-11.70	52.73	41.03	69.54	-28.51	Peak
2	3.565	-11.77	57.90	46.13	69.54	-23.41	Peak
3	3.881	-11.70	54.80	43.10	69.54	-26.44	Peak

Perpendicular



Site : chamber

Condition: 3m


Job No. : SZNS1220414-14123E-RF

Test Mode: Transmitting

Note : Perpendicular

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2.594	-11.66	52.88	41.22	69.54	-28.32	Peak
2	3.346	-11.81	56.67	44.86	69.54	-24.68	Peak
3	3.565	-11.77	57.18	45.41	69.54	-24.13	Peak

## Ground-parallel



Site : chamber

Condition: 3m

Job No. : SZNS1220414-14123E-RF

Test Mode: Transmitting


Note : Ground-parallel

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2.261	-11.48	54.10	42.62	69.54	-26.92	Peak
2	3.547	-11.77	54.82	43.05	69.54	-26.49	Peak
3	7.446	-11.39	53.02	41.63	69.54	-27.91	Peak

Part 15 Section 15.31(f)(2) (9kHz-30MHz)  
Limit @ 3m=Limit @ 300m-40\*log(3(m)/300(m))  
Limit @ 3m=Limit @ 30m-40\*log(3(m)/30(m))

30MHz~1GHz:

Horizontal



Site : chamber


Condition: 3m HORIZONTAL

Job No. : SZNS1220414-14123E-RF

Test Mode: Transmitting

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	54.332	-10.32	40.45	30.13	40.00	-9.87	Peak
2	96.648	-12.29	42.15	29.86	43.50	-13.64	Peak
3	106.292	-11.93	41.50	29.57	43.50	-13.93	Peak
4	138.327	-15.37	49.22	33.85	43.50	-9.65	Peak
5	192.334	-11.26	46.11	34.85	43.50	-8.65	Peak
6	338.845	-7.48	39.20	31.72	46.00	-14.28	Peak

Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : SZNS1220414-14123E-RF

Test Mode: Transmitting

	Freq	Read Factor	Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	47.868	-10.00	46.34	36.34	40.00	-3.66	QP
2	53.050	-10.18	47.13	36.95	40.00	-3.05	QP
3	97.413	-12.27	49.67	37.40	43.50	-6.10	Peak
4	104.811	-11.81	47.41	35.60	43.50	-7.90	Peak
5	198.936	-11.47	40.92	29.45	43.50	-14.05	Peak
6	445.828	-5.63	35.10	29.47	46.00	-16.53	Peak

\*\*\*\*\* END OF REPORT \*\*\*\*\*