



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

TEST REPORT

Report No.: **CTC20221322E01**

FCC ID.....: **2A6JVG001**

Applicant.....: **Shenzhen Unseen Technology Co., Ltd.**

Address.....: Room 1001, Pengda Moore City, No. 6002, Longgang Avenue,
Pingnan Community, Longgang Street, Longgang District,
Shenzhen

Manufacturer.....: Shenzhen Unseen Technology Co., Ltd.

Address.....: Room 1001, Pengda Moore City, No. 6002, Longgang Avenue,
Pingnan Community, Longgang Street, Longgang District,
Shenzhen

Product Name.....: **WIFI Repeater**

Trade Mark.....: /

Model/Type reference.....: GT001

Listed Model(s): /

Standard.....: **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

Date of receipt of test sample...: April 11, 2022

Date of testing.....: April 11, 2022 to April 20, 2022

Date of issue.....: April 20, 2022

Result.....: **PASS**

Compiled by:

(Printed name+signature) Zoe Xie

Supervised by:

(Printed name+signature) Miller Ma

Approved by:

(Printed name+signature) Totti Zhao

Testing Laboratory Name.....: **CTC Laboratories, Inc.**

Address.....: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park,
Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.



Table of Contents

Page

1. TEST SUMMARY	3
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION.....	3
1.3. TEST DESCRIPTION.....	4
1.4. TEST FACILITY	5
1.5. MEASUREMENT UNCERTAINTY	5
1.6. ENVIRONMENTAL CONDITIONS	6
2. GENERAL INFORMATION	7
2.1. CLIENT INFORMATION	7
2.2. GENERAL DESCRIPTION OF EUT	8
2.3. ACCESSORY EQUIPMENT INFORMATION	9
2.4. OPERATION STATE.....	10
2.5. MEASUREMENT INSTRUMENTS LIST	11
3. TEST ITEM AND RESULTS	12
3.1. CONDUCTED EMISSION.....	12
3.2. RADIATED EMISSION	15
3.3. BAND EDGE EMISSIONS (RADIATED)	20
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED)	23
3.5. DTS BANDWIDTH.....	52
3.6. PEAK OUTPUT POWER	62
3.7. POWER SPECTRAL DENSITY	64
3.8. ANTENNA REQUIREMENT	74



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices.

1.2. Report version

Revised No.	Date of issue	Description
01	April 20, 2022	Original



1.3. Test Description

FCC Part 15 Subpart C (15.247)			
Test Item	Standard Section	Result	Test Engineer
	FCC		
Antenna Requirement	15.203	Pass	Alicia Liu
Conducted Emission	15.207	Pass	Eva Feng
Radiated Band Edge and Spurious Emissions	15.205&15.209&15.247(d)	Pass	Alicia Liu
Conducted Band Edge and Spurious Emissions	15.247(d)	Pass	Alicia Liu
6dB Bandwidth	15.247(a)(2)	Pass	Alicia Liu
Conducted Max Output Power	15.247(b)(3)	Pass	Alicia Liu
Power Spectral Density	15.247(e)	Pass	Alicia Liu
Transmitter Radiated Spurious	15.209&15.247(d)	Pass	Alicia Liu

Note: The measurement uncertainty is not included in the test result.



1.4. Test Facility

CTC Laboratories, Inc.

Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.



Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.42 dB	(1)
Transmitter power Radiated	2.14 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.08 dB	(1)
Radiated Emissions 30~1000MHz	4.51 dB	(1)
Radiated Emissions 1~18GHz	5.84 dB	(1)
Radiated Emissions 18~40GHz	6.12 dB	(1)
Occupied Bandwidth	-----	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

1.6. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	21°C ~ 27°C
Relative Humidity:	40% ~ 60%
Air Pressure:	101kPa



2. GENERAL INFORMATION

2.1. Client Information

Applicant:	Shenzhen Unseen Technology Co., Ltd.
Address:	Room 1001, Pengda Moore City, No. 6002, Longgang Avenue, Pingnan Community, Longgang Street, Longgang District, Shenzhen
Manufacturer:	Shenzhen Unseen Technology Co., Ltd.
Address:	Room 1001, Pengda Moore City, No. 6002, Longgang Avenue, Pingnan Community, Longgang Street, Longgang District, Shenzhen



2.2. General Description of EUT

Product Name:	WIFI Repeater
Trade Mark:	/
Model/Type reference:	GT001
Listed Model(s):	/
Power supply:	AC110V-220V
Adapter model:	/
Hardware version:	/
Software version:	/
Serial number:	20220548779
WIFI 802.11b/ g/ n(HT20)/ n(HT40)	
Modulation:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK, QPSK, 16QAM, 64QAM)
Operation frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Channel number:	802.11b/g/n(HT20):11channels 802.11n(HT40):7channels
Channel separation:	5MHz
Antenna 1 and 2 type:	Integral Antenna
Antenna 1 and 2 gain:	1dBi Max
Antenna 1 and 2 Directional gain:	4.01dBi Max



2.3. Accessory Equipment information

Equipment Information			
Name	Model	S/N	Manufacturer
Notebook	X220	R9-NCMYL 12/04	Lenovo
/	/	/	/
Cable Information			
Name	Shielded Type	Ferrite Core	Length
Lan line	Without	Without	1.2M
/	/	/	/
Test Software Information			
Name	Versions	Powe level	/
SecureCRT.exe	8.7.1	Index	/



2.4. Operation state

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

Operation Frequency List:

Channel	Frequency (MHz)
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note: CH 01~CH 11 for 802.11b/g/n(HT20), CH 03~CH 09 for 802.11n(HT40)

Data Rated

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Mode	Data rate (worst mode)
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	HT-MCS0
802.11n(HT40)	HT-MCS0

Test mode

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit(100% duty cycle).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.



2.5. Measurement Instruments List

Tonscend JS0806-2 Test system					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	KEYSIGHT	N9020A	100231	Dec. 25, 2022
2	Spectrum Analyzer	Rohde & Schwarz	FUV40-N	101331	Mar. 15, 2023
3	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 25, 2022
4	Signal Generator	Agilent	E8257D	MY46521908	Dec. 25, 2022
5	Power Sensor	Agilent	U2021XA	MY5365004	Mar. 15, 2023
6	Power Sensor	Agilent	U2021XA	MY5365006	Mar. 15, 2023
7	High and low temperature box	ESPEC	MT3035	N/A	Mar. 24, 2023
8	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	102414	Dec. 25, 2022
9	300328 v2.2.2 test system	TONSCEND	v2.6	/	/

Radiated emission(3m chamber 2)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Jan. 12, 2023
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 24, 2022
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 25, 2022
4	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 15, 2023
5	Pre-Amplifier	SONOMA	310	186194	Dec. 25, 2022
6	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 25, 2022
7	Test Receiver	R&S	ESC17	100967	Dec. 25, 2022

Radiated emission(3m chamber 3)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-759	Nov. 09, 2023
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 24, 2022
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 25, 2022
4	Broadband Premplifier	SCHWARZBECK	BBV9743B	259	Dec. 25, 2022
5	Mirowave Broadband Amplifier	SCHWARZBECK	BBV9718C	111	Dec. 25, 2022

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101112	Dec. 25, 2022
2	LISN	R&S	ENV216	101113	Dec. 25, 2022
3	EMI Test Receiver	R&S	ESCS30	100353	Dec. 25, 2022

Test software					
Item	Test Description	Manufacturer	Model No.	Version	
1	Radiated emission/Conducted Emission	Farad	EZ-EMC	RA-03A1	

Note:1. The Cal. Interval was one year.

2. The cable loss has calculated in test result which connection between each test instruments.

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

3. TEST ITEM AND RESULTS

3.1. Conducted Emission


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration



Test Procedure


1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.

**Test Mode:**

Please refer to the clause 2.4.

Test Results

Test Voltage:	AC 120V/60 Hz
Terminal:	Line




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.1500	38.20	9.29	47.49	66.00	-18.51	QP
2	*	0.1820	36.66	9.75	46.41	64.39	-17.98	QP
3		0.2900	14.69	9.95	24.64	50.52	-25.88	AVG
4		0.3500	23.58	9.87	33.45	58.96	-25.51	QP
5		0.5020	20.60	9.88	30.48	56.00	-25.52	QP
6		0.5020	8.73	9.88	18.61	46.00	-27.39	AVG
7		0.8020	16.36	10.02	26.38	56.00	-29.62	QP
8		1.0060	4.73	9.89	14.62	46.00	-31.38	AVG
9		5.0300	6.62	10.17	16.79	50.00	-33.21	AVG
10		7.0420	12.05	10.30	22.35	50.00	-27.65	AVG
11		9.0540	25.58	10.34	35.92	60.00	-24.08	QP
12		9.0540	21.43	10.34	31.77	50.00	-18.23	AVG

Measure Level= Read Level+ Correct Factor
Margin = Measure Level-Limit



Test Voltage:	AC 120V/60 Hz
Terminal:	Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector
1	*	0.1500	40.37	9.61	49.98	66.00	-16.02	QP
2		0.1820	36.77	9.77	46.54	64.39	-17.85	QP
3		0.3140	13.64	10.15	23.79	49.86	-26.07	AVG
4		0.4260	22.14	10.05	32.19	57.33	-25.14	QP
5		0.5020	8.93	10.08	19.01	46.00	-26.99	AVG
6		0.5740	19.52	10.12	29.64	56.00	-26.36	QP
7		0.9460	4.63	10.25	14.88	46.00	-31.12	AVG
8		1.0020	16.22	10.24	26.46	56.00	-29.54	QP
9		3.0180	1.08	10.64	11.72	46.00	-34.28	AVG
10		7.0380	7.83	10.44	18.27	50.00	-31.73	AVG
11		9.0500	23.61	10.51	34.12	60.00	-25.88	QP
12		9.0500	19.71	10.51	30.22	50.00	-19.78	AVG

Measure Level= Read Level+ Correct Factor

Margin = Measure Level-Limit

3.2. Radiated Emission

Limit


FCC CFR Title 47 Part 15 Subpart C Section 15.209:

Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m).

Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup


CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
 2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
 5. Set to the maximum power setting and enable the EUT transmit continuously.
 6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW $\geq$ 1/T Peak detector for Average value.
- Note 1: For the 1/T & Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result

9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS


Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Pre-scan all antenna, only show the test data for worse case antenna on the test report.



30MHz-1GHz

Ant. Pol.	Horizontal
Test Mode:	802.11b Mode 2412MHz at ANT1
Remark:	Only worse case is reported




No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		195.1365	44.22	-15.68	28.54	43.50	-14.96	QP
2		234.1684	46.35	-14.37	31.98	46.00	-14.02	QP
3		267.5455	47.25	-13.45	33.80	46.00	-12.20	QP
4	*	301.4224	50.19	-12.77	37.42	46.00	-8.58	QP
5		318.8170	42.81	-12.27	30.54	46.00	-15.46	QP
6		332.5187	45.08	-11.88	33.20	46.00	-12.80	QP

Remarks:

- Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Measure Level= Read Level+ Correct Factor
- Margin = Measure Level-Limit



Ant. Pol.	Vertical
Test Mode:	802.11b Mode 2412MHz at ANT1
Remark:	Only worse case is reported



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		166.0680	47.27	-17.68	29.59	43.50	-13.91	QP
2		199.2855	45.06	-15.67	29.39	43.50	-14.11	QP
3		267.5455	45.85	-13.45	32.40	46.00	-13.60	QP
4		399.0302	39.66	-11.04	28.62	46.00	-17.38	QP
5		465.5994	39.60	-9.38	30.22	46.00	-15.78	QP
6	*	492.4685	41.48	-8.71	32.77	46.00	-13.23	QP

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor

2. Measure Level = Read Level + Correct Factor

3. Margin = Measure Level - Limit



Adobe 1GHz

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4824.000	58.99	-4.86	54.13	74	-19.87	H	PK
4824.000	43.72	-4.86	38.86	54	-15.14	H	AV
7236.000	55.13	1.6	56.73	74	-17.27	H	PK
7236.000	40.68	1.6	42.28	54	-11.72	H	AV
4824.000	61.82	-4.86	56.96	74	-17.04	V	PK
4824.000	41.72	-4.86	36.86	54	-17.14	V	AV
7236.000	52.77	1.6	54.37	74	-19.63	V	PK
7236.000	40.92	1.6	42.52	54	-11.48	V	AV
Middle Channel-2437MHz							
4874.000	58.84	-4.92	53.92	74	-20.08	H	PK
4874.000	41.96	-4.92	37.04	54	-16.96	H	AV
7311.000	53.01	1.5	54.51	74	-19.49	H	PK
7311.000	38.98	1.5	40.48	54	-13.52	H	AV
4874.000	58.93	-4.92	54.01	74	-19.99	V	PK
4874.000	42.13	-4.92	37.21	54	-16.79	V	AV
7311.000	56.12	1.5	57.62	74	-16.38	V	PK
7311.000	38.69	1.5	40.19	54	-13.81	V	AV
High Channel-2462MHz							
4924.000	59.35	-5.12	54.23	74	-19.77	H	PK
4924.000	42.25	-5.12	37.13	54	-16.87	H	AV
7386.000	53.84	1.55	55.39	74	-18.61	H	PK
7386.000	38.32	1.55	39.87	54	-14.13	H	AV
4924.000	57.72	-5.12	52.6	74	-21.4	V	PK
4924.000	42.29	-5.12	37.17	54	-16.83	V	AV
7386.000	53.02	1.55	54.57	74	-19.43	V	PK
7386.000	39.12	1.55	40.67	54	-13.33	V	AV

Remarks:

1. Correct (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Measure Level= Read Level+ Correct Factor
3. Margin = Measure Level-Limit
4. worse case is 802.11b Mode at ANT1.
5. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3h Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


3.3. Band Edge Emissions (Radiated)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS 247 5.5:

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.

Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.8 Duty Cycle.


Test Mode


Please refer to the clause 2.4.



Test Results

Pre-scan all antenna, only show the test data for worse case antenna on the test report.








3.4. Band edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW $\geq$ RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.


Test Results




(1) Band edge Conducted Test

Ant1:

802.11b-Low



802.11b-High



CTC Laboratories, Inc.



1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn







802.11g-High




802.11n20-Low





802.11n20-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



802.11n40-Low



802.11n40-High



CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn






Ant2:

802.11b-Low



802.11b-High



CTC Laboratories, Inc.



1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn







802.11g-High




802.11n20-Low





802.11n20-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



802.11n40-Low



802.11n40-High



CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

中国国家认证认可监督管理委员会
Certification and Accreditation Administration of the People's Republic of ChinaFor anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



CTC Laboratories, Inc.

1-2/F, Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




(2) Conducted Spurious Emissions Test

Ant1:

802.11b-Low



802.11b-Middle



CTC Laboratories, Inc.


1-2/F, Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



802.11b-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



802.11g-Low



802.11g-Middle



CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China: yz.cnca.cn



802.11g-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11n20-Low




802.11n20-Middle





802.11n20-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11n40-Low




802.11n40-Middle





802.11n40-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




Ant2:

802.11b-Low



802.11b-Middle



CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



802.11b-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11g-Low




802.11g-Middle





802.11g-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11n20-Low




802.11n20-Middle





802.11n20-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11n40-Low




802.11n40-Middle





802.11n40-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China: yz.cnca.cn




3.5. DTS Bandwidth

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2)/ RSS-247 5.2 a:

Test Item	Limit	Frequency Range(MHz)
DTS Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

Test Configuration



Test Procedure

5. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
6. DTS Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.OCB Spectrum Setting:
 - (1) Set RBW = 1% ~ 5% occupied bandwidth.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

NOTE: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

Test Mode

Please refer to the clause 2.4.


**Test Results**

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
802.11b	Ant1	2412	8.307	≥ 0.5	PASS
	Ant2	2412	7.814	≥ 0.5	PASS
	Ant1	2437	7.879	≥ 0.5	PASS
	Ant2	2437	8.654	≥ 0.5	PASS
	Ant1	2462	7.801	≥ 0.5	PASS
	Ant2	2462	8.576	≥ 0.5	PASS
802.11g	Ant1	2412	15.11	≥ 0.5	PASS
	Ant2	2412	15.69	≥ 0.5	PASS
	Ant1	2437	16.31	≥ 0.5	PASS
	Ant2	2437	15.69	≥ 0.5	PASS
	Ant1	2462	15.66	≥ 0.5	PASS
	Ant2	2462	15.10	≥ 0.5	PASS
802.11n(HT20)	Ant1	2412	15.12	≥ 0.5	PASS
	Ant2	2412	15.69	≥ 0.5	PASS
	Ant1	2437	16.89	≥ 0.5	PASS
	Ant2	2437	15.69	≥ 0.5	PASS
	Ant1	2462	15.10	≥ 0.5	PASS
	Ant2	2462	15.10	≥ 0.5	PASS
802.11n(HT40)	Ant1	2422	35.12	≥ 0.5	PASS
	Ant2	2422	35.69	≥ 0.5	PASS
	Ant1	2437	35.38	≥ 0.5	PASS
	Ant2	2437	35.11	≥ 0.5	PASS
	Ant1	2452	35.10	≥ 0.5	PASS
	Ant2	2452	35.11	≥ 0.5	PASS




Ant1:


802.11b-Low



802.11b-Middle



802.11b-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11g-Low



802.11g-Middle




802.11g-High







802.11n20-Low



802.11n20-Middle




802.11n20-High







802.11n40-Low



802.11n40-Middle






802.11n40-High






Ant2:


802.11b-Low	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Center Freq: 2.412000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref Offset 1.67 dB Ref 21.67 dBm Mkr3 2.415913 GHz 0.32867 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 3.333 ms Occupied Bandwidth 13.366 MHz Total Power 24.0 dBm Transmit Freq Error 6.696 kHz OBW Power 99.00 % x dB Bandwidth 7.814 MHz x dB -6.00 dB
802.11b-Middle	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref Offset 1.71 dB Ref 21.71 dBm Mkr3 2.441342 GHz 0.62917 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 3.333 ms Occupied Bandwidth 13.510 MHz Total Power 24.0 dBm Transmit Freq Error 14.924 kHz OBW Power 99.00 % x dB Bandwidth 8.654 MHz x dB -6.00 dB
802.11b-High	 Agilent Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref Offset 1.69 dB Ref 21.69 dBm Mkr3 2.466301 GHz -0.71840 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 30 MHz Sweep 3.333 ms Occupied Bandwidth 13.389 MHz Total Power 23.9 dBm Transmit Freq Error 13.396 kHz OBW Power 99.00 % x dB Bandwidth 8.576 MHz x dB -6.00 dB




802.11g-Low



802.11g-Middle




802.11g-High







802.11n20-Low



802.11n20-Middle




802.11n20-High







802.11n40-Low



802.11n40-Middle



802.11n40-High






3.6. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3)/ RSS-247 5.4:

Section	Test Item	Limit	Frequency Range(MHz)
CFR 47 FCC 15.247(b)(3)	Maximum conducted output power	1 Watt or 30dBm	2400~2483.5
ISED RSS-247 5.4 d	EIRP	4 Watt or 36dBm	2400~2483.5

Test Configuration



Test Procedure

1. The maximum conducted output power may be measured using a broadband Peak RF power meter.
2. Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor.
3. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.
4. Record the measurement data.

Test Mode

Please refer to the clause 2.4.

Test Result



Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
802.11b	Ant1	2412	16.86	<=30	PASS
	Ant2	2412	16.40	<=30	PASS
	Ant1	2437	16.90	<=30	PASS
	Ant2	2437	16.40	<=30	PASS
	Ant1	2462	15.20	<=30	PASS
	Ant2	2462	15.60	<=30	PASS
802.11g	Ant1	2412	13.44	<=30	PASS
	Ant2	2412	13.70	<=30	PASS
	Ant1	2437	13.45	<=30	PASS
	Ant2	2437	14.14	<=30	PASS
	Ant1	2462	13.24	<=30	PASS
	Ant2	2462	15.80	<=30	PASS
802.11n(HT20)	Ant1	2412	12.20	<=30	PASS
	Ant2	2412	15.16	<=30	PASS
	Total	2412	16.94	<=30	PASS
	Ant1	2437	12.13	<=30	PASS
	Ant2	2437	15.10	<=30	PASS
	Total	2437	16.87	<=30	PASS
	Ant1	2462	12.20	<=30	PASS
	Ant2	2462	14.73	<=30	PASS
	Total	2462	16.66	<=30	PASS
802.11n(HT40)	Ant1	2422	10.45	<=30	PASS
	Ant2	2422	12.53	<=30	PASS
	Total	2422	14.62	<=30	PASS
	Ant1	2437	10.48	<=30	PASS
	Ant2	2437	12.35	<=30	PASS
	Total	2437	14.53	<=30	PASS
	Ant1	2452	10.16	<=30	PASS
	Ant2	2452	12.44	<=30	PASS
	Total	2452	14.46	<=30	PASS




3.7. Power Spectral Density

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e)/ RSS-247 5.2 b:

Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:
Set analyzer center frequency to DTS channel center frequency.
Set the span to 1.5 times the DTS bandwidth.
Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
Set the VBW to: $\geq 3 \times \text{RBW}$
Detector: power averaging (RMS) or sample detector (when RMS not available).
Sweep time = auto couple.
Employ trace averaging (RMS) mode over a minimum of 100 traces.
Use the peak marker function to determine the maximum amplitude level.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

Test Mode




Please refer to the clause 2.4.

**Test Result**

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
802.11b	Ant1	2412	-13.165	<=8	PASS
	Ant2	2412	-12.737	<=8	PASS
	Ant1	2437	-12.880	<=8	PASS
	Ant2	2437	-12.753	<=8	PASS
	Ant1	2462	-13.198	<=8	PASS
	Ant2	2462	-12.971	<=8	PASS
802.11g	Ant1	2412	-19.814	<=8	PASS
	Ant2	2412	-19.630	<=8	PASS
	Ant1	2437	-19.736	<=8	PASS
	Ant2	2437	-20.802	<=8	PASS
	Ant1	2462	-20.368	<=8	PASS
	Ant2	2462	-7.364	<=8	PASS
802.11n(HT20)	Ant1	2412	-21.681	<=8	PASS
	Ant2	2412	-19.918	<=8	PASS
	Total	2412	-17.700	<=8	PASS
	Ant1	2437	-21.204	<=8	PASS
	Ant2	2437	-19.385	<=8	PASS
	Total	2437	-17.190	<=8	PASS
	Ant1	2462	-20.845	<=8	PASS
	Ant2	2462	-20.082	<=8	PASS
	Total	2462	-17.436	<=8	PASS
802.11n(HT40)	Ant1	2422	-23.864	<=8	PASS
	Ant2	2422	-25.231	<=8	PASS
	Total	2422	-21.484	<=8	PASS
	Ant1	2437	-24.898	<=8	PASS
	Ant2	2437	-21.131	<=8	PASS
	Total	2437	-19.608	<=8	PASS
	Ant1	2452	-24.521	<=8	PASS
	Ant2	2452	-24.685	<=8	PASS
	Total	2452	-21.592	<=8	PASS



Ant1:

802.11b-Low	
802.11b-Middle	
802.11b-High	

CTC Laboratories, Inc.

1-2/F, Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China


Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn







802.11n20-Low



802.11n20-Middle




802.11n20-High







802.11n40-Low



802.11n40-Middle



802.11n40-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059




Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



Ant2:

802.11b-Low	
802.11b-Middle	
802.11b-High	

CTC Laboratories, Inc.


1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn







802.11n20-Low



802.11n20-Middle



802.11n20-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059


Fax: (86)755-27521011

Http://www.sz-ctc.org.cn


For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn




802.11n40-Low



802.11n40-Middle



802.11n40-High



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



3.8. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

This product has an integral antenna, fulfill the requirement of this section.

*****THE END*****

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn