


Band edge

Test Model 802.11b 802.11g 802.11n(HT20) 802.11n(HT40)


Channel 1: 2412MHz Channel 3: 2422MHz



PSD(Power Spectral Density) RBW=100kHz

Test Model 802.11b 802.11g 802.11n(HT20) 802.11n(HT40)


Channel 6: 2437MHz



Unwanted Emissions In Non-Restricted Frequency Bands

Test Model 802.11b 802.11g 802.11n(HT20) 802.11n(HT40)


Channel 6: 2437MHz



PSD(Power Spectral Density) RBW=100kHz


Test Model 802.11b 802.11g 802.11n(HT20) 802.11n(HT40)

Channel 11: 2462MHz Channel 9: 2452MHz




Unwanted Emissions In Non-Restricted Frequency Bands

Test Model 802.11b 802.11g 802.11n(HT20) 802.11n(HT40)
Channel 11: 2462MHz Channel 9: 2452MHz



Band edge

Test Model 802.11b 802.11g 802.11n(HT20) 802.11n(HT40)
Channel 11: 2462MHz Channel 9: 2452MHz



7.5 RADIATED SPURIOUS EMISSION

7.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

7.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
 According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

7.5.3 Test Configuration

Test according to clause 6.2 radio frequency test setup 2

7.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting

the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

7.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

Antenna 1:

Test mode: 802.11 g Frequency: Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3068.45	V	52.90	37.11	74	54	-21.10	-16.89
7173.30	V	52.63	42.91	74	54	-21.37	-11.09
14792.42	V	52.19	37.19	74	54	-21.81	-16.81
3048.56	H	58.63	41.04	74	54	-15.37	-12.96
7098.02	H	53.18	38.96	74	54	-20.82	-15.04
14741.21	H	52.96	37.20	74	54	-21.04	-16.80

Test mode: 802.11 g Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3094.28	V	51.76	38.96	74	54	-22.24	-15.04
7179.52	V	54.33	37.09	74	54	-19.67	-16.91
14692.29	V	53.00	37.73	74	54	-21.00	-16.27
3118.52	H	56.80	37.91	74	54	-17.20	-16.09
8149.66	H	51.93	42.08	74	54	-22.07	-11.92
14692.29	H	55.46	43.08	74	54	-18.54	-10.92

Test mode: 802.11 g Frequency: Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
2965.14	V	58.37	38.71	74	54	-15.63	-15.29
5676.81	V	51.15	39.15	74	54	-22.85	-14.85
10732.58	V	58.96	43.95	74	54	-15.04	-10.05
3041.96	H	54.91	37.95	74	54	-19.09	-16.05
7694.13	H	54.86	43.65	74	54	-19.14	-10.35
11894.03	H	52.19	39.20	74	54	-21.81	-14.80

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result recorded was report as below:

Antenna 1:

Test mode: 802.11 g Frequency: Channel 1: 2412MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2383.600	H	42.16	74	36.70	54
2388.560	V	42.85	74	28.61	54

Test mode: 802.11 g Frequency: Channel 11: 2462MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2484.094	H	43.67	74	29.25	54
2484.160	V	45.79	74	30.50	54


Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant_F + Cab_L - Preamp


(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Spurious Emission in Restricted Band 2310-2390MHz			
Test Model	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)
	<input checked="" type="checkbox"/> Channel 1: 2412MHz	<input type="checkbox"/> Channel 3: 2422MHz	<input type="checkbox"/> 802.11n(HT40)
	VBW=3MHz		Polarity: H




Site: Polarization: **Horizontal** Temperature: 23 °C
Limit: FCC PART 15 B 3m_PEAK(RE) Power: AC 120V/60Hz Humidity: 58 %

Spurious Emission in Restricted Band 2310-2390MHz			
Test Model	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)
	<input checked="" type="checkbox"/> Channel 1: 2412MHz	<input type="checkbox"/> Channel 3: 2422MHz	<input type="checkbox"/> 802.11n(HT40)
	VBW=3MHz		Polarity: V




Site: Polarization: **Vertical** Temperature: 23 °C
Limit: FCC PART 15 B 3m_PEAK(RE) Power: AC 120V/60Hz Humidity: 58 %

Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz			
	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> Channel 11: 2462MHz	<input type="checkbox"/> Channel 9: 2452MHz	Polarity: H	
VBW=3MHz				



Site: Polarization: **Horizontal** Temperature: 23 °C
 Limit: FCC PART 15 B 3m_PEAK(RE) Power: AC 120V/60Hz Humidity: 58 %


Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz			
	<input type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> Channel 11: 2462MHz	<input type="checkbox"/> Channel 9: 2452MHz	Polarity: V	
VBW=3MHz				



Site: Polarization: **Vertical** Temperature: 23 °C
 Limit: FCC PART 15 B 3m_PEAK(RE) Power: AC 120V/60Hz Humidity: 58 %

- Spurious Emission below 1GHz (30MHz to 1GHz)
- All antenna modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11g recorded was report as below:

Antenna 1:




Site: Polarization: **Horizontal** Temperature: 25.0°C
 Limit: FCC Part15C Class B RE_3m Power: AC 120 V/60 Hz Humidity: 58 %
 Mode: TX 2412
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		120.2100	56.30	-19.23	37.07	43.50	-6.43	QP
2		240.4900	53.67	-16.23	37.44	46.00	-8.56	QP
3	*	359.8000	56.49	-13.41	43.08	46.00	-2.92	QP
4		600.3600	48.87	-8.37	40.50	46.00	-5.50	QP
5		839.9500	43.20	-4.58	38.62	46.00	-7.38	QP
6		960.2300	48.03	-3.66	44.37	54.00	-9.63	QP

*:Maximum data x:Over limit !:over margin

<Reference Only




Site: Polarization: **Vertical** Temperature: 25.0°C
 Limit: FCC Part15C Class B RE_3m Power: AC 120 V/60 Hz Humidity: 58 %
 Mode: TX 2412
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		120.2100	59.10	-19.23	39.87	43.50	-3.63	QP
2		240.4900	58.27	-16.23	42.04	46.00	-3.96	QP
3		359.8000	56.31	-13.41	42.90	46.00	-3.10	QP
4	*	600.3600	51.65	-8.37	43.28	46.00	-2.72	QP
5		839.9500	43.31	-4.58	38.73	46.00	-7.27	QP
6		960.2300	46.61	-3.66	42.95	54.00	-11.05	QP

*:Maximum data x:Over limit !:over margin

< Reference Only




Site: Polarization: **Horizontal** Temperature: 25.0°C
 Limit: FCC Part15C Class B RE_3m Power: AC 120 V/60 Hz Humidity: 58 %
 Mode: TX 2437
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		359.8000	53.83	-13.41	40.42	46.00	-5.58	QP
2		600.3600	49.99	-8.37	41.62	46.00	-4.38	QP
3		649.8300	50.02	-7.56	42.46	46.00	-3.54	QP
4		719.6700	47.76	-6.88	40.88	46.00	-5.12	QP
5	*	839.9500	47.06	-4.58	42.48	46.00	-3.52	QP
6		960.2300	46.97	-3.66	43.31	54.00	-10.69	QP

*:Maximum data x:Over limit l:over margin

< Reference Only




Site: Polarization: **Vertical** Temperature: 25.0°C
 Limit: FCC Part15C Class B RE_3m Power: AC 120 V/60 Hz Humidity: 58 %
 Mode: TX 2437
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	120.2100	60.18	-19.23	40.95	43.50	-2.55	QP
2	240.4900	55.74	-16.23	39.51	46.00	-6.49	QP
3	359.8000	56.86	-13.41	43.45	46.00	-2.55	QP
4	600.3600	45.68	-8.37	37.31	46.00	-8.69	QP
5 *	719.6700	50.92	-6.88	44.04	46.00	-1.96	QP
6	960.2300	46.89	-3.66	43.23	54.00	-10.77	QP

*:Maximum data x:Over limit !:over margin

<Reference Only




Site: Polarization: **Horizontal** Temperature: 25.0°C
 Limit: FCC Part15C Class B RE_3m Power: AC 120 V/60 Hz Humidity: 58 %
 Mode: TX 2462
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		120.2100	58.59	-19.23	39.36	43.50	-4.14	QP
2		239.5200	59.11	-16.25	42.86	46.00	-3.14	QP
3	*	359.8000	56.71	-13.41	43.30	46.00	-2.70	QP
4		600.3600	51.39	-8.37	43.02	46.00	-2.98	QP
5		649.8300	50.51	-7.56	42.95	46.00	-3.05	QP
6		839.9500	47.86	-4.58	43.28	46.00	-2.72	QP

*:Maximum data x:Over limit !:over margin

<Reference Only



Site: Polarization: **Vertical** Temperature: 25.0°C
 Limit: FCC Part15C Class B RE_3m Power: AC 120 V/60 Hz Humidity: 58 %
 Mode: TX 2462
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		120.2100	58.57	-19.23	39.34	43.50	-4.16	QP
2	*	239.5200	58.61	-16.25	42.36	46.00	-3.64	QP
3		359.8000	52.70	-13.41	39.29	46.00	-6.71	QP
4		480.0800	49.34	-10.71	38.63	46.00	-7.37	QP
5		600.3600	50.60	-8.37	42.23	46.00	-3.77	QP
6		960.2300	45.99	-3.66	42.33	54.00	-11.67	QP

*:Maximum data x:Over limit l:over margin

<Reference Only

7.6 CONDUCTED EMISSIONS TEST

7.6.1 Applicable Standard

According to FCC Part 15.207(a)

7.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Remark: Test results were obtained from the following equation:

$$\begin{aligned} \text{Measurement (dB}\mu\text{V)} &= \text{LISN Factor (dB)} + \text{Cable Loss (dB)} + \text{Reading (dB}\mu\text{V)} \\ \text{Over (dB)} &= \text{Measurement (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)} \end{aligned}$$

7.6.3 Test Configuration


Test according to clause 6.3 conducted emission test setup

7.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.
 Repeat above procedures until all frequency measured were complete.

7.6.5 Test Results

PASS




Site: Phase: **L1** Temperature: 22.5°C
 Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz Humidity: 49 %
 Mode: Wifi Mode
 Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1655	40.06	9.97	50.03	65.18	-15.15	QP	
2	0.1655	21.81	9.97	31.78	55.18	-23.40	AVG	
3	0.5503	8.06	9.97	18.03	56.00	-37.97	QP	
4	0.5503	3.44	9.97	13.41	46.00	-32.59	AVG	
5	0.7316	7.92	10.01	17.93	56.00	-38.07	QP	
6	0.7316	3.00	10.01	13.01	46.00	-32.99	AVG	
7	6.7017	27.50	10.24	37.74	60.00	-22.26	QP	
8	6.7017	22.10	10.24	32.34	50.00	-17.66	AVG	
9	11.3473	32.32	10.49	42.81	60.00	-17.19	QP	
10 *	11.3473	27.19	10.49	37.68	50.00	-12.32	AVG	
11	16.4112	20.66	10.95	31.61	60.00	-28.39	QP	
12	16.4112	16.02	10.95	26.97	50.00	-23.03	AVG	

*:Maximum data x:Over limit !:over margin

<Reference Only



Site: Phase: **N** Temperature: 22.5°C
 Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz Humidity: 48 %
 Mode: Wifi Mode
 Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1756	35.40	9.97	45.37	64.69	-19.32	QP	
2	0.1756	18.54	9.97	28.51	54.69	-26.18	AVG	
3	0.5375	9.28	9.97	19.25	56.00	-36.75	QP	
4	0.5375	4.36	9.97	14.33	46.00	-31.67	AVG	
5	0.7256	7.96	10.01	17.97	56.00	-38.03	QP	
6	0.7256	2.24	10.01	12.25	46.00	-33.75	AVG	
7	6.6572	27.30	10.23	37.53	60.00	-22.47	QP	
8	6.6572	21.92	10.23	32.15	50.00	-17.85	AVG	
9	11.6607	31.90	10.55	42.45	60.00	-17.55	QP	
10 *	11.6607	26.74	10.55	37.29	50.00	-12.71	AVG	
11	16.1704	20.69	10.98	31.67	60.00	-28.33	QP	
12	16.1704	16.10	10.98	27.08	50.00	-22.92	AVG	

*:Maximum data x:Over limit !:over margin

<Reference Only

7.7 ANTENNA APPLICATION

7.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

7.7.2 Result

PASS.

- The EUT has 1 antennas:a PCB Antenna for Wifi model, the gain is 0 dBi
- Note:
- Antenna uses a permanently attached antenna which is not replaceable.
 - Not using a standard antenna jack or electrical connector for antenna replacement
 - The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

----- END OF REPORT -----