

FCC TEST REPORT

FCC ID: 2A6K3-ZMLE10N

Report Number. : ZKT-220415L2477-01

Date of test..... : Apr. 14, 2022 -- Apr. 22, 2022

Date of issue : Apr. 22, 2022

Total number of pages..... : 65

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Jiangsu Jinshi Legend Technology Co., Ltd

Room 105-7, Building 17, Phase I, Human Resources Service

Address : Industrial Park, Jiangbei New District, Nanjing, No. 1, Qiliqiao North Road, Jiangbei New District, Nanjing, Jiangsu province, China

Manufacturer's name : Jiangsu Jinshi Legend Technology Co., Ltd

Room 105-7, Building 17, Phase I, Human Resources Service

Address : Industrial Park, Jiangbei New District, Nanjing, No. 1, Qiliqiao North Road, Jiangbei New District, Nanjing, Jiangsu province, China

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013
KDB558074 D0115.247 Meas Guidance v 05r02

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-112_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : Projector

Trademark : 知麻 ZEEMR

Model/Type reference : ZMLE1010, ZMLE1011, ZMLE1012, ZMLE1013, ZMLE1014,
ZMLE1015, ZMLE1016, ZMLE1017, ZMLE1018, ZMLE1019

Ratings..... : DC12.0V from adapter

Testing procedure and testing location:


Testing Laboratory : **Shenzhen ZKT Technology Co., Ltd.**

Address 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature)..... : Alen He



Reviewer (name + signature)..... : Joe Liu



Approved (name + signature) : Lake Xie



Table of Contents

	Page
1. VERSION	5
2. TEST SUMMARY	6
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 Test Setup Configuration	9
3.3 Support Equipment	9
3.4 Test Mode	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	12
4.1 Conducted emissions	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 Test Result	14
4.2 Radiated emissions	16
4.2.1 Radiated Emission Limits	16
4.2.2 TEST PROCEDURE	16
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS	18
4.2.6 TEST RESULTS	19
5. RADIATED BAND EMISSION MEASUREMENT	25
5.1 Test Requirement:	25
5.2 TEST PROCEDURE	25
5.3 DEVIATION FROM TEST STANDARD	26
5.4 TEST SETUP	26
5.5 EUT OPERATING CONDITIONS	26
5.6 TEST RESULT	27
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	29
6.1 Limit	29
6.2 Test Setup	29
6.3 Test procedure	29
6.4 DEVIATION FROM STANDARD	29
6.5 Test Result	29
7. 20DB BANDWIDTH	45
7.1 Test Setup	45
7.2 Limit	45

7.3 Test procedure	45
7.4 DEVIATION FROM STANDARD	45
7.5 Test Result	45
8. MAXIMUM PEAK OUTPUT POWER	49
8.1 Block Diagram Of Test Setup	49
8.2 Limit	49
8.3 Test procedure	49
8.4 DEVIATION FROM STANDARD	49
8.5 Test Result	49
9. HOPPING CHANNEL SEPARATION	50
9.1 Test Setup	50
9.2 Test procedure	50
9.3 DEVIATION FROM STANDARD	50
9.4 Test Result	50
10. NUMBER OF HOPPING FREQUENCY	54
10.1 Test Setup	54
10.2 Test procedure	54
10.3 DEVIATION FROM STANDARD	54
10.4 Test Result	55
11. DWELL TIME	57
11.1 Test Setup	57
11.2 Test procedure	57
11.3 DEVIATION FROM STANDARD	57
11.4 Test Result	58
12. ANTENNA REQUIREMENT	62
13. TEST SETUP PHOTO	63
14. EUT CONSTRUCTIONAL DETAILS	65

1. VERSION

Report No.	Version	Description	Approved
ZKT-220415L2477-01	Rev.01	Initial issue of report	Apr. 22, 2022

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission	PASS	
15.247(d)	Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Projector
Model No.:	ZMLE1010
Serial No.:	ZMLE1011, ZMLE1012, ZMLE1013, ZMLE1014, ZMLE1015, ZMLE1016, ZMLE1017, ZMLE1018, ZMLE1019
model difference:	There are many models of this product, only the model name and color will be different, other parts such as circuit principle, PCB, electrical structure, etc. are the same.so test model is ZMLE1010
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz~2480MHz
Modulation technology:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	FPC antenna
Antenna gain:	1.5dBi
Power supply:	AC 120V 50/60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel

see below:


Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration


Conducted Emission



Radiated Emission



Conducted Spurious



3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	ZEEMR	MODEL:SOY-1200400-327-II INPUT:100-240V 50/60Hz 1.7A max OUTPUT:12V-4A		SDOC


Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT /wifi Test Tool 
Power level setup	<10dBm

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 21, 2021	Sep. 22, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 21, 2021	Sep. 22, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Sep. 21, 2021	Sep. 22, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 21, 2021	Sep. 22, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 21, 2021	Sep. 22, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 21, 2021	Sep. 22, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 21, 2021	Sep. 22, 2022
8	Amplifier (1GHz-40GHz)	QUANJUDA	DLE-161	097	Sep. 21, 2021	Sep. 22, 2022
9	Loop Antenna (9KHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 21, 2021	Sep. 22, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 21, 2021	Sep. 22, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 21, 2021	Sep. 22, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 21, 2021	Sep. 22, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 21, 2021	Sep. 22, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 21, 2021	Sep. 22, 2022
2	LISN	CYBERTEK	EM5040A	E185040014 9	Sep. 21, 2021	Sep. 22, 2022
3	Test Cable	N/A	C01	N/A	Sep. 21, 2021	Sep. 22, 2022
4	Test Cable	N/A	C02	N/A	Sep. 21, 2021	Sep. 22, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 21, 2021	Sep. 22, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 21, 2021	Sep. 22, 2022

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test mode	BT




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1499	47.54	9.75	57.29	66.00	-8.71	QP	
2		0.1539	29.58	9.75	39.33	55.78	-16.45	AVG	
3		0.3339	40.40	9.86	50.26	59.35	-9.09	QP	
4		0.4100	27.45	9.87	37.32	47.65	-10.33	AVG	
5		0.6180	38.69	9.84	48.53	56.00	-7.47	QP	
6		0.6180	22.35	9.84	32.19	46.00	-13.81	AVG	
7		1.2300	36.79	9.73	46.52	56.00	-9.48	QP	
8		1.2420	25.14	9.72	34.86	46.00	-11.14	AVG	
9		3.5260	28.48	9.69	38.17	46.00	-7.83	AVG	
10	*	3.5340	40.15	9.69	49.84	56.00	-6.16	QP	
11		15.5979	16.50	9.64	26.14	50.00	-23.86	AVG	
12		15.7339	29.53	9.64	39.17	60.00	-20.83	QP	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test mode	



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1499	47.72	9.75	57.47	66.00	-8.53	QP	
2	0.1499	32.43	9.75	42.18	56.00	-13.82	AVG	
3	0.3140	23.55	9.87	33.42	49.86	-16.44	AVG	
4	0.3220	37.63	9.87	47.50	59.65	-12.15	QP	
5	0.6139	36.39	9.84	46.23	56.00	-9.77	QP	
6	0.6979	20.93	9.82	30.75	46.00	-15.25	AVG	
7 *	3.5459	39.86	9.69	49.55	56.00	-6.45	QP	
8	3.5539	27.56	9.69	37.25	46.00	-8.75	AVG	
9	4.7099	31.55	9.67	41.22	56.00	-14.78	QP	
10	5.5339	20.31	9.65	29.96	50.00	-20.04	AVG	
11	15.6019	28.54	9.64	38.18	60.00	-21.82	QP	
12	15.8658	16.79	9.64	26.43	50.00	-23.57	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. when charging, BT can not transmit

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test mode	BT



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test mode	BT



Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

1GHz~25GHz

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	55.92	30.55	5.77	24.66	55.80	74.00	-18.20	Pk
V	4804	39.53	30.55	5.77	24.66	39.41	54.00	-14.59	AV
V	7206	54.31	30.33	6.32	24.55	54.85	74.00	-19.15	Pk
V	7206	41.75	30.33	6.32	24.55	42.29	54.00	-11.71	AV
V	9608	51.25	30.85	7.45	24.69	52.54	74.00	-21.46	Pk
V	9608	37.02	30.85	7.45	24.69	38.31	54.00	-15.69	AV
H	4804	55.44	30.55	5.77	24.66	55.32	74.00	-18.68	Pk
H	4804	39.59	30.55	5.77	24.66	39.47	54.00	-14.53	AV
H	7206	54.05	30.33	6.32	24.55	54.59	74.00	-19.41	Pk
H	7206	39.34	30.33	6.32	24.55	39.88	54.00	-14.12	AV
H	9608	51.81	30.85	7.45	24.69	53.10	74.00	-20.90	Pk
H	9608	38.14	30.85	7.45	24.69	39.43	54.00	-14.57	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882	56.30	30.55	5.77	24.66	56.18	74.00	-17.82	Pk
V	4882	40.55	30.55	5.77	24.66	40.43	54.00	-13.57	AV
V	7323	54.09	30.33	6.32	24.55	54.63	74.00	-19.37	Pk
V	7323	39.98	30.33	6.32	24.55	40.52	54.00	-13.48	AV
V	9764	50.69	30.85	7.45	24.69	51.98	74.00	-22.02	Pk
V	9764	36.54	30.85	7.45	24.69	37.83	54.00	-16.17	AV
H	4882	55.85	30.55	5.77	24.66	55.73	74.00	-18.27	Pk
H	4882	40.38	30.55	5.77	24.66	40.26	54.00	-13.74	AV
H	7323	53.44	30.33	6.32	24.55	53.98	74.00	-20.02	Pk
H	7323	40.00	30.33	6.32	24.55	40.54	54.00	-13.46	AV
H	9764	52.60	30.85	7.45	24.69	53.89	74.00	-20.11	Pk
H	9764	36.31	30.85	7.45	24.69	37.60	54.00	-16.40	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960	54.60	30.55	5.77	24.66	54.48	74.00	-19.52	Pk
V	4960	39.60	30.55	5.77	24.66	39.48	54.00	-14.52	AV
V	7440	53.45	30.33	6.32	24.55	53.99	74.00	-20.01	Pk
V	7440	40.74	30.33	6.32	24.55	41.28	54.00	-12.72	AV
V	9920	52.74	30.85	7.45	24.69	54.03	74.00	-19.97	Pk
V	9920	38.87	30.85	7.45	24.69	40.16	54.00	-13.84	AV
H	4960	54.45	30.55	5.77	24.66	54.33	74.00	-19.67	Pk
H	4960	39.48	30.55	5.77	24.66	39.36	54.00	-14.64	AV
H	7440	53.79	30.33	6.32	24.55	54.33	74.00	-19.67	Pk
H	7440	40.38	30.33	6.32	24.55	40.92	54.00	-13.08	AV
H	9920	52.73	30.85	7.45	24.69	54.02	74.00	-19.98	Pk
H	9920	36.83	30.85	7.45	24.69	38.12	54.00	-15.88	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

 $\pi/4$ -DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	56.33	30.55	5.77	24.66	56.21	74.00	-17.79	Pk
V	4804	41.17	30.55	5.77	24.66	41.05	54.00	-12.95	AV
V	7206	53.91	30.33	6.32	24.55	54.45	74.00	-19.55	Pk
V	7206	40.24	30.33	6.32	24.55	40.78	54.00	-13.22	AV
V	9608	51.00	30.85	7.45	24.69	52.29	74.00	-21.71	Pk
V	9608	39.01	30.85	7.45	24.69	40.30	54.00	-13.70	AV
H	4804	56.15	30.55	5.77	24.66	56.03	74.00	-17.97	Pk
H	4804	42.14	30.55	5.77	24.66	42.02	54.00	-11.98	AV
H	7206	53.31	30.33	6.32	24.55	53.85	74.00	-20.15	Pk
H	7206	40.98	30.33	6.32	24.55	41.52	54.00	-12.48	AV
H	9608	52.58	30.85	7.45	24.69	53.87	74.00	-20.13	Pk
H	9608	37.36	30.85	7.45	24.69	38.65	54.00	-15.35	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	54.78	30.55	5.77	24.66	54.66	74.00	-19.34	Pk
V	4882	40.96	30.55	5.77	24.66	40.84	54.00	-13.16	AV
V	7323	54.36	30.33	6.32	24.55	54.90	74.00	-19.10	Pk

V	7323	40.66	30.33	6.32	24.55	41.20	54.00	-12.80	AV
V	9764	51.39	30.85	7.45	24.69	52.68	74.00	-21.32	Pk
V	9764	37.28	30.85	7.45	24.69	38.57	54.00	-15.43	AV
H	4882	56.09	30.55	5.77	24.66	55.97	74.00	-18.03	Pk
H	4882	41.24	30.55	5.77	24.66	41.12	54.00	-12.88	AV
H	7323	52.78	30.33	6.32	24.55	53.32	74.00	-20.68	Pk
H	7323	40.11	30.33	6.32	24.55	40.65	54.00	-13.35	AV
H	9764	51.85	30.85	7.45	24.69	53.14	74.00	-20.86	Pk
H	9764	37.69	30.85	7.45	24.69	38.98	54.00	-15.02	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960	56.64	30.55	5.77	24.66	56.52	74.00	-17.48	Pk
V	4960	39.90	30.55	5.77	24.66	39.78	54.00	-14.22	AV
V	7440	53.36	30.33	6.32	24.55	53.90	74.00	-20.10	Pk
V	7440	40.15	30.33	6.32	24.55	40.69	54.00	-13.31	AV
V	9920	51.70	30.85	7.45	24.69	52.99	74.00	-21.01	Pk
V	9920	36.76	30.85	7.45	24.69	38.05	54.00	-15.95	AV
H	4960	55.59	30.55	5.77	24.66	55.47	74.00	-18.53	Pk
H	4960	40.95	30.55	5.77	24.66	40.83	54.00	-13.17	AV
H	7440	52.92	30.33	6.32	24.55	53.46	74.00	-20.54	Pk
H	7440	40.35	30.33	6.32	24.55	40.89	54.00	-13.11	AV
H	9920	49.97	30.85	7.45	24.69	51.26	74.00	-22.74	Pk
H	9920	38.40	30.85	7.45	24.69	39.69	54.00	-14.31	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8DPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	54.67	30.55	5.77	24.66	54.55	74.00	-19.45	Pk
V	4804	42.22	30.55	5.77	24.66	42.10	54.00	-11.90	AV
V	7206	54.39	30.33	6.32	24.55	54.93	74.00	-19.07	Pk
V	7206	39.46	30.33	6.32	24.55	40.00	54.00	-14.00	AV
V	9608	52.29	30.85	7.45	24.69	53.58	74.00	-20.42	Pk
V	9608	37.65	30.85	7.45	24.69	38.94	54.00	-15.06	AV
H	4804	53.82	30.55	5.77	24.66	53.70	74.00	-20.30	Pk
H	4804	40.88	30.55	5.77	24.66	40.76	54.00	-13.24	AV
H	7206	54.17	30.33	6.32	24.55	54.71	74.00	-19.29	Pk
H	7206	40.58	30.33	6.32	24.55	41.12	54.00	-12.88	AV
H	9608	50.59	30.85	7.45	24.69	51.88	74.00	-22.12	Pk
H	9608	37.15	30.85	7.45	24.69	38.44	54.00	-15.56	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	54.65	30.55	5.77	24.66	54.53	74.00	-19.47	Pk
V	4882	40.39	30.55	5.77	24.66	40.27	54.00	-13.73	AV
V	7323	54.29	30.33	6.32	24.55	54.83	74.00	-19.17	Pk
V	7323	41.52	30.33	6.32	24.55	42.06	54.00	-11.94	AV
V	9764	51.79	30.85	7.45	24.69	53.08	74.00	-20.92	Pk
V	9764	37.91	30.85	7.45	24.69	39.20	54.00	-14.80	AV
H	4882	53.89	30.55	5.77	24.66	53.77	74.00	-20.23	Pk
H	4882	40.48	30.55	5.77	24.66	40.36	54.00	-13.64	AV
H	7323	54.28	30.33	6.32	24.55	54.82	74.00	-19.18	Pk
H	7323	38.81	30.33	6.32	24.55	39.35	54.00	-14.65	AV
H	9764	49.77	30.85	7.45	24.69	51.06	74.00	-22.94	Pk
H	9764	37.95	30.85	7.45	24.69	39.24	54.00	-14.76	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960	56.48	30.55	5.77	24.66	56.36	74.00	-17.64	Pk
V	4960	42.23	30.55	5.77	24.66	42.11	54.00	-11.89	AV
V	7440	53.13	30.33	6.32	24.55	53.67	74.00	-20.33	Pk
V	7440	40.15	30.33	6.32	24.55	40.69	54.00	-13.31	AV
V	9920	50.60	30.85	7.45	24.69	51.89	74.00	-22.11	Pk
V	9920	37.49	30.85	7.45	24.69	38.78	54.00	-15.22	AV
H	4960	55.07	30.55	5.77	24.66	54.95	74.00	-19.05	Pk
H	4960	41.48	30.55	5.77	24.66	41.36	54.00	-12.64	AV
H	7440	53.76	30.33	6.32	24.55	54.30	74.00	-19.70	Pk
H	7440	39.68	30.33	6.32	24.55	40.22	54.00	-13.78	AV
H	9920	50.44	30.85	7.45	24.69	51.73	74.00	-22.27	Pk
H	9920	36.71	30.85	7.45	24.69	38.00	54.00	-16.00	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- The limit for radiated test was performed according to FCC PART 15C.
- The tighter limit applies at the band edges.
- Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margin (dB)	Detector Type
GFSK	Low Channel: 2402MHz									
	H	2390.00	53.91	30.22	4.85	23.98	52.52	74	-21.48	PK
	H	2390.00	37.51	30.22	4.85	23.98	36.12	54	-17.88	AV
	H	2400.00	53.16	30.22	4.85	23.98	51.77	74	-22.23	PK
	H	2400.00	40.10	30.22	4.85	23.98	38.71	54	-15.29	AV
	V	2390.00	53.76	30.22	4.85	23.98	52.37	74	-21.63	PK
	V	2390.00	41.08	30.22	4.85	23.98	39.69	54	-14.31	AV
	V	2400.00	53.34	30.22	4.85	23.98	51.95	74	-22.05	PK
	V	2400.00	37.01	30.22	4.85	23.98	35.62	54	-18.38	AV
	High Channel: 2480MHz									
	H	2483.50	49.10	30.22	4.85	23.98	47.71	74	-26.29	PK
	H	2485.50	39.20	30.22	4.85	23.98	37.81	54	-16.19	AV
	H	2483.50	53.63	30.22	4.85	23.98	52.24	74	-21.76	PK
	H	2485.50	35.19	30.22	4.85	23.98	33.80	54	-20.20	AV
	V	2483.50	52.01	30.22	4.85	23.98	50.62	74	-23.38	PK
	V	2485.50	39.03	30.22	4.85	23.98	37.64	54	-16.36	AV
	V	2483.50	57.09	30.22	4.85	23.98	55.70	74	-18.30	PK
	V	2485.50	41.61	30.22	4.85	23.98	40.22	54	-13.78	AV

π/4-DQ PSK	Low Channel: 2402MHz									
	H	2390.00	56.16	30.22	4.85	23.98	54.77	74	-19.23	PK
	H	2390.00	37.61	30.22	4.85	23.98	36.22	54	-17.78	AV
	H	2400.00	52.59	30.22	4.85	23.98	51.20	74	-22.80	PK
	H	2400.00	39.25	30.22	4.85	23.98	37.86	54	-16.14	AV
	V	2390.00	50.60	30.22	4.85	23.98	49.21	74	-24.79	PK
	V	2390.00	41.81	30.22	4.85	23.98	40.42	54	-13.58	AV
	V	2400.00	51.83	30.22	4.85	23.98	50.44	74	-23.56	PK
	V	2400.00	36.84	30.22	4.85	23.98	35.45	54	-18.55	AV
	High Channel: 2480MHz									
	H	2483.50	48.71	30.22	4.85	23.98	47.32	74	-26.68	PK
	H	2485.50	36.83	30.22	4.85	23.98	35.44	54	-18.56	AV
	H	2483.50	54.00	30.22	4.85	23.98	52.61	74	-21.39	PK
	H	2485.50	39.92	30.22	4.85	23.98	38.53	54	-15.47	AV
	V	2483.50	55.96	30.22	4.85	23.98	54.57	74	-19.43	PK
	V	2485.50	41.94	30.22	4.85	23.98	40.55	54	-13.45	AV
	V	2483.50	60.12	30.22	4.85	23.98	58.73	74	-15.27	PK
	V	2485.50	42.85	30.22	4.85	23.98	41.46	54	-12.54	AV

8DPSK	Low Channel: 2402MHz									
	H	2390.00	55.04	30.22	4.85	23.98	53.65	74	-20.35	PK
	H	2390.00	36.60	30.22	4.85	23.98	35.21	54	-18.79	AV
	H	2400.00	52.04	30.22	4.85	23.98	50.65	74	-23.35	PK
	H	2400.00	39.88	30.22	4.85	23.98	38.49	54	-15.51	AV
	V	2390.00	51.73	30.22	4.85	23.98	50.34	74	-23.66	PK
	V	2390.00	42.62	30.22	4.85	23.98	41.23	54	-12.77	AV
	V	2400.00	50.80	30.22	4.85	23.98	49.41	74	-24.59	PK
	V	2400.00	37.65	30.22	4.85	23.98	36.26	54	-17.74	AV
	High Channel: 2480MHz									
	H	2483.50	48.63	30.22	4.85	23.98	47.24	74	-26.76	PK

	H	2485.50	40.11	30.22	4.85	23.98	38.72	54	-15.28	AV
	H	2483.50	53.32	30.22	4.85	23.98	51.93	74	-22.07	PK
	H	2485.50	37.43	30.22	4.85	23.98	36.04	54	-17.96	AV
	V	2483.50	55.73	30.22	4.85	23.98	54.34	74	-19.66	PK
	V	2485.50	43.82	30.22	4.85	23.98	42.43	54	-11.57	AV
	V	2483.50	57.43	30.22	4.85	23.98	56.04	74	-17.96	PK
	V	2485.50	41.47	30.22	4.85	23.98	40.08	54	-13.92	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.



6.4 DEVIATION FROM STANDARD

No deviation.



6.5 Test Result

GFSK mode:



Test channel:	Lowest channel
---------------	----------------



Test channel:	Middle channel
---------------	----------------





Test channel:	Highest channel
---------------	-----------------





$\pi/4$ -DQPSK mode:



Test channel:	Lowest channel
---------------	----------------



Test channel:	Middle channel
---------------	----------------






Test channel:	Highest channel
---------------	-----------------





8DPSK mode:

Test channel:	Lowest channel
---------------	----------------






Test channel:


Middle channel




Test channel:	Highest channel
---------------	-----------------




GFSK No-hopping Band edge-left side




GFSK Hopping Band edge-left side




GFSK No-hopping Band edge-right side




GFSK Hopping Band edge-right side




$\pi/4$ -DQPSK No-hopping Band edge-left side




$\pi/4$ -DQPSK Hopping Band edge-left side




$\pi/4$ -DQPSK No-hopping Band edge-right side




$\pi/4$ -DQPSK Hopping Band edge-right side




8DPSK No-hopping Band edge-left side




8DPSK Hopping Band edge-left side



8DPSK No-hopping Band edge-right side




8DPSK Hopping Band edge-right side



7. 20DB BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013

7.1 Test Setup



7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 20 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	1.031	Pass
	Middle	1.021	
	Highest	1.023	
$\pi/4$ -DQPSK	Lowest	1.251	Pass
	Middle	1.234	
	Highest	1.259	
8DPSK	Lowest	1.298	Pass
	Middle	1.293	
	Highest	1.321	

Test plots GFSK Low Channel



GFSK Middle Channel




GFSK High Channel




$\pi/4$ -DQPSK Low Channel




$\pi/4$ -DQPSK Middle Channel




$\pi/4$ -DQPSK High Channel



8DPSK Low Channel



8DPSK Middle Channel



8DPSK High Channel



8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Limit:	21

8.1 Block Diagram Of Test Setup



8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

8.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.4 DEVIATION FROM STANDARD

No deviation.

8.5 Test Result

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	5.628	21	Pass
	Middle	5.697		
	Highest	6.079		
$\pi/4$ -DQPSK	Lowest	7.182	21	Pass
	Middle	7.121		
	Highest	7.588		
8DPSK	Lowest	7.967	21	Pass
	Middle	7.075		
	Highest	7.58		

9. Hopping Channel Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup



9.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz , Span = 3.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


9.3 DEVIATION FROM STANDARD

No deviation.


9.4 Test Result

Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
DH5	Low	0.999	0.687	PASS
DH5	Middle	0.999	0.681	PASS
DH5	High	0.997	0.682	PASS
2DH5	Low	1.00	0.834	PASS
2DH5	Middle	0.997	0.823	PASS
2DH5	High	1.001	0.839	PASS
3DH5	Low	1.000	0.865	PASS
3DH5	Middle	1.000	0.862	PASS
3DH5	High	0.997	0.881	PASS

Test plots
DH5-Low Channel



DH5-Middle Channel




DH5-High Channel



2DH1-Low Channel



2DH3-Middle Channel



2DH5-High Channel



3DH1-Low Channel



3DH3-Middle Channel



3DH5-High Channel



10.NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

10.1 Test Setup



10.2 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD


No deviation.

10.4 Test Result


Test Plots:
79 Channels in total
GFSK



$\pi/4$ -DQPSK



8DPSK



11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

11.3 DEVIATION FROM STANDARD

No deviation.


11.4 Test Result

Frequency	Packet	Burst Width [ms/hop/ch]	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	0.3853	123.296	400	Pass
2441MHz	DH3	1.643	262.880	400	Pass
2441MHz	DH5	2.894	308.693	400	Pass
2441MHz	2DH1	0.3943	126.176	400	Pass
2441MHz	2DH3	1.646	263.360	400	Pass
2441MHz	2DH5	2.899	309.227	400	Pass
2441MHz	3DH1	0.3958	126.656	400	Pass
2441MHz	3DH3	1.649	263.840	400	Pass
2441MHz	3DH5	2.898	309.120	400	Pass


Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
Test channel: 2402MHz as blow
DH1 2DH1 3DH1 time slot= $\text{Burst Width(ms)} \times (1600 / (2 \times 79)) \times 31.6$
DH3 2DH3 3DH3 time slot= $\text{Burst Width(ms)} \times (1600 / (4 \times 79)) \times 31.6$
DH5 2DH5 3DH5 time slot= $\text{Burst Width(ms)} \times (1600 / (6 \times 79)) \times 31.6$


Test Plots
DH1 Middle Channel




DH3 Middle Channel




DH5 Middle Channel




2DH1 Middle Channel




2DH3 Middle Channel




2DH5 Middle Channel




3DH1 Middle Channel




3DH3 Middle Channel




3DH5 Middle Channel



12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna: The antenna is FPC antenna, the best case gain of the antennas are 1.5dBi, reference to the below photo for details ANT for BT/WIFI	
	

13. Test Setup Photo





14. EUT Constructional Details

Please refer to external photos file and internal photos file

***** END OF REPORT *****