



# RF Exposure Evaluation Report

**Application No.:** DNT2507180349R7717-09915  
**Applicant:** Shenzhen Tongzhou Yidao Technology CO., LTD  
**Address of Applicant:** Room 309, Building B, Chengshishanhai Center, zhongxing Road, Bantian, Longgang District, Shenzhen City, China  
**EUT Description:** Projector  
**Model No.:** TY260, TY261  
**FCC ID:** 2A6M3-TY260  
**Power supply** AC 110-240V, 50/60Hz  
**Trade Mark:** /  
47 CFR Part 2.1091  
**Standards:** FCC KDB 447498 D01 v06  
**Date of Receipt:** 2025/7/18  
**Date of Test:** 2025/7/19 to 2025/8/12  
**Date of Issue:** 2025/8/19  
**Test Result:** **PASS**

**Prepared By:** Wayne Lin (Testing Engineer)



**Reviewed By:** Pengfei Chen (Project Engineer)

**Approved By:** Yiwei Chen (Manager)

Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

**Dongguan DN Testing Co., Ltd.**

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang'an Town, Dongguan City, Guangdong P.R.China  
Web: [www.dn-testing.com](http://www.dn-testing.com) Tel: +86-769-88087383 E-mail: [service@dn-testing.com](mailto:service@dn-testing.com)

**Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	August 19, 2025	Valid	Original Report



## Contents

<b>1</b>	<b>GENERAL INFORMATION .....</b>	<b>4</b>
1.1	TEST LOCATION .....	4
1.2	GENERAL DESCRIPTION OF EUT .....	4
<b>2</b>	<b>RF EXPOSURE EVALUATION .....</b>	<b>5</b>
2.1	RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
2.1.1	Limits .....	5
2.1.2	Test Procedure .....	6
2.1.3	EUT RF Exposure Evaluation .....	6



## 1 General Information

### 1.1 Test Location

Company:	Dongguan DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xingfa Road, Wusha Liwu, Chang'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Wayne Lin

### 1.2 General Description of EUT

Manufacturer:	Shenzhen Tongzhou Yidao Technology CO., LTD
Address of Manufacturer:	Room 309, Building B, Chengshishanhai Center, zhongxing Road, Bantian, Longgang District, Shenzhen City, China
EUT Description::	Projector
Test Model No.:	TY260
Additional Model(s):	TY261
Chip Type:	RTL8733BS
Serial Number	PR2507180349R7717
Power Supply	AC 110-240V, 50/60Hz
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	BT: 2402-2480MHz 802.11b/g/n HT20: 2412 MHz-2462 MHz 802.11n HT40: 2422 MHz-2452 MHz
Type of Modulation:	BT:GFSK,π/4-DQPSK,8DPSK WIFI:DSSS/OFDM
Sample Type:	<input type="checkbox"/> Portable Device, <input type="checkbox"/> Module, <input checked="" type="checkbox"/> Mobile Device
Antenna Type:	FPC Antenna
Antenna Gain:	<input checked="" type="checkbox"/> Provided by applicant 1.95dBi

#### Remark:

\*All models are just color differences, motherboard, PCB circuit board, chip, electronic components, appearance is all the same.

\*Since the above data and/or information is provided by the applicant relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.



## 2 RF Exposure Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P<sub>d</sub> = power density in mW/cm<sup>2</sup>

P<sub>out</sub> = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P<sub>d</sub> is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



## 2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

## 2.1.3 EUT RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 / 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Test Mode	Antenna	Freq(MHz)	Power [dBm]
DH5	Ant1	2402	1.68
		2441	1.20
		2480	0.33
2DH5	Ant1	2402	1.82
		2441	1.48
		2480	0.44
3DH5	Ant1	2402	2.23
		2441	1.82
		2480	0.84
11B	Ant1	2412	15.62
		2437	17.28
		2462	16.72
11G	Ant1	2412	13.82
		2437	14.74
		2462	15.37
11N20SISO	Ant1	2412	12.13
		2437	13.12
		2462	13.98
11N40SISO	Ant1	2422	12.95
		2437	13.42
		2452	13.68

The Worst Mode	Antenna	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result	Distance (cm)
					(dBi)	(Linear)				
2.4G Band										
BT	Ant1	2.23	2±1	3	1.95	1.567	0.0006	1	Complies	20
WIFI	Ant1	17.28	17±1	18	1.95	1.567	0.0197	1	Complies	20

The End Report