



SAR Exclusion Evaluation Report

Applicant	Nexite Ltd.
Applicant address	126 Yigal Alon Street, Tel-Aviv 6744332, Israel
EUT	BLE Tag
FCC ID	FCC ID: 2A6MX13EATG30
IC	IC: 31515-NXTAG3000HB
HVIN	NX-TAG-3000-LB NX-TAG-3000-HB
FVIN	3.0
PMN	NX-TAG-3000-LB NX-TAG-3000-HB
Standard(s)	47CFR15 Section 15.247 RSS-247, Issue 3, August 2023, Section 5
Test report no.	Ra297811.01

Prepared by:	Ram Ezrah	
Reviewed by:	Lior Tenenbaum	
Test Laboratory	I.T.L. Product Testing Ltd. 3 HaOreg Street, Modi'in 7177909, Israel	
Date:	7 May 2025	



1 EUT Information

Model no.	NX-TAG-3000-LB
Power supply	-
Antenna type	Integral
Antenna gain (max.)	1.75 dBi
Assigned frequency range	2400MHz -2500MHz
Operating frequency	
Transmit power (conducted, Max.)	-15dbm
Modulation bandwidth	-
Bit rate	-
Test separation distance	5 mm
Evaluation Methods and Limits	FCC: KDB447498 D01 V06 ISED: RSS-102, Issue 6, 2023

1.1 SAR Exclusion Calculations

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

- Max. power: $0.11 + 1.5 (\text{antenna gain}) = 1.6$
- min. test separation distance: 5 mm
- f: 2.4GHz

$$1.6/5 * \sqrt{2.4} = 0.49$$

SAR Exclusion Limit (mW): 10

2 Conclusion

The SAR exclusion threshold has been evaluated using the method described above from information supplied by the manufacturer. Based on the evaluation above, the EUT is excluded from SAR testing.



- KDB447498 D01 V06

“RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices” v06, Section 4.3.1: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander”.



Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

- RSS-102, Issue 6, Dec. 2023, Sections 2.5.2, 3, and 4, table 4.

According to RSS-102, Section 3, “Devices that have a radiating element normally operating at or below 6 GHz, with a separation distance of up to 20 cm between the user and/or bystander and the device, shall undergo a SAR evaluation. Devices that have a radiating element normally operating at or below 6 GHz, with a separation distance greater than 20 cm between the user and/or bystander and the device shall undergo an RF exposure evaluation.

However, a SAR evaluation may be performed in lieu of an RF exposure evaluation for devices operating below 6 GHz with a separation distance of greater than 20 cm between the user and/or bystander and the device. Devices operating above 6 GHz regardless of the separation distance shall undergo an RF exposure evaluation.”



Table 1: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

End of Report