

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: NINGBO ZHONGXIN ELECTRONIC TECHNOLOGY CO.,LTD
Address of applicant: West workshop, floor 3, building 8, No. 818, Jinyuan Road, Yinzhou District, Ningbo City, Zhejiang Province

Manufacturer: NINGBO ZHONGXIN ELECTRONIC TECHNOLOGY CO.,LTD
Address of manufacturer: West workshop, floor 3, building 8, No. 818, Jinyuan Road, Yinzhou District, Ningbo City, Zhejiang Province

General Description of EUT:

Product Name: RGBW Rock Lights
Trade Name: /
Model No.: LF-RL-RGBW-UFA*8
Adding Model(s): LF-RL-RGBW-UFA*4
Rated Voltage: DC12V
Power Adapter: /
FCC ID: 2A6O7-LF-RL-RGBW

Technical Characteristics of EUT:

Bluetooth

Bluetooth Version: V4.0 (BLE mode)
Frequency Range: 2402-2480MHz
RF Output Power: -1.988dBm (Conducted)
Data Rate: 1Mbps
Modulation: GFSK
Quantity of Channels: 40
Channel Separation: 2MHz
Type of Antenna: PCB Antenna
Antenna Gain: 2.81dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm^2)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Bluetooth

Maximum Tune-Up output power: -1.5(dBm)

Maximum peak output power at antenna input terminal: 0.71(mW)

Prediction distance: >20(cm)

Prediction frequency: 2402(MHz)

Antenna gain: 2.81 (dBi)

Directional gain (numeric gain): 1.91

The worst case is power density at prediction frequency at 20cm: 0.0003(mw/cm^2)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm^2)

Result: Pass