

FCC ID: 2A6OAXYZ-2019

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.4WIFI :

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	7.514	5.64	7.5±0.5	8.00	6.31	<5	1.95983	3.00	YES
	2.437	7.612	5.77	7.5±0.5	8.00	6.31	<5	1.96996	3.00	YES
	2.462	7.683	5.87	7.5±0.5	8.00	6.31	<5	1.98004	3.00	YES
802.11g	2.412	6.61	4.58	6.5±0.5	7.00	5.01	<5	1.55675	3.00	YES
	2.437	6.635	4.61	6.5±0.5	7.00	5.01	<5	1.56480	3.00	YES
	2.462	6.689	4.67	6.5±0.5	7.00	5.01	<5	1.57280	3.00	YES
802.11n(HT20)	2.412	6.414	4.38	6.5±0.5	7.00	5.01	<5	1.55675	3.00	YES
	2.437	6.59	4.56	6.5±0.5	7.00	5.01	<5	1.56480	3.00	YES
	2.462	6.635	4.61	6.5±0.5	7.00	5.01	<5	1.57280	3.00	YES
802.11n(HT40)	2.412	5.44	3.50	5.5±0.5	6.00	3.98	<5	1.23657	3.00	YES
	2.437	5.565	3.60	5.5±0.5	6.00	3.98	<5	1.24296	3.00	YES
	2.462	5.367	3.44	5.5±0.5	6.00	3.98	<5	1.24932	3.00	YES

Conclusion:

For the max result : $1.98004 \leq$ FCC Limit 3.0 for 1g SAR.